

OV3600 Device Compatibility Matrix - part number 0510590-01

NOTE: - indicates that the feature is not supported on AP or not supported via OV3600's configuration interface

OV3600 Device Compatibility Matrix - part number 0510590-01

NOTE: - indicates that the feature is not supported on AP or not supported via OV3600's configuration interface

OV3600 Device Compatibility Matrix - part number 0510590-01

	3Com	Apple	BelAir	Compaq	Dell	Ericsson	Foundry	Funkwerk	IBM	Hirschmann	Intel	Intermec	Juniper	NEC	Nomadix	Siemens	Systimax	Toshiba	Vivato	Universal					
OV3600	WX100 WX1200 WX2200 WX4400 APX50	8750	Airport Base Station (Graphite)	200	WL-410 WL-510 WL-400	1170	DSSS A11	IronPoint 200 250	Artem ComPoint W-1000	AP-500	BAT-54	2011b	2011	2100 2101 2102 2106 WA21/22	NetScreen 5GT	Pasolink	HSG	AG-2000 AG-2100	AG 3000 5000	W788-2 PRO	AirSPEED 542	AP-500	VP1200	VA2200 VP2200	Any SNMP Device
Monitoring Parameters																									
SYS - Name, Desc., Location, Contact, & Uptime	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
Serial Number	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Device Bandwidth In/Out	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
Rogue Scan Support	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
User (MAC)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
User (IP)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
User (VLAN)	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
User (SSID)	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
User (Radio Mode)	●	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
User Signal Quality	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
User Bandwidth In/Out	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
User 802.11n Modo	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
User Authentication Type	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
User Cipher	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Dual Radio	●	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●						
802.11 dot11Counters	-	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
802.11 dot11QoS Counters	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Mesh / Bridge Link Monitoring	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
WiFi Tags	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
CPU / Memory Resources	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Unassociated Client Tracking	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
VisualRF Support	●	●	●	●	●	-	●	-	-	●	●	●	●	●	-	-	●	-	●						
Configuration Support																									
Template Configuration	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Firmware Update	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
SNMP	v2c, v3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	TFTP	SNMP	-						
CLI	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	v3	-	-						
Web	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Device Settings																									
System Name, Location, Contact	●	●	-	-	●	●	●	●	●	-	●	●	●	●	●	●	●	●	-						
Channel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	-						
IP address (or DHCP)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	-						
Radio Enabled/Disabled	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Antenna Configuration	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Transmit Power Level	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Interface / VLAN	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Protocol Port Mapping (SNMP/Telnet/HTTP(S))	-	●	-	●	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
Group Basic Settings																									
SNMP Trap Destination	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
IP Provisioning	●	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
SysLog Servers	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Spanning Tree Protocol	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Regulatory Domain	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
NTP Servers	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Group Radio Settings																									
Aironet Extensions	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Auto Channel Select	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Radio Cell Role	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Load Balancing	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
802.11n Operating Mode	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Software Configurable abg mode (a,b,g,b&g)	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
4.9 GHz Public Safety Radio Configuration	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
3.5 GHz WiMAX Radio Configuration	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Group Security Settings																									
SSID	●	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
802.1x authentication	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
MAC authentication (RADIUS Lookup)	●	-	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
MAC ACL	●	●	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
"Closed" Network	●	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
Publicly Secure Packet Forwarding	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
Enhanced Message Integrity Check	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
RADIUS/ACS Servers	●	-	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
Multiple SSIDs	●	-	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
VLAN Tagging per SSID	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
WEP	●	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
WEP Key Rotation Interval	●	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	-						
LEAP	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
WPA (TKIP) or Pre WPA TKIP	●	●	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
WPA2 PSK	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
WPA2 AES	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
Compatibility Mode	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	-						
Guest Access Provisioning	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
Discovery																									
Layer 2	-	-	-	-	OSU-NMS	-	OSU-NMS	WNMP	-	OSU-NMS	-	WNMP	WNMP	-	-	-	-	OSU-NMS	OSU-NMS						
SNMP Scanning	●	-	-	-	●	●	●	●	-	●	●	●	●	●	●	●	●	●	●						
HTTP Scanning	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
CDP Discovery (SNMP Switch/Router)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						

NOTE: - indicates that the feature is not supported on AP or not supported via OV3600's configuration interface.

© 2009 Alcatel-Lucent. Alcatel, Lucent, Alcatel-Lucent, and the Alcatel-Lucent logo are trademarks of Alcatel-Lucent. All rights reserved. All other trademarks are the property of their respective owners.