

Alcatel-Lucent and OmniVista 3600 Air Manager 7.5



Best Practices Guide

Copyright

© 2012 Alcatel-Lucent. All rights reserved.

Specifications in this manual are subject to change without notice.

Originated in the USA.

AOS-W, Alcatel 4302, Alcatel 4304, Alcatel 4306, Alcatel 4308, Alcatel 4324, Alcatel 4504, Alcatel 4604, Alcatel 4704, Alcatel 6000, OAW-AP41, OAW-AP68, OAW-AP60/61/65, OAW-AP70, OAW-AP80, OAW-AP92/93, OAW-AP105, OAW-AP120/121, OAW-AP124/125, OAW-AP175, OAW-IAP92/93/105, OAW-RAP2, OAW-RAP5, and Omnivista 3600 Air Manager are trademarks of Alcatel-Lucent in the United States and certain other countries.

Any other trademarks appearing in this manual are the property of their respective companies. Includes software from Litech Systems Design. The IF-MAP client library copyright 2011 Infoblox, Inc. All rights reserved. This product includes software developed by Lars Fenneberg et al.

Legal Notice

The use of Alcatel-Lucent switching platforms and software, by all individuals or corporations, to terminate Cisco or Nortel VPN client devices constitutes complete acceptance of liability by that individual or corporation for this action and indemnifies, in full, Alcatel-Lucent from any and all legal actions that might be taken against it with respect to infringement of copyright on behalf of Cisco Systems or Nortel Networks.

Preface	1
Document Organization	1
Note, Caution, and Warning Icons	2
Contacting Support	2
Chapter 1 Overview	3
Understanding Alcatel-Lucent Topology	3
Prerequisites for Integrating Alcatel-Lucent Infrastructure.....	3
Chapter 2 Configuring OV3600 for Alcatel-Lucent Infrastructure	5
Disabling Rate Limiting in OV3600 Setup > General	5
Entering Credentials in Device Setup > Communication	5
Setting Up Recommended Timeout and Retries.....	6
Setting Up Time Synchronization	7
Setting up NTP on OV3600	7
Manually Setting the Clock on a Controller	7
Enabling Support for Channel Utilization And Statistics	7
OV3600 Setup	8
Controller Setup (Master And Local)	8
Chapter 3 Configuring an Alcatel-Lucent Group in OV3600	9
Basic Monitoring Configuration	9
Advanced Configuration	10
Chapter 4 Discovering Alcatel-Lucent Infrastructure	11
Discovering Master Switches	11
Local Switch Discovery	13
Thin AP Discovery	13
Chapter 5 OV3600 and Alcatel-Lucent Integration Strategies	15
Integration Goals	15
Example Use Cases	16
When to Use Enable Stats	16
When to Use WMS Offload	16
When to Use RTLS.....	16
When to Define OV3600 as a Trap Host	16
When to use Channel Utilization	16
Prerequisites for Integration	17
Enable Stats Utilizing OV3600	17
WMS Offload with OV3600.....	18
Define OV3600 as a Trap Host using AOS-W CLI.....	18
AOS-W Traps Utilized by OV3600.....	19
Auth Traps	19

	IDS Traps	19
	ARM Traps.....	20
	Ensuring That IDS And Auth Traps Display in OV3600.....	20
	Understanding WMS Offload Impact on Alcatel-Lucent Infrastructure.....	21
Chapter 6	Alcatel-Lucent-Specific Capabilities in OV3600	23
	Alcatel-Lucent Traps for RADIUS Auth And IDS Tracking	23
	Remote AP Monitoring	24
	ARM And Channel Utilization Information	24
	VisualRF and Channel Utilization	25
	Configuring Channel Utilization Triggers.....	25
	Viewing Channel Utilization Alerts.....	26
	View Channel Utilization in RF Health Reports	26
	Viewing Switch License Information.....	26
	Rogue Device Classification	27
	Rules-Based Switch Classification.....	29
	Using RAPIDS Defaults for Switch Classification	29
	Changing RAPIDS based on Controller Classification.....	29
Appendix A	AOS-W and OV3600 CLI Commands	31
	Enable Channel Utilization Events	31
	Enable Stats With the AOS-W CLI.....	31
	Offload WMS Using the AOS-W or OV3600 CLI	31
	AOS-W CLI.....	31
	OV3600 SNMP	32
	Pushing Configs from Master to Local Switches	32
	Disable Debugging Utilizing AOS-W CLI	32
	Restart WMS on Local Switches	33
	Configure AOS-W CLI when not Offloading WMS	33
	Copy and Paste to Enable Proper Traps with the AOS-W CLI	33
Appendix B	OV3600 Data Acquisition Methods.....	35
Appendix C	WMS Offload Details	37
	State Correlation Process.....	37
	Using OV3600 as Master Device State Manager	38
Appendix D	Increasing Location Accuracy.....	39
	Understand Band Steering's Impact on Location	39
	Leveraging RTLS to Increase Accuracy	39
	Deployment Topology.....	39
	Prerequisites	40
	Enable RTLS service on the OV3600 server	40
	Enable RTLS on the Switch	41
	Troubleshooting RTLS	41
	Using the WebUI.....	41
	Using the CLI	41
	Wi-Fi Tag Setup Guidelines	43

The preface provides an overview of the best practices guide and contact information for Alcatel-Lucent, and includes the following sections:

- “Document Organization” on page 1
- “Note, Caution, and Warning Icons” on page 2
- “Contacting Support” on page 2

Document Organization

This best practices guide includes instructions and examples of optimal ways to use and integrate the OmniVista Air Manager 3600 with Alcatel-Lucent devices and infrastructure.

Table 1 *Document Organization and Purposes*

Chapter	Description
Chapter 1, “Overview” on page 3	This chapter explains the minimum requirements, prerequisites, topology of an Alcatel-Lucent infrastructure integrated with OV3600.
Chapter 2, “Configuring OV3600 for Alcatel-Lucent Infrastructure” on page 5	This chapter explains global configuration options in OV3600.
Chapter 3, “Configuring an Alcatel-Lucent Group in OV3600” on page 9	This chapter explains how to create and monitor an Alcatel-Lucent group in OV3600.
Chapter 4, “” on page 11	This chapter explains how to discover and manage your Alcatel-Lucent infrastructure.
Chapter 5, “OV3600 and Alcatel-Lucent Integration Strategies” on page 15	This chapter highlights recommended integration strategies.
Chapter 6, “Alcatel-Lucent-Specific Capabilities in OV3600” on page 23	This chapter highlights OV3600 capabilities that are specific to Alcatel-Lucent devices.
Appendix A, “AOS-W and OV3600 CLI Commands” on page 31	This appendix explains command line interface (CLI) commands.
Appendix B, “OV3600 Data Acquisition Methods” on page 35	This appendix provides a table that explains how OV3600 acquires data from Alcatel-Lucent devices.
Appendix C, “WMS Offload Details” on page 37	This appendix explains WMS Offload in further detail.
Appendix D, “Increasing Location Accuracy” on page 39	This appendix explains ways to increase location accuracy in OV3600.

Note, Caution, and Warning Icons

This document uses the following notice icons to emphasize advisories for certain actions, configurations, or concepts:



Indicates helpful suggestions, pertinent information, and important things to remember.



Indicates a risk of damage to your hardware or loss of data.



Indicates a risk of personal injury or death.

Contacting Support

Contact Center Online	
• Main Site	http://www.alcatel-lucent.com/enterprise
• Support Site	https://service.esd.alcatel-lucent.com
• Email	esd.support@alcatel-lucent.com
Service & Support Contact Center Telephone	
• North America	1-800-995-2696
• Latin America	1-877-919-9526
• Europe	+33 (0) 38 855 6929
• Asia Pacific	+65 6240 8484
• Worldwide	1-818-878-4507

This document provides best practices for leveraging OV3600 to monitor and manage your Alcatel-Lucent infrastructure. Alcatel-Lucent wireless infrastructure provides a wealth of functionality such as firewall, VPN, remote AP, IDS, IPS, and ARM, as well as an abundance of statistical information.

Follow the simple guidelines in this document to garner the full benefit of your Alcatel-Lucent infrastructure.


This overview chapter contains the following topics:

- “Understanding Alcatel-Lucent Topology” on page 3
- “Prerequisites for Integrating Alcatel-Lucent Infrastructure” on page 3

Understanding Alcatel-Lucent Topology

Figure 1 depicts typical master-local deployment for OV3600:

Figure 1 Typical Alcatel-Lucent Deployment



There should never be a local switch managed by an OV3600 server whose master switch is also not under management.

Prerequisites for Integrating Alcatel-Lucent Infrastructure

You will need the following information to monitor and manage your Alcatel-Lucent infrastructure:

- SNMP community string (monitoring and discovery)
- Telnet/SSH credentials (configuration only)

- **enable** password (configuration only)



NOTE

Without proper Telnet/SSH credentials OV3600 will not be able to acquire license and serial information from switches.

- SNMPv3 credentials are required for WMS Offload:
 - Username
 - Auth password
 - Privacy password
 - Auth protocol

This chapter explains how to optimally configure OV3600 to globally manage your global Alcatel-Lucent infrastructure, and contains the following topics:

- “Disabling Rate Limiting in OV3600 Setup > General” on page 5
- “Entering Credentials in Device Setup > Communication” on page 5
- “Setting Up Recommended Timeout and Retries” on page 6
- “Setting Up Time Synchronization” on page 7
- “Enabling Support for Channel Utilization And Statistics” on page 7

Disabling Rate Limiting in OV3600 Setup > General

The SNMP Rate Limiting for Monitored Devices option adds a small delay between each SNMP GET request, thus the actual polling intervals will be longer than what is configured. For example, setting a 10-minute polling interval will result in an actual 12-minute polling interval. Disabling rate limiting is recommended in most cases.

To disable rate limiting in OV3600, follow these steps:

1. Navigate to **OV3600 Setup > General**.
2. Locate the **Performance** section on this page.
3. In the **SNMP Rate Limiting for Monitored Devices** field, select **No**, as shown in [Figure 2](#).
4. Select **Save**.

Figure 2 SNMP Rate Limiting in OV3600 Setup > General

Performance	
Monitoring Processes (1-2):	<input type="text" value="2"/>
Maximum number of configuration processes (1-10):	<input type="text" value="5"/>
Maximum number of audit processes (1-10):	<input type="text" value="3"/>
SNMP Fetcher Count (2-6):	<input type="text" value="2"/>
Verbose logging of SNMP configuration:	<input type="radio"/> Yes <input checked="" type="radio"/> No
SNMP rate limiting for monitored devices:	<input type="radio"/> Yes <input checked="" type="radio"/> No

Entering Credentials in Device Setup > Communication

OV3600 requires several credentials to properly interface with Alcatel-Lucent devices. To enter these credentials, follow these steps:

1. Navigate to **Device Setup > Communication**.
2. In the **Default Credentials** section, select the **Edit** link next to **Alcatel-Lucent**. The page illustrated in [Figure 3](#) appears.
3. Enter the **SNMP Community String**.



Be sure to note the community string because it must match the SNMP trap community string, which is configured later in this document.

Figure 3 Credentials in **Device Setup > Communication**

The screenshot shows a configuration page for an Alcatel-Lucent device. The title bar is green and says "Alcatel-Lucent". Below it, there are several rows of configuration fields:

- Community String: [Redacted]
- Confirm Community String: [Redacted]
- Telnet/SSH Username: admin
- Telnet/SSH Password: [Redacted]
- Confirm Telnet/SSH Password: [Redacted]
- "enable" Password: [Redacted]
- Confirm "enable" Password: [Redacted]
- SNMPv3 Username: [Empty]
- Auth Password: [Empty]
- Confirm Auth Password: [Empty]
- SNMPv3 Auth Protocol: MDS (dropdown menu)
- Privacy Password: [Empty]
- Confirm Privacy Password: [Empty]
- SNMPv3 Privacy Protocol: DES (dropdown menu)

4. Enter the required fields for configuration and basic monitoring:
 - Telnet/SSH Username
 - Telnet/SSH Password
 - "enable" Password
5. Enter the required fields for WMS Offload:
 - SNMPv3 Auth Protocol
 - SNMPv3 Privacy Protocol
 - SNMPv3 Username
 - Auth Password
 - Privacy Password



The protocols should be SHA and DES in order for WMS Offload to work.

6. When finished, select **Save**.

Setting Up Recommended Timeout and Retries

To set recommended timeout and retries settings, follow these steps:

1. In the **Device Setup > Communication** page, locate the **SNMP Setting** section.
2. Change **SNMP Timeout** setting to a value of either **3**, **4**, or **5**. This is the number of seconds that the OV3600 will wait for a response from a device after sending an SNMP request, so a smaller number is more ideal.
3. Change **SNMP Retries** to **10**. This value represents the number of times OV3600 tries to poll a device when it does not receive a response within the SNMP Timeout Period or the Group's Missed SNMP Poll Threshold setting (1-100).



Although the upper limit for this value is 40, some SNMP libraries still have a hard limit of 20 retries. In these cases, any retry value that is set above 20 will still stop at 20.

Figure 4 Timeout settings in **Device Setup > Communication**

SNMP Settings	
SNMP Timeout (3-60 sec):	10
SNMP Retries (1-40):	3

4. Select **Save**.

Setting Up Time Synchronization

Setting up NTP on OV3600

On the **OV3600 Setup > Network** page, locate the **Network Time Protocol (NTP)** section. The Network Time Protocol is used to synchronize the time between OV3600 and your network reference NTP server. NTP servers synchronize with external reference time sources, such as satellites, radios, or modems.



Specifying NTP servers is optional. NTP servers synchronize the time on the OV3600 server, not on individual access points.

To disable NTP services, clear both the **Primary** and **Secondary** NTP server fields. Any problem related to communication between OV3600 and the NTP servers creates an entry in the event log. For more information on ensuring that OV3600 servers have the correct time, please see <http://support.ntp.org/bin/view/Servers/NTPPoolServers>.

Table 2 *OV3600 Setup > Network > Secondary Network Fields and Default Values*

Setting	Default	Description
Primary	ntp1.yourdomain.com	Sets the IP address or DNS name for the primary NTP server.
Secondary	ntp2.yourdomain.com	Sets the IP address or DNS name for the secondary NTP server.

You can set the clock on a controller manually or by configuring the controller to use a Network Time Protocol (NTP) server to synchronize its system clock with a central time source.

Manually Setting the Clock on a Controller

You can use either the WebUI or CLI to manually set the time on the controller's clock.

1. Navigate to the **Configuration > Management > Clock** page.
2. Under **Controller Date/Time**, set the date and time for the clock.
3. Under **Time Zone**, enter the name of the time zone and the offset from Greenwich Mean Time (GMT).
4. To adjust the clock for daylight savings time, click **Enabled** under Summer Time. Additional fields appear that allow you to set the offset from UTC, and the start and end recurrences.
5. Click **Apply**.

Enabling Support for Channel Utilization And Statistics

In order to enable support for channel utilization statistics, you must have the following:

- OV3600 7.2 or later

- AOS-W 6.0.1 or later



AOS-W 6.0.1 can report RF utilization metrics, while AOS-W 6.1 is necessary to also obtain classified interferer information.

- Access points - Alcatel-Lucent AP-105, AP-92, AP-93, AP-125, AP-124, AP-134, AP-135
- Controllers - Alcatel-Lucent 600 Series, 3000 Series, or 6000 Series

OV3600 Setup

Follow these steps in OV3600:

1. Navigate to **OV3600 Setup > General**.
2. In the **Additional OV3600 Services** section, set **Enable AMON Data Collection** to **Yes**, as shown in [Figure 5](#):

Figure 5 AMON Data Collection setting in **OV3600 Setup > General**

Additional OV3600 Services	
Enable FTP server: required to manage Cisco WLC APs; optional for FTP upgrades on supported devices.	<input type="radio"/> Yes <input checked="" type="radio"/> No
Enable RTLS collector: Aruba only	<input type="radio"/> Yes <input checked="" type="radio"/> No
Use embedded mail server:	<input checked="" type="radio"/> Yes <input type="radio"/> No
	<input type="button" value="Send Test Email"/>
Process user roaming traps from Cisco WLC:	<input checked="" type="radio"/> Yes <input type="radio"/> No
Enable AMON Data Collection:	<input checked="" type="radio"/> Yes <input type="radio"/> No

3. Select **Save**.

Controller Setup (Master And Local)



Enabling these commands on AOS-W versions prior to 6.0.1.0 can result in performance issues on the controller. If you are running previous firmware versions such as AOS-W 6.0.0.0, you should upgrade to AOS-W 6.0.1 (to obtain RF utilization metrics) or 6.1 (to obtain RF utilization *and* classified interferer information) before you enter this command.

Use SSH to access the switch's command-line interface, enter **enable** mode, and issue the following commands:

```
(Controller-Name) # configure terminal
Enter Configuration commands, one per line. End with CNTL/Z
(Controller-Name) (config) # mgmt-server type ov3600 primary-server <OV3600-IP>
(Controller-Name) (config) # write mem
```

It is prudent to establish one or more Alcatel-Lucent Groups within OV3600. During the discovery process you will move new discovered switches into this group.

This chapter contains the following topics:

- “Basic Monitoring Configuration” on page 9
- “Advanced Configuration” on page 10

Basic Monitoring Configuration

1. Navigate to **Groups > List**.
2. Select **Add**.
3. Enter a **Name** that represents the Alcatel-Lucent device infrastructure from a security, geographical, or departmental perspective and select **Add**.
4. You will be redirected to the **Groups > Basic** page for the Group you just created. On this page you will need to tweak a few Alcatel-Lucent-specific settings.
5. Find the **SNMP Polling Periods** section of the page, as illustrated in [Figure 6](#).
6. Change **Override Polling Period for Other Services** to **Yes**.
7. Ensure **User Data Polling Period** is set to 10 minutes. Do not configure this interval lower than 5 minutes.



Enabling the SNMP Rate Limiting for Monitored Devices option in the previous chapter adds a small delay between each SNMP Get request, thus the actual polling interval is 12 minutes for 10 minute polling interval.

8. Change **Device-to-Device Link Polling Period** to **30 minutes**.
9. Change **Rogue AP and Device Location Data Polling Period** to **30 minutes**.


Figure 6 SNMP Polling Periods section of **Groups > Basic**

SNMP Polling Periods	
Up/Down Status Polling Period:	5 minutes
Override Polling Period for Other Services:	<input checked="" type="radio"/> Yes <input type="radio"/> No
AP Interface Polling Period:	10 minutes
User Data Polling Period:	10 minutes
Thin AP Discovery Polling Period:	15 minutes
Device-to-Device Link Polling Period:	30 minutes
802.11 Counters Polling Period:	15 minutes
Rogue AP and Device Location Data Polling Period:	30 minutes
CDP Neighbor Data Polling Period:	30 minutes

10. Locate the **Alcatel-Lucent** section of this page, as illustrated in [Figure 7](#).

11. Configure the proper **SNMP Version** for monitoring the Alcatel-Lucent infrastructure.

Figure 7 Group SNMP Version for Monitoring



The screenshot shows a configuration window titled "Alcatel-Lucent". It contains three settings:

- SNMP Version:** A dropdown menu with "2c" selected.
- Offload WMS Database:** Radio buttons for "Yes" (selected) and "No".
- Alcatel-Lucent GUI Config:** Radio buttons for "Yes" (selected) and "No".

12. Select **Save and Apply**.

Advanced Configuration

Refer to the *OmniVista 3600 Air Manager 7.5 Configuration Guide* located at **Home > Documentation** for detailed instructions.

OV3600 utilizes Alcatel-Lucent's topology to efficiently discover downstream infrastructure. This chapter guides you through the process of discovering and managing your Alcatel-Lucent device infrastructure.

Refer to the following earlier chapters in this book before attempting discovery:

- Chapter 2, “Configuring OV3600 for Alcatel-Lucent Infrastructure” on page 5
- Chapter 3, “Configuring an Alcatel-Lucent Group in OV3600” on page 9

The following topics in this chapter walk through the basic procedure for discovering and managing Alcatel-Lucent Infrastructure:

- “Discovering Master Switches” on page 11
- “Local Switch Discovery” on page 13
- “Thin AP Discovery” on page 13



Always add one switch and its affiliated Thin APs into management or monitoring mode in a serial fashion, one at a time. Adding new devices is a very CPU intensive process for OV3600 and can quickly overwhelm all of the processing power of the server if hundreds of Thin APs are added (migrated from New to Managed or Monitoring) simultaneously.

Discovering Master Switches

Scan networks containing Alcatel-Lucent master switches from **Device Setup > Discover**.

- or -

Manually enter the master switch by following these steps in the **Device Setup > Add** page:

1. Select the **Alcatel-Lucent Switch** type and select **Add**. The page illustrated on [Figure 8](#) appears.
2. Enter the **Name** and the **IP Address** for the switch.
3. Enter **SNMP Community String**, which is required field for device discovery.



Be sure to note the community string because it must match the SNMP trap community string, which is configured later in this document.

Figure 8 Alcatel-Lucent Credentials in **Device Setup > Add**

Configure default credentials on the [Communication](#) page.

Device Communications	
Name:	<input type="text"/>
Leave name blank to read it from device	
IP Address:	<input type="text"/>
SNMP Port:	<input type="text" value="161"/>
Community String:	<input type="password" value="....."/>
Confirm Community String:	<input type="password" value="....."/>
SNMPv3 Username:	<input type="text"/>
Auth Password:	<input type="password"/>
Confirm Auth Password:	<input type="password"/>
SNMPv3 Auth Protocol:	<input type="text" value="MD5"/>
Privacy Password:	<input type="password"/>
Confirm Privacy Password:	<input type="password"/>
SNMPv3 Privacy Protocol:	<input type="text" value="DES"/>
Telnet/SSH Username:	<input type="text" value="admin"/>
Telnet/SSH Password:	<input type="password" value="....."/>
Confirm Telnet/SSH Password:	<input type="password" value="....."/>
"enable" Password:	<input type="password" value="....."/>
Confirm "enable" Password:	<input type="password" value="....."/>

Location	
Group:	<input type="text" value="East"/>
Folder:	<input type="text" value="Top"/>

Monitor Only (no changes will be made to device)
 Manage read/write (group settings will be applied to device)

4. Enter the required fields for configuration and basic monitoring:
 - Telnet/SSH Username
 - Telnet/SSH password
 - "enable" password
5. Enter the required fields for WMS Offload
 - SNMPv3 Auth Protocol
 - SNMPv3 Privacy Protocol
 - SNMPv3 Username
 - Auth Password
 - Privacy Password



The protocols should be SHA and DES in order for WMS Offload to work.



Caution: If you are using SNMPv3 and the switch's date/time is incorrect, the SNMP agent will not respond to SNMP requests from OV3600 SNMP manager. This will result in the switch and all of its downstream access points showing as Down in OV3600.

6. Assign switch to a Group and Folder.
7. Ensure **Monitor Only** option is selected.
8. Select **Add**.
9. Navigate to **APs/Devices > New** page.
10. Select the Alcatel-Lucent master switch you just added from the list of new devices.
11. Ensure **Monitor Only** option is selected.
12. Select **Add**.

Local Switch Discovery

Local switches are added to OV3600 via the master switch, by a discovery scan, or manually added in **Device Setup > Add**. After waiting for the Thin AP Polling Period interval or executing a Poll Now command from the **APs/Devices > Monitor** page, the local switches will appear on the **APs/Devices > New** page.

Add the local switch to the Group defined previously. Within OV3600, local switches can be split away from the master switch's Group.



Local Switch Discovery/monitoring may not work as expected if OV3600 is unable to communicate directly with the target device. Be sure and update any ACL/Firewall rules to allow OV3600 to communicate with your network equipment.

Thin AP Discovery

Thin APs are discovered via the local switch. After waiting for the Thin AP Polling Period or executing a Poll Now command from the **APs/Devices > Monitor** page, thin APs will appear on the **APs/Devices > New** page.

Add the thin APs to the Group defined previously. Within OV3600, thin APs can be split away from the switch's Group. You can split thin APs into multiple Groups if required.

This chapter describes strategies for integrating OV3600 and Alcatel-Lucent devices and contains the following topics:

- “Integration Goals” on page 15
- “Example Use Cases” on page 16
- “Prerequisites for Integration” on page 17
- “Enable Stats Utilizing OV3600” on page 17
- “WMS Offload with OV3600” on page 18
- “Define OV3600 as a Trap Host using AOS-W CLI” on page 18
- “Understanding WMS Offload Impact on Alcatel-Lucent Infrastructure” on page 21

Integration Goals

The following table summarizes the types of integration goals and strategies for meeting them in certain architectural contexts:

Table 3 *Integration Goals in All Masters or Master/Local Architectures*

Integration Goals	All Masters Architecture	Master/Local Architecture
Rogue And Client Info		enable stats
Rogue containment only	ssh access to controllers	ssh access to controllers
Rogue And Client containment	WMS Offload	WMS Offload
Reduce Master Switch Load		WMS Offload debugging off
IDS And Auth Tracking	Define OV3600 as trap host	Define OV3600 as trap host
Track Tag Location	enable RTLS WMS Offload	enable RTLS WMS Offload
Channel Utilization	enable AMON	enable AMON
Spectrum	enable AMON	enable AMON

Key integration points to consider include the following:

- IDS Tracking does not require WMS Offload in an all-master or master/local environment.
- IDS Tracking does require enable stats in a master/local environment.
- WMS Offload will hide the Security Summary tab on master switch’s web interface.
- WMS Offload encompasses enable stats or enable stats is a subset of WMS Offload.
- Unless you enable stats on the local switches in a master/local environment, the local switches do not populate their MIBs with any information about clients or rogue devices discovered/associated with their APs. Instead the information is sent upstream to master switch.

Example Use Cases

The following are example use cases of integration strategies:

When to Use Enable Stats

You want to pilot AMWS and doesn't want to make major configuration changes to their infrastructure or manage configuration from OV3600.



Enable Stats still pushes a small subset of commands to the switches via SSH.

See [“Enable Stats Utilizing OV3600”](#) on page 17.

When to Use WMS Offload

- You have older Alcatel-Lucent infrastructure in a master/local environment and their master switch is fully taxed. Offloading WMS will increase the capacity of the master switch by offloading statistic gathering requirements and device classification coordination to OV3600.
- You want to use OV3600 to distribute client and rogue device classification amongst multiple master switches in a master/local environment or in an All-Masters environment.
- See the following topics:
 - [“WMS Offload with OV3600”](#) on page 18
 - [“Understanding WMS Offload Impact on Alcatel-Lucent Infrastructure”](#) on page 21
 - [“WMS Offload Details”](#) on page 37

When to Use RTLS

- A hospital wants to achieve very precise location accuracy (5 -15 feet) for their medical devices which are associating to the WLAN.
- You want to locate items utilizing WiFi Tags.



RTLS could negatively impact your OV3600 server's performance.

- See [“Leveraging RTLS to Increase Accuracy”](#) on page 39.

When to Define OV3600 as a Trap Host

- You want to track IDS events within the OV3600 UI.
- You are in the process of converting their older third-party WLAN devices to Alcatel-Lucent devices and want a unified IDS dashboard for all WLAN infrastructure.
- You want to relate Auth failures to a client device, AP, Group of APs, and switch. OV3600 provides this unique correlation capability.
- See [“Define OV3600 as a Trap Host using AOS-W CLI”](#) on page 18.

When to use Channel Utilization

- You have a minimum version of AOS-W 6.1.0.0 and AP-105 or AP-135.

Prerequisites for Integration

If you have not discovered the Alcatel-Lucent infrastructure or configured credentials, refer to the previous chapters of this book:


- Chapter 2, “Configuring OV3600 for Alcatel-Lucent Infrastructure” on page 5
- Chapter 3, “Configuring an Alcatel-Lucent Group in OV3600” on page 9
- Chapter 4, “” on page 11

Enable Stats Utilizing OV3600

To enable stats on the Alcatel-Lucent switches, follow these steps:

1. Navigate to **OV3600 Setup > General** and locate the **Device Configuration** section.
2. Set the **Allow WMS Offload Configuration in Monitor-Only Mode** field to **Yes**, as shown in [Figure 9](#):


Figure 9 WMS Offload Configuration in **OV3600 Setup > General**



The screenshot shows the 'Device Configuration' section. The 'Allow WMS offload configuration in monitor-only mode' field is highlighted with a red box and has the 'Yes' radio button selected. Other fields include 'Guest User Configuration' set to 'Enabled for devices in Ma' and 'SNMP Version' set to '2c'.

3. Navigate to **Groups > Basic** for the group that contains your Alcatel-Lucent switches.
4. Locate the **Alcatel-Lucent** section on the page.
5. Set the **Offload WMS Database** field to **No**, as shown in [Figure 10](#):

Figure 10 Offload WMS Database field in **Groups > Basic**



The screenshot shows the 'Alcatel-Lucent' section. The 'Offload WMS Database' field has the 'No' radio button selected. Other fields include 'SNMP Version' set to '2c' and 'Alcatel-Lucent GUI Config' set to 'Yes'.

6. Select **Save and Apply**.
7. Select **Save**.

This will push a set of commands via SSH to all Alcatel-Lucent local switches. OV3600 must have read/write access to the switches in order to push these commands.



This process will not reboot your switches.



If you don't follow the above steps, local switches will not be configured to populate statistics. This decreases OV3600's capability to trend client signal information and to properly locate devices. See [Appendix A, “AOS-W and OV3600 CLI Commands” on page 31](#) on how to utilize the AOS-W CLI to enable stats on Alcatel-Lucent infrastructure.

If your credentials are invalid or the changes are not applied to the switch, error messages will display on the switch's **APs/Devices > Monitor** page under the **Recent Events** section. If the change fails, OV3600 does not audit these setting (display mismatches) and you will need to apply to the switch by hand. See [Appendix A, “AOS-W and OV3600 CLI Commands” on page 31](#) for detailed instructions.

These are the commands pushed by OV3600 while enabling WMS Offload (do not enter these commands):

```
configure terminal
no mobility-manager <Active WMS IP Address>
wms
general collect-stats enable
stats-update-interval 120
show wms general
write mem
```

WMS Offload with OV3600

To offload WMS on the Alcatel-Lucent switches using OV3600:

1. In **OV3600 Setup > General**, locate the **Device Configuration** section and enable or disable **Allow WMS Offload Configuration in Monitor-Only Mode**.
2. Select **Save and Apply**. This will push a set of commands via SSH to all Alcatel-Lucent master switches. If the switch does not have an SNMPv3 user that matches the OV3600 database it will automatically create a new SNMPv3 user. OV3600 must have read/write access to the switches in order to push these commands
3. Navigate to **Groups > Basic** and locate the **Alcatel-Lucent** section.
4. Set the **Offload WMS Database** field to **Yes**, as shown in [Figure 10](#).



This process will not reboot your switches. See [Appendix A, “AOS-W and OV3600 CLI Commands”](#) on page 31 on how to utilize the AOS-W CLI to enable stats or WMS Offload.



The SNMPv3 user's Auth Password and Privacy Password must be the same.

Do not enter these commands; these are pushed by OV3600 while enabling WMS Offload.

```
configure terminal
mobility-manager <OV3600 IP> user <OV3600 SNMPv3 User Name> <OV3600 Auth/Priv PW>
stats-update-interval 120
write mem
```



OV3600 will configure SNMPv2 traps with the **mobile manager** command.

Define OV3600 as a Trap Host using AOS-W CLI

To ensure the OV3600 server is defined a trap host, access the command line interface of each switch (master and local), enter “enable” mode, and issue the following commands:

```
(Switch-Name) # configure terminal
Enter Configuration commands, one per line. End with CNTL/Z

(Switch-Name) (config) # snmp-server host <OV3600 IP ADDR> version 2c <SNMP Community
String of Switch>
```



Ensure the SNMP community matches those that were configured in [Chapter 2, “Configuring OV3600 for Alcatel-Lucent Infrastructure”](#).

```
(Switch-Name) (config) # snmp-server trap source <Switch-IP>  
(Switch-Name) (config) # write mem
```



OV3600 supports SNMP v2 traps and SNMP v3 informs in AOS-W 3.4 and higher. SNMP v3 traps are not supported.

AOS-W Traps Utilized by OV3600.

The following are Auth, IDS, and ARM traps utilized by OV3600:

- “Auth Traps” on page 19
- “IDS Traps” on page 19
- “ARM Traps” on page 20

Auth Traps

- wlsxNUserAuthenticationFailed
- wlsxNAuthServerReqTimedOut

IDS Traps

- wlsxwlsxSignatureMatchAP
- wlsxSignatureMatchSta
- wlsxSignAPNetstumbler
- wlsxSignStaNetstumbler
- wlsxSignAPAsleap
- wlsxSignStaAsleap
- wlsxSignAPAirjack
- wlsxSignStaAirjack
- wlsxSignAPNullProbeResp
- wlsxSignStaNullProbeResp
- wlsxSignAPDeauthBcast
- wlsxSignStaDeauthBcastwlsxChannelFrameErrorRateExceeded
- wlsxChannelFrameFragmentationRateExceeded
- wlsxChannelFrameRetryRateExceeded
- wlsxNIpSpoofingDetected
- wlsxStaImpersonation
- wlsxReservedChannelViolation
- wlsxValidSSIDViolation
- wlsxStaPolicyViolation
- wlsxRepeatWEPIVViolation
- wlsxWeakWEPIVViolation
- wlsxFrameRetryRateExceeded
- wlsxFrameReceiveErrorRateExceeded
- wlsxFrameFragmentationRateExceeded
- wlsxFrameBandWidthRateExceeded
- wlsxFrameLowSpeedRateExceeded
- wlsxFrameNonUnicastRateExceeded

- wlsxChannelRateAnomaly
- wlsxNodeRateAnomalyAP
- wlsxNodeRateAnomalySta
- wlsxEAPRateAnomaly
- wlsxSignalAnomaly
- wlsxSequenceNumberAnomalyAP
- wlsxSequenceNumberAnomalySta
- wlsxApFloodAttack
- wlsxInvalidMacOUIAP
- wlsxInvalidMacOUISta
- wlsxStaRepeatWEPIVViolation
- wlsxStaWeakWEPIVViolation
- wlsxStaAssociatedToUnsecureAP
- wlsxStaUnAssociatedFromUnsecureAP
- wlsxAPImpersonation
- wlsxDisconnectStationAttackAP
- wlsxDisconnectStationAttackSta

ARM Traps

- AP Power Change
- AP Mode Change
- AP Channel Change

Ensuring That IDS And Auth Traps Display in OV3600

Validate your AOS-W configuration by exiting the configure terminal mode and issue the following command:

```
(Switch-Name) # show snmp trap-list
```

If any of the traps in the output of this command do not appear to be enabled enter `configure terminal` mode and issue the following command:

```
(Switch-Name) (config) # snmp-server trap enable <TRAPS FROM LIST ABOVE>
(Switch-Name) (config) # write mem
```



See Appendix A, “AOS-W and OV3600 CLI Commands” on page 31 for the full command that can be copied and pasted directly into the AOS-W CLI.

Ensure the source IP of the traps match the IP that OV3600 utilizes to manage the switch, as shown in Figure 11. Navigate to **APs/Devices > Monitor** to validate the IP address in the **Device Info** section.

Figure 11 Verify IP Address on **APs/Devices > Monitor** Page

Status: Up (OK)						
Configuration: Mismatched (The settings on the device do not match the desired configuration policy.)						
Firmware:	3.3.2.11	Licenses:	3 Expired			
Controller Role:	Local	VRRP IP:	10.1.1.242			
Type:	Aruba 3600	Last Contacted:	6/1/2009 1:50 PM	Uptime:	46 days 18 hrs 31 mins	
LAN MAC Address:	90:08:86:61:12:40	Serial:	AC0000303	Location:	1344 Server Room	
IP Address:	10.1.1.242	SSID:	-	Total APs:	266	
Notes:						
Contact:	Aruba IT		Total Users:	62	Bandwidth:	2435 kbps

Verify that there is a SNMPv2 community string that matches the SNMP Trap community string on the switch.

```
(Switch-Name) # show snmp community
SNMP COMMUNITIES
-----
COMMUNITY ACCESS      VERSION
-----
public      READ_ONLY V1, V2c
```

```
(Switch-Name) # #show snmp trap-host
```

```
SNMP TRAP HOSTS
-----
HOST          VERSION      SECURITY NAME PORT   TYPE TIMEOUT RETRY
-----
10.2.32.4     SNMPv2c     public          162   Trap N/A     N/A
```

Verify that firewall port **162** (default) is **open** between OV3600 and the switch.

Validate that traps are making it into OV3600 by issuing the following commands from OV3600 command line.

```
[root@OV3600 ~]# qlog enable snmp_traps
```

```
[root@OV3600 ~]# tail -f /var/log/ov3600_diag/snmp_traps
```

```
1241627740.392536 handle_trap|2009-05-06 09:35:40 UDP: [10.2.32.65]->[10.51.5.118]:-
32737 sends trap: DISMAN-EVENT-MIB::sysUpTimeInstance = Timeticks: (127227800) 14 days,
17:24:38.00 SNMPv2-MIB::snmpTrapOID.0 = OID: SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.2.1106 SNMPv2-SMI::enterprises.14823.2.3.1.11.1.1.60
= Hex-STRING: 07 D9 05 06 09 16 0F 00 2D 08 00      SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.5.0 = Hex-STRING: 00 1A 1E 6F 82 D0 SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.6.0 = STRING: Alcatel-Lucent-apSNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.1.0 = Hex-STRING: 00 1A 1E C0 2B 32 SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.56.0 = INTEGER: 2      SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.17.0 = STRING: Alcatel-Lucent-124-c0:2b:32 SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.18.0 = INTEGER: 11     SNMPv2-
SMI::enterprises.14823.2.3.1.11.1.1.58.0 = STRING: http://10.51.5.118/screens/wmsi/
reports.html?mode=ap&bssid=00:1a:1e:6f:82:d0
```



You will see many IDS and Auth Traps from this command. OV3600 only processes a small subset of these traps which display within OV3600. The traps that OV3600 does process are listed above.

Ensure you disable qlogging after testing as it could negatively impact OV3600 performance if left turned on:

```
[root@OV3600 ~]# qlog enable snmp_traps
```

Understanding WMS Offload Impact on Alcatel-Lucent Infrastructure


When offloading WMS, it is important to understand what functionality is migrated to OV3600 and what functionality is deprecated.

The following AOS-W tabs and sections are deprecated after offloading WMS:

- **Plan** - The tab where floor plans are stored and heatmaps are generated. Prior to offloading WMS, ensure that you have exported floor plans from AOS-W and imported them into OV3600. All functionality within the Plan Tab is incorporated with the VisualRF module in OV3600.

- **Dashboard>Security Summary** - The **Security Summary** section (Figure 12) disappears after offloading WMS. The data is still being processed by the master switch, but the summary information is not available. You must use OV3600 to view data for APs, clients and events in detail and summary from.
 - OV3600 displays information on Rogue APs in the **RAPIDS > Overview** pages.
 - Information on Suspected Rogue, Interfering and known interfering APs is available in OV3600 on each **APs/Devices > Manage** page.
 - IDS events data and reports appear on OV3600's **Reports > Generated > IDS Events** page.

Figure 12 Security Summary on Master Switch



See “Rogue Device Classification” on page 27 for more information on security, IDS, WIPS, WIDS, classification, and RAPIDS.

This chapter discusses Alcatel-Lucent-specific capabilities in OV3600, and contains the following topics:

- “Alcatel-Lucent Traps for RADIUS Auth And IDS Tracking” on page 23
- “Remote AP Monitoring” on page 24
- “ARM And Channel Utilization Information” on page 24
- “Viewing Switch License Information” on page 26
- “Rogue Device Classification” on page 27
- “Rules-Based Switch Classification” on page 29

Alcatel-Lucent Traps for RADIUS Auth And IDS Tracking

The authentication failure traps are received by the OV3600 server and correlated to the proper switch, AP, and user. See Figure 13 showing all authentication failures related to a switch.

Figure 13 RADIUS Authentication Traps in OV3600

RADIUS Authentication Issues for HQ-Aruba-Controller in group Acme Corporation in folder Top > Acme Corporation > Corporate HQ | [Return to AP/Device Monitor page](#)

Event Type ▲	Last 2 Hours	Last 24 Hours	Total
Client authentication failed	0	4	1103

1-20 of 1103 RADIUS Authentication Issues Page 1 of 56 > >|

Event	Username	User MAC Address	AP	Radio	RADIUS Server	Time ▼
<input type="checkbox"/> Client authentication failed for 00:0B:7D:0C:19:E9	-	00:0B:7D:0C:19:E9	-	-	-	4/2/2008 5:24 PM
<input type="checkbox"/> Client authentication failed for 00:17:3F:20:99:6B	-	00:17:3F:20:99:6B	-	-	-	4/2/2008 4:21 PM

The IDS traps are received by the OV3600 server and correlated to the proper switch, AP, and user. See Figure 14 showing all IDS traps related to a switch.

Figure 14 IDS Traps in OV3600

IDS Events for HQ-Aruba-Controller in group Acme Corporation in folder Top > Acme Corporation > Corporate HQ | [Return to AP/Device Monitor page](#)

Attack ▲	Last 2 Hours	Last 24 Hours	Total
Death-Broadcast	0	0	47
Netstumbler Generic	13	122	1756
Null-Probe-Response	22	263	2776
3 Attack Types	35	385	4579

1-20 ▼ of 4579 IDS Events Page 1 ▼ of 229 > >|


Attack	Attacker	AP	Radio	Channel	SNR	Precedence	Time ▼
<input type="checkbox"/> Null-Probe-Response	00:20:A6:49:92:AE	HQ-Aruba-Boardroom	802.11a	-	13	-	7/17/2008 1:58 PM
<input type="checkbox"/> Null-Probe-Response	00:0D:97:00:81:6A	HQ-Northeast-Corner-b6b6	802.11bg	-	23	-	7/17/2008 1:56 PM
<input type="checkbox"/> Null-Probe-Response	00:20:A6:49:92:AE	HQ-Southwest-Corner-eb3e	802.11a	-	39	-	7/17/2008 1:41 PM

Remote AP Monitoring

To monitor remote APs, follow these steps:

1. From the **APs/Devices > List** page, filter on the **Remote Device** column to find remote devices.
2. To view detailed information on the remote device, select the device name. The page illustrated in [Figure 15](#) appears.

Figure 15 Remote AP Detail Page



3. You can also see if there are users plugged into the wired interfaces in the Connected Users list.




This feature is only available when the remote APs are in split tunnel and tunnel modes.

ARM And Channel Utilization Information

ARM statistics And Channel utilization are very powerful tools for diagnosing capacity and other issues in your WLAN.

1. Navigate to an **APs/Devices > Monitor** page for any of the following Alcatel-Lucent models: AP-105, AP-92, AP-93, AP-124, AP-125, or AP-135.
2. In the **Radios** table, select a radio link under the **Name** column for a radio.

Figure 16 ARM and Channel Utilization Graphs




See the *OmniVista 3600 Air Manager 7.5 User Guide* in **Home > Documentation** for more information on the data displayed in the **Radio Statistics** page for these devices.

VisualRF and Channel Utilization

To view how channel utilization is impacting an area within a building, follow these steps:

1. Navigate to a floor plan by clicking on the thumbnail on a device's **APs/Devices > Monitor** page or navigating to **VisualRF > Floor Plans** page.
2. Select the **Overlays** menu.
3. Select **Utilization** overlay.
4. Select **Current** or **Maximum** (over last 24 hours).
5. Select total (default), receive, transmit, or interference (see [Figure 17](#)).

Figure 17 Channel Utilization in VisualRF (Interference)



Configuring Channel Utilization Triggers

1. Navigate to **System > Triggers** and select **Add**.
2. Select **Channel Utilization** from the **Type** drop-down menu as seen on [Figure 18](#):

Figure 18 Channel Utilization Trigger

3. Enter the duration evaluation period.
4. Select **Add New Trigger Condition**.
5. Create a trigger condition for **Radio Type** and select the frequency to evaluate.
6. Select total, receive, transmit, or interference trigger condition.
7. Set up any restrictions or notifications (refer to the *OmniVista 3600 Air Manager 7.5 User Guide* in **Home > Documentation** for more details)
8. When finished, select **Add**.

Viewing Channel Utilization Alerts

1. Navigate to **APs/Devices > Monitor** or **System > Alerts**.
2. Sort the **Trigger Type** column and find **Channel Utilization** alerts.

View Channel Utilization in RF Health Reports

1. Navigate to **Reports > Generated**.
2. Find and select a Device Summary or RF Health report.

Figure 19 Channel Utilization in an RF Health Report

Most Utilized by Channel Usage (2.4 GHz)

Rank ▲	Device	Channel Busy (%)	Interference (%)	Number of Users	Bandwidth (bps)	Location	Controller
1	AP0018.19bd.b1d0	85.43	83.86	0	14.00	ap lab	wlc 5500
2	AP001d.a1fc.ca7a	85.04	83.86	0	32.00	default location	wlc 5500
3	Cisco-13:21:1E	67.72	59.45	0	4.00	default location	wlc 5500
4	AP10	64.57	63.39	0	24.00	Sales Office-helloX	Cisco4400

Viewing Switch License Information

Follow these steps to view your switch's license information in OV3600:

1. Navigate to the **APs/Devices > Monitor** page of a switch under OV3600 management.
2. Select the **License** link in the **Device Info** section. A pop-up window appears listing all licenses.

Figure 20 License Popup from **APs/Devices > Monitor**

132: Oak Grove Guest Iss

License Table for alpha-local-1:

Service Type ▲	Installed	Expires	Flag	Key
Client Integrity Module	4/29/2005 12:36 PM		E	n9XQpMZN-kUMfht6z-j98lcV0J-TS1kt4In-xA2LFT0-v58
External Services Interface	4/29/2005 12:35 PM		E	PIF8Dr8V-nBxIkp75-+Z8TT2NS-aj4oa8/h-vVm+Cx86-zVU
External Services Interface	4/29/2005 12:34 PM		E	OMsNveDX-W3wEHSKx-TpXkQbHV-NyTb3HAN-OYA2zNY-V
Indoor Mesh Access Points: 256	10/19/2007 6:54 PM		E	lkWFlaJR-6y8p6rm+-CzOUh7tl-bMhkMA1v-1DV+2m+H-kZE
MMC AP	10/19/2007 6:54 PM		E	VP6JN8IS-y4AoaG9p-P2r7wVTK-/PXV3JgR-C0fj3d4-LLk
Ortronics Access Points: 256	10/19/2007 6:54 PM		E	+jl6oDRK-PIRXv5nF-1DMwrdJ-oES1ydXR-4K7sFEHQ-SmJ
Outdoor Mesh Access Points: 100	5/2/2007 2:51 PM	Expired		99CS0vuL-jL4Z0YkS-Q8lov2bI-BS+Y0Vxi-YkC9TT0V-5js
Outdoor Mesh Access Points: 256	10/19/2007 6:54 PM		E	RKC/wjVj-fcRQGLdI-K/F8vurv-oYRwgCuG-CsmY7wYh-w18
Outdoor Mesh Access Points: 64	8/1/2007 3:59 PM		E	C5I/bSFb-yV0xff0h-BWWUVEVe-Gib2xz4A-LKcq440D-IXQ
Policy Enforcement Firewall	4/29/2005 12:30 PM		E	vDXRo7pz-Jo8asgU2-HG7w74l+-zzl3yGKu-z7w3rj+-/1I
Remote Access Points: 256	10/19/2007 6:54 PM		E	QnR882W+-o1Kb2XcR-2vrePyl+-J++rWbxh-jtCajH3h-LPU
Remote Access Points: 48	4/29/2005 12:38 PM		E	5zz7ctjO-LpDgDbLH-4bEnzNbg-p/oEnS2a-nTtHaS8t-ms0
Voice Services Module	10/19/2007 6:54 PM		E	Lj/ByOfs-wMdJU3Xv-5djAkCD-vJ9zRok3-sWZ4Z2bn-ah4
VPN Server	4/29/2005 12:32 PM		E	SOKR1Sa8-KKMij/Gv-HlCJcwaK-uEZU Pvcs-c/Lizjg0-2IE
Wireless Intrusion Protection	4/29/2005 12:33 PM		E	xVc/lqw-Os1ei+yL-b1CqzoTr-UwGp2OAI-LD6wHOW2-gSw
xSec Module	4/29/2005 12:37 PM		E	ukUwAcB-PE+GeyB9-7u7IMTQ1-CaibELI2-LuqdRsqA-fac

Rogue Device Classification

Only complete this section if you have completed WMS Offload procedure above. After offloading WMS, OV3600 maintains the primary ARM, WIPS, and WIDS state classification for all devices discovered over-the-air.

Table 4 WIPS/WIDS to OV3600 Switch Classification Matrix

OV3600 Switch Classification	AOS-W (WIPS/WIDS)
Unclassified (default state)	Unknown
Valid	Valid
Suspected Neighbor	Interfering
Neighbor	Known Interfering
Suspected Rogue	Suspected Rogue
Rogue	Rogue
Contained Rogue	DOS

To check and reclassify rogue devices, follow these steps:

1. Navigate to the **Rogue > Detail** page for the rogue device, as shown in [Figure 21](#).

Figure 21 Rogue Detail Page Illustration

Name:	Aruba-83:43:01	Model:	-
Acknowledge:	<input type="radio"/> Yes <input checked="" type="radio"/> No	IP Address:	-
Controller Classification:	Suspected Neighbor	Confidence:	0
WMS Classification Override:	Undclassified	First Discovery Agent:	00:24:6c:c8:6e:e7
SSID:	qa-dp-vw-c3-2	Channel:	149
RAPIDS Classification:	Unclassified	WEP:	No
Classification Rule:	-	WPA:	Yes
RAPIDS Classification Override:	- No Override -	Network Type:	AP
Threat Level:	- No Override -		
Threat Level Override:	Valid		
Radio MAC Address:	Suspected Valid		
Radio Vendor:	Neighbor		
LAN MAC Address:	Suspected Neighbor		
LAN Vendor:	Suspected Rogue		
OUI Score:	Rogue		

2. Select the proper classification from the **RAPIDS Classification Override** drop-down menu.



Caution: Changing the switch's classification within the OV3600 UI will push a reclassification message to all switches managed by the OV3600 server that are in Groups with Offloading the WMS database set to Yes. To reset the switch classification of a rogue device on OV3600, change the switch classification on the OV3600 UI to unclassified.

Switch classification can also be updated from **RAPIDS > List** via the **Modify Devices** link.

All rogue devices will be set to a default switch classification of unclassified when WMS is first offloaded except for devices classified as valid. Rogue devices classified in AOS-W as valid will also be classified within OV3600 as valid for their switch classification as well. As APs report subsequent classification information about rogues, this classification will be reflected within OV3600 UI and propagated to switches that OV3600 manages. The device classification reflected in the switch's UI and in the OV3600 UI will probably not match, because the switch/APs do not reclassify rogue devices frequently.

To update a group of devices' switch classification to match the AOS-W device classification, navigate to **RAPIDS > List** and utilize the **Modify Devices** checkbox combined with the multiple sorting a filtering features.

Table 5 ARM to OV3600 Classification Matrix

OV3600	AOS-W (ARM)
Unclassified (default state)	Unknown
Valid	Valid
Contained	DOS

1. Navigate to the **Users > User Detail** page for the user.
2. Select the proper classification from the **Classification** drop-down menu as seen in [Figure 22](#):

Figure 22 User Classification

Device Information	
Username:	madisonl
Vendor:	Apple
First Seen:	1/8/2009 10:29 AM on <Deleted> for 50 mins
Last Seen:	4/11/2011 1:22 PM on 78C for 5 hrs 25 mins
Classification:	<div style="border: 1px solid gray; padding: 2px;"> Unclassified Valid Unclassified Contained </div>
Automatically populate device information:	<input type="checkbox"/>
Device Description:	



Caution: Changing User Classification within the OV3600 UI will push a user reclassification message to all switches managed by the OV3600 server that are in Groups with Offloading the WMS database set to Yes.

All users will be set to a default classification of unclassified when wms is first offloaded. As APs report subsequent classification information about users, this classification will be reflected within OV3600 UI and propagated to switches that OV3600 manages. It is probable that the user's classification reflected in the switch's UI and in the OV3600 UI will not match, because the switch/APs do not reclassify users frequently.

There is no method in the OV3600 UI to update user classification on mass to match the switch's classification. Each client must be updated individually within the OV3600 UI.


Rules-Based Switch Classification

Using RAPIDS Defaults for Switch Classification

To use the switch's classification as RAPIDS classification, follow these steps:

1. Navigate to **RAPIDS > Rules** and select the pencil icon for a rule.
2. In the **Classification** drop-down menu, select **Use Controllers Classification** as seen in [Figure 23](#).
3. Select **Save**.


Figure 23 Using Switch Classification



Changing RAPIDS based on Controller Classification

1. Navigate to **RAPIDS > Rules**.
2. In the **Classification** drop-down menu, select desired RAPIDS classification.
3. Select **Controller Classification** from drop-down menu, as shown in [Figure 24](#).

Figure 24 Configure Rules for Classification



4. Select **Add**.
5. Select desired controller classification to use as an evaluation in RAPIDS.
6. Select **Save**.

Enable Channel Utilization Events



CAUTION

Caution: Enabling these commands on AOS-W versions prior to 6.1 can result in performance issues on the switch.

To enable channel utilization events utilizing the AOS-W CLI, use SSH to access a local or master switch's command-line interface, enter **enable** mode, and issue the following commands:

```
(Switch-Name) # configure terminal
Enter Configuration commands, one per line. End with CNTL/Z

(Switch-Name) (config) # mgmt-server type ov3600 primary-server <OV3600 IP>
(Switch-Name) (config) # write mem
```

Enable Stats With the AOS-W CLI

The following commands enable collection of statistics (up to 25,000 entries) on the master switch for monitored APs and clients.



NOTE

Do not use these commands if you use the OV3600 GUI to monitor APs and Clients. Enabling these commands on AOS-W versions prior to 6.1 can result in performance issues on the switch.

Use SSH to access the master switch's command-line interface, enter **enable** mode, and issue the following commands:

```
(Switch-Name) # configure terminal
Enter Configuration commands, one per line. End with CNTL/Z

(Switch-Name) (config) # wms general collect-stats enable
(Switch-Name) (config) # write mem
```

Offload WMS Using the AOS-W or OV3600 CLI



NOTE

Do not use these commands if you use the OV3600 GUI to monitor APs and clients.

Use the following commands to offload WMS using the AOS-W command-line interface or the OV3600 SNMP Walk.

AOS-W CLI

SSH into all switches (local and master), and enter "enable" mode, and issue the following commands:

```
(Switch-Name) # configure terminal
Enter Configuration commands, one per line. End with CNTL/Z
(Switch-Name) (config) # mobility-manager <OV3600 IP> user <MMS-USER> <MMS-SNMP-
PASSWORD> trap-version 2c
```

```
(Switch-Name) (config) # write mem
```

This command creates the OV3600 server as an SNMPv3 Trap Host in the switch's running configuration. This command also creates an SNMPv3 user on the switch with authentication protocol configured to **SHA** and privacy protocol **DES**. The user and password must be at least eight characters, because the Net-SNMP package in OV3600 adheres to this IETF recommendation. AOS-W automatically creates Auth and Privacy passwords from this single password. If mobility-manager is already using a preconfigured SNMPv3 user, ensure the privacy and authentication passwords are the same.

Example:

```
mobility-manager 10.2.32.1 user ov3600123 ov3600123
```

OV3600 SNMP

Log in into the OV3600 server with proper administrative access and issue the following command for all switches (master and locals):

```
[root@OV3600 ~]# snmpwalk -v3 -a SHA -l AuthPriv -u <MMS-USER> -A <MMS-SNMP-PASSWORD> -X <MMS-SNMP-PASSWORD> <Switch-IP> wlsxSystemExtGroup
```

```
WLSX-SYSTEMEXT-MIB::wlsxSysExtSwitchIp.0 = IPAddress: 10.51.5.222
WLSX-SYSTEMEXT-MIB::wlsxSysExtHostname.0 = STRING: Alcatel-Lucent-3600-2
.
..
WLSX-SYSTEMEXT-MIB::wlsxSysExtSwitchLastReload.0 = STRING: User reboot.
WLSX-SYSTEMEXT-MIB::wlsxSysExtLastStatsReset.0 = Timeticks: (0) 0:00:00.00 response
[root@OV3600 ~]#
```

Unless this SNMP walk command is issued properly on all of the switches, they will not properly populate client and rogue statistics. Ensure the user and passwords match exactly to those entered in above sections.

Example:

```
snmpwalk -v3 -a SHA -l AuthPriv -u airwave123 -A ov3600123 -X ov3600123 10.51.3.222 wlsxSystemExtGroup
```

If you do not use the OV3600 WebUI to offload WMS, you must add a cronjob on the OV3600 server to ensure continued statistical population. Because the MIB walk/touch does not persist through a switch reboot, a cronjob is required to continually walk and touch the MIB.

Pushing Configs from Master to Local Switches

Use the following AOS-W CLI commands to ensure that the master switch is properly pushing configuration settings from the master switch to local switches. This command ensures configuration changes made on the master switch will propagate to all local switches.



Do not use these commands if you use the OV3600 GUI to monitor APs and clients.

```
(Switch-Name) (config) # cfgm mms config disable
(Switch-Name) (config) # write mem
```

Disable Debugging Utilizing AOS-W CLI

If you are experiencing performance issues on the master switch, ensure that debugging is disabled. It should be disabled by default. Debugging coupled with gathering the enhanced statistics can put a strain on the switches CPU, so it is highly recommended to disable debugging.

To disable debugging, SSH into the switch, enter “enable” mode, and issue the following commands:

```
(Switch-Name) # show running-config | include logging level debugging
```

If there is output, then use the following commands to remove the debugging:

```
(Switch-Name) # configure terminal
```

```
Enter Configuration commands, one per line. End with CNTL/Z
```

```
(Switch-Name) (config) # no logging level debugging <module from above>
```

```
(Switch-Name) (config) # write mem
```

Restart WMS on Local Switches

To ensure local switches are populating rogue information properly, use SSH to access the command-line interface of each local switch, enter enable mode, and issue the following commands:

```
(Switch-Name) # configure terminal
```

```
Enter Configuration commands, one per line. End with CNTL/Z
```

```
(Switch-Name) (config) # process restart wms
```

After executing the **restart WMS** command in AOS-W, you will need to wait until the next Rogue Poll Period on the OV3600 and execute a **Poll Now** operation for each local switch on the **APs/Devices > List page** before rogue devices begin to appear in OV3600.

Configure AOS-W CLI when not Offloading WMS

To ensure proper event correlation for IDS events when WMS is not offloaded to OV3600, access the command line interface of each switch (master and local), enter “enable” mode, and issue the following commands:

```
(Switch-Name) # configure terminal
```

```
Enter Configuration commands, one per line. End with CNTL/Z
```

```
(Switch-Name) (config) # ids management-profile
```

```
(Switch-Name) (config) # ids general-profile <name>
```

```
(Switch-Name) (config) # ids-events logs-and-traps
```

```
(Switch-Name) (config) # write mem
```

Copy and Paste to Enable Proper Traps with the AOS-W CLI

To ensure the proper traps are configured on Alcatel-Lucent switches, copy and paste the following command in config mode:

```
snmp-server trap enable wlsxNUserAuthenticationFailed
snmp-server trap enable wlsxUserAuthenticationFailed
snmp-server trap enable wlsxNAuthServerReqTimedOut
snmp-server trap enable wlsxSignatureMatchAP
snmp-server trap enable wlsxSignatureMatchSta
snmp-server trap enable wlsxSignAPNetstumbler
snmp-server trap enable wlsxSignStaNetstumbler
snmp-server trap enable wlsxSignAPAsleap
snmp-server trap enable wlsxSignStaAsleap
snmp-server trap enable wlsxSignAPAirjack
snmp-server trap enable wlsxSignStaAirjack
snmp-server trap enable wlsxSignAPNullProbeResp
snmp-server trap enable wlsxSignStaNullProbeResp
snmp-server trap enable wlsxSignAPDeauthBcast
snmp-server trap enable wlsxSignStaDeauthBcastwlsxChannelFrameErrorRateExceeded
```

```
snmp-server trap enable wlsxChannelFrameFragmentationRateExceeded
snmp-server trap enable wlsxChannelFrameRetryRateExceeded
snmp-server trap enable wlsxNIPspoofingDetected
snmp-server trap enable wlsxStaImpersonation
snmp-server trap enable wlsxReservedChannelViolation
snmp-server trap enable wlsxValidSSIDViolation
snmp-server trap enable wlsxStaPolicyViolation
snmp-server trap enable wlsxRepeatWEPIVViolation
snmp-server trap enable wlsxWeakWEPIVViolation
snmp-server trap enable wlsxFrameRetryRateExceeded
snmp-server trap enable wlsxFrameReceiveErrorRateExceeded
snmp-server trap enable wlsxFrameFragmentationRateExceeded
snmp-server trap enable wlsxFrameBandWidthRateExceeded
snmp-server trap enable wlsxFrameLowSpeedRateExceeded
snmp-server trap enable wlsxFrameNonUnicastRateExceeded
snmp-server trap enable wlsxChannelRateAnomaly
snmp-server trap enable wlsxNodeRateAnomalyAP
snmp-server trap enable wlsxNodeRateAnomalySta
snmp-server trap enable wlsxEAPRateAnomaly
snmp-server trap enable wlsxSignalAnomaly
snmp-server trap enable wlsxSequenceNumberAnomalyAP
snmp-server trap enable wlsxSequenceNumberAnomalySta
snmp-server trap enable wlsxApFloodAttack
snmp-server trap enable wlsxInvalidMacOUIAP
snmp-server trap enable wlsxInvalidMacOUISta
snmp-server trap enable wlsxStaRepeatWEPIVViolation
snmp-server trap enable wlsxStaWeakWEPIVViolation
snmp-server trap enable wlsxStaAssociatedToUnsecureAP
snmp-server trap enable wlsxStaUnAssociatedFromUnsecureAP
snmp-server trap enable wlsxAPImpersonation
snmp-server trap enable wlsxDisconnectStationAttackAP
snmp-server trap enable wlsxDisconnectStationAttackSta
```



You will need to issue the `write mem` command.


The following table describes the different methods through which OV3600 acquires data from Alcatel-Lucent devices on the network.

Table 6 Methods by which OV3600 Acquires Data from Alcatel-Lucent Devices

Data Elements	Switch/Thin AP						Alcatel-Lucent Instant	
	SNMP MIB	SNMP Traps	AMON	CLI/SSH	WMS Offload	RTLS	HTTPS	
Configuration interface								
Device configuration/audit				X			X	
User and client interfaces								
Assoc/auth/roam	X	X					X	
Bandwidth	X						X	
Signal quality	X					X	X	
Auth failures		X					N/A	
AP/radio interfaces								
CPU And memory utilization	<-----N/A----->							X
Bandwidth	X						X	
Transmit Power	X						X	
Channel utilization			X				X	
Noise floor	X						X	
Frame rates	X						X	
Error counters	X						X	
Channel summary				X			N/A	
ARM events		X					N/A	
Active interferers			X				N/A	
Active BSSIDs/SSIDs	X						X	
Security								
IDS events		X					N/A	
Neighbors/rogues	X				X		X	
Neighbor re-classification				X	X		N/A	
Client classification					X		N/A	
User deauthorization				X			N/A	

WMS Offload instructs the master switch to stop correlating ARM, WIPS, and WIDS state information amongst its local switches because OV3600 will assume this responsibility. Figure 25 depicts how OV3600 communicates state information with local switches.

Figure 25 ARM/WIPS/WIDS Classification Message Workflow



State Correlation Process

1. AP-1-3-1 hears rogue device A.
2. Local switch 1-3 evaluates devices and does initial classification and sends a classification request to the OV3600.
3. OV3600 receives message and re-classifies the device if necessary and reflects this within OV3600 GUI and via SNMP traps, if configured.
4. OV3600 sends a classification message back to all local switches managed by master switch 1, (1-1, 1-2, and 1-3).
5. OV3600 sends a classification message back to all additional local switches managed by the OV3600 server. In this example all local switches under master switch 2, (2-1, 2-2, and 2-3) would receive the classification messages.
6. If an administrative OV3600 user manually overrides the classification, then OV3600 will send a re-classification message to all applicable local switches.

7. OV3600 periodically polls each local switch's MIB to ensure state parity with the OV3600 database. If the local switch's device state does not comply with the OV3600 database, OV3600 will send a re-classification message to bring it back into compliance.



The Rogue Detail page displays a BSSID table for each rogue that displays the desired classification and the classification on the device.

Using OV3600 as Master Device State Manager

OV3600 offers the following benefits as a master device state manager:

- Ability to correlate state among multiple master switches. This will reduce delays in containing a rogue device or authorizing a valid device when devices roam across a large campus.
- Ability to correlate state of third party access points with ARM. This will ensure Alcatel-Lucent infrastructure interoperates more efficiently in a mixed infrastructure environment.
- Ability to better classify devices based on OV3600 wire-line information not currently available in AOS-W.
- OV3600 provides a near real-time event notification and classification of new devices entering air space.
- RAPIDS gains additional wire-line discovery data from Alcatel-Lucent switches.

Understand Band Steering's Impact on Location

Band steering can negatively impact location accuracy when testing in highly mobile environment. The biggest hurdle is scanning times in 5 GHz frequency.

Table 7 Location accuracy impact

Operating Frequency	Total Channels	Scanning Frequency	Scanning Time	Total Time One Pass
2.4 GHz	11 (US)	10 seconds	110 milliseconds	121.21 seconds
5 GHz	24 (US)	10 seconds	110 milliseconds	242.64 seconds

Leveraging RTLS to Increase Accuracy

This section provides instructions for integrating the OV3600, Alcatel-Lucent WLAN infrastructure and Alcatel-Lucent's RTLS feed to more accurately locate wireless clients and Wi-Fi Tags.

Deployment Topology

Figure 26 Typical Client Location





Figure 27 Typical Tag Deployment



Prerequisites

You will need the following information to monitor and manage your Alcatel-Lucent infrastructure.

- Ensure OV3600 server is already monitoring Alcatel-Lucent infrastructure
- Ensure WMS Offload process is complete
- Ensure firewall configuration for port 5050 (default port) supports bidirectional UDP communication between the OV3600 server's IP address and each access point's IP address

Enable RTLS service on the OV3600 server

To enable RTLS service on the OV3600 server, follow these steps:

1. Navigate to **OV3600 Setup > General** and locate the **OV3600 Additional Services** section
2. Select **Yes** for the **Enable RTLS Collector** option.
3. A new section will automatically appear with the following settings:
 - **RTLS Port** - the match switch default is 5050
 - **RTLS Username** - match the SNMPv3 MMS username configured on switch
 - **RTLS Password** - match the SNMPv3 MMS password configured on switch

Figure 28 RTLS Fields in **OV3600 Setup > General**

The screenshot shows the **Additional OV3600 Services** configuration page. The settings are as follows:

Field	Value
Enable FTP server: required to manage Cisco WLC APs; optional for FTP upgrades on supported devices.	<input checked="" type="radio"/> Yes <input type="radio"/> No
Enable RTLS collector: Alcatel-Lucent only	<input checked="" type="radio"/> Yes <input type="radio"/> No
RTLS Port:	5050
RTLS Username:	admin
RTLS Password:	••••••••
Confirm RTLS Password:	••••••••
Use embedded mail server:	<input checked="" type="radio"/> Yes <input type="radio"/> No

Send Test Email

4. Select **Save** at the bottom of the page.

Enable RTLS on the Switch



RTLS can only be enabled on the master switch and it will automatically propagate to all local switches.

SSH into master switch, enter **enable** mode, and issue the following commands:

```
(Switch-Name) # configure terminal
Enter Configuration commands, one per line. End with CNTL/Z

(Switch-Name) (config) # ap system-profile <Thin-AP-Profile-Name>

(Switch-Name) (AP system profile default) # rtls-server ip-addr <IP of OV3600 Server>
port 5050 key <Switch-SNMPv3-MMS-Password>

(Switch-Name) (AP system profile default) # write mem
```

To validate exit configuration mode:

```
(Switch-Name) # show ap monitor debug status ip-addr <AP-IP-Address>
...
RTLS configuration
-----
Type          Server IP    Port Frequency Active
-----
MMS           10.51.2.45  5070 120
Aeroscout    N/A         N/A   N/A
RTLS         10.51.2.45  5050 60      *
```

Troubleshooting RTLS

You can use either the WebUI or CLI to ensure the RTLS service is running on your OV3600 server.

Using the WebUI

Access the OV3600 WebUI and navigate to **System > Status**.

Scroll down Services list and look for the RTLS service, as shown below

Figure 29 RTLS System Status

Home	Groups	APs/Devices	Clients	Reports	System	Device Setup
Status	Syslog & Traps	Event Log	Triggers	Alerts	Backups	Configuration Change
RADIUS Accounting Server			OK	/var/log/radius/radius.log		
Report Runner			OK	/var/log/amp_report_runner		
Rogue Filter			OK	/var/log/rogue_filter		
RRD Write Cache			OK	-		
RTLS Collector			OK	/var/log/rtls		
SNMP Enabler			OK	/var/log/snmp_enabler		
SNMP Fetcher			OK	/var/log/snmp_fetcher		
SNMP V2 Fetcher			OK	/var/log/snmp_v2_fetcher		

Using the CLI

Use SSH to access the command-line interface of your OV3600 server, and issue the following commands:

```
[root@OV3600Server]# daemons | grep RTLS
root      17859 12809 0 10:35 ?          00:00:00 Daemon::RTLS
```

Issue the **logs** and **tail rtls** commands to check the RTLS log file and verify that Tag chirps are making it to the OV3600 server.

```
[root@OV3600Server]# logs
[root@OV3600Server]# tail rtls

payload:
00147aaf01000020001a1ec02b320000001000000137aae0100000c001a1ec02b32000001a1e82b322
590006ddff02
1224534900.588245 - got 96 bytes from 10.51.1.39 on port 5050
Mon Oct 20 13:35:00 2008: 1224534900.588338 - got 96 bytes from 10.51.1.39 on port
5050
payload:
0014c9c90100003c001a1ec05078000000200000013c9c70100000c001a1ec05078000000d54a7a280
540001ddff020013c9c80100000c001a1ec050780000000cdb8ae9a9000006c4ff02
1224534900.588245 - got 96 bytes from 10.51.1.39 on port 5050
Mon Oct 20 13:35:00 2008: 1224534900.588338 - got 96 bytes from 10.51.1.39 on port
5050
payload:
0014c9c90100003c001a1ec05078000000200000013c9c70100000c001a1ec05078000000d54a7a280
540001ddff020013c9c80100000c001a1ec050780000000cdb8ae9a9000006c4ff02
```

Ensure chirps are published to Airbus by snooping on RTLS tag reports.

```
[root@OV3600server]# airbus_snoop rtls_tag_report
Snooping on rtls_tag_report:
Mon Oct 20 13:49:03 2008 (1224535743.54077)
%
  ap_mac => 00:1A:1E:C0:50:78
  battery => 0
  bssid => 00:1A:1E:85:07:80
  channel => 1
  data_rate => 2
  noise_floor => 85
  payload =>
  rssi => -64
  tag_mac => 00:14:7E:00:4C:E4
  timestamp => 303139810
  tx_power => 19
```

Verify external applications can see WiFi Tag information by exercising the Tag XML API:

<https://<OV3600-Server-IP>/visualrf/rfid.xml>

You should see the following XML output:

```
<visualrf:rfid version=1>
  <rfid battery-level=0 chirp-interval= radio-mac=00:14:7E:00:4C:E0
    vendor=>
      <radio phy=g xmit-dbm=10.0/>
      <discovering-radio ap=SC-MB-03-AP10 dBm=-91 id=811 index=1
        timestamp=2008-10-21T12:23:30-04:00/>
      <discovering-radio ap=SC-MB-03-AP06 dBm=-81 id=769 index=1
        timestamp=2008-10-21T12:23:31-04:00/>
      <discovering-radio ap=SC-MB-01-AP06 dBm=-63 id=708 index=1
        timestamp=2008-10-21T12:23:31-04:00/>
      <discovering-radio ap=SC-MB-02-AP04 dBm=-88 id=806 index=1
        timestamp=2008-10-21T12:22:34-04:00/>
    </rfid>
  <rfid battery-level=0 chirp-interval= radio-mac=00:14:7E:00:4B:5C
    vendor=>
      <radio phy=g xmit-dbm=10.0/>
      <discovering-radio ap=SC-MB-03-AP06 dBm=-74 id=769 index=1
        timestamp=2008-10-21T12:23:20-04:00/>
      <discovering-radio ap=SC-MB-01-AP06 dBm=-58 id=708 index=1
```

```
        timestamp=2008-10-21T12:23:20-04:00/>
    <discovering-radio ap=SC-MB-03-AP02 dBm=-91 id=734 index=1
        timestamp=2008-10-21T12:23:20-04:00/>
</rfid>
<rfid battery-level=0 chirp-interval= radio-mac=00:14:7E:00:4D:06
    vendor=>
    <radio phy=g xmit-dbm=10.0/>
    <discovering-radio ap=SC-SB-GR-AP04 dBm=-91 id=837 index=1
        timestamp=2008-10-21T12:21:08-04:00/>
    <discovering-radio ap=SC-MB-03-AP06 dBm=-79 id=769 index=1
        timestamp=2008-10-21T12:22:08-04:00/>
    <discovering-radio ap=SC-MB-01-AP06 dBm=-59 id=708 index=1
        timestamp=2008-10-21T12:23:08-04:00/>
    <discovering-radio ap=SC-MB-02-AP04 dBm=-90 id=806 index=1
        timestamp=2008-10-21T12:22:08-04:00/>
</rfid>
</visualrf:ruids>
```

Wi-Fi Tag Setup Guidelines

- Ensure that the tags can be heard by at least three (3) access points from any given location. The recommended value is 4 APs.
- Ensure that the tags chirp on all regulatory channels.

