


# OmniAccess 4504XM, OmniAccess 4604, OmniAccess 4704

## WIRELESS LAN SWITCHES



The Alcatel-Lucent OmniAccess™ 4504XM, 4604 and 4704 (OAW-4504XM, OAW-4604, OAW-4704) switches are high performance, fully-featured WLAN switches that are able to aggregate up to 32, 64 and 128 campus connected access points (APs) respectively. These WLAN switches provide a true user-centric network experience, delivering follow-me connectivity, identity-based access, and application continuity services.



### F E A T U R E S

- High performance
- Scalable architecture
- Centralized WLAN switching
- Dynamic RF management
- Integrated wireless intrusion prevention
- User-centric security with stateful firewall

### B E N E F I T S

- Platforms designed from the ground up to support IEEE 802.11n high performance networks.
- Supports pay as you grow capability through software licensing model. WLAN switch AP capacity can grow by adding SW licenses.
- Allows for overlay deployments without disruption to the existing wireline infrastructure. Simplifies management task by minimizing the number of network elements.
- Provides analysis of the RF environment to facilitate deployment with self tuning access points and facilitates operation of the network with virtual real time site survey.
- Integrates both wireless networking and wireless intrusion detection and prevention thus reducing the cost of wireless infrastructure and cost of operating the wireless network.
- Prevents unauthenticated users from accessing the corporate wireless network while safely supporting guest users, contractors as well as corporate users. Decreases management burden of security through role-based security.

## FEATURES

---

- Real time location tracking
- Quality of service, extended battery capabilities, application layer gateway (ALG) for voice protocols

## BENEFITS

---

- Allows for the real time location tracking of wireless users to enrich presence information. Also supports location tracking of wireless asset tags throughout the enterprise.
- Improves voice quality through support of QoS mechanisms such as WMM, DSCP marking and prioritization, and connection admission control. Also improves voice end user experience by maximizing battery life with protocols such as U-APSD. Provides unmatched voice security through embedded stateful firewall.

The OAW-4504XM is designed for small businesses and branch offices, while the OAW-4604 and OAW-4704 are designed for medium to large enterprise or dense office deployments. These three WLAN switches can be easily deployed as an overlay without any disruption to the existing wired network.

Advanced voice-over-WLAN features such as Call Admission Control (CAC), voice-aware RF management and strict over-the-air quality of service (QoS) allow the OAW-4504XM, OAW-4604, and OAW-4704 to deliver mobile VoIP capabilities. These switches are managed via the integrated management capability of the Alcatel-Lucent OmniAccess Wireless Operating System or the Alcatel-Lucent OmniVista™ Mobility Manager.

Additionally, the OAW-4504XM, OAW-4604, OAW-4704 offer best in class, user-centric security framework to authenticate wireless users, enforce role-based access control policies and quarantine unsafe endpoints from accessing the corporate wireless network. Guest users can be easily and safely supported with the built-in captive portal server and advanced network services.

The OAW-4504XM, OAW-4604, OAW-4704 can create a secure networking environment without requiring additional VPN/firewall devices using integrated site-to-site VPN and NAT capabilities, split-tunneling and stateful firewall. Site-to-site VPN support can be integrated with all leading VPN concentrators to provide seamless integration into existing corporate VPNs

## TECHNICAL SPECIFICATIONS

---

### Performance and capacity (OAW-4504XM / OAW-4604 / OAW-4704)

- Campus-connected APs: Up to 32/64/128
- Remote APs: Up to 128/256/512
- Users: Up to 2048/4096/8192
- MAC addresses: Up to 64,000
- VLAN IP interfaces: 128/256/512
- Gigabit Ethernet ports (RJ-45 or SFP): 4
- Active firewall sessions: Up to 128,000
- Concurrent IPsec tunnels: Up to 512/4096/4096
- Firewall throughput: 3/4/4 Gbps
- Encrypted throughput (3DES, AESCBC256): 1.6/4/8 Gbps
- Encrypted throughput (AES-CCM): 0.8/2/4 Gbps

### Wireless LAN security and control features

- 802.11i security (WPA certified WPA2 and WPA)
- 802.1X user and machine authentication
- EAP-PEAP, EAP-TLS, EAP-TTLS support
- Centralized AES-CCM, TKIP and WEP encryption

- 802.11i PMK caching for fast roaming applications
- EAP offload for AAA server scalability and survivability
- Stateful 802.1X authentication for standalone APs
- MAC address, SSID and location-based authentication Multi-SSID support for operation of multiple WLANs
- SSID-based RADIUS server selection
- Secure AP control and management over IPsec or GRE
- CAPWAP compatible and upgradeable
- Distributed WLAN mode for remote AP deployments
- Simultaneous centralized and distributed WLAN support

### Identity based security features

- Captive portal, 802.1X and MAC address authentication
- Username, IP address, MAC address and encryption key binding for strong network identity creation

- Per-packet identity verification to prevent impersonation
- RADIUS and LDAP-based AAA server support
- Internal user database for AAA server failover protection
- Role-based authorization for eliminating excess privilege
- Robust policy enforcement with stateful packet inspection
- Per-user session accounting for usage auditing
- Web-based guest enrollment
- Configurable acceptable use policies for guest access
- XML-based API for external captive portal integration
- xSec option for wired LAN authentication and encryption (802.1X authentication, 256-bit AES-CBC encryption)

## Convergence features

- Voice and data on a single SSID for converged devices
- Flow-based QoS using voice flow classification (VFC)
- Alcatel-Lucent NOE, SIP, Spectralink SVP, SCCP and Vocera ALGs
- Strict priority queuing for over-the-air QoS
- 802.11e support – WMM, U-APSD and T-SPEC
- QoS policing for preventing network abuse via 802.11e
- DiffServ marking and 802.1p support for network QoS
- On-hook and off-hook VoIP client detection
- VoIP call admission control (CAC) using VFC
- Call reservation thresholds for mobile VoIP calls
- Voice-aware RF management for ensuring voice quality
- Fast roaming support for ensuring mobile voice quality
- SIP early media and ringing tone generation (RFC 3960)
- Per-user and per-role rate limits (bandwidth contracts)

## Adaptive radio management (ARM) features

- Automatic channel and power settings for thin APs
- Simultaneous air monitoring and end-user services
- Self-healing coverage-based on dynamic RF conditions
- Dense deployment options for capacity optimization
- AP load balancing-based on number of users
- AP load balancing-based on bandwidth utilization
- Coverage hole and RF interference detection
- 802.11h support for radar detection and avoidance
- Automated location detection for active RFID tags
- Built-in XML-based Location API for RFID applications

## Wireless intrusion protection features

- Integration with WLAN infrastructure
- Simultaneous or dedicated air monitoring capabilities
- Rogue AP detection and built-in location visualization
- Automatic rogue, interfering and valid AP classification
- Over-the-air and over-the-wire rogue AP containment
- Ad hoc WLAN network detection and containment
- Windows client bridging and wireless bridge detection
- Denial of service attack protection for APs and stations

- Mis-configured standalone AP detection and containment
- Third party AP performance monitoring and troubleshooting
- Flexible attack signature creation for new WLAN attacks
- EAP handshake and sequence number analysis
- Valid AP impersonation detection
- Frame floods, fake AP and Airjack attack detection
- ASLEAP, de-auth broadcast, null probe response detection
- Netstumbler-based network probe detection

## Stateful firewall features

- Stateful packet inspection tied to user identity or ports
- Location and time-of-day aware policy definition
- 802.11 station awareness for WLAN firewalling
- Over-the-air policy enforcement and station blacklisting
- Session mirroring and per-packet logs for forensic analysis
- Detailed firewall traffic logs for usage auditing
- Application layer gateway (ALG) support for NOE, SIP, SCCP, RTSP, Vocera, FTP, TFTP, PPTP
- Source and destination Network Address Translation (NAT)
- Dedicated flow processing hardware for high performance
- TCP, ICMP denial of service attack detection and protection
- Policy-based forwarding into GRE tunnels for guest traffic
- External service interface for third party security integration for inline anti-virus, anti-spam and content filtering apps
- Health checking and load balancing for external services

## VPN server features

- Site-to-site VPN support for branch office deployments
- Site-to-site interoperability with third party VPN servers
- VPN server emulation for easy integration into WLAN
- L2TP/IPSec VPN termination for Windows VPN clients
- XAUTH/IPSec VPN termination for third party clients
- PPTP VPN termination for legacy VPN integration
- RADIUS and LDAP server support for VPN authentication
- PAP, CHAP, MS-CHAP and MS-CHAPv2 authentication
- Hardware encryption for DES, 3DES, AES, MPPE
- Secure point-to-point xSec tunnels for L2 VPNs

## Networking features and advanced services

- L2 and L3 switching over-the-air and over-the-wire
- VLAN pooling for easy, scalable network designs
- VLAN mobility for seamless L2 roaming
- Proxy mobile IP and proxy DHCP for L3 roaming
- Built-in DHCP server and DHCP relay
- VRRP-based N+1 WLAN switch redundancy (L2)
- AP provisioning-based N+1 WLAN switch redundancy (L3)
- Etherchannel support for link redundancy
- 802.1d Spanning Tree Protocol (STP)
- 802.1Q VLAN tags

## WLAN switch-based management features

- RF Planning and AP Deployment Toolkit
- Centralized AP provisioning and image management
- Live coverage visualization with RF heat maps
- Detailed statistics visualization for monitoring
- Remote packet capture for RF troubleshooting
- Interoperable with Ethereal and Airokeek analyzers
- Multi-WLAN switch configuration management
- Location visualization and device tracking
- System-wide event collection and reporting

## Administration features

- Web-based user interface access over HTTP and HTTPS
- Quickstart screens for easy WLAN switch configuration
- CLI access using SSH, Telnet and console port
- Role-based access control for restricted admin access
- Authenticated access via RADIUS, LDAP or Internal DB
- SNMPv3 and SNMPv2 support for WLAN switch monitoring
- Standard MIBs and private enterprise MIBs
- Detailed message logs with syslog event notification

## Power consumption

- OAW-4504XM: 35 W maximum
- OAW-4604: 45 W maximum
- OAW-4704: 60 W maximum

## TECHNICAL SPECIFICATIONS

### Power specifications (AC input requirements)

#### OAW-4504XM

- AC Input Voltage: 90-264 V~, universal input
- AC Input Current: 1.5 A
- AC Input Frequency: 47-63 Hz

#### OAW-4604 and OAW-4704

- AC Input Voltage: 90-264 V~, universal input
- AC Input Current: 2.2 A
- AC Input Frequency: 47-63 Hz

### Operating specifications and dimensions

- Operating temperature range 0° to 40° C
- Storage temperature range 10° to 70° C
- Humidity, non-condensing 5 to 95%
- Height 1.75' (44 mm)
- Width 13.8' (351 mm)
- Depth 11.7' (297 mm)

#### Weight

- OAW-4504XM: 7.1 lbs/3.2 Kg (unboxed)
- OAW-4604 / OAW-4704: 7.4 lbs/3.4 Kg (unboxed)

### Regulatory and safety compliance

- FCC part 15 Class A CE
- Industry Canada Class A
- VCCI Class A (Japan)
- EN 55022 Class A (CISPR 22 Class A), EN 61000-3, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11, EN 55024, AS/NZS 3548
- UL 60950, EN60950
- CAN/CSA 22.2 #60950
- CE mark, cTUVus, GS, CB, C-tick, Anatel, NOM, MIC, IQC

## ORDERING INFORMATION

PART NUMBER	DESCRIPTION
<b>OAW-4504XM-0</b>	OmniAccess 4504XM - 4x 10/100/1000BaseT (RJ-45) or 1000BaseX (SFP) dual personality ports (no AP license included). Can support up to 32 APs (additional AP licenses required).
<b>OAW-4504XM-8</b>	OmniAccess 4504XM - 4x 10/100/1000BaseT (RJ-45) or 1000BaseX (SFP) dual personality ports, bundled with 8 AP license. Can support up to 32 APs (additional AP licenses required).
<b>OAW-4604-0</b>	OmniAccess 4604 - 4x 10/100/1000BaseT (RJ-45) or 1000BaseX (SFP) dual personality ports (no AP license included). Can support up to 64 APs (additional AP licenses required).
<b>OAW-4604-32</b>	OmniAccess 4604 - 4x 10/100/1000BaseT (RJ-45) or 1000BaseX (SFP) dual personality ports, bundled with 32 AP license. Can support up to 64 APs (additional AP licenses required).
<b>OAW-4704-0</b>	OmniAccess 4704 - 4x 10/100/1000BaseT (RJ-45) or 1000BaseX (SFP) dual personality ports (no AP license included). Can support up to 128 APs (additional AP licenses required).
<b>OAW-4704-64</b>	OmniAccess 4704 - 4x 10/100/1000BaseT (RJ-45) or 1000BaseX (SFP) dual personality ports, bundled with 64 AP license. Can support up to 128 APs (additional AP licenses required).
<b>OAW-SFP-SX</b>	OmniAccess Wireless SFP - 1000BaseSX, LC Connector
<b>OAW-SFP-LX</b>	OmniAccess Wireless SFP - 1000BaseLX, LC connector
<b>OAW-SFP-TX</b>	OmniAccess Wireless SFP - 1000Base-T, RJ-45 connector

To learn more, contact your dedicated Alcatel-Lucent representative, authorized reseller, or sales agent. You can also visit our Web site at [www.alcatel-lucent.com](http://www.alcatel-lucent.com).

This document is provided for planning purposes only and does not create, modify, or supplement any warranties, which may be made by Alcatel-Lucent relating to the products and/or services described herein. The publication of information contained in this document does not imply freedom from patent or other protective rights of Alcatel-Lucent or other third parties.

#### [www.alcatel-lucent.com](http://www.alcatel-lucent.com)

Alcatel, Lucent, Alcatel-Lucent and the Alcatel-Lucent logo are trademarks of Alcatel-Lucent. All other trademarks are the property of their respective owners. Alcatel-Lucent assumes no responsibility for the accuracy of the information presented, which is subject to change without notice.  
© 2011 Alcatel-Lucent. All rights reserved.