

ALCATEL-LUCENT OMNIACCESS 228 ACCESS POINTS

802.11AC FOR HARSH, WEATHER-PROTECTED AREAS

Rugged Alcatel-Lucent OmniAccess® 228 wireless access points (APs) deliver gigabit Wi-Fi® performance to 802.11ac mobile devices in harsh, weather-protected environments, such as warehouses, industrial freezers or enclosures in extreme environments, such as stadiums.



With a maximum data rate of 1.3 Gb/s in the 5-GHz band and 600 Mb/s in the 2.4-GHz band, OmniAccess 228 APs are three-times faster than 802.11n APs and provide performance similar to a wired connection.

The 228 APs include ClientMatch™ technology, which eliminates sticky clients by continuously gathering session performance metrics from mobile devices. This information is then used to steer each mobile device to the best AP and radio on the WLAN.

Proactive and deterministic, ClientMatch dynamically optimizes Wi-Fi client performance as users roam and RF conditions change. If a mobile device moves out of range of an AP or RF interference impedes performance, ClientMatch automatically steers it to a better AP.

With ClientMatch, 228 APs load web pages faster, deliver video streams with improved quality and support high densities of mobile devices. An 802.11ac network without ClientMatch performs no different than an 802.11n WLAN.

The rugged 228 APs additionally support priority handling and policy enforcement for individual Microsoft Lync media on the same device, including encrypted videoconferencing, voice, chat and desktop sharing.

BENEFITS

- Industrial design for harsh, weather-protected environments
 - Extends temperature range for indoor environments that lack heating and cooling
 - Sealed connector interfaces to lock out dust and moisture
 - Connectorized antenna ports support high gain large public venue antennas
 - Designed for enhanced physical security.
- Delivers 1.9 Gb/s aggregate throughput.
 - EtherChannel link aggregation on two Gigabit Ethernet ports provides 1.9 Gb/s throughput.
- Supports aggregate data rates up to 1.9 Gb/s
 - 802.11ac transmit beam-forming to enhance signal, throughput and multi stream operation
 - Supports 1.3 Gb/s rates in the 5 GHz band for 802.11ac clients
 - Supports up to 600 Mb/s for TurboQAM-enabled mobile devices operating in the 2.4 GHz band
- Best-in-class RF management
 - Integrated Adaptive Radio Management™ technology manages the 2.4-GHz and 5-GHz radio bands and ensures that APs stay clear of RF interference.
- Spectrum analysis
 - Capable of part-time or dedicated air monitoring, the spectrum analyzer remotely scans the 2.4-GHz and 5-GHz radio bands to identify sources of RF interference.

- Wireless mesh
 - Wireless mesh connections are convenient where Ethernet drops are not available.
- Security
 - Integrated wireless intrusion protection offers threat protection and mitigation and eliminates the need for separate RF sensors and security appliances.
 - With an OpenDNS service subscription, Instant APs deliver integrated web filtering, malware and botnet protection to every device connected to the WLAN.
 - Encrypted IPsec VPN tunnels securely connect remote users to corporate network resources.
 - Integrated Trusted Platform Module (TPM) for secure storage of credentials and keys.
 - SecureJack-capable for secure tunneling of wired Ethernet traffic.

CHOOSE YOUR OPERATING MODE

The 228 APs offer a choice of operating modes to meet your unique management and deployment requirements.

- Controller-managed AP or Remote AP (RAP) running AOS-W. When managed by OmniAccess Controllers, 228 APs offer centralized configuration, data encryption, policy enforcement and network services, as well as distributed and centralized traffic forwarding.
- Instant™ AP running InstantOS. In Alcatel-Lucent Instant mode, a single AP automatically distributes the network configuration to other Instant APs in the WLAN. Simply power-up one Instant AP, configure it over the air, and plug in the other APs – the entire process takes about five minutes.
- Spectrum analysis identifies sources of RF interference
- Air monitor provides wireless intrusion protection
- Hybrid AP serves Wi-Fi clients and provides wireless intrusion protection and spectrum analysis
- Secure enterprise mesh

If WLAN and network requirements change, a built-in migration path allows 228 Instant APs to become part of a WLAN that is centrally managed by a Controller.

TECHNICAL SPECIFICATIONS

AP228

- 2.4-GHz (600 Mb/s max) and 5-GHz (1.3 Gb/s max) radios, each with 3x3 MIMO and three combined, diplexed external antenna connectors.

WIRELESS RADIO

- AP type: Indoor, dual radio, 5 GHz 802.11ac and 2.4 GHz 802.11n
 - In addition to 802.11n data rates, the 2.4-GHz radio supports 802.11ac data rates using 256-QAM modulation. This gives TurboQAM-enabled clients a 33 percent boost above the maximum supported data rate.
- Software-configurable dual radio supports 5 GHz and 2.4 GHz
- 3x3 MIMO with three spatial streams and up to 1.3 Gb/s wireless data rate
- Supported frequency bands (country-specific restrictions apply):
 - 2.4000 GHz to 2.4835 GHz
 - 5.150 GHz to 5.250 GHz
 - 5.250 GHz to 5.350 GHz
 - 5.470 GHz to 5.725 GHz
 - 5.725 GHz to 5.850 GHz
- Available channels: Dependent upon configured regulatory domain
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
 - 802.11n/ac: 3x3 MIMO with up to three spatial streams
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM
 - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
- Transmit power: Configurable in increments of 0.5 dBm
- Maximum (aggregate, conducted total) transmit power (limited by local regulatory requirements):
 - 2.4-GHz band: +23 dBm (18 dBm per chain)
 - 5-GHz bands: +23 dBm (18 dBm per chain)
- Advanced cellular coexistence (ACC) feature to effectively deal with interference from cellular systems

- Maximum ratio combining (MRC) for improved receiver performance
- Cyclic delay diversity (CDD) for improved downlink RF performance
- Short guard interval for 20-MHz, 40-MHz and 80-MHz channels
- Space-time block coding (STBC) for increased range and improved reception
- Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
- Transmit beam-forming (TxBF) for increased reliability in signal delivery
- Supported data rates (Mb/s):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
 - 802.11n: 6.5 to 450 (MCS0 to MCS23)
 - 802.11ac: 6.5 to 1,300 (MCS0 to MCS9, NSS = 1 to 3)
- 802.11n high-throughput (HT) support: HT 20/40
- 802.11ac very high throughput (VHT) support: VHT 20/40/80
- 802.11n/ac packet aggregation: A-MPDU, A-MSDU

POWER

- Worst-case power consumption from the AP: 23W
- Power sources sold separately
- Power over Ethernet (PoE+): 802.3at-compliant

ANTENNAS

- Six RP-SMA connectors for external antennas

OTHER INTERFACES

- Two 10/100/1000BASE-T Ethernet network interfaces (RJ-45)
 - Auto-sensing link speed and MDI/MDX
 - Load balancing support to achieve platform throughput greater than one Gb/s
 - PoE-PD: 802.3at PoE+
- Serial console interface (Micro USB)

MOUNTING

- Optional mounting kits:
 - AP-130-MNT or AP-220-MNT-W1 are directly compatible
 - 270 Series outdoor AP mounts (AP-270-MNT-V1, AP-270-MNT-V2, AP-270-MNT-H1, AP-270-MNT-H2) are compatible when the AP-270-MNT-ADP adapter is utilized

MECHANICAL

- Dimensions/weight (unit, excluding mount accessories):
 - 222 mm (L) x 150 mm (W) x 75 mm (H) (8.5" (L) x 6" (W) x 2.5" (H))
 - 1.225 kg (2.700 lbs)

ENVIRONMENTAL

- Operating:
 - Temperature: -40° C to +60° C (-40° F to +140° F)
 - Humidity: 5% to 95% non-condensing
 - Storage and transportation:
 - Temperature: -40° C to +70° C (-40° F to +158° F)
 - Operating altitude: 3,000 m

REGULATORY

- FCC/Industry of Canada
- CE Marked
- R&TTE Directive 1995/5/EC
- Low Voltage Directive 72/23/EEC
- EN 300 328
- EN 301 489
- EN 301 893
- UL/IEC/EN 60950
- EN 60601-1-1, EN60601-1-2
For more country-specific regulatory information and approvals, see your Alcatel-Lucent Enterprise representative.

REGULATORY MODEL NUMBERS

- OAW-AP-228 and OAW-IAP-228: APIN0228

CERTIFICATIONS

- CB Scheme Safety, cTUVus
- UL2043 plenum rating
- Wi-Fi Alliance certified 802.11a/b/g/n/ac

WARRANTY

- Limited lifetime warranty

MINIMUM OPERATING SYSTEM SOFTWARE VERSIONS

- AOS-W 6.4.3.0
- Instant 4.1.2.0

RF PERFORMANCE TABLE

	Maximum transmit power (dBm) per transmit chain	Receiver sensitivity (dBm) per receive chain
802.11B		
1 Mb/s	23.0	-92.0
2 Mb/s	23.0	-92.0
5.5 Mb/s	23.0	-90.0
11 Mb/s	23.0	-88.0
802.11G 2.4 GHZ AND 802.11A 5 GHZ		
6 Mb/s	23.0	-88.0
54 Mb/s	18.0	-75.0
802.11N HT20 2.4 GHZ AND 5 GHZ		
MCS0/8	23.0	-88.0
MCS7/15	17.0	-71.0
802.11N HT40 2.4 GHZ AND 5 GHZ		
MCS0/8	23.0	-85.0
MCS7/15	17.0	-68.0
802.11AC VHT20 5 GHZ		
MCS0	23.0	-88.0
MCS9	16.0	-65.0
802.11AC VHT40 5 GHZ		
MCS0	23.0	-85.0
MCS9	16.0	-62.0
802.11AC VHT80 5 GHZ		
MCS0	23.0	-82.0
MCS9	16.0	-59.0

ORDERING INFORMATION**PART NUMBER****DESCRIPTION****AP228 ACCESS POINTS**

OAW-AP228	OmniAccess AP228 Temperature Hardened Wireless Access Point, 802.11ac, 3x3:3, dual radio, antenna connectors
OAW-IAP228-RW	OmniAccess IAP228 Temperature Hardened Wireless Instant Access Point, 802.11ac, 3x3:3, dual radio, antenna connectors - Unrestricted Regulatory Domain. These products should be considered as 'Rest of World' products and MUST NOT be used for deployments in the United States, Japan or Israel
OAW-IAP228-US	OmniAccess IAP228 Temperature Hardened Wireless Instant Access Point, 802.11ac, 3x3:3, dual radio, antenna connectors – Restricted regulatory domain: United States
OAW-IAP228-JP	OmniAccess IAP228 Temperature Hardened Wireless Instant Access Point, 802.11ac, 3x3:3, dual radio, antenna connectors – Restricted regulatory domain: Japan

AP228 ACCESSORIES

AP-130-MNT	OmniAccess AP130 Series Access Point Wall / Ceiling Mounting Kit
AP-220-MNT-W1	OmniAccess AP220 Series Access Point Mount Kit (basic, flat surface). Contains 1x flat surface wall/ceiling mount bracket.
AP-270-MNT-ADP	Omniaccess Adapter to allow AP-228 to use outdoor AP-270 series brackets
AP-270-MNT-V1	OAW-AP270 Series Access Point Long Mount Kit. Pole/Wall Mount for OAW-AP270 300 mm from vertical mounting asset.
AP-270-MNT-V2	OAW-AP270 Series Access Point Short Mount Kit. Pole/Wall Mount for OAW-AP270 75-mm from vertical mounting asset
AP-270-MNT-H1	OAW-AP270 Series Access Point short mounting bracket to mount to horizontal surfaces
AP-270-MNT-H2	OAW-AP270 Series Access Point Horizontal or Vertical Flush Mount kit

GENERIC INDOOR AP ACCESSORIES

PD-9001GR-AC	OAW WLAN 1 Port 802.3at PoE Midspan 10/100/1000 30W. US power cord included. Rest all power cord shall be ordered separately.
PD-9001GO-DC	Outdoor, 12 - 24 DC in, Requires 9001GO mount for most applications. Does not ship with a cable (order separately).
PD-9001GO-NA	OmniAccess 1 Port 802.3at PoE Midspan 10/100/1000 30W Outdoor; NA power cord
PD-9001GO-INTL	OmniAccess 1 Port 802.3at PoE Midspan 10/100/1000 30W Outdoor; EU/International