

Alcatel-Lucent OmniSwitch 9000

CHASSIS LAN SWITCH

The Alcatel-Lucent OmniSwitch™ 9000 Chassis LAN Switch (CLS) family offers flexible features and benefits that make it an ideal switch to use throughout the network; it works exceptionally well as a core or aggregation switch.



The OmniSwitch 9000 CLS family delivers scalable solutions with advanced security and quality of service (QoS) features for use in small-to-large enterprise cores, in the aggregation layer and in wiring closets with flexible Power over Ethernet (PoE) support. The OmniSwitch 9000 models are part of the Alcatel-Lucent end-to-end enterprise switch family.

The OmniSwitch 9000 CLS family offers a wide range of Gigabit Ethernet (GigE) and 10GigE interfaces that provide the industry's most flexible combination of Ethernet interfaces for use in a wiring closet. It also offers PoE to support IP phones, WLAN access points and video cameras. VoIP and video performance is also enhanced in an OmniSwitch-based network through the use of policy-based QoS using Alcatel-Lucent OmniVista™ 2500 NMS PolicyView.

Finally, the OmniSwitch 9000 CLS family promotes eco-sustainability by using minimal power, thus reducing energy bills and air-conditioning costs.

Key features and benefits

High availability

- Smart continuous switching for non-stop operation in redundant chassis management module (CMM) configuration
- Extensive layer-2 and layer-3 protocols support for spatial resiliency

High performance and scalability

- Wire-rate processing for simultaneous layer-2 and IPv4/IPv6 traffic
- High density in GigE (768 ports) and 10GigE (96 ports)

Comprehensive management and security

- Advanced, out-of-the-box auto-configuration, Link Layer Discovery Protocol (LLDP) network policies and dynamic VLAN allocation through Multiple VLAN Registration Protocol (MVRP)

- Flexible device/user authentication with Access Guardian (802.1x/MAC/captive portal), with built-in intrusion detection system (IDS) and quarantine enforcement mechanism
- Extensive support of Alcatel-Lucent Operating System (AOS) user-oriented features

Convergence

- Enhanced VoIP and video performance with policy-based QoS
- PoE support for IP phones, WLAN access points and video cameras with up to 2400 W of power through dedicated power shelves

Alcatel-Lucent OmniSwitch 9000 CLS family models

The OmniSwitch 9000 CLS family offers customers an extensive choice of chassis, modules and power options to match infrastructure requirements.

Chassis options

Several chassis options are offered to meet density requirements.



	OmniSwitch 9600	OmniSwitch 9700/OmniSwitch 9702	OmniSwitch 9800
NUMBER OF SLOTS			
Chassis management module (CMM)	1	2	2
Network interface (NI)	4	8	16
Power supply (AC/DC)	2	3	4
PHYSICAL			
Height	5.5U	11U	17U
Dimensions (HxWxD)	24.4 cm x 44.3 cm x 36.7 cm (9.6 in x 17.45 in x 14.45 in)	48.9 cm x 44.2 cm x 44.0 cm (19.25 in x 17.4 in x 17.3 in)	75.6 cm x 44.2 cm x 44.0 cm (29.75 in x 17.4 in x 17.3 in)
Weight (loaded/empty)	25 kg (55 lb)/10 kg (23 lb)	60 kg (130 lb)/25 kg (56 lb)	85 kg (190 lb)/36 kg (80 lb)
ENVIRONMENT			
Operating temperature	0°C to 45°C (32°F to 113°F)	0°C to 45°C (32°F to 113°F)	0°C to 45°C (32°F to 113°F)
Storage temperature	-10°C to +70°C (14°F to 158°F)	-10°C to +70°C (14°F to 158°F)	-10°C to +70°C (14°F to 158°F)
Operating and storage humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Power (chassis + fan tray)	<42 W	<80 W	<80 W
Heat dissipation (fully loaded – worst case)	<1750 BTU/hr	<3485 BTU/hr	<6480 BTU/hr

Modules available

The table below lists the modules available in the OmniSwitch 9000 CLS family.

DESCRIPTION		POWER
MANAGEMENT MODULES		
OS9600-CMM	OmniSwitch 9600 Chassis Management Module	<27 W
OS9700-CMM	OmniSwitch 9700 Chassis Management Module	<27 W
OS9800-CMM	OmniSwitch 9800 Chassis Management Module	<40 W
NETWORK INTERFACES		
OS9-XNI-U6	6 unpopulated ports of 10GBase-X (XFP MSA)	<67 W
OS9-XNI-U2	2 unpopulated ports of 10GBase-X (XFP MSA)	<36 W
OS9-GNI-U24	24 unpopulated ports of 1000Base-X MiniGBIC (SFP MSA)	<55 W
OS9-GNI-C24	24 ports of 10/100/1000Base-T/TX (RJ-45)	<51 W
OS9-GNI-P24	24 ports of 10/100/1000Base-T/TX (RJ-45), PoE-capable	<54 W
OS9-GNI-C48T	48 ports of 10/100/1000Base-T/TX (MRJ21)	<79 W
OS9-GNI-C20L	20 ports of 10/100Base-T/TX (RJ-45, software-upgradable to 10/100/1000) and 2 unpopulated ports of 100/1000Base-X MiniGBIC (SFP)	<49 W

All network interfaces and transceivers are hot-swappable and can be used in any available NI slots of any OmniSwitch 9000 CLS chassis.

Power supplies

All OmniSwitch 9000 CLS models support redundant and hot-swappable AC and DC power supplies.

	OS9-PS-0600A	OS9-PS-0725A	OS9-PS-0600D	OS9-PS-0725D
Input voltage	100 V AC to 250 V AC (auto-ranging)	100 V AC to 250 V AC (auto-ranging)	-48 V DC	-48 V DC
Input current (max)	7.5 A (110 V) 3.65 A (220 V)	7.9 A (110 V) 4.0 A (220 V)	16.7 A (48 V)	17.8 A (-48V)
Operating frequency	47 Hz to 63 Hz	47 Hz to 63 Hz	–	–
Efficiency	>75%	83%	>75%	85%
Maximum output power	600 W	725 W	600 W	725 W

PoE shelves

All OmniSwitch 9000 CLS models support an optional power shelf to provide power to PoE-capable devices.

	IPS230 (OS9600 ONLY)	IPS390 (OS9600 ONLY)	IP-SHELF
Power supply (AC)	1	1	4
PHYSICAL			
Height (19-in. and 23-in. rack mount)	1 RU	1 RU	2.9 RU
Dimensions (HxWxD)	4.4 cm x 48.3 cm x 17.9 cm (1.73 in x 19.0 in x 7.0 in)	4.4 cm x 48.3 cm x 17.9 cm (1.73 in x 19.0 in x 7.0 in)	75.6 cm x 44.2 cm x 44.0 cm (29.75 in x 17.4 in x 17.3 in)
Maximum output power	230 W	390 W	2400 W (4 x 600)
Example of PoE devices count: Class-1/Class-2	57/32	97/55	384/342

Example of PoE device count is established using 7.0 W of power for powering Class 2 devices (6.49 W) and 4.0 W for powering Class 1 devices (3.84 W per device), taking into consideration lost power that is dissipated in the cable. For reference, the Alcatel-Lucent IP Touch™ 8 Series Extended Edition 4068/4038/4028/4018 product line falls within the Class 2 power requirement and the 4008 model falls within the Class 1 power requirement.

Compliance and certifications

Emission

- FCC CFR 47 part 15 (Class A)
- ICES-003 (Class A)
- CE marking for European countries (Class A)
- VCCI (Class A)
- AS/NZS 3548 (Class A)
- EN 55022:2006 (Emission Standard)
- EN 61000-3-2:2006
- EN 61000-3-3:1995 +A2:2005

Immunity

- IECEN 55024:1998 +A1:2001 +A2:2003
- EN 61000-4-2:2001
- EN 61000-4-3:2002
- EN 61000-4-4:2004
- EN 61000-4-5:2001
- EN 61000-4-6:2004
- EN 61000-4-8:2001
- EN 61000-4-11:2004

Safety agency certifications

- US UL 60950
- IEC 60950-1:2001; all national deviations
- EN 60950-1:2001; all deviations
- CAN/CSA-C22.2 No. 60950-1-03
- NOM-019 SCFI, Mexico
- AS/NZ TS-001 and 60950:2000, Australia
- UL-AR, Argentina
- UL-GS Mark, Germany
- EN 60825-1:1993 +A1:1997 +A2:2001 Laser
- EN 60825-2:2004 Laser
- CDRH Laser

Detailed product features

Simplified manageability

Management interfaces

- Intuitive, familiar Alcatel-Lucent CLI reduces training costs
- Easy-to-use, point-and-click, web-based element manager (WebView) with built-in help for easy configuration
- Integrated with Alcatel-Lucent OmniVista™ 2500 Network Management System (NMS)
- Full configuration and reporting using Simple Network Management Protocol (SNMP) v1/2/3 across all OmniSwitch families to facilitate third-party NMS integration
- Remote switch access using Telnet or Secure Shell (SSH)
- File upload using USB, TFTP, FTP, SFTP, or SCP for faster configuration
- Human-readable ASCII-based configuration files for off-line editing, bulk configuration and out-of-the-box auto-provisioning

Monitoring and troubleshooting

- Local (on the flash) and remote server logging: Syslog and command log
- Port-based mirroring for troubleshooting and lawful interception; supports four sessions with multiple sources-to-one destination
- Policy-based mirroring allows selection of the type of traffic to mirror by using QoS policies
- Remote port mirroring facilitates passing mirrored traffic through the network to a remotely connected device
- Port monitoring feature allows capture of Ethernet packets to a file to assist in troubleshooting
- sFlow v5 and RMON for advanced monitoring and reporting of statistics, history, alarms and events
- IP tools: Ping and trace route
- ITU-T Y.1731 and IEEE 802.1ag Ethernet OA&M: Connectivity Fault Management and performance measurements (layer-2 ping and link trace)
- IEEE 802.3ah Ethernet in the First Mile (EFM) for link monitoring, remote fault detection, and loopback control (layer-1 ping)
- Unidirectional Link Detection (UDLD) detects and disables unidirectional links on fiber optic interfaces
- Digital Diagnostic Monitoring (DDM): Real-time diagnostics of fiber connections for early detection of optical signal deterioration

Network configuration

- Auto-negotiating 10/100/1000 ports automatically configure port speed and duplex setting
- Auto MDI/MDIX automatically configures transmit and receive signals to support straight-through and crossover cabling
- BOOTP/DHCP client with option 60 allows auto-configuration of switch IP information for simplified deployment
- DHCP relay to forward client requests to a DHCP server
- Alcatel-Lucent Mapping Adjacency Protocol (AMAP) for building topology maps
- IEEE 802.1AB LLDP with MED extensions for automated device discovery and IP phone provisioning
- Multiple VLAN Registration Protocol (MVRP) and GARP VLAN Registration Protocol (GVRP) for 802.1Q/1ak-compliant VLAN pruning and dynamic VLAN creation
- Auto-QoS for switch management and IP phone traffic
- Network Time Protocol (NTP) for network-wide time synchronization

Resiliency and high availability

- Smart continuous switching technology for instantaneous and transparent CMM failover in redundant CMM configuration
- ITU-T G.8032 Ethernet Ring Protection designed for loop protection and fast convergence times (sub 50 ms) in ring topologies
- Ring Rapid Spanning Tree Protocol (RRSTP) optimized for ring topology to provide less than 100-ms convergence time
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP): Encompasses IEEE 802.1D Spanning Tree Protocol (STP) and IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- Per-VLAN Spanning Tree (PVST+) and Alcatel-Lucent 1x1 STP mode
- IEEE 802.3ad Link Aggregation Control Protocol (LACP) and static LAG groups across modules are supported
- Dual-home link support for sub-second link protection without STP
- Virtual Router Redundancy Protocol (VRRP) to provide highly available routed environments
- Bidirectional Forwarding Detection (BFD) for fast failure detection and reduced re-convergence times in a routed environment
- Broadcast, unknown unicast and multicast storm control to avoid degradation in overall system performance
- Redundant and hot-swappable power supplies, transceiver modules offering uninterrupted service
- Dual image and dual configuration file storage provides backup

Advanced security

Access control

- AOS Access Guardian framework for comprehensive user-policy-based network access control (NAC)
- Autosensing 802.1X multi-client, multi-VLAN
- MAC-based authentication for non-802.1x hosts
- Web-based authentication (captive portal): A customizable web portal residing on the switch that can be used for authenticating supplicants as well as non-supplicants
- Group mobility rules and “guest” VLAN support
- Authenticated VLAN that challenges users with username and password and supports dynamic VLAN access based on user
- Host integrity check (HIC) agent on each switch makes it an HIC enforcer and facilitates endpoint device control for company policy compliance; quarantine and remediation supported as required
- User Network Profile (UNP) simplifies NAC management and control by dynamically providing pre-defined policy configuration to authenticated clients – VLAN, access control list (ACL), bandwidth, HIC
- SSH for secure CLI session with public key infrastructure (PKI) support
- Centralized RADIUS and Lightweight Directory Access Protocol (LDAP) user authentication
- TACACS+ client allows for authentication, authorization and accounting (AAA) with a remote TACACS+ server

Containment, monitoring and quarantine

- Support for Alcatel-Lucent OmniVista 2500 NMS Quarantine Manager and quarantine VLAN
- Learned Port Security (LPS) or MAC address lockdown secures the network access on user or trunk ports based on MAC address
- DHCP snooping, DHCP IP/ Address Resolution Protocol (ARP) spoof protection
- Embedded traffic anomaly detection (TAD) monitors traffic patterns typical for worm-like viruses and either shuts down the port or reports to the management system
- ARP poisoning detection
- Support of Microsoft® Network Access Protection (NAP)
- Bridge Protocol Data Unit (BPDU) blocking: Automatically shuts down user ports if an STP BPDU packet is seen to prevent topology loops
- STP Root Guard: Prevents edge devices from becoming STP root nodes

Traffic filtering

- ACLs to filter out unwanted traffic including denial of service (DoS) attacks; flow-based filtering in hardware (layer 1 to layer 4)

Converged networks

PoE

- Dynamic PoE allocation delivers only the power needed by the attached device up to the total power budget for most efficient power consumption
- PoE models support Alcatel-Lucent IP phones and WLAN access points, as well as any IEEE 802.3af-compliant end device
- Configurable per-port PoE priority and maximum power for power allocation

QoS

- Priority queues: Eight hardware-based queues per port for flexible QoS management
- Traffic prioritization: Flow-based QoS with internal and external prioritization (also known as re-marking)
- Bandwidth management: Flow-based bandwidth management, ingress rate limiting and egress rate shaping per port
- Queue management with configurable scheduling algorithm: Strict Priority Queuing (SPQ), Weighted Round Robin (WRR) and Deficit Round Robin (DRR)
- Congestion avoidance: Support for End-to-End Head-of-Line (E2E-HOL) blocking prevention and flow control
- LLDP network polices for dynamic designation of VLAN-ID and layer-2/layer-3 priority for IP phones
- Auto-QoS for switch management traffic as well as traffic from Alcatel-Lucent IP phones

IPv4 routing

- Static routing, Routing Information Protocol (RIP) v1 and v2
- Open Shortest Path First (OSPF) v2, Intermediate System-to-Intermediate System (IS-IS), Border Gateway Protocol (BGP) v4
- Generic Routing Encapsulation (GRE) tunneling
- Graceful restart extensions for OSPF and BGP
- VRRP v2
- DHCP relay (including generic UDP relay)
- ARP
- IP SLA measurement

IPv6 routing

- Static routing
- Routing Information Protocol Next Generation (RIPng)
- OSPF v3
- BGP v4 (with extensions to IPv6 routing)
- Graceful restart extensions for OSPF and BGP
- VRRP v3
- Neighbor Discovery Protocol (NDP)

IPv4/IPv6 multicast

- Internet Group Management Protocol (IGMP) v1/v2/v3 snooping for optimized multicast traffic
- Protocol Independent Multicast – Sparse Mode (PIM-SM)/Protocol Independent Multicast – Dense Mode (PIM-DM)
- Distance Vector Multicast Routing Protocol (DVMRP)
- Multicast Listener Discovery (MLD) v1/v2 snooping for optimized multicast traffic

Metro Ethernet access

- Ethernet services support per IEEE 802.1ad Provider Bridge services (also known as Q-in-Q or VLAN stacking):
 - Service VLAN (SVLAN) and Customer VLAN (CVLAN) transparent LAN services
 - Ethernet network-to-network interface (NNI) and user network interface (UNI) services
 - Service Access Point (SAP) profile identification
 - CVLAN-to-SVLAN translation
- Ethernet OA&M compliant with ITU Y.1731 and IEEE 802.1ag version 8.1 for connectivity fault and performance management and IEEE 802.3ah EFM for link OA&M
- Service Assurance Agent (SAA) for SLA compliance validation
- Private VLAN feature for user traffic segregation
- MAC-Forced Forwarding support according to RFC 4562
- DHCP Option 82: Configurable relay agent information
- IP Multicast VLAN (IPMVLAN)
- Optimized Ethernet access services delivery
 - Network bandwidth protection against overload of video traffic
 - Multicast streams isolation from multiple content providers over the same interface
- MEF 9 and 14 certified
- Managed by Alcatel-Lucent 5620 Service Aware Manager

Supported standards

IEEE standards

- IEEE 802.1D (STP)
- IEEE 802.1p (CoS)
- IEEE 802.1Q (VLANs)
- IEEE 802.1ad (Provider Bridges)
- IEEE 802.1ag (Connectivity Fault Management)
- IEEE 802.1ak (Multiple VLAN Registration Protocol)
- IEEE 802.1s (MSTP)
- IEEE 802.1w (RSTP)
- IEEE 802.1X (Port-based Network Access Control)
- IEEE 802.3i (10Base-T)
- IEEE 802.3u (Fast Ethernet)
- IEEE 802.3x (Flow Control)
- IEEE 802.3z (Gigabit Ethernet)
- IEEE 802.3ab (1000Base-T)
- IEEE 802.3ac (VLAN Tagging)
- IEEE 802.3ad (Link Aggregation)
- IEEE 802.3ae (10G Ethernet)
- IEEE 802.3af (Power over Ethernet)

ITU-T recommendations

- ITU-T G.8032, June 2007 draft (Ethernet Ring Protection)
- ITU-T Y.1731 OA&M fault and performance management

IETF standards

IPv4

- RFC 2003 IP/IP Tunneling
- RFC 2784 GRE Tunneling

OSPF

- RFC 1253/1850/2328 OSPF v2 and MIB
- RFC 1587/3101 OSPF NSSA Option
- RFC 1765 OSPF Database Overflow
- RFC 2154 OSPF MD5 Signature
- RFC 2370/3630 OSPF Opaque LSA
- RFC 3623 OSPF Graceful Restart

RIP

- RFC 1058 RIP v1
- RFC 1722/1723/2453/1724 RIP v2 and MIB
- RFC 1812/2644 IPv4 Router Requirements
- RFC 2080 RIPng for IPv6

BGP

- RFC 1269/1657 BGP v3 and v4 MIB
- RFC 1403/1745 BGP/OSPF Interaction
- RFC 1771-1774/2842/2918/3392 BGP v4
- RFC 1965 BGP AS Confederations
- RFC 1966 BGP Route Reflection
- RFC 1997/1998 BGP Communities Attribute
- RFC 2042 BGP New Attribute
- RFC 2385 BGP MD5 Signature
- RFC 2439 BGP Route Flap Damping
- RFC 2545 BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing
- RFC 2796 BGP Route Reflection
- RFC 2858 Multiprotocol Extensions for BGP-4
- RFC 3065 BGP AS Confederations

IS-IS

- RFC 1142 OSI IS-IS for Intra-domain Routing Protocol
- RFC 1195 OSI IS-IS for Routing
- RFC 2763 Dynamic Host Name
- RFC 2966 Route Leaking
- RFC 3719 Interoperable Networks
- RFC 3787 Interoperable IP Networks Using IS-IS

IP multicast

- RFC 1075 DVMRP
- RFC 1112 IGMP v1
- RFC 2236/2933 IGMP v2 and MIB
- RFC 2362/4601 PIM-SM
- RFC 2365 Multicast
- RFC 2715/2932 Multicast Routing MIB
- RFC 2934 PIM MIB for IPv4
- RFC 3376 IGMPv3
- RFC 5060 Protocol Independent Multicast MIB
- RFC 5132 IP Multicast MIB
- RFC 5240 PIM Bootstrap Router MIB

IPv6

- RFC 1886/3596 DNS for IPv6
- RFC 2292/2553/3493/3542 IPv6 Sockets
- RFC 2373/2374/3513/3587 IPv6 Addressing
- RFC 2460/2461/2462/2464 Core IPv6
- RFC 2461 NDP
- RFC 2463/2466/4443 ICMP v6 and MIB
- RFC 2452/2454 IPv6 TCP/UDP MIB
- RFC 2893/4213 IPv6 Transition Mechanisms
- RFC 3056 IPv6 Tunneling
- RFC 3595 TC for Flow Label
- RFC 4007 IPv6 Scoped Address Architecture
- RFC 4193 Unique Local IPv6 Unicast Addresses

Manageability

- RFC 854/855 Telnet and Telnet options
- RFC 959/2640 FTP
- RFC 1155/2578-2580 SMI v1 and SMI v2
- RFC 1157/2271 SNMP
- RFC 1212/2737 MIB and MIB-II
- RFC 1213/2011-2013 SNMP v2 MIB
- RFC 1215 Convention for SNMP Traps
- RFC 1350 TFTP Protocol
- RFC 1573/2233/2863 Private Interface MIB
- RFC 1643/2665 Ethernet MIB
- RFC 1901-1908/3416-3418 SNMP v2c
- RFC 2096 IP MIB
- RFC 2131 DHCP server/client
- RFC 2570-2576/3411-3415 SNMP v3
- RFC 2616/2854 HTTP and HTML
- RFC 2667 IP Tunneling MIB
- RFC 2668/3636 IEEE 802.3 MAU MIB
- RFC 2674 VLAN MIB
- RFC 3414 User-based Security Model
- RFC 4251 Secure Shell Protocol Architecture
- RFC 4252 The Secure Shell (SSH) Authentication Protocol
- RFC 4878 OA&M Functions on Ethernet-Like Interfaces

Security

- RFC 1321 MD5
- RFC 2104 HMAC Message Authentication
- RFC 2138/2865/2868/3575/2618 RADIUS Authentication and Client MIB
- RFC 2139/2866/2867/2620 RADIUS Accounting and Client MIB
- RFC 2228 FTP Security Extensions
- RFC 2284 PPP EAP
- RFC 2869/2869bis RADIUS Extension

QoS

- RFC 896 Congestion Control
- RFC 1122 Internet Hosts
- RFC 2474/2475/2597/3168/3246 DiffServ
- RFC 2697 srTCM
- RFC 2698 trTCM
- RFC 3635 Pause Control

Others

- RFC 768 UDP
- RFC 791/894/1024/1349 IP and IP/Ethernet
- RFC 792 ICMP
- RFC 793/1156 TCP/IP and MIB
- RFC 826/903 ARP and Reverse ARP
- RFC 919/922 Broadcasting Internet Datagram
- RFC 925/1027 Multi LAN ARP/Proxy ARP
- RFC 950 Subnetting
- RFC 951 BOOTP
- RFC 1151 RDP
- RFC 1191/1981 Path MTU Discovery
- RFC 1256 ICMP Router Discovery
- RFC 1305/2030 NTP v3 and Simple NTP
- RFC 1493 Bridge MIB
- RFC 1518/1519 CIDR
- RFC 1541/1542/2131/3396/3442 DHCP
- RFC 1757/2819 RMON and MIB
- RFC 2131/3046 DHCP/BOOTP Relay
- RFC 2132 DHCP Options
- RFC 2251 LDAP v3
- RFC 2338/3768/2787 VRRP and MIB
- RFC 3021 Using 31-bit Prefix
- RFC 3060 Policy Core
- RFC 3176 sFlow
- RFC 4562 MAC-Forced Forwarding

OmniSwitch 9000 CLS ordering

PART NUMBER	DESCRIPTION
BUNDLES	
OS9600-CB-A	OmniSwitch 9600 Base Bundle (1 chassis, 1 PSU and 1 CMM) for AC power
OS9700-CB-A	OmniSwitch 9700 Base Bundle (1 chassis, 2 PSUs and 1 CMM) for AC power
OS9800-CB-A	OmniSwitch 9800 Base Bundle (1 chassis, 3 PSUs and 1 CMM) for AC power
OS9600-RCB-A	OmniSwitch 9600 Redundant Bundle (1 chassis, 2 PSUs and 1 CMMs) for AC power
OS9700-RCB-A	OmniSwitch 9700 Redundant Bundle (1 chassis, 3 PSUs and 2 CMMs) for AC power
OS9800-RCB-A	OmniSwitch 9800 Redundant Bundle (1 chassis, 4 PSUs and 2 CMMs) for AC power
CHASSIS AND POWER SUPPLIES	
OS9600-CHASSIS	5-slot chassis – 4 dedicated slots for any OmniSwitch 9000 NIs, 1 dedicated slot for OS9600-CMM/OS9700-CMM (management and switching fabric)
OS9700-CHASSIS	10-slot chassis – 8 dedicated slots for any OmniSwitch 9000 NIs, 2 dedicated slots for OS9600-CMM/OS9700-CMM (management and switching fabric)
OS9702-CHASSIS	10-slot chassis – 8 dedicated slots for any OmniSwitch 9000 NIs, 2 dedicated slots for OS9600-CMM/OS9700-CMM (management and switching fabric), NEBS ready
OS9800-CHASSIS	18-slot chassis – 16 dedicated slots for any OmniSwitch 9000 NIs, 2 dedicated slots for OS9800-CMM (management and switching fabric)
OS9-PS-0725A	725 W AC power supply for OmniSwitch 9000/9000E
OS9-PS-0600D	600 W DC power supply for OmniSwitch 9000/9000E
OS9-PS-0725D	725 W DC power supply for OmniSwitch 9000/9000E
OS9-IP-SHELF	PoE rack (4-slot) for OmniSwitch 9000 chassis. Rack to include a 600 W AC PSU (OS9-IPS-0600A)
OS9-IPS-0230A	PoE rack (1-slot) for OmniSwitch 9600 chassis. Rack to include a 230 W AC power supply
OS9-IPS-0390A	PoE rack (1-slot) for OmniSwitch 9600 chassis. Rack to include a 390 W AC power supply
OS9-IPS-0600A	600 W AC PoE PSU (100 V to 240 V) for use within OS9-IP-SHELF only
MANAGEMENT AND SWITCHING FABRIC MODULES	
OS9600-CMM	OmniSwitch 9600 Chassis Management Module for use in the OmniSwitch 9600/9700/9702 chassis
OS9700-CMM	OmniSwitch 9700 Chassis Management Module for use in the OmniSwitch 9600/9700/9702 chassis
OS9800-CMM	OmniSwitch 9800 Chassis Management Module for use in the OmniSwitch 9800 chassis
NETWORK INTERFACE CARDS	
OS9-XNI-U2	OmniSwitch 9000 Network Interface with 2 unpopulated ports of 10GBase-X (XFP MSA)
OS9-XNI-U6	OmniSwitch 9000 Network Interface with 6 unpopulated ports of 10GBase-X (XFP MSA)
OS9-GNI-U24	OmniSwitch 9000 Network Interface with 24 unpopulated ports of 1000Base-X MiniGBIC (SFP MSA)
OS9-GNI-C24	OmniSwitch 9000 Network Interface with 24 ports of 10/100/1000Base-T/TX (RJ-45)
OS9-GNI-P24	OmniSwitch 9000 Network Interface with 24 ports of 10/100/1000Base-T/TX (RJ-45), PoE-capable
OS9-GNI-C48T	OmniSwitch 9000 Network Interface with 48 ports of 10/100/1000Base-T/TX (MRJ21)
OS9-GNI-C20L	OmniSwitch 9000 Network Interface with 20 ports of 10/100Base-T/TX (RJ-45, software-upgradable to 10/100/1000) and 2 ports 1000Base-X MiniGBIC (SFP)
ADVANCED SOFTWARE	
OS9-C20L-UPG	Software upgrade for one OS9-GNI-C20L module to provide 1000Base-T support
OS9-SW-IPSEC	IPSec software license for OmniSwitch 9000/9000E to enable support of IPSec for securing IPv6 routing protocols (RIPng/OSPFv3)
ACCESSORIES	
OS9600-FTTC	Low noise fan tray for OmniSwitch 9600 systems
OS9000-FTTC	Low noise fan tray for OmniSwitch 9700/9702/9800 systems

Contact your Alcatel-Lucent reseller for additional information on country-specific power cords and a complete list of Alcatel-Lucent SFP and XFP transceivers and MRJ21 cables.

Service and support

Warranty

Limited warranty to the original owner of one year on hardware and 90 days on software.

www.alcatel-lucent.com Alcatel, Lucent, Alcatel-Lucent, the Alcatel-Lucent logo, IP Touch, OmniSwitch and OmniVista are trademarks of Alcatel-Lucent. All other trademarks are the property of their respective owners. The information presented is subject to change without notice. Alcatel-Lucent assumes no responsibility for inaccuracies contained herein. Copyright © 2010 Alcatel-Lucent. All rights reserved. EPG3310100403 (05)

