



8-Port Gigabit PoE Smart Switch with 2 Gigabit

PoE to Power and Connect Devices and Gigabit Speed for Small Businesses

Gigabit Speed for Small Businesses

The EGS2110P is a Smart PoE Switch that offers 8 Gigabit ports with IEEE802.3af PoE Support on all its ports and 2 SFP slots for fiber uplinks.

Power Over Ethernet (PoE)

EnGenius Smart PoE (Power-over-Ethernet) Gigabit Switches are specifically designed to meet the needs of start-up and small-to-medium sized businesses. It's ideal for companies that need a way to connect and power VoIP phone systems, IP Cameras and Wireless Access Points throughout their facilities. These robust and fully-managed, yet cost-effective switches will help to keep their employees connected, safe and productive. The EGS2110P delivers up to 15.4 watts over connected Ethernet cables to powered devices. Total PoE budget is 61.6 watts.

Management

EnGenius switches also include embedded QoS intelligence to prioritize delay-sensitive services such as voice and video, simplify unified communications deployments, and help ensure consistent network performance for all services. For example, automated voice VLAN capabilities let you plug any IP phone into your IP telephony network and receive an immediate dial tone.

Key Features

- + 8 Gigabit ports with IEEE802.3af PoE support
- + 2 SFP Slots
- + External Power Adapter with 61.6w PoE
- + Budget
- + Provides PoE Management on all ports
- + Loopback Detection
- + IGMP Snooping
- + Bandwidth Control
- + IEEE802.1Q VLAN
- + IEEE802.1p QoS

Standard

Switching Capacity: 20 Gbps
Max. Forwarding Rate (64kBytes): 14.88Mpps
Forwarding Mode: Store and Forward
Packet Buffer memory: 512K Bytes
Flash Memory: 4 MB

Port Functions

8 10/100/1000Mbps Ports in the front panel
2 1000Mbps SFP Slot

PoE Capability

PoE standard: Port 1~8 Support IEEE 802.3af
PoE Capable Ports: Port 1~8 can output up to 15.4W
PoE budget: 61.6 Watts

LED Indicator

Device:
Power LED x1
Fault LED x1
PoE Max LED x1
LAN Mode LED x1
PoE Mode LED x1
SFP/Copper Ports:
LAN/PoE Mode, Link/Act

Environment & Mechanical

Temperature Range
Operating: 32 to 104°F / 0 to 40°C
Storage: -40 to 158°F / -40 to 70 °C

Humidity (non-condensing)

5% - 95%

L2 Features

Loopback Detection
IGMP Snooping v1/v2
Port Mirroring: one to one and many to one
Static MAC Address
Dynamic MAC List
Bandwidth Control

802.1Q VLAN
Port-based VLAN
Storm Control

PoE Management

Power on/off per port
Power Class Configuration
Power feeding with priority
User defined power limit

BootP/DHCP Client

Firmware Burn-Proof
Cable Diagnostic

