

# EAP150

## Business Class, Indoor Long Range Wireless-N Access Point/WDS/Repeater



### Key Differentiators

#### HIGH-POWER, LONG-RANGE WI-FI

Up to 26dBm RF Tx power provides greater Wi-Fi coverage compared to mainstream competitors

#### WIRELESS-N 3X SPEED OVER 802.11G NETWORKS

Maximum data rate up to 150Mbps

Backward compatible with 802.11 b/g

#### AESTHETIC DESIGN

"Smoke Detector" Design – Unobtrusive design can be easily mounted to wall and ceiling

#### SSID TO VLAN MAPPING

Supports 802.1q mapping of SSIDs with up to 4 VLANs

#### 802.3AF POE COMPATIBLE

Supports Power over Ethernet (IEEE 802.3af) and allows deployment in areas where power outlets are not available

#### INTEGRATED ANTENNA

Internal 5dBi antenna with optimized configuration and RF performance

### Ideal For:



- HOTELS & RESORTS
- CAMPUSES & CLASSROOMS
- PUBLIC HOTSPOTS
- CONFERENCE ROOMS
- MULTI-STORY HOMES
- COMMON AREAS
- WAREHOUSES
- RESTAURANTS

SSID TO VLAN MAPPING SEGMENTS USERS ON THE NETWORK



# EAP150 – Technical Specifications

Specifications may change without notice.

## HARDWARE SPECIFICATIONS

MCU/RF	RTL8196C + RTL8188RE
Memory	32 MB
Flash	4 MB
Physical Interface	LAN: 1 x 10/100 Fast Ethernet RJ-45 Reset Button Power Jack
LED Indicators	Power Status LAN (10/100Mbps) WLAN (Wireless connection)
Power requirement	Power Supply: 90 to 240 VDC ± 10%, 50/60 Hz (depends on different countries) Active Ethernet (Power over Ethernet, IEEE802.3af) 48 VDC/0.375A Device: 12V/1A

## RF SPECIFICATIONS

Wireless standard	IEEE802.11 b/g/n																											
Frequency	2.400 ~ 2.484GHz (b/g/n)																											
Modulation Technologies	OFDM: BPSK, QPSK, 16-QAM, 64-QAM DBPSK, DQPSK, CCK																											
Operating Channels	11 channels																											
Transmit Power	<table border="1"> <tr> <th>802.11b(2.412 ~ 2.472GHz)</th> <th>802.11g(2.412 ~ 2.472GHz)</th> <th>802.11n(2.412 ~ 2.472GHz)</th> </tr> <tr> <td>26 dBm @ 1Mbps</td> <td>26 dBm @ 6Mbps</td> <td>26 dBm @ MCS0/MCS8</td> </tr> <tr> <td>26 dBm @ 2Mbps</td> <td>26 dBm @ 9Mbps</td> <td>26 dBm @ MCS1/MCS9</td> </tr> <tr> <td>26 dBm @ 5.5Mbps</td> <td>25 dBm @ 12Mbps</td> <td>25 dBm @ MCS2/MCS10</td> </tr> <tr> <td>26 dBm @ 11Mbps</td> <td>25 dBm @ 18Mbps</td> <td>25 dBm @ MCS3/MCS11</td> </tr> <tr> <td></td> <td>24 dBm @ 24Mbps</td> <td>24 dBm @ MCS4/MCS12</td> </tr> <tr> <td></td> <td>24 dBm @ 36Mbps</td> <td>24 dBm @ MCS5/MCS13</td> </tr> <tr> <td></td> <td>23 dBm @ 48Mbps</td> <td>23 dBm @ MCS6/MCS14</td> </tr> <tr> <td></td> <td>23 dBm @ 54Mbps</td> <td>23 dBm @ MCS7/MCS15</td> </tr> </table>	802.11b(2.412 ~ 2.472GHz)	802.11g(2.412 ~ 2.472GHz)	802.11n(2.412 ~ 2.472GHz)	26 dBm @ 1Mbps	26 dBm @ 6Mbps	26 dBm @ MCS0/MCS8	26 dBm @ 2Mbps	26 dBm @ 9Mbps	26 dBm @ MCS1/MCS9	26 dBm @ 5.5Mbps	25 dBm @ 12Mbps	25 dBm @ MCS2/MCS10	26 dBm @ 11Mbps	25 dBm @ 18Mbps	25 dBm @ MCS3/MCS11		24 dBm @ 24Mbps	24 dBm @ MCS4/MCS12		24 dBm @ 36Mbps	24 dBm @ MCS5/MCS13		23 dBm @ 48Mbps	23 dBm @ MCS6/MCS14		23 dBm @ 54Mbps	23 dBm @ MCS7/MCS15
802.11b(2.412 ~ 2.472GHz)	802.11g(2.412 ~ 2.472GHz)	802.11n(2.412 ~ 2.472GHz)																										
26 dBm @ 1Mbps	26 dBm @ 6Mbps	26 dBm @ MCS0/MCS8																										
26 dBm @ 2Mbps	26 dBm @ 9Mbps	26 dBm @ MCS1/MCS9																										
26 dBm @ 5.5Mbps	25 dBm @ 12Mbps	25 dBm @ MCS2/MCS10																										
26 dBm @ 11Mbps	25 dBm @ 18Mbps	25 dBm @ MCS3/MCS11																										
	24 dBm @ 24Mbps	24 dBm @ MCS4/MCS12																										
	24 dBm @ 36Mbps	24 dBm @ MCS5/MCS13																										
	23 dBm @ 48Mbps	23 dBm @ MCS6/MCS14																										
	23 dBm @ 54Mbps	23 dBm @ MCS7/MCS15																										
Receiver Sensitivity	802.11b (2.412 ~ 2.472 GHz) best ≤ -90 dBm 802.11g (2.412 ~ 2.472 GHz) best ≤ -88 dBm 802.11n (2.412 ~ 2.472 GHz) best ≤ -85 dBm																											
Antenna	Embedded omnidirectional antenna (Diversity support) Antenna Gain = 5 dBi																											

## SOFTWARE SPECIFICATIONS




Topology	Infrastructure/Ad-Hoc
Operation Mode	Access Point/WDS/Repeater
Multiple BSSID	Supports up to 4 BSSIDs
LAN	IP (check validity and DHCP server IP range) MAC
VLANs	Supports 802.1q (up to 4 VLANs) SSID to VLAN mapping
Spanning Tree	Supports 802.1d Spanning Tree Protocol
Wireless	Wireless mode: 11b/11g/11n Channel selection (setting varies by country) Channel bandwidth (Auto, 20MHz, 40MHz) Transmission rate: 11n only, 11b/g/n mix, 11b only, 11b/g, 11g only
VPN	VPN pass-through (PPTP, L2TP, IPSEC)
QoS	WMM
WPS	Software only
Security	WEP Encryption - 64/128 bit WPA Personal (WPA-PSK using TKIP or AES) WPA Enterprise (WPA-EAP using TKIP) 802.1x Authenticator SSID broadcast enable/disable MAC Address Filter(AP mode) WLAN L2 isolation(AP mode) Wireless STA (Client) connected list (Idle/Connection Time, Pkt statistics)

## MANAGEMENT

Tx Power Control	Adjust transmit power by dBm
Configuration	Web-based configuration (HTTP)/Telnet
Telnet Server	Supports up to 4 BSSIDs
LAN	CLI
Firmware Upgrade	Upgrade firmware via web browser
Administrator Setting	Administrator Username & Password change
Reset Setting	Reboot (press 1 second). Reset to Factory Default (press 10 second)
System Monitoring	Status Statistic and Event log
SNMP	V1 , V2c
MIB	MIB 1 , MIB II(RFC1213) and Private MIB
Traffic Measurement	Per interface
Auto-channel Selection	Automatically selecting least congested channel
Bandwidth Measurement	IP range and bandwidth management
Backup & Restore	Save & restore settings through Web interface
Diagnosis	IP pingng statistics

## ENVIRONMENT & PHYSICAL

Temperature Range	Operating: 0 to 50° C (32° to 122° F) Storage: -20 to 60° C (-4° to 140° F)
Humidity (non-condensing)	Operating: 90% or less Storage: 90% of less
Dimensions	Diameter: 4.73" (120mm) Height: 1.97" (50mm)
Weight	0.62 lb. (280g)
Certifications	FCC, CE, IC



EnGenius Technologies 1580 Scenic Avenue • Costa Mesa, CA 92626, USA  
888.735.7888

