

ESR350





Key Features

- + Up to 300 Mbps on 2.4 GHz
- + Extended Signal Coverage with Xtra Range™ Technology
- + Gigabit Ports for High AV Performance
- + Parental Controls
- + Guest Network Settings

Wireless N300 Home Router

Single Band N300 Router + Gigabit Switch + USB Media Streaming

The work-n-play Wireless N router with extended signal coverage for your home.

Robust and Reliable Wireless Performance

The ESR350 Wireless N300 Home Pod is an Xtra Range 2.4 GHz, 4-Port Wireless-N Router with wireless speeds up to 300 Mbps. This cost-effective router offers robust wired and wireless connectivity and performance for computers, smartphones, tablet PCs and home entertainment devices in a home.

Gigabit Wired Speed & Shared USB Media

Includes a built-in 4-Port Gigabit Switch and Gigabit WAN port for 10x faster throughput than Fast Ethernet making large file transfers, video and other media streaming incredibly fast. USB port to attach storage so connected devices in your home can access and stream video, music, and other media.

Industry-Standard Wireless Security

The ESR350 supports several security features and settings including industry-standard WPA/WPA2 wireless encryption to prevent unauthorized access to the network; a SPI (Stateful Packet Inspection) firewall to block malicious software from the Internet from accessing networked devices; MAC Address filtering to grant only known computers and devices network access; and URL filtering to block access to unwanted or offensive websites.

USB Media Anywhere with EnShare™

Attach a storage device to the router's USB port and with EnShare you can start sharing media content like photos, music, or videos throughout the home or even access and download that content when you're away from home to your mobile devices like smartphones or tablet and laptop PCs. EnShare also enables you to upload files to your attached storage device anywhere you can get an Internet connection.





Technical Specifications

Device Interface

1x Gigabit WAN Port

4x Gigabit LAN Ports

1x USB2.0 Port

1x Push Button for WPS

1x Reset

IEEE Standards

802.11b/g/n 802.3i/u/ab

LED Indicators

Power

WLAN (Wireless Connection)

Internet

Package Contents

1x ESR350

1x Power Adapter (12V 1A)

1x Ouick Start Guide

1x EnShare™ Guide

1x RJ-45 Ethernet Cable

Power Specification

External Power Adapter DC IN, 12V 1A

Certification

FCC/CE/IC

Physical/Environmental Condition

Operation Temperature: Temperature $0^{\circ} \approx 40^{\circ}$ Humidity 90% or less (Non-condensing) Storage Temperature: Temperature $-20^{\circ} \approx 60^{\circ}$ Humidity 95% or less (Non-condensing)

Software Features

Operation Mode:

AP Router/WDS

Wireless Features:

Auto Channel Selection

Output Power Control

WMM (WiFi Multimedia)

MSSID (Multiple SSID)

Security:

WEP/WPA-PSK/WPA2-PSK

TKIP/AES

Hidden SSID

Maximum data rates are based on IEEE 802.11 standards. Actual throughput and range may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment, and mix of devices in the network. EnGenius Technologies, Inc. EnShareTM supports both FAT32 and NTFS USB formats. Transfer speeds of data from your router-attached USB storage device to a remote/mobile device may vary based on Internet uplink and downlink speeds, bandwidth traffic at either send or receive locations, the data retrieval performance of the attached storage device or other factors. EnGenius does not guarantee compatibility with all USB drives. EnGenius does not warrant its products or EnShare from loss of data or loss of productivity time. Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. For United States of America: Copyright ©2013 EnGenius Technologies, Inc. All rights reserved.

MAC Address Filtering 802.1X Authentication

DDoS

DHCP Server/Client

NAT

Port Forwarding

DMZ

Port Mapping/Triggering

VPN Server (PPTP/L2TP)

VPN Client (PPTP/L2TP)

VPN Pass-trough (PPTP/L2TP/IPSec)

VPN Tunnel (Max. 5)

QoS

IP Filtering

Port Filtering

DDNS

IPv6 Pass-through

MAC Clone

Traffic Monitor

WAN Type: PPPoE/DHCP/Static IP

USB Features: SAMBA

Warranty

1 Year Limited Warranty

Physical Interface

1. Wireless LED 5. Power Connector

2. Power LED3. Internet LED4. USB Port & WPS Button6. WAN Port7. LAN Ports8. Reset Button



