



Features :

- 1-Line Digital Long Range Cordless, Base w/ Dialing Keypad & Speakerphone
- Frequency band: 863~865MHz
- **38** channel auto-scan
- Channel spacing: 50KHz
- Long range
 - Default up to **1km**
- Expandable handset (up to **9** handsets)
- Multi-base (up to 4 bases)
- Vibration mode
- Mono display
- LCD backlight (White)
- Display multiple language –

English / French / German / Italian / Spanish

- ETSI Caller ID supported
- Call log (Dialed/Received/Missed call)
- Date/Time stamp (For Caller ID)
- Key guard
- Call timer
- 50 names / number phonebook
- Handset speakerphone
- Two-way intercom
- Broadcasting
- Call hold
- Call Barring (For outgoing call)
- Call manager
- Call park
- Mute
- Flash (100ms ~ 900ms)
- Redial (Last 10 calls)
- Call barring (For outgoing call)
- 6 level volume control
- Feature call
- Auto-answer
- Any key answer
- Auto hang up
- Prefix
- Keytone volume
- Ringer volume
- Selectable ring tone (For Incoming call)
- Selectable ring tone (For intercom)
- Low battery alarm and display
- Hearing aid compatible
- External handset/base antenna
- Built-in 2.5mm headset jack
- Optional outdoor antenna – sold separately
- Programmable PBX option key
- Regulatory Compliance (mandatory)

- ETSI EN 301 357-2 (Radio for Cordless Audio)
- ETSI EN 301 489-3 (EMC for Cordless Audio)
- EN 60950
- EN 50371 (RF safety)
- RoHS compliant
- Handset Keypad:
 - Talk/Flash
 - Speakerphone
 - PTT (Broadcast)
 - End/Power
 - Intercom
 - Caller ID
 - Hold
 - Softkey x 2
 - Up/Down key
 - Standard dialing keys (0-9, *, #)
 - Redial (softkey)
 - Menu (softkey)
 - Mute (softkey)
- Base keypad:
 - Up/Down key
 - Standard dialing keys (0-9, *, #)
 - Redial/P
 - Flash
 - Hold
 - Memory
 - Transfer
 - Speakerphone
 - Intercom/Broadcast
 - Reset (rear)
 - REG (rear)
- Base LED:
 - Power
 - In Use

- Broadcast
- DC jack
- Tel jack
- Line jack
- Battery:
 - Standard: 1100mAh, Li-ion
 - Optional: 1700mAh, Li-ion
- Standby time: 50Hours (80 hours for optional battery)
- Talk time: 3 hours (4~5 hours for optional battery)
- Charger (single slot for handset only)

EP801 Technical Specification

Electrical Specifications	Base Station	Portable Handset
Frequency	863-865 MHz	863-865 MHz
RF Output Power (Option)	Peak: 8 dBm	Peak: 10 dBm
Channel Spacing	50 kHz	50 kHz
Number of Channels	38	38
Modulation	MSK	MSK
TDDFrame Length	10 ms	10 ms
Number of Slots/Frame	2	2
Receiver Sensitivity	<-118dBm (@ BER 10-2)	<-118dBm (@ BER 10-2)
Antenna Gain	2 dBi	0 dBi
Antenna Connector	Reverse TNC	Reverse SMA
Telephone Interface	RJ11 x 2	NA
Channel Coding	½ rateConvolutional + CRC	½ rateConvolutional + CRC
Transmission Data Rate	42.667kbps	42.667kbps
Speech Coding	8 kbps G.729A	8 kbps G.729A
User Data Rate	32kbps duplex	32kbps duplex
Duplex	Time Division Duplex (TDD)	Time Division Duplex (TDD)
Multiple Access	FDMA	FDMA
Voice Quality	TBR21 (Optional)	TBR21 (Optional)
Number of System ID	65,536	65,536
Ring Signal	20-50 Hz, 12-90 Vrms	NA
Flash Time	100-900 ms programmable	NA
Power Source	AC/DC 12V/1A Adapter	3.7 V/1100mAh Li-Ion Battery 3.7 V/1700mAh Li-Ion Battery (optional)

Charger Current	NA	700mA (900 mA for spare battery slot)
Charge Time	NA	3hours
Regulation Compliance	EN 301 357-2 (RF) EN 301 489 (EMC) EN 60950 (Safety)	EN 301 357-2 (RF) EN 301 489 (EMC) EN 60950 (Safety) EN 50371 (RF safety)
Operating Temperature	0 – 50 °C	-10 – 60 °C
Storage Temperature	-40– 70 °C	-40– 70 °C
Humidity	20 – 75 %	20 – 75 %
Dimension with antenna	188*161*42 mm	161*58*31 mm
Weight	424 g	175 g

Notes:

1. NA = Not Applicable.
2. The manufacturer reserves the right to change designs and specifications without notice.