

RUCKUS Analytics Release Notes Version 2.5

Copyright, Trademark and Proprietary Rights Information

© 2021 CommScope, Inc. All rights reserved.

No part of this content may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from CommScope, Inc. and/or its affiliates ("CommScope"). CommScope reserves the right to revise or change this content from time to time without obligation on the part of CommScope to provide notification of such revision or change.

Export Restrictions

These products and associated technical data (in print or electronic form) may be subject to export control laws of the United States of America. It is your responsibility to determine the applicable regulations and to comply with them. The following notice is applicable for all products or technology subject to export control:

These items are controlled by the U.S. Government and authorized for export only to the country of ultimate destination for use by the ultimate consignee or end-user(s) herein identified. They may not be resold, transferred, or otherwise disposed of, to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. government or as otherwise authorized by U.S. law and regulations.

Disclaimer

THIS CONTENT AND ASSOCIATED PRODUCTS OR SERVICES ("MATERIALS"), ARE PROVIDED "AS IS" AND WITHOUT WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED. TO THE FULLEST EXTENT PERMISSIBLE PURSUANT TO APPLICABLE LAW, COMMSCOPE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TITLE, NON-INFRINGEMENT, FREEDOM FROM COMPUTER VIRUS, AND WARRANTIES ARISING FROM COURSE OF DEALING OR COURSE OF PERFORMANCE. CommScope does not represent or warrant that the functions described or contained in the Materials will be uninterrupted or error-free, that defects will be corrected, or are free of viruses or other harmful components. CommScope does not make any warranties or representations regarding the use of the Materials in terms of their completeness, correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise. As a condition of your use of the Materials, you warrant to CommScope that you will not make use thereof for any purpose that is unlawful or prohibited by their associated terms of use.

Limitation of Liability

IN NO EVENT SHALL COMMSCOPE, COMMSCOPE AFFILIATES, OR THEIR OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, SUPPLIERS, LICENSORS AND THIRD PARTY PARTNERS, BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, EXEMPLARY OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER, EVEN IF COMMSCOPE HAS BEEN PREVIOUSLY ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT, OR ANY OTHER THEORY ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIALS. Because some jurisdictions do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of liability for consequential or incidental damages, some of the above limitations may not apply to you.

Trademarks

ARRIS, the ARRIS logo, COMMSCOPE, RUCKUS, RUCKUS WIRELESS, the Ruckus logo, the Big Dog design, BEAMFLEX, CHANNELFLY, FASTIRON, ICX, SMARTCELL and UNLEASHED are trademarks of CommScope, Inc. and/or its affiliates. Wi-Fi Alliance, Wi-Fi, the Wi-Fi logo, Wi-Fi Certified, the Wi-Fi CERTIFIED logo, Wi-Fi Protected Access, the Wi-Fi Protected Setup logo, Wi-Fi Protected Setup, Wi-Fi Multimedia and WPA2 and WMM are trademarks or registered trademarks of Wi-Fi Alliance. All other trademarks are the property of their respective owners.

Contents

- RUCKUS Analytics Introduction..... 4**
- New in This Release..... 4**
 - Changed Behavior..... 4
 - New Features..... 4
- Known Issues 5**
- Resolved Issues..... 6**

RUCKUS Analytics Introduction

RUCKUS Analytics is a cloud service for network intelligence and service assurance.

Powered by machine learning and artificial intelligence, it gives IT comprehensive visibility into network operations. It accelerates troubleshooting and helps IT teams meet their network SLAs. RUCKUS Analytics automatically identifies service assurance incidents, classifies them by severity, traces root causes and makes specific recommendations for remediation. It automatically monitors network health relative to customer defined SLA. Advanced client troubleshooting and incident analytics give IT teams the power to address service issues for individual users and devices. The service also delivers robust reporting and informative dashboards. Create custom dashboards and data visualizations with the Data Explorer tool—and flexibly explore your network data warehouse with drag-and-drop ease.

RUCKUS Analytics aggregates raw data and automatically transforms it into deep insight into network operations. This ML- and AI-powered analytics service frees IT teams a wide variety of manual tasks associated with service assurance. Comprehensive network intelligence helps deliver network service level agreements in support of users, devices and applications.

- Supported Browsers
 - Chrome
 - Firefox
 - Safari

RUCKUS Analytics runs on licenses purchased. A grace period of seven days is available after the license expires and you can only view your historical data for six months after it expires.

New in This Release

Changed Behavior

This section describes changes in product behavior, in this release.

- New dimensions Device Type and OS Vendor Type are included to Client Sessions and Client Info and Statistic data cubes.
RUCKUS Analytics is aligned to the rogue policies defined in SmartZone 5.1.1 and later. This implies that new rogue types will also appear in RUCKUS Analytics.
- Related configuration changes will now be displayed for all AP reboot incidents.
- Audit trail for mute/unmute incident action is now available by hovering over “Unmute” in the Action column in the Analytics page.
- Exact time for roaming events above 4 sec will now be displayed by hovering over the roaming event in Client Troubleshooting page.

New Features

RUCKUS Analytics has the following features.

- Service Validation now supports 2 options - **Virtual Client** and **Virtual Wireless Client**. For the Virtual Client option, the target AP to be tested will itself emulate as a Wi-Fi client and test the connection stages, without any actual RF transmission over the air. The benefit of this option is that Service Validation tests for the non-wireless portion of the network (e.g. DHCP, RADIUS, DNS, etc.) and can be simultaneously tested quickly over a large number of APs with no impact on existing Wi-Fi services.

For the Virtual Wireless Client option, there will be actual RF transmissions over the air. For every target AP to be tested, a corresponding "station AP" is selected. The station AP is a neighboring AP with the best signal strength, and during the test, this station AP will behave as a station (i.e. a Wi-Fi client) and wirelessly connect to the target AP, just like a regular Wi-Fi client, for the test. The benefit of this option is that the Service Validation test will comprehensively cover both wireless and wired portions of the network. However, during this test, the

station AP may need to switch its operating channel to be the same as the target AP. This change in channel may cause some disruptions to the end user Wi-Fi experience (e.g. during video calls). Thus, when Virtual Wireless Client is selected, the test procedure will be done one AP at a time to minimize disruption to the network, resulting in a longer test duration compared to the Virtual Client option.

NOTE

AP firmware version required to support this feature is 6.0.0.0.3067 and later.

Known Issues

This section describes the known caveats and limitations of the product.

- For Service Validation with virtual wireless client, only a neighbor on the same radio band can be used as the station AP. For example, if AP-1 has its 2.4 GHz radio turned off, it will not be used as the station AP for AP-2 even if AP-1 is the closest to AP-2.
- For Service Validation with virtual wireless client, there must be actual client traffic going through the target SSID. Otherwise, the test will fail.
- Mesh APs cannot operate as station APs in Service Validation with virtual wireless client.
- For new SSIDs, Service Validation tests with virtual wireless client are only available 24 hours after the SSID is created.
- In RUCKUS Cloud, the AP uptime data in Data Explorer is incorrect.
- For scheduled reports and dashboards, if the query times out, no reports or dashboards will be sent.
- For Configuration Change feature:
 - Firmware changes at the SmartZone are not recorded as a configuration change.
 - Indoor channel set to "auto" is displayed as 0 in the configuration change table.
 - Configuration change entries are created for both licensed and unlicensed APs.
 - SmartZone controller configuration changes at system level, domain level, profile configuration, creating and deleting zone, WLAN, WLAN group, AP group, AP and those related to moving APs between zones and AP groups are not supported.
 - KPI health metrics are displayed based on before and after time even if there are no configuration changes because various environment factors contribute to KPI changes other than configuration change.
 - Some configuration values such as Channel fly optimization period and AP time zone and so on do not appear in user-friendly format.
 - Multi-level configuration for parameters such as SNMP v2/v3 agent information and AP model specific configurations are not displayed.
 - Values of configuration parameters such as vlan_pool when disabled appear as 0.
 - Configuration change entries are not displayed when WLAN QosMapSet state is changed from disable to enable, after editing Internal DPSK WLAN, after changing RGRE to SGRE in CCM GBP, and for QinQ.
 - When AP configuration is changed for the first time after disabling mesh configuration, configuration change continues to detect change in mesh configuration.
 - When a configuration change is made on the SmartZone web interface, two changes are updated in the backend to maintain backward compatibility of features. RUCKUS Analytics displays this information for greater visibility of configuration changes.
 - Configuration change feature is not yet supported for RUCKUS Cloud tenants
- The Wi-Fi Connection Quality field is empty sometimes if the participants are not connected to a RUCKUS Wi-Fi network for the entire duration of the zoom call.
- If the Zoom call participants are connected through the VPN, then the Zoom server reports the clients as "wired" though they are connected to RUCKUS Wi-Fi.
- Creating a report in the Data Explorer page renders **Session Count** values ending with "k" such as 13.6k because the median number of the **Session Count** column is larger than 1000. The representation continues when the values grow into millions and billions as "m" and "b" respectively.

Resolved Issues

This section describes resolved issues. .

- An issue with the edit function for custom dashboards in Data Explorer has been resolved (ER-10698).

COMMScope®
RUCKUS®

© 2021 CommScope, Inc. All rights reserved.
350 West Java Dr., Sunnyvale, CA 94089 USA
<https://www.commscope.com>