

Ruckus ICX 7650 Switch Technical Specifications

Copyright Notice and Proprietary Information

© 2018 ARRIS Enterprises, LLC. All rights reserved.

No part of this documentation may be used, reproduced, transmitted, or translated, in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without prior written permission of or as expressly provided by under license from ARRIS.

Destination Control Statement

Technical data contained in this publication may be subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

THIS DOCUMENTATION AND ALL INFORMATION CONTAINED HEREIN ("MATERIAL") IS PROVIDED FOR GENERAL INFORMATION PURPOSES ONLY. ARRIS and RUCKUS WIRELESS, INC. AND THEIR LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THE MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE, OR THAT THE MATERIAL IS ERROR-FREE, ACCURATE OR RELIABLE. ARRIS and RUCKUS RESERVE THE RIGHT TO MAKE CHANGES OR UPDATES TO THE MATERIAL AT ANY TIME.

Limitation of Liability

IN NO EVENT SHALL ARRIS or RUCKUS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, OR DAMAGES FOR LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY YOU OR ANY THIRD PARTY, WHETHER IN AN ACTION IN CONTRACT OR TORT, ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIAL.

Trademarks

Ruckus Wireless, Ruckus, the bark logo, BeamFlex, ChannelFly, Dynamic PSK, FlexMaster, ICX, Simply Better Wireless, SmartCell, SmartMesh, SmartZone, Unleashed, ZoneDirector and ZoneFlex are trademarks of Ruckus Wireless, Inc. in the United States and in other countries. Other trademarks may belong to third parties.

Contents

Ruckus ICX 7650 Specifications

System specifications	5
Ethernet	5
LEDs	6
Other	6
Weight and physical dimensions	6
Environmental requirements	7
Power supply specifications (per PSU)	7
Power consumption (typical configuration)	7
Power consumption (maximum configuration)	8
Power consumption (modules)	8
Data port specifications (Ethernet)	9
Serial port specifications (pinout - USB Type-C)	9
Serial port specifications (pinout RJ-45)	10
Serial port specifications (protocol)	10
Memory specifications	11
Regulatory compliance (EMC)	11
Regulatory compliance (safety)	11
Regulatory compliance (environmental)	11

Ruckus ICX 7650 Specifications

- System specifications 5
- Ethernet..... 5
- LEDs 6
- Other 6
- Weight and physical dimensions..... 6
- Environmental requirements 7
- Power supply specifications (per PSU) 7
- Power consumption (typical configuration) 7
- Power consumption (maximum configuration) 8
- Power consumption (modules) 8
- Data port specifications (Ethernet) 9
- Serial port specifications (pinout - USB Type-C) 9
- Serial port specifications (protocol) 10
- Memory specifications..... 11
- Regulatory compliance (EMC)..... 11
- Regulatory compliance (safety) 11
- Regulatory compliance (environmental)..... 11

System specifications

System component	Description
Enclosure	Stackable up to 12 switches per stack, chassis-mountable (1U) in a standard 2 or 4-post rack
Power supplies	Dual redundant, hot-swappable power supplies supported with 250 W AC intake or exhaust airflow for non-PoE switches, 1000 W AC with intake or exhaust airflow for PoE switches.
Fans	Dual redundant, hot-swappable fan units with intake or exhaust airflow
Cooling	Forced-air cooling front-to-back or back-to-front
System architecture	Non-blocking shared-memory switch
System processors	BCM58712D with quad-core ARM Cortex-A57 processor running at 1.6 GHz

Ethernet

These are standard modules for shipping bundles. For Ruckus ICX 7650 non-bundled switches, expansion modules need to be ordered separately.

System component	Description	Maximum ports supported
100 GbE QSFP28 ports	40/100 GbE QSFP28 stacking or uplink port	2 (Module 3)
40 GbE QSFP+ ports	40 GbE QSFP+ stacking or uplink port	2 (Module 3)
10 GbE SFP+ ports	10 GbE SFP+ port	24 (ICX 7650-48F)
1 GbE SFP ports	1 GbE SFP port	24 (ICX 7650-48F)

Ruckus ICX 7650 Specifications

LEDs

System component	Description	Maximum ports supported
10 GbE RJ-45 ports	100M/1/2.5/5/10 GbE RJ-45 port	24 (ICX 7650-48ZP)
1 GbE RJ-45 ports	10/100/1000 Mbps RJ-45 port	24 (ICX 7650-48ZP) 48 (ICX 7650-48P)
Ethernet management port	10/100/1000 Mbps RJ-45 port	1

LEDs

System component	Description
Switch status and management	Seven LED types indicate switch status: PWR and PWR2 (power supply units) DIAG (diagnostics) SYS (system status) MSTR (stacking configuration) CLD (cloud management) UPDATE (software update) STAT, SPD, ID, USB, PoE status mode
Ports	LEDs indicate port status or switch ID based on the status mode selection

Other

System component	Description
Serial cable	1 (RJ-45 to RJ-45)
RJ-45 to DB9 adapter	1
AC power cord	IEC 320-C14

Weight and physical dimensions

Model	Height	Width	Depth	Weight (with basic modules)
ICX 7650-48ZP	4.37 cm 1.72 inches	44.00 cm 17.32 inches	40.64 cm 16 inches	8.01 kg 17.82 lb
ICX 7650-48P	4.37 cm 1.72 inches	44.00 cm 17.32 inches	40.64 cm 16 inches	7.50 kg 16.5 lb
ICX 7650-48F	4.37 cm 1.72 inches	44.00 cm 17.32 inches	40.64 cm 16 inches	7.10 kg 15.62 lb

Environmental requirements

Condition	Operational	Non-operational
Ambient Temperature	0°C to 45°C (32°F to 113°F) at sea level	-40°C to 70°C (-40°F to 158°F)
Relative Humidity (non-condensing)	10% to 90% at 50°C (122°F)	10% to 90% at 70°C (158°F)
Altitude (above sea level)	0 to 3,048 m (10,000 ft)	0 to 12,000 m (39,370 ft)
Shock	20 G, 11 ms, half-sine wave	33 G, 11 ms, half-sine wave
Vibration	1 G sine, 0.4 grms random, 5-500 Hz	2.4 G sine, 1.1 grms random, 5-500 Hz
Airflow	Nominal: 10-25 cfm, Maximum: 54-57 cfm.	N/A
Heat dissipation (+/- 5%)	NOTE: Refer to "Power consumption (typical configuration)" on page 7 and "Power consumption (maximum configuration)" on page 8 for detailed information on heat dissipation.	N/A
Operating noise	ICX 7650-48ZP: 56.4 dBA ICX 7650-48P: 46.7 dBA ICX 7650-48F: 48.3 dBA	N/A

Power supply specifications (per PSU)

Power supply model	Maximum output power rating (DC)	Input voltage	Input line frequency	Maximum input current	Input line protection	Maximum inrush current
RPS15-E	250 W	100-240 V~	50-60 Hz	4.0 A	Fuses	35 A
RPS15-I	250 W	100-240 V~	50-60 Hz	4.0 A	Fuses	35 A
RPS16-E	1000 W	100-240 V~	50-60 Hz	11.8 A	Fuses	35 A
RPS16-I	1000 W	100-240 V~	50-60 Hz	11.8 A	Fuses	35 A

Power consumption (typical configuration)

All 1-GbE and two 10-GbE ports are linked up (no other port links), loading with 10 percent traffic rate and no PoE load. Two fan FRUs, 4x10GF uplink. Fans at nominal speed.

ICX7650-48ZP: 24 1-GbE + 24 2.5-GbE and Slot 2: Empty, Slot 3: 2x40GQ ports are linked up, loading with 10 percent traffic rate. Two fans at nominal speed.

Model name (Input power ±5%)	@100 VAC input	@200 VAC input	Minimum number of power supplies	Notes
ICX 7650-48ZP	120.46 W 411.14 BTU/hr	118.59 W 404.76 BTU/hr	1 x 1000 W AC	1 PSU, no PoE load.
	130.57 W 445.65 BTU/hr	128.32 W 437.97 BTU/hr	2 x 1000 W AC	2 PSUs, no PoE load
ICX 7650-48P	129.7 W 443 BTU/hr	143 W 488 BTU/hr	1 x 1000 W AC	1 PSU, no PoE load.
	128.2 W 438 BTU/hr	141.1 W 482 BTU/hr	1 x 1000 W AC	2 PSUs, no PoE load

Ruckus ICX 7650 Specifications

Power consumption (maximum configuration)

Model name (Input power ±5%)	@100 VAC input	@200 VAC input	Minimum number of power supplies	Notes
ICX 7650-48F	141.4 W 420 BTU/hr	139.6 W 477 BTU/hr	1 x 250 W AC	1 PSU
	152.8 W 522 BTU/hr	151.6 W 518 BTU/hr	1 x 250 W AC	2 PSUs

Power consumption (maximum configuration)

All 1-GbE and two 10-GbE ports are linked up (no other port links), loading with 100 percent traffic rate and 100 percent PoE load. Two PSUs, two fan FRUs, 4x10GF uplink, fans at high speed.

ICX7650-48ZP: 24 1-GbE + 24 10-GbE and Slot 2: 4x10GF, Slot 3: 2x100GQ are linked up, 100 percent traffic and PoE load.

Model name (Input power ±5%)	@100 VAC input	@200 VAC input	Minimum number of power supplies	Notes
ICX 7650-48ZP	167.1 W 570.33 BTU/hr	164.06 W 559.95 BTU/hr	2 x 1000 W AC	1 PSU
	11853.08 W 6324.71 BTU/hr	1763.55 W 6019.14 BTU/hr	2 x 1000 W AC	2 PSUs required for PoE loading
ICX 7650-48P	998 W 3406 BTU/hr	958 W 3270 BTU/hr	1 x 1000 W AC	1 PSU
	1809 W 6174 BTU/hr	1769 W 6038 BTU/hr	1 x 1000 W AC	2 PSUs required for PoE loading
ICX 7650-48F	178.3 W 609 BTU/hr	175.7 W 606 BTU/hr	1 x 250 W AC	1 PSU
	196.4 W 670 BTU/hr	194.1 W 663 BTU/hr	1 x 250 W AC	2 PSUs

Power consumption (modules)

Name	Description	Power consumption
ICX7650-4X10GF	4-port 1/10 GbE SFP+ expansion module	Typical = 12.96 W Maximum = 15.72 W
ICX7650-2X40GQ	2-port 40 GbE QSFP+ data uplink / stacking module	Typical = 5.64 W Maximum = 7.38 W
ICX7650-1X100GQ	1-port 100 GbE QSFP28 data uplink / stacking module	Typical = 5.64 W Maximum = 7.38 W
ICX-FAN12-E	Power-supply exhaust airflow fan (two fans required if two power supplies are used)	Typical = 4.68 W Maximum = 16.68 W
ICX-FAN12-I	Power-supply intake airflow fan (two fans required if two power supplies are used)	Typical = 4.68 W Maximum = 16.68 W

Data port specifications (Ethernet)

Model name	Port type	Number (in module)	Description
ICX 7650-48ZP	100 GbE	2 (slot 3)	QSFP28 stacking ports, 40/100 Gbps, compatible with optical transceivers, or direct attached copper cable.
	40 GbE	2 (slot 3)	QSFP+ stacking ports, 40 Gbps, compatible with optical transceivers, or direct attached copper cable.
	10 GbE	24 (slot 1)	100M/1/2.5/5/10 GbE RJ-45 ports with PoE support
	1 GbE	24 (slot 1)	10/100M/1 GbE RJ-45 ports with PoE support
ICX 7650-48P	100 GbE	2 (slot 3)	QSFP28 stacking ports, 40/100 Gbps, compatible with optical transceivers, or direct attached copper cable.
	40 GbE	2 (slot 3)	QSFP+ stacking ports, 40 Gbps, compatible with optical transceivers, or direct attached copper cable.
	1 GbE	48 (slot 1)	10/100M/1 GbE RJ-45 ports with PoE support
ICX 7650-48F	100 GbE	2 (slot 3)	QSFP28 stacking ports, 40/100 Gbps, compatible with optical transceivers, or direct attached copper cable.
	40 GbE	2 (slot 3)	QSFP+ stacking ports, 40 Gbps, compatible with optical transceivers, or direct attached copper cable.
	10 GbE	24 (slot 1)	SFP+ ports, compatible with ER, LR, LRM, SR, ZR, or USR optical transceivers
	1 GbE	24 (slot 1)	SFP ports, compatible with 100Base-FX IR or LR SFP optic for SMF, 100Base-FX SFP optic MMF, 1000Base-BXD SFP optic SMF, 1000Base-BXU SFP optic SMF, 1000Base-LHA SFP optic SMF, 1000Base-LX SFP optic SMF, 1000Base-SX SFP optic MMF, 1000BASE-TX SFP Copper
ICX7650-1X100GQ	100 GbE	1 (slot 2)	Pluggable module with QSFP28 uplink port, compatible with optical transceivers, or direct attached copper cable
ICX7650-2X40GQ	40 GbE	2 (slot 2)	Pluggable module with QSFP+ uplink ports, compatible with optical transceivers, or direct attached copper cable
ICX7650-4X10GF	10 GbE	4 (slot 2)	Pluggable module with SFP+ uplink ports, compatible with ER, LR, LRM, SR, ZR, or USR optical transceivers

Serial port specifications (pinout - USB Type-C)

Pin	Signal	Description
A1	USB-C_GND	Ground
A2	Reserved	Not used
A3	Reserved	Not used
A4	USB_TYPE_C_5V_IN	5 V bus power
A5	USB-C_CC1	Configuration channel
A6	USB-C_AD1+	Data A positive
A7	USB-C_AD1-	Data A negative
A8	Reserved	Not used
A9	USB_TYPE_C_5V_IN	5 V bus power
A10	Reserved	Not used
A11	Reserved	Not used

Ruckus ICX 7650 Specifications
Serial port specifications (pinout RJ-45)

Pin	Signal	Description
A12	USB-C_GND	Ground
B1	USB-C_GND	Ground
B2	Reserved	Not used
B3	Reserved	Not used
B4	USB_TYPE_C_5V_IN	5 V bus power
B5	Reserved	Not used
B6	USB-C_BD2+	Data B positive
B7	USB-C_BD2-	Data B negative
B8	Reserved	Not used
B9	USB_TYPE_C_5V_IN	5 V bus power
B10	Reserved	Not used
B11	Reserved	Not used
B12	USB-C_GND	Ground

Serial port specifications (pinout RJ-45)

Pin	Signal	Description
1	Not supported	N/A
2	Not supported	N/A
3	UART1_TXD	Transmit data to ICX
4	GND	Logic ground
5	Not supported	N/A
6	UART1_RXD	Receive data from ICX
7	Not supported	N/A
8	Not supported	N/A

Serial port specifications (protocol)

Parameter	Value
Baud	9600
Data bits	8
Parity	None
Stop bits	1
Flow control	None

Memory specifications

Memory	Type	Size
Main memory	DDR4 2133 SO-DIMM	4 GB
Boot Flash	SPI Flash	16 MB
M.2 Flash Module	NAND flash	16 GB

Regulatory compliance (EMC)

- FCC Part 15, Subpart B (Class A)
- EN 55032 (CE mark) (Class A)
- EN 55024 (CE mark) (Immunity) for Information Technology Equipment
- ICES-003 (Canada) (Class A)
- AS/NZ 55032 (Australia/New Zealand) (Class A)
- VCCI (Japan) (Class A)
- EN 300 386
- CNS 13438 (BSMI) (Taiwan) (Class A)
- KN 32 (South Korea) (Class A)
- KN 35 (South Korea) (Class A)
- TCVN 7189 / TCVN 7317 (Vietnam) (Class A)
- EN 61000-3-2
- EN 61000-3-3

Regulatory compliance (safety)

- CAN/CSA-C22.2 No. 60950/UL 60950 - Safety of Information Technology Equipment
- EN 60825 Safety of Laser Products - Part 1: Equipment Classification, Requirements and User's Guide
- EN 60950/IEC 60950 Safety of Information Technology Equipment

Regulatory compliance (environmental)

- 2014/35/EU and 2014/30/EU
- 2011/65/EU - Restriction of the use of certain hazardous substance in electrical and electronic equipment (EU RoHS)
- 2012/19/EU - Waste electrical and electronic equipment (EU WEEE)
- 94/62/EC - packaging and packaging waste (EU)
- 2006/66/EC - batteries and accumulators and waste batteries and accumulators (EU battery directive)
- 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (EU REACH)
- Section 1502 of the Dodd-Frank Wall Street Reform and Consumer Protection Act of 2010 - U.S. Conflict Minerals
- 30/2011/TT-BCT - Vietnam circular

Ruckus ICX 7650 Specifications

Regulatory compliance (environmental)

- SJ/T 11363-2006 Requirements for Concentration Limits for Certain Hazardous Substances in EIPs (China)
- SJ/T 11364-2006 Marking for the Control of Pollution Caused by EIPs (China)