

RUCKUS FastIron Debug Command Reference, 09.0.00

Supporting FastIron Software Release 09.0.00

Copyright, Trademark and Proprietary Rights Information

© 2021 CommScope, Inc. All rights reserved.

No part of this content may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from CommScope, Inc. and/or its affiliates ("CommScope"). CommScope reserves the right to revise or change this content from time to time without obligation on the part of CommScope to provide notification of such revision or change.

Export Restrictions

These products and associated technical data (in print or electronic form) may be subject to export control laws of the United States of America. It is your responsibility to determine the applicable regulations and to comply with them. The following notice is applicable for all products or technology subject to export control:

These items are controlled by the U.S. Government and authorized for export only to the country of ultimate destination for use by the ultimate consignee or end-user(s) herein identified. They may not be resold, transferred, or otherwise disposed of, to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. government or as otherwise authorized by U.S. law and regulations.

Disclaimer

THIS CONTENT AND ASSOCIATED PRODUCTS OR SERVICES ("MATERIALS"), ARE PROVIDED "AS IS" AND WITHOUT WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED. TO THE FULLEST EXTENT PERMISSIBLE PURSUANT TO APPLICABLE LAW, COMMSCOPE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TITLE, NON-INFRINGEMENT, FREEDOM FROM COMPUTER VIRUS, AND WARRANTIES ARISING FROM COURSE OF DEALING OR COURSE OF PERFORMANCE. CommScope does not represent or warrant that the functions described or contained in the Materials will be uninterrupted or error-free, that defects will be corrected, or are free of viruses or other harmful components. CommScope does not make any warranties or representations regarding the use of the Materials in terms of their completeness, correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise. As a condition of your use of the Materials, you warrant to CommScope that you will not make use thereof for any purpose that is unlawful or prohibited by their associated terms of use.

Limitation of Liability

IN NO EVENT SHALL COMMSCOPE, COMMSCOPE AFFILIATES, OR THEIR OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, SUPPLIERS, LICENSORS AND THIRD PARTY PARTNERS, BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, EXEMPLARY OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER, EVEN IF COMMSCOPE HAS BEEN PREVIOUSLY ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT, OR ANY OTHER THEORY ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIALS. Because some jurisdictions do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of liability for consequential or incidental damages, some of the above limitations may not apply to you.

Trademarks

ARRIS, the ARRIS logo, COMMSCOPE, RUCKUS, RUCKUS WIRELESS, the Ruckus logo, the Big Dog design, BEAMFLEX, CHANNELFLY, FASTIRON, ICX, SMARTCELL and UNLEASHED are trademarks of CommScope, Inc. and/or its affiliates. Wi-Fi Alliance, Wi-Fi, the Wi-Fi logo, Wi-Fi Certified, the Wi-Fi CERTIFIED logo, Wi-Fi Protected Access, the Wi-Fi Protected Setup logo, Wi-Fi Protected Setup, Wi-Fi Multimedia and WPA2 and WMM are trademarks or registered trademarks of Wi-Fi Alliance. All other trademarks are the property of their respective owners.

Contents

Preface.....	9
Contacting RUCKUS Customer Services and Support.....	9
What Support Do I Need?.....	9
Open a Case.....	9
Self-Service Resources.....	10
Document Feedback.....	10
RUCKUS Product Documentation Resources.....	10
Online Training Resources.....	10
Document Conventions.....	11
Notes, Cautions, and Safety Warnings.....	11
Command Syntax Conventions.....	11
About This Document.....	13
What's new in this document.....	13
New Commands for FastIron 09.0.00.....	13
Modified Commands for FastIron 09.0.00.....	14
Deprecated Commands for FastIron 09.0.00.....	14
Supported Hardware.....	15
Using diagnostic commands.....	17
Enabling Debugs.....	17
Debug.....	17
Distributed Logger.....	17
Disabling debug commands.....	17
Log Manager	18
Viewing logs for debugs enabled using debug utility.....	19
Viewing logs for debugs enabled using distributed logger utility.....	25
Debug Commands A - G.....	29
debug 802.1w all_802_1w_events.....	29
debug 802.1w messages.....	31
debug 802.1w timer.....	33
debug 802.1w transitions.....	34
debug bfd.....	35
debug bum-statistics.....	38
debug coa.....	39
debug dhcp-client alarms.....	40
debug dhcp-client events.....	41
debug dhcp-client warnings.....	44
debug forwarding hw-clear.....	45
Debug Commands H - P.....	47
debug hw.....	47
debug igmp-snoop add-del-oif all.....	48
debug igmp-snoop clear.....	49
debug igmp-snoop error.....	50
debug igmp-snoop group.....	51
debug igmp-snoop level.....	52

debug igmp-snoop packet.....	54
debug igmp-snoop port ethernet.....	55
debug igmp-snoop show.....	56
debug igmp-snoop source.....	57
debug igmp-snoop timer.....	58
debug igmp-snoop vlan.....	59
debug ikev2.....	60
debug ip aaa.....	74
debug ip arp.....	75
debug ip bgp.....	76
debug ip bgp dampening.....	77
debug ip bgp events.....	78
debug ip bgp graceful-restart.....	79
debug ip bgp keepalives.....	80
debug ip bgp updates.....	81
debug ip gre keepalive.....	82
debug ip gre log.....	83
debug ip gre packet.....	85
debug ip icmp events.....	86
debug ip icmp packets.....	87
debug ip igmp add-del-oif.....	88
debug ip igmp add-del-oif stack.....	92
debug ip igmp clear.....	95
debug ip igmp enable.....	96
debug ip igmp error.....	97
debug ip igmp group.....	98
debug ip igmp level.....	99
debug ip igmp physical-port ethernet.....	103
debug ip igmp protocol.....	104
debug ip igmp proxy clear.....	106
debug ip igmp proxy error.....	107
debug ip igmp proxy event.....	108
debug ip igmp proxy packet.....	109
debug ip igmp proxy rx.....	110
debug ip igmp proxy show.....	111
debug ip igmp proxy tx.....	112
debug ip igmp proxy vrf.....	113
debug ip igmp rx.....	114
debug ip igmp show.....	115
debug ip igmp source.....	116
debug ip igmp tx.....	117
debug ip igmp vrf.....	118
debug ip msdp.....	119
debug ip ntp.....	121
debug ip ospf.....	124
debug ip ospf adj.....	125
debug ip ospf all-vrfs route.....	126
debug ip ospf error.....	127
debug ip ospf event.....	128
debug ip ospf flood.....	129

debug ip ospf graceful-restart.....	130
debug ip ospf log-empty-lsa.....	132
debug ip ospf lsa-generation.....	134
debug ip ospf lsa-id.....	135
debug ip ospf max-metric.....	136
debug ip ospf packet.....	137
debug ip ospf retransmission.....	141
debug ip ospf route.....	142
debug ip ospf spf.....	143
debug ip ospf vrf.....	144
debug ip pim.....	145
debug ip pim add-del-oif.....	146
debug ip pim bootstrap.....	148
debug ip pim clear.....	149
debug ip pim event.....	150
debug ip pim group.....	152
debug ip pim join-prune.....	153
debug ip pim level.....	155
debug ip pim nbr.....	158
debug ip pim packet.....	159
debug ip pim regproc.....	162
debug ip pim rp.....	163
debug ip pim show.....	164
debug ip pim source.....	165
debug ip pim vrf.....	166
debug ip pimsm-snoop.....	167
debug ip ssh.....	169
debug ip sync.....	170
debug ip tcp.....	172
debug ip tcp driver.....	175
debug ip tcp memory.....	176
debug ip tcp packet.....	177
debug ip tcp sack.....	178
debug ip tcp transactions.....	179
debug ip udp.....	180
debug ip vrrp packet.....	181
debug ip vrrp events.....	182
debug ip vrrp packet v4.....	183
debug ip vrrp packet v6.....	184
debug ip vrrp vrid.....	185
debug ip web.....	186
debug ip web-ssl.....	187
debug ipsec all.....	188
debug ipsec esp.....	189
debug ipsec in.....	190
debug ipsec out.....	191
debug ipsec policy.....	192
debug ipv6.....	193
debug ipv6 dhcp relay.....	194
debug ipv6 mld.....	195

debug ipv6 mld add-del-oif.....	197
debug ipv6 mld add-del-oif stack.....	198
debug ipv6 mld clear.....	200
debug ipv6 mld enable.....	201
debug ipv6 mld error.....	202
debug ipv6 mld group.....	203
debug ipv6 mld phy-port ethernet.....	204
debug ipv6 mld protocol.....	205
debug ipv6 mld rx.....	207
debug ipv6 mld show.....	208
debug ipv6 mld source.....	209
debug ipv6 mld tx.....	210
debug ipv6 mld vrf.....	211
debug ipv6 nd.....	213
debug ipv6 ospf ipsec.....	214
debug ipv6 ospf ism.....	215
debug ipv6 ospf ism-events.....	216
debug ipv6 ospf ism-status.....	217
debug ipv6 ospf lsa.....	218
debug ipv6 ospf lsa-flooding.....	221
debug ipv6 ospf lsa-generation.....	222
debug ipv6 ospf lsa-install.....	224
debug ipv6 ospf lsa-inter-area.....	225
debug ipv6 ospf lsa-refresh.....	226
debug ipv6 ospf nsm.....	228
debug ipv6 ospf nsm-events.....	229
debug ipv6 ospf nsm-status.....	230
debug ipv6 ospf packet.....	231
debug ipv6 ospf packet-dd.....	233
debug ipv6 ospf packet-hello.....	234
debug ipv6 ospf packet-lsa-ack.....	235
debug ipv6 ospf packet-lsa-req.....	236
debug ipv6 ospf packet-lsa-update.....	237
debug ipv6 ospf route.....	238
debug ipv6 ospf route-calc-external.....	239
debug ipv6 ospf route-calc-inter-area.....	240
debug ipv6 ospf route-calc-intra-area.....	241
debug ipv6 ospf route-calc-spf.....	242
debug ipv6 ospf route-install.....	243
debug ipv6 pim.....	244
debug ipv6 pim add-del-oif.....	245
debug ipv6 pim bootstrap.....	248
debug ipv6 pim clear.....	249
debug ipv6 pim event.....	250
debug ipv6 pim group.....	253
debug ipv6 pim join-prune.....	254
debug ipv6 pim level.....	255
debug ipv6 pim nbr.....	256
debug ipv6 pim packet.....	258
debug ipv6 pim regproc.....	259

debug ipv6 pim rp.....	260
debug ipv6 pim show.....	261
debug ipv6 pim source.....	262
debug ipv6 pim vrf.....	263
debug ipv6 pimsm-snoop.....	266
debug ipv6 ra.....	268
debug ipv6 rguard.....	270
debug ipv6 rip events.....	271
debug ipv6 rip receive.....	272
debug keychain.....	273
debug lacp messages.....	275
debug license.....	277
debug loop-detect.....	278
debug loop-detect level.....	279
debug loop-detect port.....	280
debug mac.....	282
debug mecid.....	283
debug mem-leak.....	285
debug metro-ring bpdu.....	286
debug metro-ring diags.....	287
debug metro-ring event.....	288
debug metro-ring ring-id.....	289
debug metro-ring trace-l2.....	292
debug metro-ring tx_bpdu.....	293
debug mld-snoop.....	294
debug mld-snoop add-del-oif all.....	296
debug mld-snoop clear.....	297
debug mld-snoop error.....	298
debug mld-snoop group.....	299
debug mld-snoop packet.....	300
debug mld-snoop show.....	301
debug mld-snoop timer.....	302
debug mstp bpdu.....	303
debug mstp enable.....	314
debug mstp events.....	315
debug mstp msti.....	316
debug mstp ports.....	318
debug mstp port-level.....	319
debug mstp show.....	320
debug mstp state.....	321
debug mstp verbose.....	322
debug mvrp.....	323
debug packet-capture.....	325
debug packet-capture filter.....	326
debug packet-capture filter match.....	328
debug packet-capture filter none.....	329
debug packet-capture filter show.....	330
debug packet-capture mode.....	331
debug pki.....	332
debug port hw-state.....	333

debug port port.....	334
debug port ten-gig.....	337
debug port up-down.....	338
debug port vlan.....	340
debug pp-trunk-hash.....	342
debug pvlan cli.....	344
debug pvlan egr-trans.....	346
debug pvlan event.....	348
debug pvlan vlan.....	350
Debug Commands Q - Z.....	353
restconf platform-debug-level.....	353
restconf protocol-debug-level.....	354
debug rate-limiting.....	355
debug rip database.....	355
debug rip events.....	357
debug sflow.....	358
debug span all_802_1d_events.....	359
debug span config.....	360
debug span timers.....	361
debug system campram.....	362
debug system mem-leak.....	363
debug system optics.....	364
debug trunk.....	365
debug web events.....	370
debug webauth timers.....	371
debug webauth events.....	372
show debug.....	373
show log debug management restconf all.....	374
show tech-support.....	376
supportsave.....	381
supportsave.....	384
supportsave add_cust_cmd index.....	387
supportsave del_cust_cmd all.....	388
supportsave del_cust_cmd index.....	389
supportsave info disable.....	390
supportsave info enable.....	391
supportsave list_cust_cmd.....	394
supportsave show.....	395

Preface

- [Contacting RUCKUS Customer Services and Support](#)..... 9
- [Document Feedback](#)..... 10
- [RUCKUS Product Documentation Resources](#)..... 10
- [Online Training Resources](#)..... 10
- [Document Conventions](#)..... 11
- [Command Syntax Conventions](#)..... 11

Contacting RUCKUS Customer Services and Support

The Customer Services and Support (CSS) organization is available to provide assistance to customers with active warranties on their RUCKUS products, and customers and partners with active support contracts.

For product support information and details on contacting the Support Team, go directly to the RUCKUS Support Portal using <https://support.ruckuswireless.com>, or go to <https://www.ruckuswireless.com> and select **Support**.

What Support Do I Need?

Technical issues are usually described in terms of priority (or severity). To determine if you need to call and open a case or access the self-service resources, use the following criteria:

- Priority 1 (P1)—Critical. Network or service is down and business is impacted. No known workaround. Go to the **Open a Case** section.
- Priority 2 (P2)—High. Network or service is impacted, but not down. Business impact may be high. Workaround may be available. Go to the **Open a Case** section.
- Priority 3 (P3)—Medium. Network or service is moderately impacted, but most business remains functional. Go to the **Self-Service Resources** section.
- Priority 4 (P4)—Low. Requests for information, product documentation, or product enhancements. Go to the **Self-Service Resources** section.

Open a Case

When your entire network is down (P1), or severely impacted (P2), call the appropriate telephone number listed below to get help:

- Continental United States: 1-855-782-5871
- Canada: 1-855-782-5871
- Europe, Middle East, Africa, Central and South America, and Asia Pacific, toll-free numbers are available at <https://support.ruckuswireless.com/contact-us> and Live Chat is also available.
- Worldwide toll number for our support organization. Phone charges will apply: +1-650-265-0903

We suggest that you keep a physical note of the appropriate support number in case you have an entire network outage.

Self-Service Resources

The RUCKUS Support Portal at <https://support.ruckuswireless.com> offers a number of tools to help you to research and resolve problems with your RUCKUS products, including:

- Technical Documentation—<https://support.ruckuswireless.com/documents>
- Community Forums—<https://forums.ruckuswireless.com/ruckuswireless/categories>
- Knowledge Base Articles—<https://support.ruckuswireless.com/answers>
- Software Downloads and Release Notes—https://support.ruckuswireless.com/#products_grid
- Security Bulletins—<https://support.ruckuswireless.com/security>

Using these resources will help you to resolve some issues, and will provide TAC with additional data from your troubleshooting analysis if you still require assistance through a support case or RMA. If you still require help, open and manage your case at https://support.ruckuswireless.com/case_management.

Document Feedback

RUCKUS is interested in improving its documentation and welcomes your comments and suggestions.

You can email your comments to RUCKUS at #Ruckus-Docs@commscope.com.

When contacting us, include the following information:

- Document title and release number
- Document part number (on the cover page)
- Page number (if appropriate)

For example:

- RUCKUS SmartZone Upgrade Guide, Release 5.0
- Part number: 800-71850-001 Rev A
- Page 7

RUCKUS Product Documentation Resources

Visit the RUCKUS website to locate related documentation for your product and additional RUCKUS resources.

Release Notes and other user documentation are available at <https://support.ruckuswireless.com/documents>. You can locate the documentation by product or perform a text search. Access to Release Notes requires an active support contract and a RUCKUS Support Portal user account. Other technical documentation content is available without logging in to the RUCKUS Support Portal.

White papers, data sheets, and other product documentation are available at <https://www.ruckuswireless.com>.

Online Training Resources

To access a variety of online RUCKUS training modules, including free introductory courses to wireless networking essentials, site surveys, and products, visit the RUCKUS Training Portal at <https://training.ruckuswireless.com>.

Document Conventions

The following table lists the text conventions that are used throughout this guide.

TABLE 1 Text Conventions

Convention	Description	Example
monospace	Identifies command syntax examples	<code>device(config)# interface ethernet 1/1/6</code>
bold	User interface (UI) components such as screen or page names, keyboard keys, software buttons, and field names	On the Start menu, click All Programs .
<i>italics</i>	Publication titles	Refer to the <i>RUCKUS Small Cell Release Notes</i> for more information.

Notes, Cautions, and Safety Warnings

Notes, cautions, and warning statements may be used in this document. They are listed in the order of increasing severity of potential hazards.

NOTE

A NOTE provides a tip, guidance, or advice, emphasizes important information, or provides a reference to related information.

ATTENTION

An ATTENTION statement indicates some information that you must read before continuing with the current action or task.



CAUTION

A CAUTION statement alerts you to situations that can be potentially hazardous to you or cause damage to hardware, firmware, software, or data.



DANGER

A DANGER statement indicates conditions or situations that can be potentially lethal or extremely hazardous to you. Safety labels are also attached directly to products to warn of these conditions or situations.

Command Syntax Conventions

Bold and italic text identify command syntax components. Delimiters and operators define groupings of parameters and their logical relationships.

Convention	Description
bold text	Identifies command names, keywords, and command options.
<i>italic text</i>	Identifies a variable.
[]	Syntax components displayed within square brackets are optional. Default responses to system prompts are enclosed in square brackets.
{x y z}	A choice of required parameters is enclosed in curly brackets separated by vertical bars. You must select one of the options.
x y	A vertical bar separates mutually exclusive elements.
< >	Nonprinting characters, for example, passwords, are enclosed in angle brackets.
...	Repeat the previous element, for example, <i>member[member...]</i> .
\	Indicates a "soft" line break in command examples. If a backslash separates two lines of a command input, enter the entire command at the prompt without the backslash.

About This Document

- [What's new in this document.....](#) 13
- [Supported Hardware.....](#) 15

What's new in this document

Removed support for RUCKUS ICX 7750 in 09.0.00 release.

The following changes were made to this guide in FastIron software release 09.0.00.

TABLE 2 Summary of changes in FastIron release 09.0.00

Feature	Description	Location
Distributed Logger	Distributed Logger is a simple debug log filtering facility for application debug logs. It provides a common infrastructure for each of the applications to filter logs at sub-module level and the corresponding sub-modules further with different severity levels. This filtering capability provided by the distributed logger helps to perform detailed debugging with complete control on enabling debug logs.	Refer to Distributed Logger on page 17
Accessing debug logs through Log Manager	Beginning with 09.0.00 release, the logs that are generated using the debug and distributed logger utilities are sent to the Log Manager. The Log Manager infrastructure provides the capability to store the application log files in a centralized repository. The centralized repository can be accessed to display the log files using the show logging debug command.	Refer to Log Manager on page 18
Log Manager	Log manager is enhanced to upload the fetched logs to an external server. It also allows you to monitor real-time updates to the specified logs on local units.	Refer to Log Manager on page 18

New Commands for FastIron 09.0.00

The following commands have been added (new for this release).

- **debug mem-leak**
- **debug system mem-leak**
- **debug ipv6 pim add-del-oif**
- **debug ipv6 pim level**
- **debug ipv6 pim vrf**
- **debug ipv6 mld event**

About This Document

What's new in this document

- `debug ipv6 mld ifname`
- `debug ipv6 mld ipc`
- `debug ipv6 mld profile`

Modified Commands for FastIron 09.0.00

The following commands have been modified in this release.

- `debug ip pim nbr`
- `debug ipv6 pim nbr`

Deprecated Commands for FastIron 09.0.00

The following commands have been deprecated in this release.

- `debug all`
- `debug acl log`
- `debug bum-rate-limit`
- `debug cluster aging-disable`
- `debug cluster all`
- `debug cluster bpdu-forwarding`
- `debug cluster ccp`
- `debug cluster client-auto-detect`
- `debug cluster config`
- `debug cluster forwarding`
- `debug cluster fsm`
- `debug cluster icl-na-disable`
- `debug cluster intf-mac`
- `debug cluster mdup`
- `debug cluster show`
- `debug cluster stp`
- `debug ddos-attack`
- `debug destination`
- `debug dot1x hitless`
- `debug dot1x-events`
- `debug dot1x-filter`
- `debug dot1x-misc`
- `debug dot1x-mka`
- `debug dot1x-packets`
- `debug dot1x-timers`
- `debug gvrp`
- `debug ip arp inspection`

- debug ip dhcp snooping
- debug ip igmp add-del-oif all
- debug ip igmp down-port
- debug ip igmp packet
- debug ip igmp prime-port ethernet
- debug ip igmp timer
- debug ip pim control-source
- debug ip pim physical-port ethernet
- debug ip source guard
- debug ip source_guard_print_counter
- debug ip source_guard_print_timers
- debug ip source_guard_reset_counter
- debug ip source_guard_transaction-db
- debug ipv6 mld add-del-oif all
- debug ipv6 mld detail
- debug ipv6 mld mcache-group
- debug ipv6 mld prime-port ethernet
- debug ipv6 mld timer
- debug ipv6 mld vlan
- debug ipv6 rguard
- debug mac-authentication
- debug mld-snoop mcache-group
- debug pp-bum-trunk-hash
- debug stack pe control
- debug stack pe mac
- debug stack pe topo
- debug tcam-snapshot-dump
- debug traffic-policy
- show tech-support
- restconf platform-debug-level
- restconf protocol-debug-level

Supported Hardware

This guide supports the following RUCKUS products:

- RUCKUS ICX 7850 Switch
- RUCKUS ICX 7650 Switch
- RUCKUS ICX 7550 Switch
- RUCKUS ICX 7450 Switch

About This Document

Supported Hardware

- RUCKUS ICX 7250 Switch
- RUCKUS ICX 7150 Switch

For information about what models and modules these devices support, refer to the hardware installation guide for the specific product family.

Using diagnostic commands

- [Enabling Debugs.....](#) 17

Enabling Debugs

This chapter describes how to use debug commands to monitor and troubleshoot the device configurations. The debug commands are accessible from the Privileged EXEC mode in the RUCKUS command line interface (CLI).

Many debug commands are specifically designed to be used in conjunction with calls to RUCKUS Technical Support. If you report a problem, the support engineer may ask you to execute one or more of the debug commands described in this guide.

ATTENTION

Some debug commands report information about internal hardware settings and registers, which is relevant primarily to the RUCKUS engineering staff. These commands are not described in this document.

There are 2 ways to enable debugs:

- Debug
- Distributed Logger

The logs that are generated using debug and distributed logger utilities are sent to Log Manager. For more information refer to [Log Manager](#) on page 18.

Debug

The debug commands display information about the device operations, generated or received traffic, and any error messages. The output from the **debug** commands provides diagnostic information that include a variety of events relating to protocol status and network activity in general.

Distributed Logger

Distributed Logger (dlogger) is a simple debug log filtering facility for application debug logs. It provides a common infrastructure for each of the applications to filter logs at sub-module level and the corresponding sub-modules further with different severity levels. This filtering capability provided by the distributed logger helps to perform detailed debugging with complete control on enabling debug logs.

It has the capability to classify always-on logs and on-demand logs based on severity level. The always-on logs that is, logs with high severity (0-4), are logged into Log Manager by default. Manual configuration is required to log the low-severity logs.

There are certain modules that are supported in distributed logger but do not have the filtering capability. Their logs are directly logged only into the circular buffer and will not be logged in the Log Manager. These logs can be displayed using the **show dlogger logs** command. For more information on enabling distributed logger and viewing the debug logs, refer to [Viewing logs for debugs enabled using distributed logger utility](#) on page 25.

Disabling debug commands

When activated, most debug commands instruct the system to collect specific information about router configurations and activity. In all cases, adding **no** in front of the command disables the debug function.

Log Manager

The Log Manager infrastructure provides the capability to store the application log files in a centralized repository. The centralized repository can be accessed for viewing the log files (to aid in taking appropriate troubleshooting actions). By default, all logs are enabled and the log files are categorized based on module, sub-module, and severity levels. Each entry in a log file has important information, including module, sub-module, severity level, unit number, and timestamp.

Log Manager provides the list of supported modules and sub-modules. To display the module and sub-module hierarchy, use the **logmgr hierarchy** command.

NOTE

You must use the exact module names and sub-module names as listed in the log manager hierarchy for all Log Manager operations.

Log Manager provides the following options:

- **List Logs:** Allows you to list the size of existing logs on any connected units using the **logmgr list** command. The logs are listed separately for each unit.
- **Fetch Logs:** Allows you to collect logs from any connected units and store them locally using the **logmgr fetch** command.
- **Display Logs:** Allows you to view the fetched logs using the **show logging debug** command. When viewing multiple logs, the log files are merged, sorted by timestamp, and stored in a file. If a fetch operation is not run or the fetched logs have been cleared using the **logmgr clear-fetched-logs** command, only local logs are displayed.
- **Upload Logs:** Allows you to upload the fetched logs to an external server using the **logmgr upload** command.
- **Monitor Logs:** Allows you to monitor real-time updates to the specified logs on local units.

You can use the **logmgr help** command to get the details about the usage, syntax, and examples of Log Manager commands.

The total memory reserved for all the log files in a unit is restricted to 5 MB on the RUCKUS ICX 7150, and 10 MB for all other ICX 7xxx platforms.

Log Message Severity Levels

The severity levels of the log messages are described in the following table.

TABLE 3 Log Message Severity Levels

Numerical Code	Severity	Description
0	Emergency	System is unusable
1	Alert	Action must be taken immediately
2	Critical	Critical conditions
3	Error	Error conditions
4	Warning	Warning conditions
5	Notice	Normal but significant conditions
6	Informational	Informational messages
7	Debug	Debug-level messages

Severity levels are further categorized into High and Low:

- **High:** Emergency, Alert, Critical, and Error
- **Low:** Warning, Notice, Informational, and Debug

Viewing logs for debugs enabled using debug utility

The following example shows the configuration steps to generate and view debug logs using debug utility.

1. Enable all debug functions or enable debugging for a specific module.

```
device# debug metro-ring bpdu
```

The logs will be generated and maintained in the Log Manager.

Using diagnostic commands

Enabling Debugs

2. Find the Log Manager hierarchy of the supported modules and sub-modules.

```
device# logmgr hierarchy
-----
| Module           | Submodule           | Size (KB) |
-----
system            system_sub           472.5
system            Total                472.5
platform          platform_sub        94.5
platform          chassis             94.5
platform          link                94.5
platform          plm                 94.5
platform          poe                 94.5
platform          Total               472.5
infra             stacking            109.4
infra             cfg_sync_lib        65.6
infra             cfg_sync_proc       65.6
infra             qos                 65.6
infra             logmgr_lib          65.6
infra             logmgr_proc         65.6
infra             log_clf_fe          21.9
infra             log_clf_be          21.9
infra             conf_archive        65.6
infra             infra_cmn            21.9
infra             fitrace_fe          21.9
infra             rcm                 109.4
infra             itc                 65.6
infra             ssave              21.9
infra             Total               787.6
12               l2_sub              27.8
12               vlan                27.8
12               lag                 27.8
12               udld                27.8
12               mvrp                27.8
12               fdb                 27.8
12               pvlan               27.8
12               stp                 27.8
12               rstp                27.8
12               mstp                27.8
12               mrp                 27.8
12               lldp                27.8
12               erlb                27.8
12               loam                27.8
12               l2port              27.8
12               mct                 27.8
12               flexlink            27.8
12               Total               472.5
13               l3_sub              472.5
13               Total               472.5
mcast            mcast_sub           94.5
mcast            l3mcast             94.5
mcast            mcrep               94.5
mcast            igmp-snoop          94.5
mcast            mld-snoop            94.5
mcast            Total               472.5
security          security_sub        22.5
security          ra_gaurd            22.5
security          dhcp6snoop          22.5
security          dhcpsnoop           22.5
security          ndi                 22.5
security          macsec              22.5
security          acl_accounting      22.5
security          flexauth            22.5
security          webauth             22.5
security          fvcmgr              22.5
security          aclinfra            22.5
security          pbrl                22.5
security          brl                 22.5
security          utp                 22.5
security          gendistfw           22.5
security          sflow               22.5
```

security	ippolicy	22.5
security	sourceguard	22.5
security	aclhitless	22.5
security	dai	22.5
security	ddos	22.5
security	Total	472.5
management	nms_sub	31.5
management	clish	52.5
management	cli_dict	52.5
management	clam	52.5
management	lldp	31.5
management	restconf	31.5
management	dhcpv4_client	31.5
management	dhcpv4_server	31.5
management	dhcpv6_server	31.5
management	snmpagentd	31.5
management	manager	52.5
management	plugin	31.5
management	slam	31.5
management	aaa	31.5
management	snmpd_traps	31.5
management	web	31.5
management	rcm	52.5
management	cfg_par	52.5
management	nginx	31.5
management	uwsgi	31.5
management	rconsole	31.5
management	Total	787.6
fi_debug	debug_logs	472.5
fi_debug	Total	472.5

You must use the exact module names and sub-module names as listed in the log manager hierarchy for all Log Manager operations.

In this example for “metro-ring”, the corresponding module and sub-module names in the log manager hierarchy are “L2” and “mrp” .

3. Fetch (create a local copy) the required logs from local and remote units. Fetch is used for stack environment.

```
device# logmgr fetch l2 mrp all all
```

Using diagnostic commands

Enabling Debugs

4. View debug logs from the log manager.

```
device# show logging debug l2 mrp all all
May 28 14:29:59:998237:debug:l2:mrp:1:659616782353921: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1370
May 28 14:29:59:898500:debug:l2:mrp:1:659599602484737: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1369
May 28 14:29:59:798146:debug:l2:mrp:1:659586717582849: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1368
May 28 14:29:59:704492:debug:l2:mrp:1:659556652811777: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1367
May 28 14:29:59:598217:debug:l2:mrp:1:659526588040705: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1366
May 28 14:29:59:498257:debug:l2:mrp:1:659522293073409: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1365
May 28 14:29:59:398655:debug:l2:mrp:1:659517998106113: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1364
May 28 14:29:59:298205:debug:l2:mrp:1:659513703138817: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1363
May 28 14:29:59:198234:debug:l2:mrp:1:659509408171521: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1362
May 28 14:29:59:098150:debug:l2:mrp:1:659483638367745: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1361
May 28 14:29:58:998129:debug:l2:mrp:1:659479343400449: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1360
May 28 14:29:58:898510:debug:l2:mrp:1:659462163531265: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1359
May 28 14:29:58:798604:debug:l2:mrp:1:659453573596673: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1358
May 28 14:29:58:698561:debug:l2:mrp:1:659440688694785: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1357
May 28 14:29:58:598168:debug:l2:mrp:1:659419213858305: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1356
May 28 14:29:58:498128:debug:l2:mrp:1:659414918891009: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1355
May 28 14:29:58:398702:debug:l2:mrp:1:659406328956417: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1354
May 28 14:29:58:298202:debug:l2:mrp:1:659397739021825: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1353
May 28 14:29:58:198209:debug:l2:mrp:1:659393444054529: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1352
May 28 14:29:58:101057:debug:l2:mrp:1:659371969218049: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1351
May 28 14:29:57:998183:debug:l2:mrp:1:659324724577793: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1350
May 28 14:29:57:898609:debug:l2:mrp:1:659320429610497: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1349
May 28 14:29:57:798197:debug:l2:mrp:1:659311839675905: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1348
May 28 14:29:57:698229:debug:l2:mrp:1:659298954774017: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1347
May 28 14:29:57:598799:debug:l2:mrp:1:659273184970241: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1346
May 28 14:29:57:498128:debug:l2:mrp:1:659264595035649: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1345
May 28 14:29:57:398716:debug:l2:mrp:1:659251710133761: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1344
May 28 14:29:57:298657:debug:l2:mrp:1:659243120199169: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1343
May 28 14:29:57:198594:debug:l2:mrp:1:659234530264577: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1342
May 28 14:29:57:098158:debug:l2:mrp:1:659213055428097: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1341
May 28 14:29:56:998116:debug:l2:mrp:1:659208760460801: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1340
May 28 14:29:56:898522:debug:l2:mrp:1:659204465493505: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1339
May 28 14:29:56:798210:debug:l2:mrp:1:659195875558913: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1338
May 28 14:29:56:698104:debug:l2:mrp:1:659191580591617: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1337
```

```
May 28 14:29:56:598673:debug:12:mrp:1:659170105755137: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1336  
May 28 14:29:56:503194:debug:12:mrp:1:659165810787841: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1335  
May 28 14:29:56:407092:debug:12:mrp:1:659161515820545: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1334  
May 28 14:29:56:298204:debug:12:mrp:1:659152925885953: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1333  
May 28 14:29:56:198137:debug:12:mrp:1:659148630918657: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1332  
May 28 14:29:56:101185:debug:12:mrp:1:659122861114881: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1331  
May 28 14:29:55:998206:debug:12:mrp:1:659118566147585: rhp-processing : MASTER(ring3) dropping  
RHP(ring#3) sequence number 1330
```

Using diagnostic commands

Enabling Debugs

5. Optionally, view real-time updates to the specified logs on local units.

```
device# logmgr monitor l2:mrp:all
==> /logmgr/logs//l2/mrp_low_tmp.log <==
May 28 14:29:48:098137:debug:l2:mrp:1:658079184061953: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1251
May 28 14:29:48:198297:debug:l2:mrp:1:658104953865729: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1252
May 28 14:29:48:298275:debug:l2:mrp:1:658109248833025: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1253
May 28 14:29:48:398603:debug:l2:mrp:1:658113543800321: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1254
May 28 14:29:48:500269:debug:l2:mrp:1:658117838767617: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1255
May 28 14:29:48:598161:debug:l2:mrp:1:658139313604097: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1256
May 28 14:29:48:698116:debug:l2:mrp:1:658160788440577: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1257
May 28 14:29:48:798215:debug:l2:mrp:1:658173673342465: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1258
May 28 14:29:48:898517:debug:l2:mrp:1:658182263277057: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1259
May 28 14:29:48:998207:debug:l2:mrp:1:658190853211649: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1260

==> /logmgr/logs//l2/mrp_low_tmp.log <==
May 28 14:29:49:098163:debug:l2:mrp:1:658195148178945: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1261
May 28 14:29:49:198520:debug:l2:mrp:1:658220917982721: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1262
May 28 14:29:49:300810:debug:l2:mrp:1:658225212950017: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1263
May 28 14:29:49:398608:debug:l2:mrp:1:658229507917313: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1264
May 28 14:29:49:498174:debug:l2:mrp:1:658233802884609: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1265
May 28 14:29:49:598270:debug:l2:mrp:1:658238097851905: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1266
May 28 14:29:49:698679:debug:l2:mrp:1:658263867655681: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1267
May 28 14:29:49:798155:debug:l2:mrp:1:658298227394049: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1268
May 28 14:29:49:901303:debug:l2:mrp:1:658315407263233: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1269
May 28 14:29:49:998135:debug:l2:mrp:1:658328292165121: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1270
May 28 14:29:50:101427:debug:l2:mrp:1:658332587132417: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1271
May 28 14:29:50:198157:debug:l2:mrp:1:658358356936193: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1272
May 28 14:29:50:298291:debug:l2:mrp:1:658362651903489: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1273
May 28 14:29:50:398631:debug:l2:mrp:1:658366946870785: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1274
May 28 14:29:50:498190:debug:l2:mrp:1:658371241838081: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1275
May 28 14:29:50:598267:debug:l2:mrp:1:658375536805377: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1276
May 28 14:29:50:698145:debug:l2:mrp:1:658397011641857: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1277
May 28 14:29:50:798501:debug:l2:mrp:1:658401306609153: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1278
May 28 14:29:50:901608:debug:l2:mrp:1:658414191511041: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1279
May 28 14:29:50:998128:debug:l2:mrp:1:658418486478337: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1280
May 28 14:29:51:098291:debug:l2:mrp:1:658422781445633: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1281
May 28 14:29:51:198188:debug:l2:mrp:1:658448551249409: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1282
May 28 14:29:51:298162:debug:l2:mrp:1:658452846216705: rhp-processing : MASTER(ring3) dropping
```

```
RHP(ring#3) sequence number 1283
May 28 14:29:51:405487:debug:l2:mrp:1:658461436151297: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1284
May 28 14:29:53:898510:debug:l2:mrp:1:658813623469569: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1309
May 28 14:29:54:001360:debug:l2:mrp:1:658826508371457: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1310
May 28 14:29:54:104241:debug:l2:mrp:1:658830803338753: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1311
May 28 14:29:54:198134:debug:l2:mrp:1:658856573142529: rhp-processing : MASTER(ring3) dropping
RHP(ring#3) sequence number 1312
^Cteln@device#
```

This command enables the monitoring mode and simultaneously blocks the CLI. Press Ctrl+C to cancel the monitoring mode.

6. Optionally, upload the fetched logs to an external server.

```
device# logmgr upload tftp 10.198.137.97 GZ.tar
```

Viewing logs for debugs enabled using distributed logger utility

The following example shows the configuration steps to generate and view debug logs using distributed logger utility.

1. Enable debugging for a module registered with distributed logger.

```
device# dlogger module sec_macsec sub-module cli sev all
device# dlogger module sec_macsec sub-module keygen sev all
device# dlogger module sec_macsec sub-module mka sev all
device# dlogger module sec_macsec sub-module tx sev all
device# dlogger module sec_macsec sub-module rx sev all
device# dlogger module sec_macsec sub-module pdu sev all
device# dlogger module sec_macsec sub-module stacking sev all
device# dlogger module sec_macsec sub-module platform sev all
```

The logs will be generated and maintained in the Log Manager.

Using diagnostic commands

Enabling Debugs

2. Find the mapping of distributed logger modules to Log Manager modules and sub-modules.

```
device# show dlogger module filter lm-map
Total Module 40
Logger Module to Log Manger Mapping:
-----
Idx  Logger-M          LogMgr-M          LogMgr-Sub-M
-----
  2  l3interface        fi_debug         debug_logs
  4  l3mcast            fi_debug         debug_logs
  6  bfd                fi_debug         debug_logs
  8  arp                fi_debug         debug_logs
 11  nexthop-mgr       fi_debug         debug_logs
 13  mcrep-sc          fi_debug         debug_logs
 16  ipv4-unicast      fi_debug         debug_logs
 17  ipv6-unicast      fi_debug         debug_logs
 18  openflow          fi_debug         debug_logs
 19  urpf              fi_debug         debug_logs
 21  ip-nexthop        fi_debug         debug_logs
 22  keychain          fi_debug         debug_logs
 23  remote-ping       fi_debug         debug_logs
 24  remote-traceroute fi_debug         debug_logs
 25  igmp-snoop        fi_debug         debug_logs
 26  mld-snoop         fi_debug         debug_logs
 27  mcrep-lc          fi_debug         debug_logs
 28  sec_acl           security         security_sub
 29  sec_acl_acct      fi_debug         debug_logs
 30  sec_macsec        security         macsec
 31  sec_dhcpnoop      security         security_sub
 32  sec_dhcp6snoop    fi_debug         debug_logs
 33  sec_ndi           fi_debug         debug_logs
 34  sec_raguard       fi_debug         debug_logs
 35  sec_brl           fi_debug         debug_logs
 36  sec_pbrl          fi_debug         debug_logs
 37  sec_aclinfra      fi_debug         debug_logs
 38  webauth           security         webauth
 39  flexauth          security         flexauth
```

You must use the exact Log manager module names and Log manager sub-module names that correspond to the distributed logger module as listed in the **show dlogger module filter lm-map** command output for all Log Manager operations.

In this example for “*sec_macsec*” distributed logger module, the corresponding Log manager module and sub-module names are “*security*” and “*macsec*” respectively.

3. Fetch (create a local copy) the required logs from local and remote units.

```
device# logmgr fetch security macsec all all
```

4. View debug logs from the log manager.

```

device# show logging debug security macsec all all
May 29 19:36:50:904422:err:security:macsec:3:34132105102080: cli:[LOGON][CONFIG] - Key is not
configured
May 29 19:36:50:902259:err:security:macsec:3:34132105102080: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 0
May 29 19:36:50:901984:err:security:macsec:3:34132105102080: stacking:[Master][Port-Indication][Req]
Port 2/2/4
May 29 19:36:50:901807:err:security:macsec:3:34132105102080: Suppressed 1 times: stacking:[Master]
[Port-Cfg] Port 2/2/4, Enable 1
May 29 19:36:50:901254:err:security:macsec:3:34132105102080: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 1
May 29 19:36:50:004782:err:security:macsec:3:33449205302016: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 0
May 29 19:36:41:906799:err:security:macsec:3:27324581937920: cli:[LOGON][CONFIG] - Key is not
configured
May 29 19:36:41:905105:err:security:macsec:3:27324581937920: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 0
May 29 19:36:41:904694:err:security:macsec:3:27324581937920: stacking:[Master][Port-Indication][Req]
Port 2/2/4
May 29 19:36:41:904658:err:security:macsec:3:27324581937920: Suppressed 1 times: stacking:[Master]
[Port-Cfg] Port 2/2/4, Enable 1
May 29 19:36:41:903809:err:security:macsec:3:27324581937920: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 1
May 28 09:27:02:228373:err:security:macsec:3:34114925232896: cli:[LOGON][CONFIG] - Key is not
configured
May 28 09:27:02:226751:err:security:macsec:3:34114925232896: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 0
May 28 09:27:02:226484:err:security:macsec:3:34114925232896: stacking:[Master][Port-Indication][Req]
Port 2/2/4
May 28 09:27:02:226445:err:security:macsec:3:34114925232896: Suppressed 1 times: stacking:[Master]
[Port-Cfg] Port 2/2/4, Enable 1
May 28 09:27:02:225577:err:security:macsec:3:34114925232896: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 1
May 28 09:27:01:328816:err:security:macsec:3:33436320400128: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 0
May 28 09:26:53:204026:err:security:macsec:3:27328876905216: cli:[LOGON][CONFIG] - Key is not
configured
May 28 09:26:53:195392:err:security:macsec:3:27328876905216: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 0
May 28 09:26:53:194386:err:security:macsec:3:27328876905216: stacking:[Master][Port-Indication][Req]
Port 2/2/4
May 28 09:26:53:194264:err:security:macsec:3:27328876905216: Suppressed 1 times: stacking:[Master]
[Port-Cfg] Port 2/2/4, Enable 1
May 28 09:26:53:191865:err:security:macsec:3:27328876905216: stacking:[Master][Port-Cfg] Port 2/2/4,
Enable 1

```

Using diagnostic commands

Enabling Debugs

5. Optionally, view real-time updates to the specified logs on local units.

```
device# logmgr monitor security:macsec:all
==> /logmgr/logs//security/macsec_high_tmp.log <==
May 29 19:36:41:904658:err:security:macsec:3:27324581937920: Suppressed 1 times: stacking:[Master]
[Port-Cfg] Port 2/2/4, Enable 1
May 29 19:36:41:904694:err:security:macsec:3:27324581937920: stacking:[Master] [Port-Indication] [Req]
Port 2/2/4
May 29 19:36:41:905105:err:security:macsec:3:27324581937920: stacking:[Master] [Port-Cfg] Port 2/2/4,
Enable 0
May 29 19:36:41:906799:err:security:macsec:3:27324581937920: cli:[LOGON][CONFIG] - Key is not
configured
May 29 19:36:50:004782:err:security:macsec:3:33449205302016: stacking:[Master] [Port-Cfg] Port 2/2/4,
Enable 0
May 29 19:36:50:901254:err:security:macsec:3:34132105102080: stacking:[Master] [Port-Cfg] Port 2/2/4,
Enable 1
May 29 19:36:50:901807:err:security:macsec:3:34132105102080: Suppressed 1 times: stacking:[Master]
[Port-Cfg] Port 2/2/4, Enable 1
May 29 19:36:50:901984:err:security:macsec:3:34132105102080: stacking:[Master] [Port-Indication] [Req]
Port 2/2/4
May 29 19:36:50:902259:err:security:macsec:3:34132105102080: stacking:[Master] [Port-Cfg] Port 2/2/4,
Enable 0
May 29 19:36:50:904422:err:security:macsec:3:34132105102080: cli:[LOGON][CONFIG] - Key is not
configured
```

This command enables the monitoring mode and simultaneously blocks the CLI. Press Ctrl+C to cancel the monitoring mode.

6. (Optional) View the filter configuration of distributed logger modules and sub-modules.

```
device# show dlogger module filter config-fltr
```

7. (Optional) View the logged messages from circular buffer maintained by the distributed logger module.

```
device# show dlogger logs module sec_macsec
```

8. Optionally, upload the fetched logs to an external server.

```
device# logmgr upload tftp 10.198.137.97 GZ.tar
```

Debug Commands A - G

debug 802.1w all_802_1w_events

Debugs all the RSTP transactions, timers, and packets on a specific VLAN.

Syntax

```
debug 802.1w all_802_1w_eventsvlandecimal
```

Parameters

decimal

Refers to the number of the VLAN.

Modes

Privileged EXEC mode

Debug Commands A - G

debug 802.1w all_802_1w_events

Examples

If the events are enabled, output similar to the following is displayed.

```
device# debug 802.1w all_802_1w_events vlan 2
RSTP Enabling All events Debugging for VLAN 2
device# RSTP[daa69]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) ,
VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/2(1) VLAN 2
RSTP: PTX =>ROLE is ALTERNATE or BACKUP , port 1/1/2(1), VLAN 2
RSTP[daa69]: Timer Alert - helloWhen timer_expired On port 1/1/9(8) , VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/9(8) VLAN 2
RSTP[daa69]: Tx RST Config BPDU Port 1/1/9(8) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00004e20
8000002438154580 08 09 0100 1400 0200 0f00
RSTP: Rcvd RST Config BPDU: Port 1/1/1(0) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 01 0000 0000 0000 0000
RSTP: PRT =>no valid transition found ,no error, port 1/1/1(0) VLAN 2
RSTP: Rcvd RST Config BPDU: Port 1/1/2(1) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 02 0000 0000 0000 0000
RSTP[daa7d]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) , VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/2(1) VLAN 2
RSTP: PTX =>ROLE is ALTERNATE or BACKUP , port 1/1/2(1), VLAN 2
RSTP[daa7d]: Timer Alert - helloWhen timer_expired On port 1/1/9(8) , VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/9(8) VLAN 2
RSTP[daa7d]: Tx RST Config BPDU Port 1/1/9(8) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00004e20
8000002438154580 08 09 0100 1400 0200 0f00
RSTP: Rcvd RST Config BPDU: Port 1/1/1(0) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 01 0000 0000 0000 0000
RSTP: PRT =>no valid transition found ,no error, port 1/1/1(0) VLAN 2
RSTP: Rcvd RST Config BPDU: Port 1/1/2(1) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 02 0000 0000 0000 0000
RSTP[daa91]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) , VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/2(1) VLAN 2
RSTP: PTX =>ROLE is ALTERNATE or BACKUP , port 1/1/2(1), VLAN 2
RSTP[daa91]: Timer Alert - helloWhen timer_expired On port 1/1/9(8) , VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/9(8) VLAN 2
RSTP[daa91]: Tx RST Config BPDU Port 1/1/9(8) VLAN 2
```

If the events are disabled, output similar to the following is displayed.

```
device# no debug 802.1w all_802_1w_events vlan 2
RSTP Disabling All 802.1w Debugging for VLAN 2
```

debug 802.1w messages

Displays BPDU information on a VLAN.

Syntax

debug 802.1w messages vlan *decimal*

no debug 802.1w messages vlan *decimal*

Parameters

decimal

Refers to the number of the VLAN.

Modes

Privileged EXEC mode

Examples

If the 802.1w messages are enabled, output similar to the following is displayed.

```
device# debug 802.1w messages vlan 2
RSTP Enabling packets Debugging for VLAN 2
device# RSTP: Rcvd RST Config BPDU: Port 1/1/1(0) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 01 0000 0000 0000 0000
RSTP: Rcvd RST Config BPDU: Port 1/1/2(1) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 02 0000 0000 0000 0000
RSTP[db06d]: Tx RST Config BPDU Port 1/1/9(8) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00004e20
8000002438154580 08 09 0100 1400 0200 0f00
RSTP: Rcvd RST Config BPDU: Port 1/1/1(0) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 01 0000 0000 0000 0000
RSTP: Rcvd RST Config BPDU: Port 1/1/2(1) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 02 0000 0000 0000 0000
RSTP[db081]: Tx RST Config BPDU Port 1/1/9(8) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00004e20
8000002438154580 08 09 0100 1400 0200 0f00
RSTP: Rcvd RST Config BPDU: Port 1/1/1(0) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 01 0000 0000 0000 0000
RSTP: Rcvd RST Config BPDU: Port 1/1/2(1) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 02 0000 0000 0000 0000
RSTP[db095]: Tx RST Config BPDU Port 1/1/9(8) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00004e20
8000002438154580 08 09 0100 1400 0200 0f00
device# RSTP: Rcvd RST Config BPDU: Port 1/1/1(0) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 01 0000 0000 0000 0000
RSTP: Rcvd RST Config BPDU: Port 1/1/2(1) VLAN 2
0000 02 02 7e 80000012f2dbfd80 00000000
80000012f2dbfd80 08 02 0000 0000 0000 0000
```

Debug Commands A - G
debug 802.1w messages

If the 802.1w messages are disabled, output similar to the following is displayed.

```
device# no debug 802.1w messages valn 2  
RSTP Disabling Packets Debugging for VLAN 2
```

debug 802.1w timer

Debugs the RSTP (802.1w) timer expiration.

Syntax

```
debug 802.1w timer vlan decimal
```

```
no debug 802.1w timer vlan decimal
```

Parameters

decimal

Refers to the number of the VLAN.

Modes

Privileged EXEC mode

Examples

If the timer is enabled, output similar to the following is displayed.

```
device# debug 802.1w timer vlan 2
device# RSTP[db6fd]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) ,
VLAN 2
RSTP[db6fd]: Timer Alert - helloWhen timer_expired On port 1/1/9(8) , VLAN 2
RSTP[db711]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) , VLAN 2
RSTP[db711]: Timer Alert - helloWhen timer_expired On port 1/1/9(8) , VLAN 2
RSTP[db725]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) , VLAN 2
RSTP[db725]: Timer Alert - helloWhen timer_expired On port 1/1/9(8) , VLAN 2
RSTP[db739]: Timer Alert - helloWhen timer_expired On port 1/1/2(1) , VLAN 2
```

If the timer is disabled, output similar to the following is displayed.

```
device# no debug 802.1w timer vlan 2
RSTP Disabling Timer Debugging for VLAN 2
```

debug 802.1w transitions

Debugs the RSTP state machine transitions.

Syntax

debug 802.1w transitions *vlan decimal*

no debug 802.1w transitions *vlan decimal*

Parameters

decimal

Refers to the number of the VLAN.

Modes

Privileged EXEC mode

Examples

If the 802.1w transitions are enabled, output similar to the following is displayed.

```
device# debug 802.1w transitions vlan 2
RSTP Enabling Events Debugging for VLAN 2
device# RSTP: PRT =>no valid transition found ,no error, port 1/1/1(0) VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/2(1) VLAN 2
RSTP: PTX =>ROLE is ALTERNATE or BACKUP , port 1/1/2(1), VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/9(8) VLAN 2
RSTP: PRT =>no valid transition found ,no error, port 1/1/1(0) VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/2(1) VLAN 2
RSTP: PTX =>ROLE is ALTERNATE or BACKUP , port 1/1/2(1), VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/9(8) VLAN 2
RSTP: PRT =>no valid transition found ,no error, port 1/1/1(0) VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/2(1) VLAN 2
RSTP: PTX =>ROLE is ALTERNATE or BACKUP , port 1/1/2(1), VLAN 2
RSTP: PTX entering the Periodic state , port 1/1/9(8) VLAN 2
```

If the 802.1w transitions are disabled, output similar to the following is displayed.

```
device# no debug 802.1w transitions vlan 2
RSTP Disabling Events Debugging for VLAN 2
```

debug bfd

Displays debugging information about Bidirectional Forwarding Detection (BFD).

Syntax

debug bfd all
debug bfd application
debug bfd arp-nbr
debug bfd clear
debug bfd error
debug bfd event
debug bfd ha
debug bfd holdtime
debug bfd ip-addr *ip-address*
debug bfd ipc
debug bfd ipv6-addr *ipv6-address*
debug bfd issu
debug bfd itc
debug bfd ptimer
debug bfd session-id*session-id*
debug bfd state
debug bfd vrf*vrf-name*

Parameters

all
Displays debugging information about all BFD events.

application
Displays debugging information about BFD applications.

arb-nbr
Displays debugging information about Address Resolution Protocol (ARP) and neighbor changes.

clear
Displays debugging information about clear BFD settings.

error
Displays debugging information about BFD errors encountered.

event
Displays debugging information about BFD events.

Debug Commands A - G

debug bfd

ha

Displays debugging information about HA and stack-related processing.

holdtime

Displays debugging information about BFD holdtime.

ip-addr *ip-address*

Displays debugging information about BFD for the specified IP address.

ipc

Displays debugging information about BFD interprocess communication (IPC) activities.

ipv6-addr *ipv6-address*

Displays debugging information about BFD for the specified IPv6 address.

itc

Displays debugging information about BFD inter-task communication (ITC) activities.

ptimer

Displays debugging information about internal BFD timers.

session-id

Displays debugging information about a specified BFD session.

state

Displays debugging information about the BFD state.

vrfvrf-id

Displays debugging information about BFD for the specified VRF.

Modes

Privileged EXEC mode

Usage Guidelines

This command is supported for ICX 7850 device.

Examples

The following example displays debugging information about the BFD holdtime.

```
device# debug bfd holdtime
```

```
BFD: holdtime debugging is on
```

The following example displays debugging information about BFD events.

```
device# debug bfd event
```

```
BFD: event debugging is on
```

History

Release version	Command history
08.0.90	This command was introduced.

debug bum-statistics

Enables BUM rate limit statistics debugging.

Syntax

debug bum-statistics *unit/slot/port bum-type*

no debug bum-statistics *unit/slot/port bum-type*

Parameters

unit/slot/port

Specifies the interface.

bum-type

Specifies the number that indicates the traffic type.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables BUM rate limit statistics debugging.

Examples

The following example enables BUM rate limit statistics debugging.

```
device#debug bum-statistics 1/3/2 0
Port-id : 1/3/2 BUM-type: BROADCAST
Unit-num: 1 Traffic Policy: 64-tp_129_0
```

```
device#debug bum-statistics 1/3/2 1
Port-id : 1/3/2 BUM-type: L2_MULTICAST
Unit-num: 1 Traffic Policy: 64-tp_129_1
Port-id : 1/3/2 BUM-type: L3_MULTICAST
Unit-num: 1 Traffic Policy: 64-tp_129_3
```

```
device#debug bum-statistics 1/3/2 2
Port-id : 1/3/2 BUM-type: UNKNOWN_UNICAST
Unit-num: 1 Traffic Policy: 64-tp_129_2
```

debug coa

Enables debugging of Change of Authorization (COA) messages.

Syntax

`debug coa`

`undebug coa`

Modes

Privileged EXEC mode

Usage Guidelines

Examples

The following example enables debugging of COA messages.

```
device# debug coa
```

debug dhcp-client alarms

Displays the debugging information of the Dynamic Host Configuration Protocol (DHCP) client on a particular port ID.

Syntax

debug dhcp-client alarms

no debug dhcp-client alarms

Modes

Privileged EXEC mode

Examples

The following example displays information related to the debugging of the DHCP client on a particular port ID.

```
device# debug dhcp-client alarms

"DHCPC: failed to initialize port; dhcpc unable to continue"
"DHCPC: failed to initialize protocol timer"
"DHCPC: no tftp server address or name found. unable to download configuration
file"
"DHCPC: unable to construct dns request"
"DHCPC: dns failed to resolve tftp server name"
"DHCPC: dns aborted"
"DHCPC: No DHCP Servers found on any ports"
"DHCPC: No DHCP Servers found on any ports"
"DHCPC: setting 0 seconds lease time"
"DHCPC: setting 0 seconds lease time on port port-id"
"DHCPC: No DHCP Servers found on any ports"
"DHCPC: failed to allocate a dhcpc packet on port port-id"
"DHCPC: failed to send message on port port-id"
"DHCPC: failed to allocate a dhcpc packet on port port-id"
"DHCPC: failed to send message on port port-id "
"DHCPC: get_an_ip_send_packet () failed on port port-id"
```

History

Release version	Command history
08.0.80	This command was modified to include information in the output for option 67 enhancements where both the image type and flash location are specified by the user.

debug dhcp-client events

Displays debugging information about Dynamic Host Configuration Protocol (DHCP) client events related to configuration.

Syntax

debug dhcp-client events

no debug dhcp-client events

Modes

Privileged EXEC mode

Examples

The following example displays debugging information about DHCP client events related to the configuration.

```
device# debug dhcp-client events

"DHCPC: failed to delete static ip-address to ip-address"
"DHCPC: failed to set the port ip-address to ip-address; subnet mask ip-address"
"DHCPC: changing port port-id state from REQUEST to BOUND"
"DHCPC: exceeds maximum some-number DNS servers"
"DHCPC: added ip-address dns-server address"
"DHCPC: failed to set the port ip-address to ip-address; subnet mask ip-address"
"DHCPC: TFTP timeout error for bootfile name %s"
"DHCPC: TFTP client busy"
"DHCPC: TFTP error wrong file type"
"DHCPC: TFTP long file name error"
"DHCPC: TFTP vlan-id invalid"
"DHCPC: TFTP flash write errors"
"DHCPC: TFTP error out of buffer space"
"DHCPC: TFTP flash read error"
"DHCPC: TFTP flash preparation for read failed"
"DHCPC: TFTP flash preparation for write failed"
"DHCPC: %s failed to save running-configuration"
"DHCPC: changing protocol from running to stopped"
"DHCPC: changing protocol from stopped to running"
"DHCPC: Auto update in progress, cannot change DHCP client state on port port-id "
"DHCPC: invalid parameter for "
"DHCPC: dhcp_get_next_port() bad port number port-id"
"DHCPC: sent DHCP-REQUEST message on port port-id \"
"DHCPC: sent DHCP-RENEWING message on port port-id"
"DHCPC: sent DHCP-REBINDING message on port port-id "
"DHCPC: sent DHCP-RELEASE message on port port-id "
"DHCPC: received packet port port-id"
"DHCPC: received bad packet port port-id, no DHCP END OPT found"
"DHCPC: received offer message on port port-id"
"DHCPC: recieved non matching 'xid' (0x%X) in offer message"
"DHCPC: changing port port-id state from INIT-SELECTING to INIT-SELECTING"
"DHCPC: changing port port-id state from INIT-SELECTING to REQUEST"
"DHCPC: received DHCPACK message on port port-id"
"DHCPC: recieved non matching 'xid' (0x%X) in DHCPACK message"
"DHCPC: changing timer-event to SEEKING_CONFIGURATION_AND_WAITING_FOR_OFFERS"
"DHCPC: recieved non matching 'xid' (0x%X) in DHCPNAK message"
"DHCPC: deleting existing ip address configuration on port port-id"
"DHCPC: received DHCPNAK packet on port port-id"
"DHCPC: changing port port-id state from REQUEST to INIT-SELECTING"
"DHCPC: received DHCPCOFFER packet on port port-id> while in bound state"
"DHCPC: received DHCPREQUEST packet on port port-id while in bound state"
"DHCPC: received DHCPDECLINE packet on port port-id while in bound state"
"DHCPC: received DHCPACK packet on port port-id while in bound state"
"DHCPC: received DHCPNAK packet on port port-id while in bound state"
"DHCPC: received DHCPRELEASE packet on port port-id while in bound state"
"DHCPC: received DHCPINFORM packet on port port-id while in bound state"
"DHCPC: received DHCPINFORM packet on port port-id while in bound state"
"DHCPC: received unknown packet on port port-id while in bound state"
"DHCPC: received DHCPACK packet in renewal-state on port port-id"
"DHCPC: received non matching 'xid' (0x%X) in RENEWAL message"
"DHCPC: TFTP flash read error"
"DHCPC: changing port port-id state from RENEWING to BOUND"
"DHCPC: received non matching 'xid' (0x%X) in DHCPNAK message"
"DHCPC: received DHCPNAK packet in renewal-state on port port-id"
"DHCPC: changing port port-id state from RENEWING to INIT-SELECTING"
"DHCPC: received DHCPACK packet in rebind-state on port port-id"
"DHCPC: received non matching 'xid' (0x%X) in REBIND message"
"DHCPC: changing port port-id state from REBINDING to BOUND"
"DHCPC: received non matching 'xid' (0x%X) in DHCPNAK message"
"DHCPC: received DHCPNAK packet in renewal-state on port port-id"
"DHCPC: changing port port-id state from REBIND to INIT-SELECTING"
"DHCPC: sending packet port port-id"
"DHCPC: send completion called on port: port-id"
"DHCPC: Freeing packet"
"DHCPC: unable to get some-number option from dhcp message from port port-id"
```

```
"DHCPC: received server id address option: ip-address from port port-id"
"DHCPC: received lease-time option: some-number from port port-id"
"DHCPC: received domain-name option: %s from port port-id"
"DHCPC: received dns-server address option: ip-address from port port-id"
"DHCPC: received default-router address option: ip-address from port port-id"
"DHCPC: received TFTP server name option: %s from port port-id"
"DHCPC: received TFTP server address option: ip-address from port port-id"
"DHCPC: received Bootfile name option: %s from port port-id"
"DHCPC: received 'hostname' option: %s from port port-id"
"DHCPC: received maximum message size option: some-number from port port-id"
"DHCPC: lease timer events called with invalid port"
"DHCPC: changing port port-id state from BOUND to REBINDING"
"DHCPC: changing port port-id state from BOUND to RENEWING"
"DHCPC: deleting existing ip address configuration on port port-id"
"DHCPC: changing port port-id state from REQUESTING to INIT-SELECTING"
"DHCPC: failed to renew ip address with dhcp server; continuing with lease period"
"DHCPC: changing port port-id state from REBINDING to INIT_SELECTING"
"DHCPC: changing port port-id state from REBINDING to REQUESTING"
```

History

Release version	Command history
08.0.80	This command was modified to include information in the output for option 67 enhancements where both the image type and flash location are specified by the user.

debug dhcp-client warnings

Displays debugging information about the Dynamic Host Configuration Protocol (DHCP) client.

Syntax

`debug dhcp-client warnings`

`no debug dhcp-client warnings`

Modes

Privileged EXEC mode

Examples

The following example displays debugging information related to DHCP client warnings.

```
device# debug dhcp-client warnings
```

History

Release version	Command history
08.0.80	This command was modified to include information in the output for option 67 enhancements where both the image type and flash location are specified by the user.

debug forwarding hw-clear

Debugs the events which trigger MAC clear in hardware.

Syntax

```
debug forwarding hw-clear{debug-enable|disable |timer|}
```

```
no debug forwarding hw-clear{debug-enable|disable |timer|}
```

Parameters

debug-enable

Enables debugging of the events which trigger MAC clear in hardware in MCT scenario, port down scenario, and so on.

disable

Specifies MAC clear disable debugging.

timer

Resets the timer associated debug prints of clear mac debugs.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables debugging of MAC clear in hardware.

Examples

The following example enables debugging of the events which trigger MAC clear in hardware.

```
device#debug forwarding hw-clear debug-enable
```


Debug Commands H - P

debug hw

Enables the hardware backplane debugging feature in a device.

Syntax

debug hw

no debug hw

Examples

```
device# debug hw  
HW BP: backplane debugging is on
```

debug igmp-snoop add-del-oif all

Displays information about the addition or deletion of all outgoing interfaces (OIFs).

Syntax

debug igmp-snoop add-del-oif all

no debug igmp-snoop add-del-oif all

Modes

Privileged EXEC mode

Examples

```
device# debug igmp-snoop add-del-oif all
Jun 25 18:42:05:428348:info:fi_debug:debug_logs:1:61767334847579649: Add e3/2/3 to (11.4.1.2 225.1.1.1)
vlan 100
Jun 25 18:42:05:432216:info:fi_debug:debug_logs:1:61767339142546945: Add e3/2/3 to (11.4.1.2 225.1.1.2)
vlan 100
Jun 25 18:42:18:605037:info:fi_debug:debug_logs:1:61768614747833857: Del e3/2/3 from (11.4.1.2
225.1.1.1) vlan 100
Jun 25 18:42:18:606885:info:fi_debug:debug_logs:1:61768619042801153: Del e3/2/3 from (11.4.1.2
225.1.1.2) vlan 100
```

debug igmp-snoop clear

Clears all the IGMP snooping debug settings.

Syntax

debug igmp-snoop clear

no debug igmp-snoop clear

Modes

Privileged EXEC mode

Examples

```
device# debug igmp-snoop clear
```

debug igmp-snoop error

Displays the IGMP snooping multicast error messages.

Syntax

debug igmp-snoop error

no debug igmp-snoop error

Modes

Privileged EXEC mode

Examples

```
device# debug igmp-snoop error
Jun 25 19:05:44:929668:info:fi_debug:debug_logs:1:61905950622090753: IGMP: Error! ttl=255 (!= 1),
discard, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=28
Jun 25 19:05:45:929071:info:fi_debug:debug_logs:1:61906070881175041: IGMP: Error! ttl=255 (!= 1),
discard, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=28
Jun 25 19:05:46:919730:info:fi_debug:debug_logs:1:61906161075488257: IGMP: Error! ttl=255 (!= 1),
discard, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=28
Jun 25 19:05:47:913334:info:fi_debug:debug_logs:1:61906229794964993: IGMP: Error! ttl=255 (!= 1),
discard, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=28
```

debug igmp-snoop group

Displays the IGMP snooping multicast group information.

Syntax

```
debug igmp-snoop group group_address
no debug igmp-snoop group group_address
```

Parameters

group_address
 Specifies the address of the IGMP snoop multicast group.

Modes

Privileged EXEC mode

Examples

```
device# debug igmp-snoop group 225.1.1.1
Jun 25 19:12:16:714795:info:fi_debug:debug_logs:1:61944089931679233: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:12:16:714909:info:fi_debug:debug_logs:1:61944089931679233: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:12:16:715022:info:fi_debug:debug_logs:1:61944089931679233:         forward to router fid 0x4FFF
Jun 25 19:12:19:815556:info:fi_debug:debug_logs:1:61944364809586177:
-----
Jun 25 19:12:19:815671:info:fi_debug:debug_logs:1:61944364809586177: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:12:19:815781:info:fi_debug:debug_logs:1:61944364809586177: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:12:19:815902:info:fi_debug:debug_logs:1:61944364809586177:         consume pkt
Jun 25 19:12:25:531587:info:fi_debug:debug_logs:1:61944927450301953:
-----
Jun 25 19:12:25:531701:info:fi_debug:debug_logs:1:61944927450301953: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:12:25:531815:info:fi_debug:debug_logs:1:61944927450301953: IGMP: rcvd Leave(t=23)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:12:25:531902:info:fi_debug:debug_logs:1:61944927450301953:         V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 25 19:12:25:531988:info:fi_debug:debug_logs:1:61944927450301953: IGMP del VL100 (e3/2/3) from group
entry 225.1.1.1
Jun 25 19:12:25:532068:info:fi_debug:debug_logs:1:61944927450301953:         forward to router fid 0x4FFF
```

debug igmp-snoop level

Sets the debugging level of IGMP snooping activity.

Syntax

debug igmp-snoop level*decimal*

no debug igmp-snoop level*decimal*

Parameters

decimal

Specifies the debugging level of IGMP snooping activity and it can take values from 1 through 3.

Modes

Privileged EXEC mode

Usage Guidelines

Level 3 displays more information than level 2, and level 0 displays no information.

Examples

```

device#debug igmp-snoop
device#debug igmp-snoop level 3
Jun 25 19:29:14:421310:info:fi_debug:debug_logs:1:62043033093277185: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:29:14:421423:info:fi_debug:debug_logs:1:62043033093277185: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:29:14:421534:info:fi_debug:debug_logs:1:62043033093277185:      group: 225.1.1.1, life = 1020
Jun 25 19:29:14:421612:info:fi_debug:debug_logs:1:62043033093277185:      forward to router fid 0x4FFF
Jun 25 19:29:14:422213:info:fi_debug:debug_logs:1:62043037388244481:
-----
Jun 25 19:29:14:422297:info:fi_debug:debug_logs:1:62043037388244481: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:29:14:422396:info:fi_debug:debug_logs:1:62043037388244481: IGMP: rcvd Report-V2(t=22)
g=225.1.1.2 resp=0, pkt S=11.3.1.2 to 225.1.1.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:29:14:422491:info:fi_debug:debug_logs:1:62043037388244481:      group: 225.1.1.2, life = 1020
Jun 25 19:29:14:422564:info:fi_debug:debug_logs:1:62043037388244481:      forward to router fid 0x4FFF
Jun 25 19:29:16:292982:info:fi_debug:debug_logs:1:62043252136609281:
-----
Jun 25 19:29:16:293091:info:fi_debug:debug_logs:1:62043252136609281: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:29:16:293202:info:fi_debug:debug_logs:1:62043252136609281: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:29:16:293312:info:fi_debug:debug_logs:1:62043252136609281:      group: 225.1.1.1, life = 1020
Jun 25 19:29:16:293387:info:fi_debug:debug_logs:1:62043252136609281:      igmp-report-control, filter out
Jun 25 19:29:16:293474:info:fi_debug:debug_logs:1:62043252136609281:      consume pkt
Jun 25 19:29:24:047698:info:fi_debug:debug_logs:1:62044008050853377:
-----
Jun 25 19:29:24:048390:info:fi_debug:debug_logs:1:62044008050853377: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:29:24:048509:info:fi_debug:debug_logs:1:62044008050853377: IGMP: rcvd Report-V2(t=22)
g=225.1.1.2 resp=0, pkt S=11.3.1.2 to 225.1.1.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:29:24:048611:info:fi_debug:debug_logs:1:62044008050853377:      group: 225.1.1.2, life = 1020
Jun 25 19:29:24:048685:info:fi_debug:debug_logs:1:62044008050853377:      igmp-report-control, filter out
Jun 25 19:29:24:048774:info:fi_debug:debug_logs:1:62044008050853377:      consume pkt
Jun 25 19:29:33:205523:info:fi_debug:debug_logs:1:62044914288952833:
-----
Jun 25 19:29:33:205633:info:fi_debug:debug_logs:1:62044914288952833: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:29:33:205745:info:fi_debug:debug_logs:1:62044914288952833: IGMP: rcvd Leave(t=23)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:29:33:205830:info:fi_debug:debug_logs:1:62044914288952833:      V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 25 19:29:33:205920:info:fi_debug:debug_logs:1:62044914288952833:      forward to router fid 0x4FFF
Jun 25 19:29:33:206503:info:fi_debug:debug_logs:1:62044918583920129:
-----
Jun 25 19:29:33:206586:info:fi_debug:debug_logs:1:62044918583920129: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:29:33:206684:info:fi_debug:debug_logs:1:62044918583920129: IGMP: rcvd Leave(t=23)
g=225.1.1.2 resp=0, pkt S=11.3.1.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:29:33:206762:info:fi_debug:debug_logs:1:62044918583920129:      V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 25 19:29:33:206842:info:fi_debug:debug_logs:1:62044918583920129:      forward to router fid 0x4FFF
Jun 25 19:29:40:830761:info:fi_debug:debug_logs:1:62045644433393153:
-----
Jun 25 19:29:40:830873:info:fi_debug:debug_logs:1:62045644433393153: igmp_snoop_receive: receive igmp
on vlan 500, src_port 1/1/16 from 609c.9fbb.d94c
Jun 25 19:29:40:830985:info:fi_debug:debug_logs:1:62045644433393153: IGMP: rcvd Query(t=17) V2
g=0.0.0.0 resp=100, pkt S=150.1.1.2 to 224.0.0.1, on VL500 (phy lg4), igmp_size=8
Jun 25 19:29:40:831068:info:fi_debug:debug_logs:1:62045644433393153:      L2 fwd

```

debug igmp-snoop packet

Displays debugging information related to the IGMP snoop packets.

Syntax

debug igmp-snoop packets*source_address group_address*

no debug igmp-snoop packets*source_address group_address*

Parameters

source_address

Specifies the source address of the IGMP snoop packet.

group_address

Specifies the address of the IGMP snoop multicast group.

Modes

Privileged EXEC mode

Examples

```
device#debug igmp-snoop group 225.1.1.1
Jun 25 19:12:16:714795:info:fi_debug:debug_logs:1:61944089931679233: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:12:16:714909:info:fi_debug:debug_logs:1:61944089931679233: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:12:16:715022:info:fi_debug:debug_logs:1:61944089931679233:         forward to router fid 0x4FFF
Jun 25 19:12:19:815556:info:fi_debug:debug_logs:1:61944364809586177:
-----
Jun 25 19:12:19:815671:info:fi_debug:debug_logs:1:61944364809586177: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:12:19:815781:info:fi_debug:debug_logs:1:61944364809586177: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:12:19:815902:info:fi_debug:debug_logs:1:61944364809586177:         consume pkt
Jun 25 19:12:25:531587:info:fi_debug:debug_logs:1:61944927450301953:
-----
Jun 25 19:12:25:531701:info:fi_debug:debug_logs:1:61944927450301953: igmp_snoop_receive: receive igmp
on vlan 100, src_port 3/2/3 from 0010.9400.0002
Jun 25 19:12:25:531815:info:fi_debug:debug_logs:1:61944927450301953: IGMP: rcvd Leave(t=23)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 19:12:25:531902:info:fi_debug:debug_logs:1:61944927450301953:         V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 25 19:12:25:531988:info:fi_debug:debug_logs:1:61944927450301953: IGMP del VL100 (e3/2/3) from group
entry 225.1.1.1
Jun 25 19:12:25:532068:info:fi_debug:debug_logs:1:61944927450301953:         forward to router fid 0x4FFF
```

debug igmp-snoop port ethernet

Displays the IGMP snooping related debug information for the specified Ethernet interface.

Syntax

```
debug igmp-snoop port ethernet num
```

```
no debug igmp-snoop port ethernet num
```

Parameters

num

Specifies the stack ID, slot number, and port number of a specific Ethernet port.

Modes

Privileged EXEC mode

Examples

```
device# debug igmp-snoop port ethernet 1/1/2
IGMP: rcvd Report-V2(t=22) g=228.1.1.6 resp=0, pkt S=10.13.13.2 to 228.1.1.6, on
VL130 (phy e1/1/2), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=228.1.1.8 resp=0, pkt S=10.13.13.2 to 228.1.1.8, on
VL130 (phy e1/1/2), igmp_size=8
```

debug igmp-snoop show

Displays all the IGMP snooping debug settings.

Syntax

```
debug igmp-snoop show  
no debug igmp-snoop show
```

Modes

Privileged EXEC mode

Examples

```
device# debug igmp-snoop show  
igmp debug-enable-any = 1  
debug igmpsnoop is enabled  
IGMP: rcvd Query(t=17) V2 g=0.0.0.0 resp=100, pkt S=10.1.15.1 to 224.0.0.1, on  
VL100 (phy e3/1/6), igmp_size=8  
IGMP: rcvd Report-V2(t=22) g=230.1.1.12 resp=0, pkt S=10.85.1.3 to 230.1.1.12, on  
VL100 (phy e1/1/48), igmp_size=8  
IGMP: rcvd Report-V2(t=22) g=230.1.4.148 resp=0, pkt S=10.85.1.3 to 230.1.4.148,  
on VL100 (phy e1/1/48), igmp_size=8  
IGMP: rcvd Report-V2(t=22) g=230.1.2.22 resp=0, pkt S=10.85.1.3 to 230.1.2.22, on  
VL100 (phy e1/1/48), igmp_size=8  
IGMP: rcvd Report-V2(t=22) g=230.1.1.92 resp=0, pkt S=10.85.1.3 to 230.1.1.92, on  
VL100 (phy e1/1/48), igmp_size=8
```

debug igmp-snoop source

Displays the IGMP snooping related debug information for the specified source address

Syntax

debug igmp-snoop source*source_address*

no debug igmp-snoop source*source_address*

Parameters

source_address

Specifies the source address.

Modes

Privileged EXEC mode

Examples

```
device#debug igmp-snoop vlan 100
device#debug igmp-snoop source 100.1.3.2
Jun 14 14:09:49:387272:info:fi_debug:debug_logs:1:126061127287178753: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=100.1.3.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 14 14:09:49:387423:info:fi_debug:debug_logs:1:126061127287178753: forward to router fid 0xE1D
Jun 14 14:09:49:388627:info:fi_debug:debug_logs:1:126061131582146049: IGMP: rcvd Report-V2(t=22)
g=225.1.1.2 resp=0, pkt S=100.1.3.2 to 225.1.1.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 14 14:09:49:388748:info:fi_debug:debug_logs:1:126061131582146049: forward to router fid 0xE1D
Jun 14 14:09:55:677565:info:fi_debug:debug_logs:1:126061784417175041: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=100.1.3.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 14 14:09:55:677720:info:fi_debug:debug_logs:1:126061784417175041: consume pkt
Jun 14 14:09:55:899507:info:fi_debug:debug_logs:1:126061805892011521: IGMP: rcvd Report-V2(t=22)
g=225.1.1.2 resp=0, pkt S=100.1.3.2 to 225.1.1.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 14 14:09:55:899664:info:fi_debug:debug_logs:1:126061805892011521: consume pkt
Jun 14 14:09:58:363620:info:fi_debug:debug_logs:1:126062076474951169: IGMP: rcvd Leave(t=23)
g=225.1.1.1 resp=0, pkt S=100.1.3.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 14 14:09:58:363745:info:fi_debug:debug_logs:1:126062076474951169: V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 14 14:09:58:363839:info:fi_debug:debug_logs:1:126062076474951169: forward to router fid 0xE1D
Jun 14 14:09:58:364904:info:fi_debug:debug_logs:1:126062080769918465: IGMP: rcvd Leave(t=23)
g=225.1.1.2 resp=0, pkt S=100.1.3.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 14 14:09:58:365004:info:fi_debug:debug_logs:1:126062080769918465: V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 14 14:09:58:365087:info:fi_debug:debug_logs:1:126062080769918465: forward to router fid 0xE1D
```

debug igmp-snoop timer

Displays information about the IGMP snooping related timer events.

Syntax

debug igmp-snoop timer

no debug igmp-snoop timer

Modes

Privileged EXEC mode

Examples

```
device#debug igmp-snoop timer
Jun 25 20:09:38:129526:info:fi_debug:debug_logs:1:507852705613480704: IGMP timer, VL100(e3/2/3) change
Vl client age out
Jun 25 20:09:59:084433:info:fi_debug:debug_logs:1:507870113115931392: igmp timer, 225.1.1.1
VL100(e3/2/3) switch back to include mode
```

debug igmp-snoop vlan

Displays the IGMP snooping related debug information for the specified VLAN ID.

Syntax

```
debug igmp-snoop vlan vlan_id
```

```
no debug igmp-snoop vlan vlan_id
```

Parameters

vlan_id

Specifies the VLAN ID.

Modes

Privileged EXEC mode

Examples

```
device#debug igmp-snoop vlan 100
Jun 25 20:12:51:080503:info:fi_debug:debug_logs:1:508013371750089472: IGMP send Query(t=17) V2,
s=9.9.9.9 0.0.0.0 to VL100(ethe 3/2/3 lag lg6 ) rsp=200 igmp=8B, pkt=46B
Jun 25 20:12:51:081330:info:fi_debug:debug_logs:1:508013371750089472: IGMP send Query(t=17) V3,
s=9.9.9.9 0.0.0.0 to VL100(lag lg1 ) rsp=137 igmp=12B, pkt=50B
Jun 25 20:12:51:734767:info:fi_debug:debug_logs:1:62298343129220609: IGMP: rcvd Report-V2(t=22)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 225.1.1.1, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 20:12:51:736548:info:fi_debug:debug_logs:1:62298343129220609:         forward to router fid 0x4FFF
Jun 25 20:12:51:737200:info:fi_debug:debug_logs:1:62298347424187905: IGMP: rcvd Report-V2(t=22)
g=225.1.1.2 resp=0, pkt S=11.3.1.2 to 225.1.1.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 20:12:51:739037:info:fi_debug:debug_logs:1:62298347424187905:         forward to router fid 0x4FFF
Jun 25 20:12:53:900280:info:fi_debug:debug_logs:1:62298557877585409: IGMP: rcvd Leave(t=23)
g=225.1.1.1 resp=0, pkt S=11.3.1.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 20:12:53:900405:info:fi_debug:debug_logs:1:62298557877585409:         V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 25 20:12:53:901592:info:fi_debug:debug_logs:1:62298557877585409:         forward to router fid 0x4FFF
Jun 25 20:12:53:902213:info:fi_debug:debug_logs:1:62298562172552705: IGMP: rcvd Leave(t=23)
g=225.1.1.2 resp=0, pkt S=11.3.1.2 to 224.0.0.2, on VL100 (phy e3/2/3), igmp_size=8
Jun 25 20:12:53:902307:info:fi_debug:debug_logs:1:62298562172552705:         V2 leave. fast-leave-v2, not
rtr port. removed immediately
Jun 25 20:12:53:904511:info:fi_debug:debug_logs:1:62298562172552705:         forward to router fid 0x4FFF
```

debug ikev2

Enables IKEV2 debugging.

Syntax

debug ikev2{all|error|event|packet[detail|receive|send]|peerip-address|trace[info]}

no debug ikev2{all|error|event|packet[detail|receive|send]|peerip-address|trace[info]}

Parameters

all

Enables debugging of all IKEV2 instances.

error

Enables IKEV2 error debugging.

event

Enables IKEV2 event debugging.

packet

Enables IKEV2 packet debugging.

detail

Enables detailed IKEV2 packet debugging.

receive

Enables IKEV2 receive packet debugging.

send

Enables IKEV2 send packet debugging.

peerip-address

Enables IKEV2 peer debugging to filter messages for a specific peer.

trace

Enables IKEV2 trace debugging.

info

Enables IKEV2 trace debugging information.

Modes

Privileged EXEC mode

Examples

The following command debugs IKEv2 event during tunnel down and rekeying.

```
device# debug ikev2 event

May 27 11:33:23:860083:info:fi_debug:debug_logs:1:85943137406550784: IKE:
ipike_isakmp_resend_tmo_cb() :: for tunnel 1
May 27 11:33:19:629815:info:fi_debug:debug_logs:1:5041527101326849: IKE:
ike_ipsec_fpga_ingress_spi_hash_index_write:ingress spi 4935 removed from dummy fpga bucket 234
```

The following command debugs IKEv2 error during mismatch in algorithms.

```
device# debug ikev2 error

IKEV2: ike error is enabled
Debug: Mar 13 20:14:08 IKE: ipike_isakmp_resend_tmo_cb() :: for tunnel 44
Debug: Mar 13 20:14:39 IKE: ipike_ipsec_sadb_sa_rekey() :: rekey timeout for IPsec SA 0x1224Debug: Mar
13 20:14:08
IKE: ipike_isakmp_resend_tmo_cb() :: for tunnel 44
Debug: Mar 13 20:14:39 IKE: ipike_ipsec_sadb_sa_rekey() :: rekey timeout for IPsec SA 0x1224
Debug: Mar 13 20:21:39 IKE: ipike_payload_notify_process_error() :: exchange rejected with
NO_PROPOSAL_CHOSEN for tunnel 31
Debug: Mar 13 20:21:39 IKE: ipike_exchange_sa_init_on_delete() :: the exchange was not finished,
removing (incomplete)
IKE SA for tunnel 31
Debug: Mar 13 20:21:44 IKE: ipike_policy_select_sa_param: no proposal was accepted
Debug: Mar 13 20:21:44 IKE: ipike_exchange_sa_init_on_delete() :: the exchange was not finished,
removing (incomplete)
IKE SA for tunnel 31
Debug: Mar 13 20:21:49 IKE: ipike_payload_notify_process_error() :: exchange rejected with
NO_PROPOSAL_CHOSEN for tunnel 31
Debug: Mar 13 20:21:49 IKE: ipike_exchange_sa_init_on_delete() :: the exchange was not finished,
removing (incomplete)
IKE SA for tunnel 31
Debug: Mar 13 20:21:54 IKE: ike_wr_policy_accept_id return 1
```

Debug Commands H - P

debug ikev2

The following command debugs IKEv2 trace.

```
device# debug ikev2 trace
```

```
Debug: Mar 13 20:28:40 IKE: Locking IKE SA (ref count 1)
Debug: Mar 13 20:28:40 IKE:   initiator cookie: 0xe6e53f1404a54b7c
Debug: Mar 13 20:28:40 IKE:   responder cookie: 0xf81e5e7816388386
Debug: Mar 13 20:28:40 IKE: Locking IKE SA (ref count 2)
Debug: Mar 13 20:28:40 IKE:   initiator cookie: 0xe6e53f1404a54b7c
Debug: Mar 13 20:28:40 IKE:   responder cookie: 0xf81e5e7816388386
Debug: Mar 13 20:28:40 IKE: ipike_isakmp_hash_obj_cookie() :: hash key: id=721, type=37, init=1 -> val = 816f120f
Debug: Mar 13 20:28:40 IKE: ipike_isakmp_hash_add() :: hash: id=721, type=37, init=1, phasel=0
Debug: Mar 13 20:28:40 IKE: Sending request to 103.1.1.2 [500]
Debug: Mar 13 20:28:40 IKE: Message encrypted 88 bytes
Debug: Mar 13 20:28:40 IKE: Send 88 octets from 106.1.1.1:500 to 103.1.1.2:500
Debug: Mar 13 20:28:40 IKE: Releasing IKE SA (ref count 1), for tunnel 2
Debug: Mar 13 20:28:40 IKE:   initiator cookie: 0xe6e53f1404a54b7c
Debug: Mar 13 20:28:40 IKE:   responder cookie: 0xf81e5e7816388386
Debug: Mar 13 20:28:40 IKE: Locking IKE SA (ref count 1)
Debug: Mar 13 20:28:40 IKE:   initiator cookie: 0xb23c157874ab5638
Debug: Mar 13 20:28:40 IKE:   responder cookie: 0x599cb6ala4d3d0fb
Debug: Mar 13 20:28:40 IKE: Releasing IKE SA (ref count 0), for tunnel 17
Debug: Mar 13 20:28:40 IKE:   initiator cookie: 0xb23c157874ab5638
Debug: Mar 13 20:28:40 IKE:   responder cookie: 0x599cb6ala4d3d0fb
Debug: Mar 13 20:28:40 IKE: ipv4 packet received with src 103.1.1.2 and dest 106.1.1.1 vrf 0 length 88
Debug: Mar 13 20:28:40 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=721, type=37, init=1
Debug: Mar 13 20:28:40 IKE: Message decrypted 88 bytes
Debug: Mar 13 20:28:40 IKE: ipike_check_payloads() :: no payloads exist according to the ISAKMP header
Debug: Mar 13 20:28:40 IKE: ipike_isakmp_process_message_response() :: destroying completed exchange
Debug: Mar 13 20:28:40 IKE: ipike_isakmp_free_exchange() :: exchange 193/1/9 type - INFORMATIONAL
Debug: Mar 13 20:28:40 IKE: ipike_isakmp_hash_obj_cookie() :: hash key: id=0, type=0, init=0 -> val = 816f120f
Debug: Mar 13 20:28:40 IKE: Releasing IKE SA (ref count 0), for tunnel 2
Debug: Mar 13 20:28:40 IKE:   initiator cookie: 0xe6e53f1404a54b7c
Debug: Mar 13 20:28:40 IKE:   responder cookie: 0xf81e5e7816388386
```

The following command debugs IKEv2 trace info.

```
device# debug ikev2 trace info
```

```
IKEV2: trace info is enabled
DUT1#Debug: Mar 13 20:27:18 IKE: Received response 18.18.18.2[500], INFORMATIONAL, #2(2), ID 2da
Debug: Mar 13 20:27:18 IKE: informational exchange done
Debug: Mar 13 20:27:18 IKE: Received response 13.13.13.2[500], INFORMATIONAL, #2(2), ID 2
Debug: Mar 13 20:27:18 IKE: informational exchange done
Debug: Mar 13 20:27:18 IKE: Received response 4.4.4.2[500], INFORMATIONAL, #2(2), ID 2bc
Debug: Mar 13 20:27:18 IKE: informational exchange done
Debug: Mar 13 20:27:28 IKE: Received response 22.22.22.2[500], INFORMATIONAL, #2(2), ID 2de
Debug: Mar 13 20:27:28 IKE: informational exchange done
Debug: Mar 13 20:27:28 IKE: Received response 2.2.2.2[500], INFORMATIONAL, #2(2), ID 2c7
Debug: Mar 13 20:27:28 IKE: informational exchange done
```

The following command debugs IKEv2 packet.

```
device# debug ikev2 packet

IKEV2: packet debugging is on
Debug: Mar 13 20:29:26 ike ipv4 packet received with src 122.1.1.2 and dest 120.1.1.1 vrf 3 length 88
Debug: Mar 13 20:29:26 ike_transmit_packet send packet to 122.1.1.2:500 from 120.1.1.1:500 vrf:3 length 88
Debug: Mar 13 20:29:26 IKE sub task: packet transmitted to 122.1.1.2
Debug: Mar 13 20:29:37 ike ipv4 packet received with src 102.1.1.2 and dest 100.1.1.1 vrf 0 length 88
Debug: Mar 13 20:29:37 ike_transmit_packet send packet to 102.1.1.2:500 from 100.1.1.1:500 vrf:0 length 88
Debug: Mar 13 20:29:37 IKE sub task: packet transmitted to 102.1.1.2
Debug: Mar 13 20:29:41 ike_transmit_packet send packet to 12.12.12.2:500 from 12.12.12.1:500 vrf:0 length 88
Debug: Mar 13 20:29:41 IKE sub task: packet transmitted to 12.12.12.2
Debug: Mar 13 20:29:41 ike ipv4 packet received with src 12.12.12.2 and dest 12.12.12.1 vrf 0 length 88
Debug: Mar 13 20:29:58 IKE: Create notify payload with message type 16393
Debug: Mar 13 20:29:58 IKE: Create notify payload with message type 16394
Debug: Mar 13 20:29:58 ike_transmit_packet send packet to 20.20.20.2:500 from 20.20.20.1:500 vrf:0 length 248
Debug: Mar 13 20:29:58 IKE sub task: packet transmitted to 20.20.20.2
Debug: Mar 13 20:29:58 ike ipv4 packet received with src 20.20.20.2 and dest 20.20.20.1 vrf 0 length 248
Debug: Mar 13 20:29:58 IKE: Process initial contact notify payload for tunnel 20
Debug: Mar 13 20:29:58 ike_transmit_packet send packet to 20.20.20.2:500 from 20.20.20.1:500 vrf:0 length 88
Debug: Mar 13 20:29:58 IKE sub task: packet transmitted to 20.20.20.2
Debug: Mar 13 20:29:58 ike ipv4 packet received with src 20.20.20.2 and dest 20.20.20.1 vrf 0 length 88
Debug: Mar 13 20:29:58 ike ipv4 packet received with src 20.20.20.2 and dest 20.20.20.1 vrf 0 length 88
Debug: Mar 13 20:29:58 ike_transmit_packet send packet to 20.20.20.2:500 from 20.20.20.1:500 vrf:0 length 88
Debug: Mar 13 20:29:58 IKE sub task: packet transmitted to 20.20.20.2
```

The following command debugs IKEv2 send packet.

```
device# debug ikev2 packet send

Debug: Mar 13 20:30:53 ike_transmit_packet send packet to 19.19.19.2:500 from 19.19.19.1:500 vrf:0 length 88
```

The following command debugs IKEv2 receive packet.

```
device# debug ikev2 packet receive

Debug: Debug: Mar 13 20:31:32 ike ipv4 packet received with src 13.13.13.2 and dest 13.13.13.1 vrf 0 length 80
Debug: Mar 13 20:32:10 ike ipv4 packet received with src 122.1.1.2 and dest 120.1.1.1 vrf 3 length 88
Debug: Mar 13 20:32:11 ike ipv4 packet received with src 122.1.1.2 and dest 120.1.1.1 vrf 3 length 88
Debug: Mar 13 20:32:26 ike ipv4 packet received with src 18.18.18.2 and dest 18.18.18.1 vrf 0 length 88
Debug: Mar 13 20:32:26 ike ipv4 packet received with src 4.4.4.2 and dest 4.4.4.1 vrf 0 length 88
```

Debug Commands H - P

debug ikev2

The following command debugs IKEv2 packets in detail.

```
device# debug ikev2 packet detail
```

```
Debug: Mar 13 20:33:17 +++ ISAKMP package start (message # 1) +++
Debug: Mar 13 20:33:17 < IKE Header >
Debug: Mar 13 20:33:17 IKE_SA Initiator's SPI: 0x333aa6c1ea301ed5
Debug: Mar 13 20:33:17 IKE_SA Responder's SPI: 0xb311338eb36cd7de
Debug: Mar 13 20:33:17 Next Payload: none (0)
Debug: Mar 13 20:33:17 Version: 2.0
Debug: Mar 13 20:33:17 Exchange Type: INFORMATIONAL
Debug: Mar 13 20:33:17 Flags: [ INITIATOR ]
Debug: Mar 13 20:33:17 Message ID: 684
Debug: Mar 13 20:33:17 Length: 28 (#x)
Debug: Mar 13 20:33:17 --- ISAKMP package end (message # 1) ---
Debug: Mar 13 20:33:17 +++ ISAKMP package start (message # 2) +++
Debug: Mar 13 20:33:17 < IKE Header >
Debug: Mar 13 20:33:17 IKE_SA Initiator's SPI: 0x333aa6c1ea301ed5
Debug: Mar 13 20:33:17 IKE_SA Responder's SPI: 0xb311338eb36cd7de
Debug: Mar 13 20:33:17 Next Payload: none (0)
Debug: Mar 13 20:33:17 Version: 2.0
Debug: Mar 13 20:33:17 Exchange Type: INFORMATIONAL
Debug: Mar 13 20:33:17 Flags: [ RESPONSE ]
Debug: Mar 13 20:33:17 Message ID: 684
Debug: Mar 13 20:33:17 Length: 28 (#x)
Debug: Mar 13 20:33:17 --- ISAKMP package end (message # 2) ---
Debug: Mar 13 20:33:23 +++ ISAKMP package start (message # 1) +++
Debug: Mar 13 20:33:23 < IKE Header >
Debug: Mar 13 20:33:23 IKE_SA Initiator's SPI: 0x506e28a9b3870d90
Debug: Mar 13 20:33:23 IKE_SA Responder's SPI: 0xb860b97a5b1995b8
Debug: Mar 13 20:33:23 Next Payload: none (0)
Debug: Mar 13 20:33:23 Version: 2.0
Debug: Mar 13 20:33:23 Exchange Type: INFORMATIONAL
Debug: Mar 13 20:33:23 Flags: [ ]
Debug: Mar 13 20:33:23 Message ID: 2
Debug: Mar 13 20:33:23 Length: 28 (#x)
```

The following command debugs all IKEv2 instances.

```
device# debug ikev2 all

Debug: Mar 13 20:38:39 ike ipv4 packet received with src 102.1.1.2 and dest 100.1.1.1 vrf 0 length 88
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=6, type=37, init=0
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=6, type=37, init=0
Debug: Mar 13 20:38:39 IKE: New exchange started (INFORMATIONAL with Message ID: 6)
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 1)
Debug: Mar 13 20:38:39 IKE: initiator cookie: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE: responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA in SADB database, id=tunnel44,
looking up in config database
Debug: Mar 13 20:38:39 IKE: Releasing IKE SA (ref count 0), for tunnel 44
Debug: Mar 13 20:38:39 IKE: initiator cookie: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE: responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA configuration based on SADB
entry
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 1)
Debug: Mar 13 20:38:39 IKE: initiator cookie: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE: responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA in SADB database, id=tunnel44,
looking up in config database
Debug: Mar 13 20:38:39 IKE: Releasing IKE SA (ref count 0), for tunnel 44
Debug: Mar 13 20:38:39 IKE: initiator cookie: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE: responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA configuration based on SADB
entry
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 1)
Debug: Mar 13 20:38:39 IKE: initiator cookie: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE: responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_obj_cookie() :: hash key: id=6, type=37, init=0 -> val =
f2d6968f
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_add() :: hash: id=6, type=37, init=0, phasel=0
Debug: Mar 13 20:38:39 IKE: Received request 102.1.1.2[500], INFORMATIONAL, #1(2), ID 6
Debug: Mar 13 20:38:39 IKE: Message decrypted 88 bytes
Debug: Mar 13 20:38:39 +++ ISAKMP package start (message # 1) +++
Debug: Mar 13 20:38:39 < IKE Header >
Debug: Mar 13 20:38:39 IKE_SA Initiator's SPI: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE_SA Responder's SPI: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 Next Payload: delete (42)
Debug: Mar 13 20:38:39 Version: 2.0
Debug: Mar 13 20:38:39 Exchange Type: INFORMATIONAL
Debug: Mar 13 20:38:39 Flags: [ INITIATOR ]
Debug: Mar 13 20:38:39 Message ID: 6
Debug: Mar 13 20:38:39 Length: 40 (#x)
Debug: Mar 13 20:38:39 IKE: < delete >
Debug: Mar 13 20:38:39 IKE: Next Payload: none (0)
Debug: Mar 13 20:38:39 IKE: Payload Length: 12 (#x)
Debug: Mar 13 20:38:39 IKE: protocol ID: IPSEC_ESP
Debug: Mar 13 20:38:39 IKE: SPI 1: 00001748
Debug: Mar 13 20:38:39 --- ISAKMP package end (message # 1) ---
Debug: Mar 13 20:38:39 IKE: Deleting IPsec SA
Debug: Mar 13 20:38:39 IKE: Deleting IPsec SA
Debug: Mar 13 20:38:39 IKE: Sending response to 102.1.1.2 [500]
Debug: Mar 13 20:38:39 +++ ISAKMP package start (message # 2) +++
Debug: Mar 13 20:38:39 < IKE Header >
Debug: Mar 13 20:38:39 IKE_SA Initiator's SPI: 0xd762b2alb460a8da
Debug: Mar 13 20:38:39 IKE_SA Responder's SPI: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 Next Payload: delete (42)
Debug: Mar 13 20:38:39 Version: 2.0
Debug: Mar 13 20:38:39 Exchange Type: INFORMATIONAL
Debug: Mar 13 20:38:39 Flags: [ RESPONSE ]
Debug: Mar 13 20:38:39 Message ID: 6
Debug: Mar 13 20:38:39 Length: 40 (#x)
Debug: Mar 13 20:38:39 IKE: < delete >
Debug: Mar 13 20:38:39 IKE: Next Payload: none (0)
Debug: Mar 13 20:38:39 IKE: Payload Length: 12 (#x)
Debug: Mar 13 20:38:39 IKE: protocol ID: IPSEC_ESP
Debug: Mar 13 20:38:39 IKE: SPI 1: 00000b81
Debug: Mar 13 20:38:39 --- ISAKMP package end (message # 2) ---
```

Debug Commands H - P

debug ikev2

```
Debug: Mar 13 20:38:39 IKE: Sending message 102.1.1.2[500]: INFORMATIONAL, #2(2), ID 6
Debug: Mar 13 20:38:39 IKE: Message encrypted 88 bytes
Debug: Mar 13 20:38:39 IKE: Send 88 octets from 100.1.1.1:500 to 102.1.1.2:500
Debug: Mar 13 20:38:39 IKE: informational exchange done
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_add_ipsec_negotiation() :: Adding IPsec negotiation for
'tunnel44'
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_add_ipsec_negotiation() :: looking up IKE SA based on addresses
Debug: Mar 13 20:38:39 IKE:      local address: 100.1.1.1
Debug: Mar 13 20:38:39 IKE:      remote address: 102.1.1.2
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 2)
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_add_ipsec_negotiation() :: ipsec sa will not be started by
responder for tunnel 44
Debug: Mar 13 20:38:39 IKE: Releasing IKE SA (ref count 1), for tunnel 44
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_dispatch_start_sa_negotiation() :: failed to start IPSec negotiation
(tunnel44_0)

SYSLOG: <14> Mar 13 20:38:39 DUT1 IPsec: IPSec session down Source 102.1.1.2 Destination 100.1.1.1 VRF
0 SPI 0xb81 Direction Ingress

SYSLOG: <14> Mar 13 20:38:39 DUT1 IPsec: IPSec session down Source 100.1.1.1 Destination 102.1.1.2 VRF
0 SPI 0x1748 Direction Egress
Debug: Mar 13 20:38:39 IKE: ipv4 packet received with src 102.1.1.2 and dest 100.1.1.1 vrf 0 length 88
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=7, type=37, init=0
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=7, type=37, init=0
Debug: Mar 13 20:38:39 IKE: New exchange started (INFORMATIONAL with Message ID: 7)
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 2)
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA in SADB database, id=tunnel44,
looking up in config database
Debug: Mar 13 20:38:39 IKE: Releasing IKE SA (ref count 1), for tunnel 44
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA configuration based on SADB
entry
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 2)
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA in SADB database, id=tunnel44,
looking up in config database
Debug: Mar 13 20:38:39 IKE: Releasing IKE SA (ref count 1), for tunnel 44
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_lookup_config() :: Found IKE SA configuration based on SADB
entry
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 2)
Debug: Mar 13 20:38:39 IKE:      initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE:      responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_obj_cookie() :: hash key: id=7, type=37, init=0 -> val =
bec1679
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_add() :: hash: id=7, type=37, init=0, phase1=0
Debug: Mar 13 20:38:39 IKE: Received request 102.1.1.2[500], INFORMATIONAL, #1(2), ID 7
Debug: Mar 13 20:38:39 IKE: Message decrypted 88 bytes
Debug: Mar 13 20:38:39 +++ ISAKMP package start (message # 1) +++
Debug: Mar 13 20:38:39 < IKE Header >
Debug: Mar 13 20:38:39 IKE_SA Initiator's SPI: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE_SA Responder's SPI: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 Next Payload:      delete (42)
Debug: Mar 13 20:38:39 Version:          2.0
Debug: Mar 13 20:38:39 Exchange Type:  INFORMATIONAL
Debug: Mar 13 20:38:39 Flags:          [ INITIATOR ]
Debug: Mar 13 20:38:39 Message ID:      7
Debug: Mar 13 20:38:39 Length:          36 (#x)
Debug: Mar 13 20:38:39 IKE: < delete >
Debug: Mar 13 20:38:39 IKE:      Next Payload: none (0)
Debug: Mar 13 20:38:39 IKE:      Payload Length: 8 (#x)
Debug: Mar 13 20:38:39 IKE:      protocol ID: ISAKMP
Debug: Mar 13 20:38:39 --- ISAKMP package end (message # 1) ---
```

```

Debug: Mar 13 20:38:39 IKE: Setting IKE SA (ref count 2) state to dying
Debug: Mar 13 20:38:39 IKE: initiator cookie: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE: responder cookie: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 IKE: Sending response to 102.1.1.2 [500]
Debug: Mar 13 20:38:39 +++ ISAKMP package start (message # 2) +++
Debug: Mar 13 20:38:39 < IKE Header >
Debug: Mar 13 20:38:39 IKE_SA Initiator's SPI: 0xd762b2a1b460a8da
Debug: Mar 13 20:38:39 IKE_SA Responder's SPI: 0x22e7083e0ef7753a
Debug: Mar 13 20:38:39 Next Payload: none (0)
Debug: Mar 13 20:38:39 Version: 2.0
Debug: Mar 13 20:38:39 Exchange Type: INFORMATIONAL
Debug: Mar 13 20:38:39 Flags: [ RESPONSE ]
Debug: Mar 13 20:38:39 Message ID: 7
Debug: Mar 13 20:38:39 Length: 32 (#x)
Debug: Mar 13 20:38:39 --- ISAKMP package end (message # 2) ---
Debug: Mar 13 20:38:39 IKE: Sending message 102.1.1.2[500]: INFORMATIONAL, #2(2), ID 7
Debug: Mar 13 20:38:39 IKE: Message encrypted 88 bytes
Debug: Mar 13 20:38:39 IKE: Send 88 octets from 100.1.1.1:500 to 102.1.1.2:500
Debug: Mar 13 20:38:39 IKE: informational exchange done
Debug: Mar 13 20:38:39 IKE sub task: packet transmitted to 102.1.1.2

SYSLOG: <14> Mar 13 20:38:39 DUT1 IKEv2: IKEv2 session down Source 100.1.1.1 Destination 102.1.1.2 VRF
0 SPI 0xd762b2a1b460a8da

SYSLOG: <14> Mar 13 20:38:39 DUT1 PORT: tn44 down due to - IKE session down

SYSLOG: <14> Mar 13 20:38:39 DUT1 System: Interface ipsec_tunnl 44, state down - IKE session down
Debug: Mar 13 20:38:39 IKE: local public DH value
2520515a f7536f69 27413bc7 0efc4262 0f501aa6 0deeed19 6ad81b3e 192ca278
cbc09936 34d4fe3d a60c2239 254a28f5 74225709 0bb186e0 95ee7777 134fdc4c
b6c021f4 39894aba 4c3dc91a elf8c018 089b1570 57179b21 2ddcfd10 284cb2a8

Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_obj_cookie() :: hash key: id=0, type=0, init=1 -> val =
78a81769
Debug: Mar 13 20:38:39 IKE: ipike_isakmp_hash_add() :: hash: id=0, type=34, init=1, phase1=1
Debug: Mar 13 20:38:39 Add Payload 33
Debug: Mar 13 20:38:39 Add Payload 47
Debug: Mar 13 20:38:39 Add Payload 41
Debug: Mar 13 20:38:39 Add Payload 34
Debug: Mar 13 20:38:39 Add Payload 40
Debug: Mar 13 20:38:39 IKE: Sending request to 102.1.1.2 [500]
Debug: Mar 13 20:38:39 +++ ISAKMP package start (message # 1) +++
Debug: Mar 13 20:38:39 < IKE Header >
Debug: Mar 13 20:38:39 IKE_SA Initiator's SPI: 0x4731b3c6a38c0641
Debug: Mar 13 20:38:39 IKE_SA Responder's SPI: 0x0000000000000000
Debug: Mar 13 20:38:39 Next Payload: security association (33)
Debug: Mar 13 20:38:39 Version: 2.0
Debug: Mar 13 20:38:39 Exchange Type: IKE_SA_INIT
Debug: Mar 13 20:38:39 Flags: [ INITIATOR ]
Debug: Mar 13 20:38:39 Message ID: 0
Debug: Mar 13 20:38:39 Length: 248 (#x)
Debug: Mar 13 20:38:39 IKE: < security association >
Debug: Mar 13 20:38:39 IKE: Next Payload: key exchange (34)
Debug: Mar 13 20:38:39 IKE: Payload Length: 48 (#x)
Debug: Mar 13 20:38:39 << proposal >>
Debug: Mar 13 20:38:39 Proposal #: 1
Debug: Mar 13 20:38:39 Protocol ID: ISAKMP
Debug: Mar 13 20:38:39 SPI Size: 0
Debug: Mar 13 20:38:39 IKE: # of Transforms: 4
Debug: Mar 13 20:38:39 <<< transform >>>
Debug: Mar 13 20:38:39 Type: dh
Debug: Mar 13 20:38:39 ID: ecp384
Debug: Mar 13 20:38:39 <<< transform >>>
Debug: Mar 13 20:38:39 Type: prf
Debug: Mar 13 20:38:39 ID: sha384
Debug: Mar 13 20:38:39 <<< transform >>>
Debug: Mar 13 20:38:39 Type: encr
Debug: Mar 13 20:38:39 ID: aes
Debug: Mar 13 20:38:39 Attr: 800e0100
Debug: Mar 13 20:38:39 <<< transform >>>
Debug: Mar 13 20:38:39 Type: integ
Debug: Mar 13 20:38:39 ID: sha384

```

Debug Commands H - P

debug ikev2

```
Debug: Mar 13 20:38:39 IKE: < key exchange >
Debug: Mar 13 20:38:39 IKE:     Next Payload: nonce (40)
Debug: Mar 13 20:38:39 IKE:     Payload Length: 104 (#x)
Debug: Mar 13 20:38:39 IKE:     dh group: 'ecp384'
Debug: Mar 13 20:38:39 IKE:     data:
2520515a f7536f69 27413bc7 0efc4262 0f501aa6 0deeed19 6ad81b3e 192ca278
cbc09936 34d4fe3d a60c2239 254a28f5 74225709 0bb186e0 95ee7777 134fdc4c
b6c021f4 39894aba 4c3dc91a e1f8c018 089b1570 57179b21 2ddcfd10 284cb2a8

Debug: Mar 13 20:38:39 IKE: < nonce >
Debug: Mar 13 20:38:39 IKE:     Next Payload: none (0)
Debug: Mar 13 20:38:39 IKE:     Payload Length: 68 (#x)
Debug: Mar 13 20:38:39 IKE:     data:
434bf3f8 3efe8553 e8c81844 2e3eed96 00380268 1908602d cd1437c2 624f4190
d00d7fe2 4e7fc709 20bdcc44 7373f178 0dfdd62c 370a97dc c01d7f35 3a0f6a3e

Debug: Mar 13 20:38:39 --- ISAKMP package end (message # 1) ---
Debug: Mar 13 20:38:39 IKE: Sending message 102.1.1.2[500]: IKE_SA_INIT, #1(4), ID 0
Debug: Mar 13 20:38:39 IKE: Send 248 octets from 100.1.1.1:500 to 102.1.1.2:500
Debug: Mar 13 20:38:39 IKE: Locking IKE SA (ref count 2)
Debug: Mar 13 20:38:39 IKE:     initiator cookie: 0x4731b3c6a38c0641
Debug: Mar 13 20:38:39 IKE:     responder cookie: 0x0000000000000000
Debug: Mar 13 20:38:39 IKE: Releasing IKE SA (ref count 1), for tunnel 44
Debug: Mar 13 20:38:39 IKE:     initiator cookie: 0x4731b3c6a38c0641
Debug: Mar 13 20:38:39 IKE:     responder cookie: 0x0000000000000000
Debug: Mar 13 20:38:39 ike_transmit_packet send packet to 102.1.1.2:500 from 100.1.1.1:500 vrf:0 length
248
Debug: Mar 13 20:38:39 IKE sub task: packet transmitted to 102.1.1.2
Debug: Mar 13 20:38:42 ike_ipv4 packet received with src 102.1.1.2 and dest 100.1.1.1 vrf 0 length 248
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=0, type=0, init=0
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=0, type=0, init=0
Debug: Mar 13 20:38:42 IKE: New exchange started (IKE_SA_INIT with Message ID: 0)
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_lookup_config() :: Found IKE SA configuration based on
addresses
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_lookup_config() :: Found IKE SA configuration based on
addresses
Debug: Mar 13 20:38:42 IKE: Setting IKE SA (ref count 0) state to constructing
Debug: Mar 13 20:38:42 IKE:     initiator cookie: 0x20beacbe38bc465
Debug: Mar 13 20:38:42 IKE:     responder cookie: 0x7f672fffc23b040d
Debug: Mar 13 20:38:42 IKE: Locking IKE SA (ref count 1)
Debug: Mar 13 20:38:42 IKE:     initiator cookie: 0x20beacbe38bc465
Debug: Mar 13 20:38:42 IKE:     responder cookie: 0x7f672fffc23b040d
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_hash_obj_cookie() :: hash key: id=0, type=0, init=0 -> val =
9b36fb21
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_hash_add() :: hash: id=0, type=34, init=0, phase1=1
Debug: Mar 13 20:38:42 IKE: Received request 102.1.1.2[500], IKE_SA_INIT, #1(4), ID 0
Debug: Mar 13 20:38:42 +++ ISAKMP package start (message # 1) +++
Debug: Mar 13 20:38:42 < IKE Header >
Debug: Mar 13 20:38:42   IKE_SA Initiator's SPI: 0x20beacbe38bc465
Debug: Mar 13 20:38:42   IKE_SA Responder's SPI: 0x0000000000000000
Debug: Mar 13 20:38:42   Next Payload: security association (33)
Debug: Mar 13 20:38:42   Version: 2.0
Debug: Mar 13 20:38:42   Exchange Type: IKE_SA_INIT
Debug: Mar 13 20:38:42   Flags: [ INITIATOR ]
Debug: Mar 13 20:38:42   Message ID: 0
Debug: Mar 13 20:38:42   Length: 248 (#x)
Debug: Mar 13 20:38:42 IKE: < security association >
Debug: Mar 13 20:38:42 IKE:     Next Payload: key exchange (34)
Debug: Mar 13 20:38:42 IKE:     Payload Length: 48 (#x)
Debug: Mar 13 20:38:42 <<< proposal >>>
Debug: Mar 13 20:38:42   Proposal #: 1
Debug: Mar 13 20:38:42   Protocol ID: ISAKMP
Debug: Mar 13 20:38:42   SPI Size: 0
Debug: Mar 13 20:38:42 IKE:     # of Transforms: 4
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42   Type: dh
Debug: Mar 13 20:38:42   ID: ecp384
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42   Type: prf
Debug: Mar 13 20:38:42   ID: sha384
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42   Type: encr
```

```
Debug: Mar 13 20:38:42 ID: aes
Debug: Mar 13 20:38:42 Attr: 800e0100
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: integ
Debug: Mar 13 20:38:42 ID: sha384
Debug: Mar 13 20:38:42 IKE: < key exchange >
Debug: Mar 13 20:38:42 IKE: Next Payload: nonce (40)
Debug: Mar 13 20:38:42 IKE: Payload Length: 104 (#x)
Debug: Mar 13 20:38:42 IKE: dh group: 'ecp384'
Debug: Mar 13 20:38:42 IKE: data:
d4d789d3 2d30c979 d856295d 5b740be8 32a7b1ff 6626d3d1 0d51f79c 9573fa48
4d158059 89d81198 1b525537 1c96102b e97e073d 8fe4b757 ebbbc40c 6ef76a3a
f5ac68f4 b24c094c 9af9c60d c8a02faa 9506dad8 5be9fe78 cf979743 22856a11

Debug: Mar 13 20:38:42 IKE: < nonce >
Debug: Mar 13 20:38:42 IKE: Next Payload: none (0)
Debug: Mar 13 20:38:42 IKE: Payload Length: 68 (#x)
Debug: Mar 13 20:38:42 IKE: data:
2d9db0d5 6453b7f2 0accc5d2 6117d17c 77518abf 1ff952d6 540658e0 98f4019d
c65b6824 ac19716d 25a398cd 16717c6d dc870989 149cff89 9ca77cf8 bbccb6f9

Debug: Mar 13 20:38:42 --- ISAKMP package end (message # 1) ---
Debug: Mar 13 20:38:42 IKE: selected 'aes' as encryption algorithm
Debug: Mar 13 20:38:42 IKE: selected '256' as key length
Debug: Mar 13 20:38:42 IKE: selected 'sha384' as hash algorithm
Debug: Mar 13 20:38:42 IKE: selected 'sha384' as integrity algorithm
Debug: Mar 13 20:38:42 IKE: selected 'ecp384' as DH group description
Debug: Mar 13 20:38:42 IKE: local public DH value
f20a76e2 a5f4ffd3 f1e602db 175e27a5 de6ee0bb 5398912b e42aa726 3707bffa
af06f3ab 07b36d5e 91977b7d 71c29893 c6319ef9 5a8d8dbf 7d2f177c c6dd270b
01f81f5d 8fb8c352 6da36969 1c8252aa 4c251cda 68c6d48e 4dff1b3b 93644bbd

Debug: Mar 13 20:38:42 IKE: remote public DH value
d4d789d3 2d30c979 d856295d 5b740be8 32a7b1ff 6626d3d1 0d51f79c 9573fa48
4d158059 89d81198 1b525537 1c96102b e97e073d 8fe4b757 ebbbc40c 6ef76a3a
f5ac68f4 b24c094c 9af9c60d c8a02faa 9506dad8 5be9fe78 cf979743 22856a11

Debug: Mar 13 20:38:42 IKE: g^xy
23eb98ce 75f9e6b9 db74f391 943d6e62 99c1a70e 99661d30 5f2115b4 006abec2
d8c75633 dbac2fed 34812aea a6b37510
Debug: Mar 13 20:38:42 IKE: SKEYSEED: 6460e276 5e8521ee 2c660e02 672a1b40 1f9360af a9fa2d6a 3f2d7d7b
f063f98f
9c10967d 06c5267b ab3fd497 28ce695e
Debug: Mar 13 20:38:42 IKE: Key d: d7c69fef 8f72fc49 0e059883 0a2809ce ea4a0920 e64914b7 da218b46
2b8b72fe
1f9e9c1c 5beda8da d4d4de43 3ba53661
Debug: Mar 13 20:38:42 IKE: Key ai: 4489ba21 e8a914c5 3a13694f f647c46b fbf0cef7 0ceb4c5d bdb623a5
5f4b01c5
62558333 0da07993 c6d187e0 1e638cb7
Debug: Mar 13 20:38:42 IKE: Key ar: 377095ad 1251bd49 265d66ef 3aaa090d d353bfff e98f651b 96a0ecfb
cd7c68d4
5058e99d 7e332161 8169a04e 8bae393f
Debug: Mar 13 20:38:42 IKE: Key ei: 8c31e91d f8011cdd c1674ea5 73b0ad12 6e60cc70 74cbf967 dbd35a49
99f0a679

Debug: Mar 13 20:38:42 IKE: Key er: 8e7881ff bf853fe2 a7b43864 67f9a587 827740e9 7f63125b 34526ac1
510b23fe

Debug: Mar 13 20:38:42 IKE: Key pi: f2646dde d9f565c4 72c1382e 94febb13 49762791 1152c357 64e7613f
00c538bb
ec2f5d4b 8c63b249 405769e9 35d8936c
Debug: Mar 13 20:38:42 IKE: Key pr: a917acb3 b370f56e 7501c8bc 50209201 375c7d6e 48820e68 f442c1a0
011d5f49
3773a2e1 23e8e867 6c288dcc f8d59a13
Debug: Mar 13 20:38:42 Add Payload 33
Debug: Mar 13 20:38:42 Add Payload 47
Debug: Mar 13 20:38:42 Add Payload 41
Debug: Mar 13 20:38:42 Add Payload 34
Debug: Mar 13 20:38:42 Add Payload 40
Debug: Mar 13 20:38:42 Add Payload 38
Debug: Mar 13 20:38:42 IKE: Sending response to 102.1.1.2 [500]
Debug: Mar 13 20:38:42 +++ ISAKMP package start (message # 2) +++
```

Debug Commands H - P

debug ikev2

```
Debug: Mar 13 20:38:42 < IKE Header >
Debug: Mar 13 20:38:42 IKE_SA Initiator's SPI: 0x20beache38bcb465
Debug: Mar 13 20:38:42 IKE_SA Responder's SPI: 0x7f672fffc23b040d
Debug: Mar 13 20:38:42 Next Payload: security association (33)
Debug: Mar 13 20:38:42 Version: 2.0
Debug: Mar 13 20:38:42 Exchange Type: IKE_SA_INIT
Debug: Mar 13 20:38:42 Flags: [ RESPONSE ]
Debug: Mar 13 20:38:42 Message ID: 0
Debug: Mar 13 20:38:42 Length: 248 (#x)
Debug: Mar 13 20:38:42 IKE: < security association >
Debug: Mar 13 20:38:42 IKE: Next Payload: key exchange (34)
Debug: Mar 13 20:38:42 IKE: Payload Length: 48 (#x)
Debug: Mar 13 20:38:42 << proposal >>
Debug: Mar 13 20:38:42 Proposal #: 1
Debug: Mar 13 20:38:42 Protocol ID: ISAKMP
Debug: Mar 13 20:38:42 SPI Size: 0
Debug: Mar 13 20:38:42 IKE: # of Transforms: 4
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: encr
Debug: Mar 13 20:38:42 ID: aes
Debug: Mar 13 20:38:42 Attr: 800e0100
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: integ
Debug: Mar 13 20:38:42 ID: sha384
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: prf
Debug: Mar 13 20:38:42 ID: sha384
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: dh
Debug: Mar 13 20:38:42 ID: ecp384
Debug: Mar 13 20:38:42 IKE: < key exchange >
Debug: Mar 13 20:38:42 IKE: Next Payload: nonce (40)
Debug: Mar 13 20:38:42 IKE: Payload Length: 104 (#x)
Debug: Mar 13 20:38:42 IKE: dh group: 'ecp384'
Debug: Mar 13 20:38:42 IKE: data:
f20a76e2 a5f4ffd3 f1e602db 175e27a5 de6ee0bb 5398912b e42aa726 3707bffa
af06f3ab 07bd6d5e 91977b7d 71c29893 c6319ef9 5a8d8dbf 7d2f177c c6dd270b
01f81f5d 8fb8c352 6da36969 1c8252aa 4c251cda 68c6d48e 4dff1b3b 93644bbd

Debug: Mar 13 20:38:42 IKE: < nonce >
Debug: Mar 13 20:38:42 IKE: Next Payload: none (0)
Debug: Mar 13 20:38:42 IKE: Payload Length: 68 (#x)
Debug: Mar 13 20:38:42 IKE: data:
1d49d2fa 0b2c88d1 c01bcd5e 70dedfcd ef78d6dc e71584f0 df6beb24 38ff4e28
a431ba8f 892328dd e0f6029 9df67ff7 0d68de7a 143ca305 c42bbe53 78493a7f

Debug: Mar 13 20:38:42 --- ISAKMP package end (message # 2) ---
Debug: Mar 13 20:38:42 IKE: Sending message 102.1.1.2[500]: IKE_SA_INIT, #2(4), ID 0
Debug: Mar 13 20:38:42 IKE: Send 248 octets from 100.1.1.1:500 to 102.1.1.2:500
Debug: Mar 13 20:38:42 ike_transmit_packet send packet to 102.1.1.2:500 from 100.1.1.1:500 vrf:0 length
248
Debug: Mar 13 20:38:42 IKE sub task: packet transmitted to 102.1.1.2
Debug: Mar 13 20:38:42 ike ipv4 packet received with src 102.1.1.2 and dest 100.1.1.1 vrf 0 length 248
Debug: Mar 13 20:38:42 IKE: ipike_isakmp_hash_get_from_cookie() :: hash key: id=0, type=0, init=0
Debug: Mar 13 20:38:42 IKE: Received request 102.1.1.2[500], IKE_AUTH, #3(4), ID 1
Debug: Mar 13 20:38:42 IKE: Message decrypted 248 bytes
Debug: Mar 13 20:38:42 +++ ISAKMP package start (message # 3) +++
Debug: Mar 13 20:38:42 < IKE Header >
Debug: Mar 13 20:38:42 IKE_SA Initiator's SPI: 0x20beache38bcb465
Debug: Mar 13 20:38:42 IKE_SA Responder's SPI: 0x7f672fffc23b040d
Debug: Mar 13 20:38:42 Next Payload: notify (41)
Debug: Mar 13 20:38:42 Version: 2.0
Debug: Mar 13 20:38:42 Exchange Type: IKE_AUTH
Debug: Mar 13 20:38:42 Flags: [ INITIATOR ]
Debug: Mar 13 20:38:42 Message ID: 1
Debug: Mar 13 20:38:42 Length: 188 (#x)
Debug: Mar 13 20:38:42 IKE: < notify >
Debug: Mar 13 20:38:42 IKE: Next Payload: identification initiator (35)
Debug: Mar 13 20:38:42 IKE: Payload Length: 8 (#x)
Debug: Mar 13 20:38:42 IKE: message type: ESP_TFC_PADDING_NOT_SUPPORTED (16394)
Debug: Mar 13 20:38:42 IKE: < identification initiator >
Debug: Mar 13 20:38:42 IKE: Next Payload: authentication (39)
```

```

Debug: Mar 13 20:38:42 IKE: Payload Length: 12 (#x)
Debug: Mar 13 20:38:42 IKE: id type: address
Debug: Mar 13 20:38:42 IKE: id data: 00000000
Debug: Mar 13 20:38:42 IKE: < authentication >
Debug: Mar 13 20:38:42 IKE: Next Payload: security association (33)
Debug: Mar 13 20:38:42 IKE: Payload Length: 56 (#x)
Debug: Mar 13 20:38:42 IKE: method: 'pre_shared_key'
Debug: Mar 13 20:38:42 IKE: data:
bf993791 8f2d42f5 3bc3ccad 59b8f2a5 761d9a83 d195d5d2 0f70de64 a5d0e677
25c2613a 47e72571 446cb83c 578f7b89
Debug: Mar 13 20:38:42 IKE: < security association >
Debug: Mar 13 20:38:42 IKE: Next Payload: traffic selector initiator (44)
Debug: Mar 13 20:38:42 IKE: Payload Length: 36 (#x)
Debug: Mar 13 20:38:42 << proposal >>
Debug: Mar 13 20:38:42 Proposal #: 1
Debug: Mar 13 20:38:42 Protocol ID: IPSEC_ESP
Debug: Mar 13 20:38:42 SPI Size: 4
Debug: Mar 13 20:38:42 IKE: spi data: 0000230e
Debug: Mar 13 20:38:42 IKE: # of Transforms: 2
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: encr
Debug: Mar 13 20:38:42 ID: aes256gcm
Debug: Mar 13 20:38:42 Attr: 800e0100
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42 Type: esn
Debug: Mar 13 20:38:42 ID: off
Debug: Mar 13 20:38:42 IKE: < traffic selector initiator >
Debug: Mar 13 20:38:42 IKE: Next Payload: traffic selector responder (45)
Debug: Mar 13 20:38:42 IKE: Payload Length: 24 (#x)
Debug: Mar 13 20:38:42 IKE: Protocol: any
Debug: Mar 13 20:38:42 IKE: Address start: 0.0.0.0
Debug: Mar 13 20:38:42 IKE: Address end: 255.255.255.255
Debug: Mar 13 20:38:42 IKE: Port start: 0
Debug: Mar 13 20:38:42 IKE: Port end: 65535
Debug: Mar 13 20:38:42 IKE: < traffic selector responder >
Debug: Mar 13 20:38:42 IKE: Next Payload: none (0)
Debug: Mar 13 20:38:42 IKE: Payload Length: 24 (#x)
Debug: Mar 13 20:38:42 IKE: Protocol: any
Debug: Mar 13 20:38:42 IKE: Address start: 0.0.0.0
Debug: Mar 13 20:38:42 IKE: Address end: 255.255.255.255
Debug: Mar 13 20:38:42 IKE: Port start: 0
Debug: Mar 13 20:38:42 IKE: Port end: 65535
Debug: Mar 13 20:38:42 --- ISAKMP package end (message # 3) ---
Debug: Mar 13 20:38:42 IKE: Process initial contact notify payload for tunnel 44
Debug: Mar 13 20:38:42 IKE: ipike_crypto_read_cert: could not open tunnel_44
Debug: Mar 13 20:38:42 IKE: Message:
20beacbe 38bcb465 00000000 00000000 21202208 00000000 000000f8 22000030
0000002c 01010004 03000008 04000014 03000008 02000006 0300000c 0100000c
800e0100 00000008 0300000d 28000068 00140000 d4d789d3 2d30c979 d856295d
5b740be8 32a7b1ff 6626d3d1 0d51f79c 9573fa48 4d158059 89d81198 1b525537
1c96102b e97e073d 8fe4b757 ebbbc40c 6ef76a3a f5ac68f4 b24c094c 9af9c60d
c8a02faa 9506dad8 5be9fe78 cf979743 22856a11 00000044 2d9db0d5 6453b7f2
0acc5d2d 6117d17c 77518abf 1ff952d6 540658e0 98f4019d c65b6824 ac19.
Debug: Mar 13 20:38:42 IKE: Authentication key:
7f602adf 7481a350 d4904150 ed0804b5 0a176fc3 46559ff4 19986e5f 5547be73
695b66ab 24eeabf4 1e9eabfa a0b0c75c
Debug: Mar 13 20:38:42 IKE: Authentication data:
bf993791 8f2d42f5 3bc3ccad 59b8f2a5 761d9a83 d195d5d2 0f70de64 a5d0e677
25c2613a 47e72571 446cb83c 578f7b89
Debug: Mar 13 20:38:42 IKE: Message:
20beacbe 38bcb465 7f672fff c23b040d 21202220 00000000 000000f8 22000030
0000002c 01010004 0300000c 0100000c 800e0100 03000008 0300000d 03000008
02000006 00000008 04000014 28000068 00140000 f20a76e2 a5f4ffd3 f1e602db
175e27a5 de6ee0bb 5398912b e42aa726 3707bffa af06f3ab 07bd6d5e 91977b7d
71c29893 c6319ef9 5a8d8dbf 7d2f177c c6dd270b 01f81f5d 8fb8c352 6da36969
1c8252aa 4c251cda 68c6d48e 4dff1b3b 93644bbd 00000044 1d49d2fa 0b2c88d1
c01bcd5e 70dedfcd ef78d6dc e71584f0 df6beb24 38ff4e28 a431ba8f 8923.
Debug: Mar 13 20:38:42 IKE: Authentication key:
7f602adf 7481a350 d4904150 ed0804b5 0a176fc3 46559ff4 19986e5f 5547be73
695b66ab 24eeabf4 1e9eabfa a0b0c75c
Debug: Mar 13 20:38:42 IKE: Authentication data:
3d9760af 143f7e57 7cd521b6 8034ddab e23e101c 54a584de d7ab54e9 0ce3365b

```

Debug Commands H - P

debug ikev2

```
ab6d5db3 69d288eb 294c2aed f7f19a2c
Debug: Mar 13 20:38:42 IKE: use_esn from config: off

Debug: Mar 13 20:38:42 IKE: selected 'aes256gcm' as encryption algorithm
Debug: Mar 13 20:38:42 IKE: selected '256' as key length
Debug: Mar 13 20:38:42 IKE: selected 'off' for ESN
Debug: Mar 13 20:38:42 Add Payload 47
Debug: Mar 13 20:38:42 Add Payload 41
Debug: Mar 13 20:38:42 IKE: Create notify payload with message type 16394
Debug: Mar 13 20:38:42 Add Payload 36
Debug: Mar 13 20:38:42 Add Payload 37
Debug: Mar 13 20:38:42 Add Payload 39
Debug: Mar 13 20:38:42 Add Payload 33
Debug: Mar 13 20:38:42 Add Payload 44
Debug: Mar 13 20:38:42 Add Payload 45
Debug: Mar 13 20:38:42 Add Payload 48
Debug: Mar 13 20:38:42 IKE: Sending response to 102.1.1.2 [500]
Debug: Mar 13 20:38:42 +++ ISAKMP package start (message # 4) +++
Debug: Mar 13 20:38:42 < IKE Header >
Debug: Mar 13 20:38:42   IKE_SA Initiator's SPI: 0x20beacbe38bcb465
Debug: Mar 13 20:38:42   IKE_SA Responder's SPI: 0x7f672fffc23b040d
Debug: Mar 13 20:38:42   Next Payload: notify (41)
Debug: Mar 13 20:38:42   Version: 2.0
Debug: Mar 13 20:38:42   Exchange Type: IKE_AUTH
Debug: Mar 13 20:38:42   Flags: [ RESPONSE ]
Debug: Mar 13 20:38:42   Message ID: 1
Debug: Mar 13 20:38:42   Length: 188 (#x)
Debug: Mar 13 20:38:42 IKE: < notify >
Debug: Mar 13 20:38:42 IKE:   Next Payload: identification responder (36)
Debug: Mar 13 20:38:42 IKE:   Payload Length: 8 (#x)
Debug: Mar 13 20:38:42 IKE:   message type: ESP_TFC_PADDING_NOT_SUPPORTED (16394)
Debug: Mar 13 20:38:42 IKE: < identification responder >
Debug: Mar 13 20:38:42 IKE:   Next Payload: authentication (39)
Debug: Mar 13 20:38:42 IKE:   Payload Length: 12 (#x)
Debug: Mar 13 20:38:42 IKE:   id type: address
Debug: Mar 13 20:38:42 IKE:   id data: 00000000
Debug: Mar 13 20:38:42 IKE: < authentication >
Debug: Mar 13 20:38:42 IKE:   Next Payload: security association (33)
Debug: Mar 13 20:38:42 IKE:   Payload Length: 56 (#x)
Debug: Mar 13 20:38:42 IKE:   method: 'pre_shared_key'
Debug: Mar 13 20:38:42 IKE:   data:
3d9760af 143f7e57 7cd521b6 8034ddab e23e101c 54a584de d7ab54e9 0ce3365b
ab6d5db3 69d288eb 294c2aed f7f19a2c
Debug: Mar 13 20:38:42 IKE: < security association >
Debug: Mar 13 20:38:42 IKE:   Next Payload: traffic selector initiator (44)
Debug: Mar 13 20:38:42 IKE:   Payload Length: 36 (#x)
Debug: Mar 13 20:38:42 << proposal >>
Debug: Mar 13 20:38:42   Proposal #: 1
Debug: Mar 13 20:38:42   Protocol ID: IPSEC_ESP
Debug: Mar 13 20:38:42   SPI Size: 4
Debug: Mar 13 20:38:42 IKE:   spi data: 000007fe
Debug: Mar 13 20:38:42 IKE:   # of Transforms: 2
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42   Type: esn
Debug: Mar 13 20:38:42   ID: off
Debug: Mar 13 20:38:42 <<< transform >>>
Debug: Mar 13 20:38:42   Type: encr
Debug: Mar 13 20:38:42   ID: aes256gcm
Debug: Mar 13 20:38:42   Attr: 800e0100
Debug: Mar 13 20:38:42 IKE: < traffic selector initiator >
Debug: Mar 13 20:38:42 IKE:   Next Payload: traffic selector responder (45)
Debug: Mar 13 20:38:42 IKE:   Payload Length: 24 (#x)
Debug: Mar 13 20:38:42 IKE:   Protocol: any
Debug: Mar 13 20:38:42 IKE:   Address start: 0.0.0.0
Debug: Mar 13 20:38:42 IKE:   Address end: 255.255.255.255
Debug: Mar 13 20:38:42 IKE:   Port start: 0
Debug: Mar 13 20:38:42 IKE:   Port end: 65535
Debug: Mar 13 20:38:42 IKE: < traffic selector responder >
Debug: Mar 13 20:38:42 IKE:   Next Payload: none (0)
Debug: Mar 13 20:38:42 IKE:   Payload Length: 24 (#x)
Debug: Mar 13 20:38:42 IKE:   Protocol: any
Debug: Mar 13 20:38:42 IKE:   Address start: 0.0.0.0
```

```

Debug: Mar 13 20:38:42 IKE:      Address end:   255.255.255.255
Debug: Mar 13 20:38:42 IKE:      Port start:    0
Debug: Mar 13 20:38:42 IKE:      Port end:     65535
Debug: Mar 13 20:38:42 --- ISAKMP package end (message # 4) ---
Debug: Mar 13 20:38:42 IKE: Sending message 102.1.1.2[500]: IKE_AUTH, #4(4), ID 1
Debug: Mar 13 20:38:42 IKE: Message encrypted 248 bytes
Debug: Mar 13 20:38:42 IKE: Send 248 octets from 100.1.1.1:500 to 102.1.1.2:500
Debug: Mar 13 20:38:42 IKE: ipike_sadb_get_from_ike_config() :: no IKE SA for peer 102.1.1.2, config id
'tunnel44'
Debug: Mar 13 20:38:42 IKE: Enc key inbound:  2d551d4a f27a5382 d6139507 9cd7ba09 b801f9f8 585ecd81
2703818e ff5aad8f
2720eb1c
Debug: Mar 13 20:38:42 IKE: Enc key outbound: c1984de9 10338d76 7d7c1d7a d47b84ee e9d7ba33 a116b639
dbab15f4 19fb8280
3e30fe3d

```

History

Release version	Command history
8.0.41	This command was introduced.

debug ip aaa

Activates the debugging of IP AAA/RADIUS protocol transactions.

Syntax

```
debug ip aaa  
undebug ip aaa
```

Modes

Privileged EXEC mode

Usage Guidelines

Examples

The following example activates the debugging of IP AAA/RADIUS protocol transactions.

```
device# debug ip aaa
```

debug ip arp

Activates the debugging of ARP packets.

Syntax

debug ip arp *ip-addr*

no debug ip arp *ip-addr*

Parameters

ip-addr

Specifies a particular route.

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip arp 10.29.29.53
ARP: packets debugging is on
device# show arp

Total number of ARP entries: 3, maximum capacity: 4000
No.   IP Address      MAC Address      Type      Age Port      Status
1     10.29.29.53      0000.0034.1b60  Dynamic  0    2/1/15-2/1/16 Valid
2     10.200.200.45    0000.00cf.c400  Dynamic  0    1/1/13-1/1/14 Valid
3     10.30.30.31      0000.0023.0f00  Dynamic  0    2/1/9-2/1/10  Valid

device# clear arp
next hop router 10.29.29.53 ARP mapping deleted
device# ARP: sent packet oper=request, src 10.29.29.111 0000.0076.2c80: dst 10.29.29.53 0000.0000.0000:
Port v29
ARP: sent packet oper=request, src 10.200.200.111 0000.0076.2c80: dst 10.200.200.45 0000.0000.0000:
Port v2000
ARP: sent packet oper=request, src 10.30.30.111 0000.0076.2c80: dst 10.30.30.31 0000.0000.0000: Port
v300
ARP: sent packet oper=request, src 10.20.67.111 0000.0076.2c80: dst 10.20.10.11 0000.0000.0000: Port
mgmt1
```

debug ip bgp

Enables common BGP debugging information to be displayed for all virtual routing and forwarding events (VRFs) or for a specific VRF.

Syntax

```
debug ip bgp neighbor_ip_address
```

```
no debug ip bgp neighbor_ip_address
```

Parameters

neighbor_ip_address

The *neighbor_ip_address* variable refers to the IP address of the immediate neighbor.

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip bgp 10.1.34.10
      BGP: neighbor 10.1.34.10 debugging is on
device# BGP: 10.1.34.10 rcv UPDATE w/attr: Origin=IGP AS_PATH=AS_CONFED_SEQUENCE(3) 64519
NextHop=10.1.34.10 MED=0 LOCAL_PREF=100
BGP: 10.1.34.10 rcv UPDATE 10.1.22.0/24
BGP: 10.1.34.10 rcv UPDATE w/attr: Origin=IGP AS_PATH=AS_CONFED_SEQUENCE(3) 64519 NextHop 10.1.34.10
MED=0 LOCAL_PREF=100
BGP: 10.1.34.10 rcv UPDATE 10.1.23.0/24
```

debug ip bgp dampening

Displays information about dampening process configurations, route penalties, durations, restraint, and release.

Syntax

debug ip bgp dampening

no debug ip bgp dampening

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip bgp dampening
BGP: 10.1.1.2 Decay 10.1.1.32/32, ostate <d>, oPnlty=6805, nPnlty=840, time=2712
BGP: 10.1.1.2 reuse_list_index=258, curr_offset=45
BGP: 10.1.1.2 10.1.1.32/32 not ready, state <d>, reuse_threshold=750, new_index=61, offset=45
BGP: 10.1.1.2 Decay 10.1.1.32/32, ostate <d>, oPnlty=6805, nPnlty=840, time=2712
BGP: 10.1.1.2 reuse_list_index=258, curr_offset=45
BGP: 10.1.1.2 10.1.1.32/32 not ready, state <d>, reuse_threshold=750, new_index=61, offset=45
BGP: 10.1.1.2 Decay 10.1.1.32/32, ostate <d>, oPnlty=6805, nPnlty=840, time=2712
BGP: 10.1.1.2 reuse_list_index=258, curr_offset=45
BGP: 10.1.1.2 10.1.1.32/32 not ready, state <d>, reuse_threshold=750, new_index=61, offset=45
BGP: 10.1.1.2 Decay 10.1.1.32/32, ostate <d>, oPnlty=6805, nPnlty=840, time=2712
BGP: 10.1.1.2 reuse_list_index=258, curr_offset=45
BGP: 10.1.1.2 10.1.1.32/32 not ready, state <d>, reuse_threshold=750, new_index=61, offset=45
```

debug ip bgp events

Generates information about BGP events, such as connection attempts and keepalive timer activity.

Syntax

debug ip bgp events

no debug ip bgp events

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip bgp events
      BGP:  events debugging is on
device# BGP: 10.1.34.10 rcv notification: CEASE Message
BGP: 10.1.34.10 Peer went to IDLE state (Rcv Notification)
BGP: 10.1.35.10 rcv notification: CEASE Message
BGP: 10.1.35.10 Peer went to IDLE state (Rcv Notification)
BGP: 10.1.34.10 sending Graceful Restart cap, rbit 0, fbit 0, time 120, length 6
BGP: 10.1.35.10 sending Graceful Restart cap, rbit 0, fbit 0, time 120, length 6
BGP: 10.1.34.10 rcv GR capability afi/safi=1/1 fbit 0
BGP: 10.1.34.10 Peer went to ESTABLISHED state
BGP: 10.1.35.10 rcv GR capability afi/safi=1/1 fbit 0
BGP: 10.1.35.10 Peer went to ESTABLISHED state
BGP: 10.1.34.10 rcv UPDATE EOR (0), waiting EOR 0
BGP: 10.1.35.10 rcv UPDATE EOR (0), waiting EOR 0
BGP: 10.1.34.10 sending EOR (safi 0)...
BGP: 10.1.35.10 sending EOR (safi 0)...
```

debug ip bgp graceful-restart

Displays information about BGP graceful restarts. The graceful restart feature minimizes disruptions in forwarding and route flapping when a router restarts.

Syntax

```
debug ip bgp graceful-restart
```

```
no debug ip bgp graceful-restart
```

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip bgp graceful-restart
      BGP: graceful-restart debugging is on
BGP: 10.1.251.6 save graceful restart parameters, #RIB_out 2 (safi 0)
10.1.251.6 RIB_out peer reset #RIB_out 2 (safi 0)
      BGP: 10.1.251.6 sending Graceful Restart cap, rbit 0, fbit 0, time 120, length 6
BGP: 10.1.251.6 sending Graceful Restart cap, rbit 0, fbit 0, time 120, length 6
BGP: 10.1.251.6 sending Graceful Restart cap, rbit 0, fbit 0, time 120, length 6
BGP: 10.1.251.6 rcv GR capability afi/safi=1/1 fbit 1
BGP: 10.1.251.6 sending EOR (safi 0)...
```

debug ip bgp keepalives

Displays information about the status of a resource such as BGP.

Syntax

```
debug ip bgp keepalives  
no debug ip bgp keepalives
```

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip bgp keepalives  
BGP: 10.1.1.2 sending KEEPALIVE  
BGP: 10.1.1.2 KEEPALIVE received
```

debug ip bgp updates

Displays BGP receive, transmit, or receive and transmit update messages about debug processing.

Syntax

debug ip bgp updates

no debug ip bgp updates

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip bgp updates
BGP: safi(0): 10.1.1.1.2 sending UPDATE w/attr: Origin=IGP AS_PATH=65538 NEXT_HOP=10.1.1.1 MED=1
BGP: (0): 10.1.1.1.2 sending UPDATE Label=0 2001:DB8:83:e8:00:04:78:64:10.1.1.1/32
BGP: 10.1.1.2 rcv bad UPDATE (saif 0) due to AS loop, take as implicit withdraw!
BGP: BGP: 10.1.1.2 rcv UPDATE w/attr: Origin=INCOMP AS_PATH= AS_SEQ(2) 3 NextHop=10.1.1.2 MED=30
BGP: (0): 10.1.1.2 rcv UPDATE 10.1.1.2/32
BGP: 10.1.1.2 rcv bad UPDATE (saif 0) due to AS loop, take as implicit withdraw!
BGP: BGP: 10.1.1.2 rcv UPDATE w/attr: Origin=IGP AS_PATH= AS_SEQ(2) 3 NextHop=10.1.1.2 MED=5
BGP: (0): 10.1.1.2 rcv UPDATE 10.10.10.10/32
BGP: (0): 10.1.1.2 rcv UPDATE 10.213.0.0/16
BGP: (0): 10.1.1.2 rcv UPDATE 10.200.200.200/32
BGP: (0): 10.1.1.2 rcv UPDATE 10.18.18.0/24
BGP: (0): 10.1.1.2 rcv UPDATE 10.1.1.32/32
```

debug ip gre keepalive

Activates Generic Routing Encapsulation (GRE) keepalive debugging.

Syntax

```
debug ip gre keepalive  
no debug ip gre keepalive
```

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip gre keepalive  
GRE_MP: Keepalive Bring DOWN GRE Tunnel 11  
GRE_MP: Keepalive Bring UP GRE on Tunnel 11 - port is 2/1/2  
GRE_MP: RX Keepalive packet on tnnl 11 src 10.22.33.254, dst 10.22.33.252  
GRE_MP: TX Keepalive packet on tnnl 11 we need to find outgoing port  
GRE_MP: TX Keepalive packet on tnnl 11 - outgoing_port is 2/1/2 with mac 0000.00bb.ef40 vlan 2  
GRE_MP KEEPALIVE: NO FREE BUFFER AVAILABLE  
GRE_MP: For Tunnel 11, Keepalive timeout after 3 seconds  
GRE_MP: For Tunnel 11, stop keep-alive  
GRE_MP: For Tunnel 11, start keep-alive  
GRE_MP: enqueue Keepalive packet on tunnel 11 at index 23  
GRE_MP: dequeue Keepalive packet on tunnel 11 at index 23
```

debug ip gre log

Activates the tunnel events debugging.

Syntax

debug ip gre log

no debug ip gre log

Modes

Privileged EXEC mode

Usage Guidelines

The no form disables tunnel events debugging

Examples

```

device# debug ip gre log
Apply mtu 1400 failed for tunnel 11 as all mtu profiles are used
Clearing PMTU for tunnel 11 due to ip mtu 1400 configuration
Tunnel Create Sync-Receive event for tunnel: 11
Tunnel Create Sync-Successful for tunnel: 11
Tunnel Update TS Sync-Receive event for tunnel: 11
Tunnel Update TS Sync-Successful for tunnel: 11
Tunnel Update Nhop Sync-Receive event for tunnel: 11
Tunnel Update Nhop Sync-Successful for tunnel: 11
Tunnel Update TTI Sync-Receive event for tunnel: 11
Tunnel Port Up Sync-Receive event for tunnel: 11
Tunnel Port Up Sync-Successful for tunnel: 11
Tunnel Port Down Sync-Receive event for tunnel: 11
Tunnel Port Down Sync-Successful for tunnel: 11
Tunnel Update MTU Sync-Receive event for tunnel: 11
Tunnel Update MTU Sync-Successful for tunnel: 11
Tunnel Delete Sync-Receive event for tunnel: 11
Tunnel Delete Sync-Successful for tunnel: 11
Tunnel Delete Nhop Sync-Receive event for tunnel: 11
Tunnel Delete Nhop Sync-Successful for tunnel: 11
Tunnel Delete TTI Sync-Receive event for tunnel: 11
Tunnel Delete Origination entry Sync-Receive event for tunnel: 11
Tunnel Delete Origination entry Sync-Successful for tunnel: 11
process_one_l3_unicast_update: entryType 6
Fill Sync Tunnel Entry-Bad parameters. Failed for tunnel: 11
Fill Sync Tunnel Entry-Bad TS entry. Failed for tunnel: 11
pack_tunnel_entry_change called with tunnel_index: 11 operation: TUNNEL_SYNC_UPDATE_NHOP
pack_tunnel_entry_list called with tunnel_index: 11 operation: TUNNEL_SYNC_CREATE_ALL, from_beginning: 1
Sync-ing tunnel entry 11
[pp_puma_tunnel_hotswap_insert] No tunnel start info for tunnel 11
DEBUG 0x8: Tunnel 11 already deleted
DEBUG 0x8: Tunnel 11 pp_delete_tunnel_entry
DEBUG 0x8: Can not find route for tunnel id 11, hw index 23, src 10.22.33.254, dest 10.22.33.252
DEBUG 0x8: create GRE tunnel origination because find route for tunnel id 11, hw index 23, src
10.22.33.254, dest 10.22.33.252
DEBUG 0x8: Route for tunnel id 11 is via another tunnel or management port 22
DEBUG 0x8: Direct route for tunnel id 11 dest 10.22.33.252 has unresolved ARP
DEBUG 0x8: indirect route for tunnel id 11 dest 10.22.33.252 next hop 10.11.25.5 has unresolved ARP
DEBUG 0x8: indirect route for tunnel id 11 destination 10.22.33.252 next hop 10.11.25.5 has resolved
ARP - CMD => route
DEBUG 0x8: Set next hop to Drop for tunnel id 11, hw index 23, src 10.22.33.254, dest 10.22.33.252
DEBUG 0x8: Tunnel 11 - next hop 10.11.25.5 has no link-layer
DEBUG 0x8: bring tunnel id 11 up with drop
DEBUG 0x8: Create tunnel id 11 with next hop 185276677 - old next hop is 125276633
DEBUG 0x8: bring tunnel id 11 up
Update_hw_routes for Tunnel 11
Path MTU: Tunnel 11 - reset path mtu timer 456 (3344)
Path MTU: Tunnel 11 - failed to reset path mtu timer 456 (3344)

```

debug ip gre packet

Activates the debugging of GRE packet processing.

Syntax

debug ip gre packet

no debug ip gre packet

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip gre packet
GRE: Error - IP GRE packet with invalid Ptype 0x1A4
GRE: Error - IP GRE packet with invalid first word 0x2C
GRE: Error - IP GRE packet with invalid first word 0x2C
GRE fragment : Rx IP GRE Pkt: src 10.22.33.254, dst 224.0.0.5, len 64 id 324
GRE Packet too big - need extra processing: Rx IP GRE Pkt: src 10.22.33.254, dst 224.0.0.5, len 64
GRE Reassembly: Rx IP GRE Pkt: src 10.22.33.254, dst 224.0.0.5, len 64
GRE : Rx IP GRE Pkt: src 10.22.33.254, dst 224.0.0.5, len 64
GRE: Error - Rx IP Pkt with invalid Inner IPv4 header
GRE: Error - Rx IP Pkt with 2 GRE headers: Inner src 10.22.33.254, Inner dst 224.0.0.5, len 64
GRE: Dropping the packet as GRE tunnel 11 is not UP
GRE_LP: Error - LP TX GRE packet is in LOOP
GRE : FORWARD IP to GRE tunnel 11 - Pkt: src 10.22.33.254, dst 224.0.0.5, len 64
GRE : Failed to FORWARD IP to GRE tunnel 11 - Pkt: src 10.22.33.254, dst 224.0.0.5, No route
```

debug ip icmp events

Activates ICMP events debugging.

Syntax

debug ip icmp events

no debug ip icmp events

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip icmp events
        ICMP:  events debugging is on

device# ICMP: rcvd echo request packet of length 40 from 10.44.22.11
ICMP: send echo reply packet of length 60 to 10.44.22.11
ICMP: rcvd echo request packet of length 40 from 10.44.22.11
ICMP: send echo reply packet of length 60 to 10.44.22.11
ICMP: rcvd echo request packet of length 40 from 10.44.22.11
ICMP: send echo reply packet of length 60 to 10.44.22.11
ICMP: rcvd echo request packet of length 40 from 10.44.22.11
ICMP: send echo reply packet of length 60 to 10.44.22.11
```

debug ip icmp packets

Activates ICMP packets debugging.

Syntax

debug ip icmp packets

no debug ip icmp packets

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip icmp packets
        ICMP: packets debugging is on
device# !SR_SWITCH_ROUTER!ICMP_DEBUG_RX
ICMP: Received message from 10.44.22.11 to 10.44.22.36 port 1/1/1 size 40
!SR_SWITCH_ROUTER!ICMP_DEBUG_RX
ICMP: Received message from 10.44.22.11 to 10.44.22.36 port 1/1/1 size 40
!SR_SWITCH_ROUTER!ICMP_DEBUG_RX
ICMP: Received message from 10.44.22.11 to 10.44.22.36 port 1/1/1 size 40
!SR_SWITCH_ROUTER!ICMP_DEBUG_RX
ICMP: Received message from 10.44.22.11 to 10.44.22.36 port 1/1/1 size 40
```

debug ip igmp add-del-oif

Displays information about the addition or deletion of the outgoing interfaces (OIFs).

Syntax

debug ip igmp add-del-oif

no debug ip igmp add-del-oif

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```

device# debug ip igmp add-del-oif
add-del-oif enabled
device# debug ip igmp show
igmp debug-enable-any = 1
debug ip igmp add-del-oif is enabled
device# debug ip igmp
device# IGMP: rcvd Report-V2(t=22) g=239.0.0.147 resp=100, pkt S=10.17.17.222 to 239.0.0.147, on v17
(phy 2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.148 resp=100, pkt S=10.17.17.222 to 239.0.0.148, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.149 resp=100, pkt S=10.17.17.222 to 239.0.0.149, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.150 resp=100, pkt S=10.17.17.222 to 239.0.0.150, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.151 resp=100, pkt S=10.17.17.222 to 239.0.0.151, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.152 resp=100, pkt S=10.17.17.222 to 239.0.0.152, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.153 resp=100, pkt S=10.17.17.222 to 239.0.0.153, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.154 resp=100, pkt S=10.17.17.222 to 239.0.0.154, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.155 resp=100, pkt S=10.17.17.222 to 239.0.0.155, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.156 resp=100, pkt S=10.17.17.222 to 239.0.0.156, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.157 resp=100, pkt S=10.17.17.222 to 239.0.0.157, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.158 resp=100, pkt S=10.17.17.222 to 239.0.0.158, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.159 resp=100, pkt S=10.17.17.222 to 239.0.0.159, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.160 resp=100, pkt S=10.17.17.222 to 239.0.0.160, on v17 (phy
2/1/17), igmp_size=8

device# IGMP: rcvd Report-V2(t=22) g=239.0.0.161 resp=100, pkt S=10.17.17.222 to 239.0.0.161, on v17
(phy 2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.162 resp=100, pkt S=10.17.17.222 to 239.0.0.162, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.163 resp=100, pkt S=10.17.17.222 to 239.0.0.163, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.164 resp=100, pkt S=10.17.17.222 to 239.0.0.164, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.165 resp=100, pkt S=10.17.17.222 to 239.0.0.165, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.166 resp=100, pkt S=10.17.17.222 to 239.0.0.166, on v17 (phy
2/1/17), igmp_size=8
nIGMP: rcvd Report-V2(t=22) g=239.0.0.167 resp=100, pkt S=10.17.17.222 to 239.0.0.167, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.168 resp=100, pkt S=10.17.17.222 to 239.0.0.168, on v17 (phy
2/1/17), igmp_size=8
o IGMP: rcvd Report-V2(t=22) g=239.0.0.169 resp=100, pkt S=10.17.17.222 to 239.0.0.169, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.170 resp=100, pkt S=10.17.17.222 to 239.0.0.170, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.171 resp=100, pkt S=10.17.17.222 to 239.0.0.171, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.172 resp=100, pkt S=10.17.17.222 to 239.0.0.172, on v17 (phy
2/1/17), igmp_size=8
dIGMP: rcvd Report-V2(t=22) g=239.0.0.173 resp=100, pkt S=10.17.17.222 to 239.0.0.173, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.174 resp=100, pkt S=10.17.17.222 to 239.0.0.174, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.175 resp=100, pkt S=10.17.17.222 to 239.0.0.175, on v17 (phy
  
```



```
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.212 resp=100, pkt S=10.17.17.222 to 239.0.0.212, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.213 resp=100, pkt S=10.17.17.222 to 239.0.0.213, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.214 resp=100, pkt S=10.17.17.222 to 239.0.0.214, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.215 resp=100, pkt S=10.17.17.222 to 239.0.0.215, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.216 resp=100, pkt S=10.17.17.222 to 239.0.0.216, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.217 resp=100, pkt S=10.17.17.222 to 239.0.0.217, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.218 resp=100, pkt S=10.17.17.222 to 239.0.0.218, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.219 resp=100, pkt S=10.17.17.222 to 239.0.0.219, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.220 resp=100, pkt S=10.17.17.222 to 239.0.0.220, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.221 resp=100, pkt S=10.17.17.222 to 239.0.0.221, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.222 resp=100, pkt S=10.17.17.222 to 239.0.0.222, on v17 (phy
2/1/17), igmp_size=8
aIGMP: rcvd Report-V2(t=22) g=239.0.0.223 resp=100, pkt S=10.17.17.222 to 239.0.0.223, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.224 resp=100, pkt S=10.17.17.222 to 239.0.0.224, on v17 (phy
2/1/17), igmp_size=8
lIGMP: rcvd Report-V2(t=22) g=239.0.0.225 resp=100, pkt S=10.17.17.222 to 239.0.0.225, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.226 resp=100, pkt S=10.17.17.222 to 239.0.0.226, on v17 (phy
2/1/17), igmp_size=8
lIGMP: rcvd Report-V2(t=22) g=239.0.0.227 resp=100, pkt S=10.17.17.222 to 239.0.0.227, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.228 resp=100, pkt S=10.17.17.222 to 239.0.0.228, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.229 resp=100, pkt S=10.17.17.222 to 239.0.0.229, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.0.230 resp=100, pkt S=10.17.17.222 to 239.0.0.230, on v17 (phy
2/1/17), igmp_size=8
```

```
Debug message destination: default (console)
All possible debuggings have been turned off
tracking is off and all results are cleared
Turn off stack trace of write table
Disable shadow register write will disable all writes from shadow to hardware
```

debug ip igmp add-del-oif stack

Monitors and displays instances of multicast cache activity, such as OIF additions or deletions, and generates a stack trace of the add or delete event.

Syntax

```
debug ip igmp add-del-oif stack
```

```
no debug ip igmp add-del-oif stack
```

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```

device# debug ip igmp add-del-oif stack
add-del-oif stack enabled
device# debug ip igmp show
igmp debug-enable-any = 1
debug ip igmp add-del-oif stack is enabled
device# debug ip ig
device# IGMP: rcvd Report-V2(t=22)  g=239.0.1.8  resp=100, pkt S=10.17.17.222 to 239.0.1.8, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.9  resp=100, pkt S=10.17.17.222 to 239.0.1.9, on v17 (phy 2/1/17),
igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.10  resp=100, pkt S=10.17.17.222 to 239.0.1.10, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.11  resp=100, pkt S=10.17.17.222 to 239.0.1.11, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.12  resp=100, pkt S=10.17.17.222 to 239.0.1.12, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.13  resp=100, pkt S=10.17.17.222 to 239.0.1.13, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.14  resp=100, pkt S=10.17.17.222 to 239.0.1.14, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.15  resp=100, pkt S=10.17.17.222 to 239.0.1.15, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.16  resp=100, pkt S=10.17.17.222 to 239.0.1.16, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.17  resp=100, pkt S=10.17.17.222 to 239.0.1.17, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.18  resp=100, pkt S=10.17.17.222 to 239.0.1.18, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.19  resp=100, pkt S=10.17.17.222 to 239.0.1.19, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.20  resp=100, pkt S=10.17.17.222 to 239.0.1.20, on v17 (phy
2/1/17), igmp_size=8
nIGMP: rcvd Report-V2(t=22)  g=239.0.1.21  resp=100, pkt S=10.17.17.222 to 239.0.1.21, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.22  resp=100, pkt S=10.17.17.222 to 239.0.1.22, on v17 (phy
2/1/17), igmp_size=8
oIGMP: rcvd Report-V2(t=22)  g=239.0.1.23  resp=100, pkt S=10.17.17.222 to 239.0.1.23, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.24  resp=100, pkt S=10.17.17.222 to 239.0.1.24, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.25  resp=100, pkt S=10.17.17.222 to 239.0.1.25, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.26  resp=100, pkt S=10.17.17.222 to 239.0.1.26, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.27  resp=100, pkt S=10.17.17.222 to 239.0.1.27, on v17 (phy
2/1/17), igmp_size=8
dIGMP: rcvd Report-V2(t=22)  g=239.0.1.28  resp=100, pkt S=10.17.17.222 to 239.0.1.28, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.29  resp=100, pkt S=10.17.17.222 to 239.0.1.29, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.30  resp=100, pkt S=10.17.17.222 to 239.0.1.30, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.31  resp=100, pkt S=10.17.17.222 to 239.0.1.31, on v17 (phy
2/1/17), igmp_size=8
eIGMP: rcvd Report-V2(t=22)  g=239.0.1.32  resp=100, pkt S=10.17.17.222 to 239.0.1.32, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.33  resp=100, pkt S=10.17.17.222 to 239.0.1.33, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.34  resp=100, pkt S=10.17.17.222 to 239.0.1.34, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22)  g=239.0.1.35  resp=100, pkt S=10.17.17.222 to 239.0.1.35, on v17 (phy
2/1/17), igmp_size=8
bIGMP: rcvd Report-V2(t=22)  g=239.0.1.36  resp=100, pkt S=10.17.17.222 to 239.0.1.36, on v17 (phy
2/1/17), igmp_size=8
  
```

Debug Commands H - P

debug ip igmp add-del-of stack

```
IGMP: rcvd Report-V2(t=22) g=239.0.1.37 resp=100, pkt S=10.17.17.222 to 239.0.1.37, on v17 (phy
2/1/17), igmp_size=8
uIGMP: rcvd Report-V2(t=22) g=239.0.1.38 resp=100, pkt S=10.17.17.222 to 239.0.1.38, on v17 (phy
2/1/17), igmp_size=8
gIGMP: rcvd Report-V2(t=22) g=239.0.1.39 resp=100, pkt S=10.17.17.222 to 239.0.1.39, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.40 resp=100, pkt S=10.17.17.222 to 239.0.1.40, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.41 resp=100, pkt S=10.17.17.222 to 239.0.1.41, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.42 resp=100, pkt S=10.17.17.222 to 239.0.1.42, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.43 resp=100, pkt S=10.17.17.222 to 239.0.1.43, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.44 resp=100, pkt S=10.17.17.222 to 239.0.1.44, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.45 resp=100, pkt S=10.17.17.222 to 239.0.1.45, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.46 resp=100, pkt S=10.17.17.222 to 239.0.1.46, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.47 resp=100, pkt S=10.17.17.222 to 239.0.1.47, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.48 resp=100, pkt S=10.17.17.222 to 239.0.1.48, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.49 resp=100, pkt S=10.17.17.222 to 239.0.1.49, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.50 resp=100, pkt S=10.17.17.222 to 239.0.1.50, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.51 resp=100, pkt S=10.17.17.222 to 239.0.1.51, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.52 resp=100, pkt S=10.17.17.222 to 239.0.1.52, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.53 resp=100, pkt S=10.17.17.222 to 239.0.1.53, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.54 resp=100, pkt S=10.17.17.222 to 239.0.1.54, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.55 resp=100, pkt S=10.17.17.222 to 239.0.1.55, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.56 resp=100, pkt S=10.17.17.222 to 239.0.1.56, on v17 (phy
2/1/17), igmp_size=8
aIGMP: rcvd Report-V2(t=22) g=239.0.1.57 resp=100, pkt S=10.17.17.222 to 239.0.1.57, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.58 resp=100, pkt S=10.17.17.222 to 239.0.1.58, on v17 (phy
2/1/17), igmp_size=8
lIGMP: rcvd Report-V2(t=22) g=239.0.1.59 resp=100, pkt S=10.17.17.222 to 239.0.1.59, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.60 resp=100, pkt S=10.17.17.222 to 239.0.1.60, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.61 resp=100, pkt S=10.17.17.222 to 239.0.1.61, on v17 (phy
2/1/17), igmp_size=8
lIGMP: rcvd Report-V2(t=22) g=239.0.1.62 resp=100, pkt S=10.17.17.222 to 239.0.1.62, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.63 resp=100, pkt S=10.17.17.222 to 239.0.1.63, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.64 resp=100, pkt S=10.17.17.222 to 239.0.1.64, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.65 resp=100, pkt S=10.17.17.222 to 239.0.1.65, on v17 (phy
2/1/17), igmp_size=8
IGMP: rcvd Report-V2(t=22) g=239.0.1.66 resp=100, pkt S=10.17.17.222 to 239.0.1.66, on v17 (phy
2/1/17), igmp_size=8
```

```
Debug message destination: default (console)
All possible debuggings have been turned off
tracking is off and all results are cleared
Turn off stack trace of write table
Disable shadow register write will disable all writes from shadow to hardware
```

debug ip igmp clear

Clears all the IGMP debug settings.

Syntax

`debug ip igmp clear`

`no debug ip igmp clear`

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip igmp clear  
no debug ip igmp is enabled
```

debug ip igmp enable

Enables IGMP debugging.

Syntax

debug ip igmp enable

no debug ip igmp enable

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug ip igmp enable  
debug ip igmp is enabled
```

debug ip igmp error

Displays the IGMP multicast error messages.

Syntax

debug ip igmp error

no debug ip igmp error

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
Device# debug ip igmp error
IGMP.VRF3.ERR: Rx packet ttl 255 not 1. Dropping packet
IGMP.VRF3.ERR: Rx packet ttl 255 not 1. Dropping packet
IGMP.VRF3.ERR: Rx packet ttl 255 not 1. Dropping packet
```

debug ip igmp group

Matches the IGMP-enabled group based on the IP address.

Syntax

```
debug ip igmp group ipaddr
```

```
no debug ip igmp group ipaddr
```

Parameters

ipaddr

Refers to the IP address of the IGMP group.

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp group 10.11.66.62  
IGMP: No L3 mcast, pkt S=10.11.66.62 to 225.1.1.167, on v8 (phy 1/2/4),  
igmp_size=8  
IGMP: rcvd Report-V2 (t=22) g=225.1.1.167 resp=0, pkt S=10.11.66.62 to  
225.1.1.167, on VL8 (phy 1/2/4), igmp_size=8
```

debug ip igmp level

Sets the debug level of the IGMP.

Syntax

debug ip igmp level *decimal*

no debug ip igmp level *decimal*

Parameters

decimal

Specifies the level of the IGMP. The valid values are from 1 through 3.

Modes

Privileged EXEC mode

Examples

```

device# debug ip igmp level 1
debug level = 1
device# debug ip ig show
igmp debug-enable-any = 1
debug ip igmp level 1 is enabled
device# debug ip igmp
device# IGMP: rcvd Report-V2(t=22) g=239.0.1.240 resp=100, pkt S=10.17.17.222 to
239.0.1.240, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.241 resp=100, pkt S=10.17.17.222 to
239.0.1.241, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.242 resp=100, pkt S=10.17.17.222 to
239.0.1.242, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.243 resp=100, pkt S=10.17.17.222 to
239.0.1.243, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.244 resp=100, pkt S=10.17.17.222 to
239.0.1.244, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.245 resp=100, pkt S=10.17.17.222 to
239.0.1.245, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.246 resp=100, pkt S=10.17.17.222 to
239.0.1.246, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.247 resp=100, pkt S=10.17.17.222 to
239.0.1.247, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.1.248 resp=100, pkt S=10.17.17.222 to
239.0.1.248, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.5 resp=100, pkt S=10.17.17.222 to 239.0.0.5,
on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.6 resp=100, pkt S=10.17.17.222 to 239.0.0.6,
on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.7 resp=100, pkt S=10.17.17.222 to 239.0.0.7,
on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.8 resp=100, pkt S=10.17.17.222 to 239.0.0.8,
on v17 (phy 2/1/17), igmp_size=8
consume pkt
nIGMP: rcvd Report-V2(t=22) g=239.0.0.9 resp=100, pkt S=10.17.17.222 to
239.0.0.9, on v17 (phy 2/1/17), igmp_size=8
consume pkt
oIGMP: rcvd Report-V2(t=22) g=239.0.0.10 resp=100, pkt S=10.17.17.222 to
239.0.0.10, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.11 resp=100, pkt S=10.17.17.222 to
239.0.0.11, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.12 resp=100, pkt S=10.17.17.222 to
239.0.0.12, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.13 resp=100, pkt S=10.17.17.222 to
239.0.0.13, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.14 resp=100, pkt S=10.17.17.222 to
239.0.0.14, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.15 resp=100, pkt S=10.17.17.222 to
239.0.0.15, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.16 resp=100, pkt S=10.17.17.222 to
239.0.0.16, on v17 (phy 2/1/17), igmp_size=8
consume pkt

```

```
IGMP: rcvd Report-V2(t=22) g=239.0.0.17 resp=100, pkt S=10.17.17.222 to
239.0.0.17, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.18 resp=100, pkt S=10.17.17.222 to
239.0.0.18, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.19 resp=100, pkt S=10.17.17.222 to
239.0.0.19, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.20 resp=100, pkt S=10.17.17.222 to
239.0.0.20, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.21 resp=100, pkt S=10.17.17.222 to
239.0.0.21, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.22 resp=100, pkt S=10.17.17.222 to
239.0.0.22, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.23 resp=100, pkt S=10.17.17.222 to
239.0.0.23, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.24 resp=100, pkt S=10.17.17.222 to
239.0.0.24, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.25 resp=100, pkt S=10.17.17.222 to
239.0.0.25, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.26 resp=100, pkt S=10.17.17.222 to
239.0.0.26, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.27 resp=100, pkt S=10.17.17.222 to
239.0.0.27, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.28 resp=100, pkt S=10.17.17.222 to
239.0.0.28, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.29 resp=100, pkt S=10.17.17.222 to
239.0.0.29, on v17 (phy 2/1/17), igmp_size=8
consume pkt
dIGMP: rcvd Report-V2(t=22) g=239.0.0.30 resp=100, pkt S=10.17.17.222 to
239.0.0.30, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.31 resp=100, pkt S=10.17.17.222 to
239.0.0.31, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.32 resp=100, pkt S=10.17.17.222 to
239.0.0.32, on v17 (phy 2/1/17), igmp_size=8
consume pkt
eIGMP: rcvd Report-V2(t=22) g=239.0.0.33 resp=100, pkt S=10.17.17.222 to
239.0.0.33, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.34 resp=100, pkt S=10.17.17.222 to
239.0.0.34, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.35 resp=100, pkt S=10.17.17.222 to
239.0.0.35, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.36 resp=100, pkt S=10.17.17.222 to
239.0.0.36, on v17 (phy 2/1/17), igmp_size=8
consume pkt
bIGMP: rcvd Report-V2(t=22) g=239.0.0.37 resp=100, pkt S=10.17.17.222 to
239.0.0.37, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.38 resp=100, pkt S=10.17.17.222 to
239.0.0.38, on v17 (phy 2/1/17), igmp_size=8
consume pkt
uIGMP: rcvd Report-V2(t=22) g=239.0.0.39 resp=100, pkt S=10.17.17.222 to
239.0.0.39, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.40 resp=100, pkt S=10.17.17.222 to
239.0.0.40, on v17 (phy 2/1/17), igmp_size=8
consume pkt
```

Debug Commands H - P

debug ip igmp level

```
gIGMP: rcvd Report-V2(t=22) g=239.0.0.41 resp=100, pkt S=10.17.17.222 to
239.0.0.41, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.42 resp=100, pkt S=10.17.17.222 to
239.0.0.42, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.43 resp=100, pkt S=10.17.17.222 to
239.0.0.43, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.44 resp=100, pkt S=10.17.17.222 to
239.0.0.44, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.45 resp=100, pkt S=10.17.17.222 to
239.0.0.45, on v17 (phy 2/1/17), igmp_size=8
consume pkt
aIGMP: rcvd Report-V2(t=22) g=239.0.0.46 resp=100, pkt S=10.17.17.222 to
239.0.0.46, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.47 resp=100, pkt S=10.17.17.222 to
239.0.0.47, on v17 (phy 2/1/17), igmp_size=8
consume pkt
lIGMP: rcvd Report-V2(t=22) g=239.0.0.48 resp=100, pkt S=10.17.17.222 to
239.0.0.48, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.49 resp=100, pkt S=10.17.17.222 to
239.0.0.49, on v17 (phy 2/1/17), igmp_size=8
consume pkt
lIGMP send Query(t=17) V2, s=10.17.17.52 0.0.0.0 to v17(all) rsp=100 igmp=8B,
pkt=46B
IGMP send Query(t=17) V2, s=19.19.19.52 0.0.0.0 to v19(all) rsp=100 igmp=8B,
pkt=46B
IGMP: rcvd Report-V2(t=22) g=239.0.0.50 resp=100, pkt S=10.17.17.222 to
239.0.0.50, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.51 resp=100, pkt S=10.17.17.222 to
239.0.0.51, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.52 resp=100, pkt S=10.17.17.222 to
239.0.0.52, on v17 (phy 2/1/17), igmp_size=8
consume pkt
IGMP: rcvd Report-V2(t=22) g=239.0.0.53 resp=100, pkt S=10.17.17.222 to
239.0.0.53, on v17 (phy 2/1/17), igmp_size=8
consume pkt
Debug message destination: default (console)
All possible debuggings have been turned off
tracking is off and all results are cleared
Turn off stack trace of write table
Disable shadow register write will disable all writes from shadow to hardware
```

debug ip igmp physical-port ethernet

Matches the physical port that is connected.

Syntax

```
debug ip igmp physical-port ethernetstackid | slot | port
```

```
no debug ip igmp physical-port ethernet stackid | slot | port
```

Parameters

stackid | slot | port

Refers to the stack ID, slot number, and port number of a specific Ethernet port.

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp physical-port ethernet 1/2/4
IGMP: rcvd Leave(t=23) g=225.1.1.31 resp=0, pkt S=10.11.66.62 to 224.0.0.2, on
VL8 (phy 1/2/4), igmp_size=8
IGMP: No L3 mcast, pkt S=10.11.66.62 to 224.0.0.2, on v8 (phy 1/2/4), igmp_size=8
IGMP: rcvd Leave(t=23) g=225.1.1.32 resp=0, pkt S=10.11.66.62 to 224.0.0.2, on
VL8 (phy 1/2/4), igmp_size=8
IGMP: No L3 mcast, pkt S=10.11.66.62 to 224.0.0.2, on v8 (phy 1/2/4), igmp_size=8
IGMP: rcvd Leave(t=23) g=225.1.1.33 resp=0, pkt S=10.11.66.62 to 224.0.0.2, on
VL8 (phy 1/2/4), igmp_size=8
```

debug ip igmp protocol

Displays debugging information about the IGMP queries and reports transmitted and received.

Syntax

```
debug ip igmp protocol [ query | report ]
```

```
no debug ip igmp protocol [ query | report ]
```

Parameters

query

Displays debugging information about the IGMP queries transmitted and received.

report

Displays debugging information about the IGMP reports transmitted and received.

Modes

Privileged EXEC mode

Examples

The following is the sample output from the **debug ip igmp protocol query** command.

```
device# debug ip igmp protocol query
device# IGMP.VRF0: [ Port 1/1/15,v74. Grp 0.0.0.0 ] Sent version 3 Query. size
12. Src 10.0.0.18
IGMP.VRF0: [ Port 1/1/15,v74 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 2/1/15,v75. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 2/1/15,v75 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 3/1/39,v76. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 3/1/39,v76 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 6/1/22,v77. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 6/1/22,v77 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 4/1/22,v78. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 4/1/22,v78 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 5/1/22,v79. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 5/1/22,v79 ] Sent General Query version 3 using src 10.0.0.18
```

The following is the truncated sample output from the **debug ip igmp protocol report** command.

```

device# debug ip igmp protocol report
device# IGMP.VRF0: [ Port 1/1/15,v74. Grp 0.0.0.0 ] Sent version 3 Query. size
12. Src 10.0.0.18
IGMP.VRF0: [ Port 1/1/15,v74 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 2/1/15,v75. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 2/1/15,v75 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 3/1/39,v76. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 3/1/39,v76 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 6/1/22,v77. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 6/1/22,v77 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 4/1/22,v78. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 4/1/22,v78 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: [ Port 5/1/22,v79. Grp 0.0.0.0 ] Sent version 3 Query. size 12. Src
10.0.0.18
IGMP.VRF0: [ Port 5/1/22,v79 ] Sent General Query version 3 using src 10.0.0.18
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.52
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.43
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.22
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.16
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.34
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.54
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.4
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.90
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.33
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.15
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.61
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.37
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.59
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.8
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.1
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.46
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.7
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.1
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.94
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.99
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.98
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.96
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.35
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.91
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.64
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.5
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.92
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.20
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.41
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.80
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.76
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.36
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.39
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.93
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.31
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.38
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.33
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.72
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.57
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.79
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.2
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.99
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.73
IGMP.VRF0: Type V2 Report Port 6/1/22,v77 Grp 228.0.0.59
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.40
IGMP.VRF0: Type V2 Report Port 5/1/22,v79 Grp 228.0.0.84
  
```

Debug Commands H - P
debug ip igmp proxy clear

debug ip igmp proxy clear

Clears all the IGMP proxy debug settings.

Syntax

debug ip igmp proxy clear

no debug ip igmp proxy clear

Modes

Privileged EXEC mode

debug ip igmp proxy error

Displays the IGMP proxy error messages.

Syntax

debug ip igmp proxy error

no debug ip igmp proxy error

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy error
Debug: Jan 2 03:26:25 ld 3:26:43 - MCPROXY_ERROR: ref count 1 for group entry
235.5.4.145
Debug: Jan 2 03:46:35 - MCPROXY_ERROR: ref count 1 for group entry 235.5.4.241
Debug: Jan 2 03:48:55 - MCPROXY_ERROR: ref count 1 for group entry 235.5.4.49
```

debug ip igmp proxy event

Enables debugging of IGMP proxy events.

Syntax

debug ip igmp proxy event

no debug ip igmp proxy event

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy event
Debug: Jan 1 20:53:56 20:54:14 - MCPCROXY_EVENT: [IPv4:default-vrf] receive group
229.2.1.1 state change
Debug: Jan 1 20:54:11 20:54:29 - MCPCROXY_EVENT: [IPv4:default-vrf] receive group
229.2.1.1 state change
Debug: Jan 1 20:54:33 20:54:51 - MCPCROXY_EVENT: [IPv4:default-vrf] receive group
229.2.1.1 state change
Debug: Jan 1 20:54:40 20:54:58 - MCPCROXY_EVENT: [IPv4:default-vrf] receive group
229.2.1.1 state change
```

debug ip igmp proxy packet

Displays debugging information related to the IGMP proxy packets.

Syntax

debug ip igmp proxy packet

no debug ip igmp proxy packet

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy packet
device# debug ip igmp enable
device# Debug: Jan  2 00:42:25 1d 0:42:34 - MCPROXY_TX: [IPv4:default-vrf] sending v1v2 grp 225.1.1.1
rprt
  to vir port v10 phy port 4/1/33
device# Debug: Jan  2 00:42:35 1d 0:42:43 - MCPROXY_TX: [IPv4:default-vrf] sending v1v2 grp 225.1.1.1
rprt
  to vir port v10 phy port 4/1/33
Debug: Jan  2 00:42:36 1d 0:42:44 - MCPROXY_TX: [IPv4:default-vrf] sending v1v2 grp 225.1.1.1 rprt
to vir port v10 phy port 4/1/33
```

Debug Commands H - P
debug ip igmp proxy rx

debug ip igmp proxy rx

Displays the IGMP proxy packets received.

Syntax

debug ip igmp proxy rx
no debug ip igmp proxy rx

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy rx  
device# 0:29:31 - MCPROXY_RX: [IPv4:default-vrf] receive general query on port e2/1/3 max resp code 100
```

debug ip igmp proxy show

Displays the IGMP proxy debug settings.

Syntax

debug ip igmp proxy show

no debug ip igmp proxy show

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy show
Mcast Proxy debug for IPv4:
Receive debug is enable
Transmit debug is enable
Error debug is enable
```

debug ip igmp proxy tx

Displays the IGMP proxy packets transmitted.

Syntax

```
debug ip igmp proxy tx
no debug ip igmp proxy tx
```

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy tx
device# debug ip igmp enable
device# Debug: Jan  2 00:43:20 1d 0:43:29 - MCPROXY_TX: [IPv4:default-vrf] sending v1v2 grp 225.1.1.1
rprt
  to vir port v10 phy port 4/1/33
device# Debug: Jan  2 00:43:27 1d 0:43:36 - MCPROXY_TX: [IPv4:default-vrf] sending v1v2 grp 225.1.1.1
rprt
  to vir port v10 phy port 4/1/33
Debug: Jan  2 00:43:28 1d 0:43:37 - MCPROXY_TX: [IPv4:default-vrf] sending v1v2 grp 225.1.1.1 rprt
to vir port v10 phy port 4/1/33
```

debug ip igmp proxy vrf

Displays IGMP proxy related debug information for the specified VRF.

Syntax

```
debug ip igmp proxy vrf vrf_name
```

```
no debug ip igmp proxy vrf vrf_name
```

Parameters

vrf_name

Specifies the VRF name.

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp proxy vrf vrf1
Debug: Jan 1 21:43:08 21:43:26 - MCPCROXY_TX: [IPv4:1] sending vlv2 grp 229.2.1.1
rprt to vir port v85 phy port 2/13
Debug: Jan 1 21:43:08 21:43:26 - MCPCROXY_TX: [IPv4:1] receive group query
229.2.1.1 on port e2/13 max resp code 10
Debug: Jan 1 21:43:09 21:43:27 - MCPCROXY_TX: [IPv4:1] receive group query
229.2.1.1 on port e2/13 max resp code 10
Debug: Jan 1 21:43:22 21:43:39 - MCPCROXY_TX: [IPv4:1] sending vlv2 grp 229.2.1.1
rprt to vir port v85 phy port 2/13
Debug: Jan 1 21:43:23 21:43:41 - MCPCROXY_TX: [IPv4:1] sending vlv2 grp 229.2.1.1
rprt to vir port v85 phy port 2/13
```

debug ip igmp rx

Displays the IGMP packets received.

Syntax

debug ip igmp rx

no debug ip igmp rx

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp rx
device# debug ip igmp protocol query
IGMP.VRF1: Query Port 1/1/3*1/1/14,v25 Grp 0.0.0.0
IGMP.QRY: [ Port 1/1/3*1/1/14,v25. Grp 0.0.0.0 ]. Processing version 2 query
IGMP.VRF1: Query Port 1/1/3*1/1/14,v25 Grp 0.0.0.0
IGMP.QRY: [ Port 1/1/3*1/1/14,v25. Grp 0.0.0.0 ]. Processing version 2 query
und allIGMP.VRF3: Query Port 1/1/3*1/1/14,v26 Grp 0.0.0.0
IGMP.QRY: [ Port 1/1/3*1/1/14,v26. Grp 0.0.0.0 ]. Processing version 2 query
```

debug ip igmp show

Displays the IGMP debug settings.

Syntax

debug ip igmp show *decimal*

no debug ip igmp show *decimal*

Parameters

decimal

Specifies the level of the IGMP. The valid values are from 1 through 3.

Modes

Privileged EXEC mode

Usage Guidelines

Do not use the **show debug** command for this purpose. The **show debug** command displays general debug information.

Examples

```
device# debug ip igmp show
igmp debug-enable-any = 1
debug ip igmp port-down is enabled
debug ip igmp detail is enabled
debug ip igmp level 2 is enabled
```

debug ip igmp source

Matches the source of the control packet or IGMP V3 source packets.

Syntax

```
debug ip igmp source ipaddr
```

```
no debug ip igmp source ipaddr
```

Parameters

ipaddr

Specifies the IP address of the IGMP source.

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp source 16.16.16.222  
device# IGMP: rcvd Report-V2 (t=22) g=239.0.0.5 resp=100, pkt S=16.16.16.222 to  
239.0.0.5, on v16 (phy 1/1/8), igmp_size=8
```

debug ip igmp tx

Displays the IGMP packets transmitted.

Syntax

debug ip igmp tx

no debug ip igmp tx

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp tx
device# debug ip igmp protocol query
IGMP.VRF2: [ Port 1/1/3*1/1/14,v21. Grp 0.0.0.0 ] Sent version 2 Query. size 8.
Src 21.0.0.6
IGMP.VRF2: [ Port 1/1/3*1/1/14,v21 ] Sent General Query version 2 using src
21.0.0.6
IGMP.VRF0: [ Port 1/1/7-1/1/8,tn11. Grp 0.0.0.0 ] Sent version 2 Query. size 8.
Src 61.0.0.6
IGMP.VRF0: [ Port 1/1/7-1/1/8,tn11 ] Sent General Query version 2 using src
61.0.0.6
IGMP.VRF0: [ Port 1/1/1-1/1/2,v91. Grp 0.0.0.0 ] Sent version 2 Query. size 8. Src
91.0.0.6
IGMP.VRF0: [ Port 1/1/1-1/1/2,v91 ] Sent General Query version 2 using src
91.0.0.6
```

debug ip igmp vrf

Displays IGMP-related debug information for the specified VRF.

Syntax

```
debug ip igmp vrf vrf_name
```

```
no debug ip igmp vrf vrf_name
```

Modes

Privileged EXEC mode

Examples

```
device# debug ip igmp group 225.1.1.1
device# debug ip igmp protocol report
device# debug ip igmp enable
device# debug ip igmp vrf br_vrf_1
device# Debug: Jan  2 00:24:23 IGMP.VRF1: Type V2 Report Port 2/1/21,v1 Grp 225.1.1.1
```

debug ip msdp

Generates information about Multicast Source Discovery Protocol (MSDP) activities.

Syntax

debug ip msdp [**alarms** | **clear** | **enable** | **events** | **group** *group-address* | **message** | **peer** *peer-address* | **rpf-peer** | **show** | **source** *source-address*]

no debug ip msdp [**alarms** | **clear** | **enable** | **events** | **group** *group-address* | **message** | **peer** *peer-address* | **rpf-peer** | **show** | **source** *source-address*]

Parameters

alarms

Displays TCP packet related errors such as header length error, content error, and so on.

clear

Removes the debug commands enabled in MSDP.

enable

Enables all MSDP related debugs. This command needs to be clubbed with other debug commands.

events

Displays information about the MSDP events.

group *group-address*

Displays MSDP debugs limited to a group.

message

Displays information about the MSDP messages.

peer *peer-address*

Displays MSDP debugs limited to a peer.

rpf-peer

Displays debug message whenever MSDP SA message IP address fails RPF - PEER check.

show

Displays all the MSDP commands enabled in the system.

source *source-address*

Displays MSDP debugs limited to a source address.

vrf *vrf-name*

Displays MSDP debugs limited to a specific VRF.

Modes

Privileged EXEC mode

Examples

The following example displays information about the MSDP processing alarms.

```
device# debug ip msdp alarms
:MSDP[default-vrf]: Bad Header Read - Close connection to peer 8.1.1.1
```

The following example displays information about the MSDP events.

```
device# debug ip msdp
events
May 18 03:28:52:625984:info:fi_debug:debug_logs:1:84083343552938752: : MSDP[vrf1]: Originating SA
message ...
May 18 03:28:52:625898:info:fi_debug:debug_logs:1:84083343552938752: : MSDP[default-vrf]: Originating
SA message ...
May 18 03:28:40:576341:info:fi_debug:debug_logs:1:84072391386333952: : MSDP[vrf1]: Initiate Transport
Connection to MSDP peer 40.89.0.2 (Peer num=3):
May 18 03:28:40:576271:info:fi_debug:debug_logs:1:84072391386333952: : MSDP[vrf1]: Process START event
for peer 40.89.0.2, local = 40.89.0.1
May 18 03:28:36:550897:info:fi_debug:debug_logs:1:84068723484263168: : MSDP[default-vrf]: Keep Alive
timer expired: send keep alive to peer 40.70.0.1
May 18 03:28:30:000181:info:fi_debug:debug_logs:1:84062749184754432: : MSDP[vrf1]: Peer 40.89.0.2 back
to IDLE state
May 18 03:28:30:000102:info:fi_debug:debug_logs:1:84062749184754432: : MSDP[vrf1]: Closing TCP
connection to peer 40.89.0.2
```

The following example displays information about MSDP debugs limited to a group.

```
device# debug ip msdp message
device#debug ip msdp group
236.1.1.1
03:31:39:226887:info:fi_debug:debug_logs:1:84235278021034752: : MSDP[default-vrf]: 40.70.0.1: State=4,
Rcv KA
May 18 03:31:37:241508:info:fi_debug:debug_logs:1:84233456954901248: : MSDP[default-vrf]: Peer
40.70.0.1: Xmt KA
May 18 03:31:22:178854:info:fi_debug:debug_logs:1:84219798958899968: : MSDP[vrf1]: 8.1.1.1: State=4,
Rcv KA
May 18 03:31:07:117002:info:fi_debug:debug_logs:1:84206037883683584: : (40.71.0.2,236.1.1.1)
(40.84.0.2,236.1.1.1)
May 18 03:31:07:116958:info:fi_debug:debug_logs:1:84206037883683584: : RP 40.70.0.1, SA count 4
May 18 03:31:07:116896:info:fi_debug:debug_logs:1:84206037883683584: : MSDP[default-vrf]: 40.70.0.1:
State=4, Rcv SA
May 18 03:31:05:110713:info:fi_debug:debug_logs:1:84204216817550080: : MSDP[vrf1]: Peer 8.1.1.1: Xmt KA
May 18 03:30:53:064816:info:fi_debug:debug_logs:1:84193251766043392: : MSDP[vrf1]: Originating SA
message ...
May 18 03:30:53:064726:info:fi_debug:debug_logs:1:84193251766043392: : MSDP[default-vrf]: Originating
SA message ...
May 18 03:30:39:023490:info:fi_debug:debug_logs:1:84180448468534016: : MSDP[default-vrf]: 40.70.0.1:
State=4, Rcv KA
May 18 03:30:37:010585:info:fi_debug:debug_logs:1:84178635992335104: : MSDP[default-vrf]: Peer
40.70.0.1: Xmt KA
May 18 03:30:21:945124:info:fi_debug:debug_logs:1:84164857737249536: : MSDP[vrf1]: 8.1.1.1: State=4,
Rcv KA
```

debug ip ntp

Displays NTP system information.

Syntax

```
debug ip ntp [ algorithms | association | broadcast | clockadjust | errors | packet | server ]
```

Parameters

algorithms

Displays information about the NTP system algorithms.

association

Displays information about the NTP server and peer association.

broadcast

Displays information about the NTP broadcast server and client.

clockadjust

Displays information about the NTP clock-adjust process.

errors

Displays information about the NTP error events.

packet

Displays information about the NTP input and output packets.

server

Displays information about the NTP server.

Modes

Privileged EXEC mode

Examples

The following example displays information about the NTP system algorithms.

```
device# debug ip ntp algorithms
NTP: ntp_peer_unfit: dist exceeded - root dist 16.00527999 of peer 10.25.96.13 has
exceeded max dist 1.50096000
NTP: ntp_peer_unfit: unreachable - peer 10.25.96.13 is not reachable [peer->reach
0]
device(config-ntp)# NTP: ntp_clock_filter: Adding offset 0, delay 0, disp 16 to
filter[0] for peer 10.25.96.13
NTP: ntp_clock_filter: No acceptable samples available
NTP: ntp_clock_filter: Adding offset 0.01133625, delay 0.27379156, disp
0.00001936 to filter[1] for peer 10.25.96.13
NTP: ntp_clock_filter: mitigated sample stats: n 1 offset 0.01133625 del
0.27379156 dsp 7.93750968 jit 0.00001525
NTP: ntp_peer_unfit: dist exceeded - root dist 8.07442072 of peer 10.25.96.13 has
exceeded max dist 1.50096000
NTP: ntp_clock_select: number of final survivors 0 and leap vote 0
NTP: ntp_clock_select: No survivors found. sys peer is set to NULL
NTP: ntp_clock_filter: Adding offset 0.02724471, delay 0.30800050, disp
0.00001988 to filter[2] for peer 10.25.96.13
NTP: ntp_clock_filter: mitigated sample stats: n 2 offset 0.02724471 del
0.30800050 dsp 3.93752228 jit 0.00001525
NTP: ntp_peer_unfit: dist exceeded - root dist 4.09153779 of peer 10.25.96.13 has
exceeded max dist 1.50096000
NTP: ntp_clock_update: at 430 sample 430 associd 2
NTP: ntp_rstclock: mu 67 new state 5 old state 5 offset -0.00001326
```

The following example displays information about the NTP server and peer association.

```
device# debug ip ntp association
NTP: peer_clear: peer 10.25.96.13 next 646 refid INIT
NTP: newpeer: 10.25.96.13 mode client vers 4 poll 6 10 key 00000000
Flags Flags -> iBURST
SYSLOG: <14>Mar 21 17:44:33 Murali NTP: client association is mobilized for
10.25.96.13.
SYSLOG: <14>Mar 21 17:44:33 Murali NTP: The system clock is not synchronized to
any time source.
SYSLOG: <14>Mar 21 17:44:40 Murali NTP: Stratum is changed to 2.
SYSLOG: <14>Mar 21 17:44:40 Murali NTP: System clock is synchronized to
10.25.96.13.
```

The following example displays information about the NTP clock-adjust process.

```
device# debug ip ntp clockadjust
NTP: ntp_clock_update: at 327 sample 327 associd 3
NTP: ntp_local_clock: huffbuf - ptr 1 mindly 0.23329046 huffpuff correction
-0.00067095
NTP: ntp_local_clock: clk offset 0.00917431 clk jit 0 clk stab 0 sys_poll 6
NTP: ntp_set_freq: drift 0.00000010, old freq 50000000
NTP: ntp_set_freq: new freq 49999995
NTP: ntp_adj_host_clock: new offset 0.00917431, freq 49999995
NTP: Adjusting the clock. offset 0.00917431, calib used 251687
NTP: After adjusting the clock. offset 0.00817431, calib used 252687
NTP: Adjusting the clock. offset 0.00817431, calib used 252687
NTP: After adjusting the clock. offset 0.00717431, calib used 253687
NTP: Adjusting the clock. offset 0.00717431, calib used 253687
```

The following example displays information about the NTP input and output packets.

```
device# debug ip ntp packet
NTP: Sending the NTP client packet to 10.25.96.13 port 123 via port id INVALID
Leap 3, Version 4, Mode client, Stratum 16, Poll 6,
Precision 2**-16, Root delay 0, Root disp 167, Ref Id INIT,
Ref time 0.0 (00:00:00.0 GMT+00 Mon Jan 01 0)
Org 0.0 (00:00:00.0 GMT+00 Mon Jan 01 0)
Rec 0.0 (00:00:00.0 GMT+00 Mon Jan 01 0)
Xmt 230.745068249 (00:03:50.745068249 GMT+00 Mon Jan 01 0) pkt len = 48 key 0
NTP: Received NTP server packet from 10.25.96.13 on port 123 via port id mgmt1 at
00:03:50.1959316492 GMT+00 Mon Jan 01 0
Leap 0, Version 4, Mode server, Stratum 1, Poll 6,
Precision 2**-29, Root delay 0, Root disp 0, Ref Id 10.67.84.83,
Ref time 3572876227.2200200252 (17:37:07.2200200252 GMT+00 Thu Mar 21 2013)
Org 230.745068249 (00:03:50.745068249 GMT+00 Mon Jan 01 0)
Rec 3572876241.37257170 (17:37:21.37257170 GMT+00 Thu Mar 21 2013)
Xmt 3572876241.37302765 (17:37:21.37302765 GMT+00 Thu Mar 21 2013) pkt len =
48 key 0
NTP: Sending the NTP client packet to 10.25.96.13 port 123 via port id INVALID
Leap 3, Version 4, Mode client, Stratum 16, Poll 6,
Precision 2**-16, Root delay 0, Root disp 169, Ref Id INIT,
Ref time 0.0 (00:00:00.0 GMT+00 Mon Jan 01 0)
Org 3572876241.37302765 (17:37:21.37302765 GMT+00 Thu Mar 21 2013)
Rec 230.1959316492 (00:03:50.1959316492 GMT+00 Mon Jan 01 0)
Xmt 232.784360585 (00:03:52.784360585 GMT+00 Mon Jan 01 0) pkt len = 48 key 0
NTP: Received NTP server packet from 10.25.96.13 on port 123 via port id mgmt1 at
00:03:52.1904063455 GMT+00 Mon Jan 01 0
Leap 0, Version 4, Mode server, Stratum 1, Poll 6,
Precision 2**-29, Root delay 0, Root disp 0, Ref Id 10.67.84.83,
Ref time 3572876227.2200200252 (17:37:07.2200200252 GMT+00 Thu Mar 21 2013)
Org 232.784360585 (00:03:52.784360585 GMT+00 Mon Jan 01 0)
Rec 3572876243.75963892 (17:37:23.75963892 GMT+00 Thu Mar 21 2013)
Xmt 3572876243.76010686 (17:37:23.76010686 GMT+00 Thu Mar 21 2013) pkt len =
48 key 0
```

The following example displays information about the NTP server.

```
device# debug ip ntp server
NTP: Received NTP client packet from 172.26.67.52 on port 123 via port id mgmt1 at
18:02:44.1139927355 GMT+00 Thu Mar 21 2013
Leap 0, Version 4, Mode client, Stratum 3, Poll 6,
Precision 2**-16, Root delay 16102, Root disp 90471, Ref Id 172.26.67.65,
Ref time 3572877762.1183164018 (18:02:42.1183164018 GMT+00 Thu Mar 21 2013)
Org 3572877762.1141785444 (18:02:42.1141785444 GMT+00 Thu Mar 21 2013)
Rec 3572877762.1183164018 (18:02:42.1183164018 GMT+00 Thu Mar 21 2013)
Xmt 3572877764.1137502159 (18:02:44.1137502159 GMT+00 Thu Mar 21 2013) pkt len
= 48 key 0
device(config-ntp)# NTP: poll_update: for peer 10.250.229.100 hpoll 6 burst 0
retry 0 throttle 62 next poll 64
NTP: Received NTP server packet from 10.250.229.100 on port 123 via port id mgmt1
at 18:03:09.1891314446 GMT+00 Thu Mar 21 2013
Leap 0, Version 4, Mode server, Stratum 1, Poll 6,
Precision 2**-29, Root delay 0, Root disp 0, Ref Id 10.67.84.83,
Ref time 3572877762.155297680 (18:02:42.155297680 GMT+00 Thu Mar 21 2013)
Org 3572877789.878229501 (18:03:09.878229501 GMT+00 Thu Mar 21 2013)
Rec 3572877789.1401109720 (18:03:09.1401109720 GMT+00 Thu Mar 21 2013)
Xmt 3572877789.1401162509 (18:03:09.1401162509 GMT+00 Thu Mar 21 2013) pkt len
= 48 key 0
NTP: poll_update: for peer 10.250.229.100 hpoll 6 burst 0 retry 0 throttle 62 next
poll 67
```

debug ip ospf

Generates OSPF debugging information for the specified IP address. Output indicates state transitions, hello packets received, LSA acknowledgements received, LSA processing, flooding information, and database descriptions.

Syntax

debug ip ospf

no debug ip ospf

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip ospf 10.1.1.2
OSPF: debug ospf neighbor 10.1.1.2
device(config)# OSPF: rcvd hello from 10.1.1.2 area 0 on interface 10.1.1.1,
state DR, DR 10.1.1.1, BDR 10.1.1.2
OSPF: Neighbor 10.1.1.2, int v115, state FULL processing event HELLO_RECEIVED
OSPF: rcvd hello from 10.1.1.2 area 0 on interface 10.1.1.1, state DR, DR
10.1.1.1, BDR 10.1.1.2
OSPF: Neighbor 10.1.1.2, int v115, state FULL processing event HELLO_RECEIVED
OSPF: rcvd hello from 10.1.1.2 area 0 on interface 10.1.1.1, state DR, DR
10.1.1.1, BDR 10.1.1.2
OSPF: Neighbor 10.1.1.2, int v115, state FULL processing event HELLO_RECEIVED
```

debug ip ospf adj

Displays information about OSPF adjacencies and authentication, including designated router (DR) and backup designated router (BDR) elections, sent and received hello packets, neighbor state transitions, and database description information.

Syntax

```
debug ip ospf adj decimal  
nodebug ip ospf adjdecimal
```

Parameters

decimal
Refers to a specific adjacency event.

Modes

Privileged EXEC mode

Examples

```
device# debug ip ospf adj  
OSPF: adjacency events debugging is on  
device# debug ip ospf adj OSPF: send hello on area 0 interface 10.1.1.1  
OSPF: rcvd hello from 10.1.1.2 area 0 on interface 10.1.1.1, state DR, DR  
10.1.1.1, BDR 10.1.1.2  
OSPF: Neighbor 10.1.1.2, int v115, state FULL processing event HELLO_RECEIVED  
OSPF: send hello on area 0 interface 10.1.1.1  
OSPF: rcvd hello from 10.1.1.2 area 0 on interface 10.1.1.1, state DR, DR  
10.1.1.1, BDR 10.1.1.2  
OSPF: Neighbor 10.1.1.2, int v115, state FULL processing event HELLO_RECEIVED  
OSPF: send hello on area 0 interface 10.1.1.1  
OSPF: rcvd hello from 10.1.1.2 area 0 on interface 10.1.1.1, state DR, DR  
10.1.1.1, BDR 10.1.1.2  
OSPF: Neighbor 10.1.1.2, int v115, state FULL processing event HELLO_RECEIVED
```

debug ip ospf all-vrfs route

Displays OSPF debugging information for all VPN routing and forwarding activity.

Syntax

debug ip ospf all-vrfs route

no debug ip ospf all-vrfs route

Modes

Privileged EXEC mode

Examples

```
device# debug ip ospf all-vrfs route
SPF: redistribute into ospf 10.3.13.0 with ffffffff00 forwarding address 10.4.4.3
OSPF: originate external lsa 10.3.13.0 with ffffffff00
OSPF: Originate external advs ext fwding address 10.4.4.3
```

debug ip ospf error

Reports the receipt of OSPF packets with errors, or mismatches between hello packet options.

Syntax

debug ip ospf error

no debug ip ospf error

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip ospf error
OSPF: errors debugging is on
device(config-vif-9)# Debug: Jan 1 03:37:11 OSPF: invalid header or unable to
find neighbor, drop
Debug: Jan 1 03:37:11 OSPF: rcv from:10.9.9.2 Intf:ve 9 Hello L:48 A:1
Rid:10.2.2.2 DR:10.9.9.2 BDR:0.0.0.0
Debug: Jan 1 03:37:23 OSPF: invalid header or unable to find neighbor, drop
Debug: Jan 1 03:37:23 OSPF: rcv from:10.9.9.2 Intf:ve 9 Hello L:48 A:1
Rid:10.2.2.2 DR:10.9.9.2 BDR:0.0.0.0
Debug: Jan 1 03:37:34 OSPF: invalid header or unable to find neighbor, drop
Debug: Jan 1 03:37:34 OSPF: rcv from:10.9.9.2 Intf:ve 9 Hello L:48 A:1
Rid:10.2.2.2 DR:10.9.9.2 BDR:0.0.0.0
```

debug ip ospf event

Displays information about internal OSPF events related to configuration or interaction with the standby management processor and interface state transitions.

Syntax

debug ip ospf event

no debug ip ospf event

Modes

Privileged EXEC mode

Examples

```
device# debug ip ospf event
OSPF: events debugging is on
device# OSPF: Interface ve 18 (10.1.18.1) state Waiting processing event Wait
Timer
OSPF: DR/BDR election for 10.1.18.1 on ve 18
OSPF: Neighbor 10.213.213.213 int v18, state 2_WAY processing event ADJACENCY_OK
OSPF: send DBD to 10.213.213.213 on ve 18 flag 0x7 seq 0x18a3b9 len 32
OSPF: elect BDR(backup designated router): Router ID 10.213.213.213 IP interface
10.1.18.2
OSPF: elect DR(designated router): Router ID 10.10.10.77, IP interface 10.1.18.1
OSPF: Neighbor 10.116.116.1 int 2/1/21, state FULL processing event HELLO_RECEIVED
OSPF: Neighbor 10.116.116.1 int v511, state FULL processing event HELLO_RECEIVED
OSPF: Neighbor 10.116.116.1 int v911, state FULL processing event HELLO_RECEIVED
OSPF: Neighbor 41.41.41.41 int v35, state FULL processing event HELLO_RECEIVED
OSPF: Neighbor 10.213.213.213 int 2/1/14, state 2_WAY processing event
HELLO_RECEIVED
OSPF: Neighbor 10.116.116.1 int v511, state FULL processing event HELLO_RECEIVED
OSPF: send DBD to 10.213.213.213 on ve 18 flag 0x7 seq 0x18a3b9 len 32
OSPF: Neighbor 49.2.3.4 int v34, state FULL processing event HELLO_RECEIVED
OSPF: Neighbor 10.213.213.213 int v18, state EXCHANGE_START processing event
HELLO_RECEIVED
OSPF: Neighbor 10.213.213.213 int 4/1/12, state FULL processing event
HELLO_RECEIVED
device# OSPF: Interface ethernet 4/1/12 (10.1.51.2) state Down processing event
Interface Up
virtual interface 10.1.51.2 up, state changed to Other from Point To Point
no deOSPF: Neighbor 10.213.213.213 int 4/1/12, state DOWN processing event
HELLO_RECEIVED
OSPF: Neighbor 10.213.213.213 int 4/1/12, state INITIALIZING processing event
ONE_WAY
bug ip OSPF: Neighbor 10.213.213.213 int 4/1/12, state INITIALIZING processing
event HELLO_RECEIVED
```

debug ip ospf flood

Displays information about LSA flooding activity

Syntax

debug ip ospf flood

no debug ip ospf flood

Modes

Privileged EXEC mode

Examples

```
device# debug ip ospf flood
OSPF: flooding debugging is on
device(config-if-e1000-1/1/15)#OSPF: flood LSA Type:1 AdvRtr:10.2.1.1 Age:0
LsId:10.2.1.1
OSPF: flood advertisement 10.2.1.1 throughout a specific area = 0
OSPF: flood LSA Type:1 AdvRtr:10.2.1.1 Age:0 LsId:10.2.1.1
OSPF: flood advertisement 10.2.1.1 throughout a specific area = 0
OSPF: flooding type 1 advertisement out interface 10.1.1.1
OSPF: attempting to flood rcvd LSA area = 0 interface type = 1
OSPF: flood LSA Type:1 AdvRtr:10.3.1.1 Age:1 LsId:10.3.1.1
OSPF: flood advertisement 10.3.1.1 throughout a specific area = 0
OSPF: attempting to flood rcvd LSA area = 0 interface type = 1
OSPF: flood LSA Type:2 AdvRtr:10.3.1.1 Age:3600 LsId:10.1.1.2
OSPF: flood advertisement 10.1.1.2 throughout a specific area = 0
OSPF: flood LSA Type:1 AdvRtr:10.2.1.1 Age:0 LsId:10.2.1.1
OSPF: flood advertisement 10.2.1.1 throughout a specific area = 0
OSPF: flooding type 1 advertisement out interface 10.1.1.1
OSPF: attempting to flood rcvd LSA area = 0 interface type = 1
OSPF: flood LSA Type:1 AdvRtr:10.3.1.1 Age:1 LsId:10.3.1.1
OSPF: flood advertisement 10.3.1.1 throughout a specific area = 0
OSPF: attempting to flood rcvd LSA area = 0 interface type = 1
OSPF: flood LSA Type:2 AdvRtr:10.3.1.1 Age:1 LsId:10.1.1.2
OSPF: flood advertisement 10.1.1.2 throughout a specific area = 0
```

Debug Commands H - P

debug ip ospf graceful-restart

debug ip ospf graceful-restart

Enable this command to receive information about OSPF graceful restart events, including restart phases, graceful Link-State Advertisement (LSA) transmit and receive activity, and syslog messages.

Syntax

debug ip ospf graceful-restart

no debug ip ospf graceful-restart

Modes

Privileged EXEC mode

Examples

```

device# debug ip ospf graceful-restart
OSPF: graceful-restart debugging is on
device# LSA flush rcvd Type:4 AdvRtr:83.83.10.11 LsId:10.213.213.213
LSA flush rcvd Type:4 AdvRtr:83.83.10.11 LsId:10.213.213.213
LSA flush rcvd Type:4 AdvRtr:10.116.116.1 LsId:10.205.205.205
LSA flush rcvd Type:4 AdvRtr:10.116.116.1 LsId:10.205.205.205
rcv GRACE LSA from 10.1.14.1, age 0, Adv 10.213.213.213
install new GraceLSA, int 269, neighbor 10.1.14.1, age 0
rcv Grace_LSA from 10.1.14.1, area 0.0.0.10
Recvd grace lsa id=50331648 state=8 0x2dd5d5d5 0x2dd5d5d5 age=0 gr-state=0
neighbor 10.1.14.1 entering graceful restart state, timer 120, lsa age 0, max
120, helping 0
flood grace LSA, AdvRtr:10.213.213.213, Age:0
rcv GRACE LSA from 10.1.51.1, age 0, Adv 10.213.213.213
install new GraceLSA, int 779, neighbor 10.1.51.1, age 0
rcv Grace_LSA from 10.1.51.1, area 0.0.0.10
Recvd grace lsa id=50331648 state=8 0x2dd5d5d5 0x2dd5d5d5 age=0 gr-state=0
neighbor 10.1.51.1 entering graceful restart state, timer 120, lsa age 0, max
120, helping 0
flood grace LSA, AdvRtr:10.213.213.213, Age:0
rcv GRACE LSA from 10.1.18.2, age 0, Adv 10.213.213.213
install new GraceLSA, int 2050, neighbor 10.1.18.2, age 0
rcv Grace_LSA from 10.1.18.2, area 0.0.0.10
Recvd grace lsa id=50331648 state=8 0x2dd5d5d5 0x2dd5d5d5 age=0 gr-state=0
neighbor 10.1.18.2 entering graceful restart state, timer 120, lsa age 0, max
120, helping 0
flood grace LSA, AdvRtr:10.213.213.213, Age:0
rcv GRACE LSA from 10.1.14.1, age 0, Adv 10.213.213.213
Update same instance GRACE LSA age to 0 in database, refresh neighbor 10.1.14.1
restart timer to 120
rcv GRACE LSA from 10.1.51.1, age 0, Adv 10.213.213.213
Update same instance GRACE LSA age to 0 in database, refresh neighbor 10.1.51.1
restart timer to 120
rcv GRACE LSA from 10.1.18.2, age 0, Adv 10.213.213.213
Update same instance GRACE LSA age to 0 in database, refresh neighbor 10.1.18.2
restart timer to 120
rcv GRACE LSA from 10.1.14.1, age 0, Adv 10.213.213.213
Update same instance GRACE LSA age to 0 in database, refresh neighbor 10.1.14.1
restart timer to 120
rcv GRACE LSA from 10.1.51.1, age 0, Adv 10.213.213.213
Update same instance GRACE LSA age to 0 in database, refresh neighbor 10.1.51.1
restart timer to 120
rcv GRACE LSA from 10.1.18.2, age 0, Adv 10.213.213.213
Update same instance GRACE LSA age to 0 in database, refresh neighbor 10.1.18.2
restart timer to 120
device# no debug ip ospf graceful-restart
OSPF: graceful-restart debugging is off
  
```

debug ip ospf log-empty-lsa

Displays information about empty link state advertisements (LSAs).

Syntax

debug ip ospf log-empty-lsa

no debug ip ospf log-empty-lsa

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```

device# debug ip ospf log-empty-lsa
device(config-if-e1000-1/1/15)# debug ip ospf log-empty-lsa
OSPF: empty-LSA logging debugging is on
device(config-if-e1000-1/1/15)# debug ip ospf f1OSPF: originate router LSA, area
0
OSPF: No difference found, restart 0
OSPF: send ls request to neighbor 10.1.1.2, retrans 0
OSPF: sending ls request last size 36, count 1
OSPF: LSA rcvd Type:1 AdvRtr:10.2.1.1 Age:297 LsId:10.2.1.1 Seq-Num 8000000e from
Neighbor 10.1.1.2
OSPF: Received self originated LSA type 1 with id = 10.2.1.1 Seq-Num 8000000e
OSPF: install a new lsa, type 1, ls_id 10.2.1.1, age 0, seq 8000000f area-id 0
OSPF: NSR Sync ACK received for LSA
OSPF: ls_header.id 10.2.1.1 type 1 ToBesyncedState 2
OSPF: NSR : Sync node add, type 1, ls_id 10.2.1.1, age 0, seq 8000000f
OSPF: send ls update to interface 10.1.1.1 (224.0.0.6) tb 962478204, retrans 0
OSPF: tx LSA Type:1 AdvRtr:10.2.1.1 Age:1 LsId:10.2.1.1
OSPF: originate router LSA, area 0
OSPF: originate_router_links_advertisement gen new instance set 10.2.1.1 (not
sent - wait for MinLSInterval)
OSPF: LSA rcvd Type:1 AdvRtr:10.3.1.1 Age:1 LsId:10.3.1.1 Seq-Num 8000000f from
Neighbor 10.1.1.2
OSPF: install a new lsa, type 1, ls_id 10.3.1.1, age 1, seq 8000000f area-id 0
OSPF: NSR Sync ACK received for LSA
OSPF: ls_header.id 10.3.1.1 type 1 ToBesyncedState 2
OSPF: NSR : Sync node add, type 1, ls_id 10.3.1.1, age 1, seq 8000000f
OSPF: LSA rcvd Type:2 AdvRtr:10.3.1.1 Age:3600 LsId:10.3.1.1 Seq-Num 80000005
from Neighbor 10.1.1.2
OSPF: install a new lsa, type 2, ls_id 10.1.1.2, age 3600, seq 80000005 area-id 0
OSPF: NSR Sync ACK received for LSA
OSPF: ls_header.id 10.1.1.2 type 2 ToBesyncedState 2
OSPF: NSR : Sync node add, type 2, ls_id 10.1.1.2, age 3600, seq 80000005
oOSPF: trying age out LSA, id 10.1.1.2, len 32, type 2, from 10.3.1.1, age 3600
genNewLsa 0 area 0
OSPF: age out and remove lsa data base 10.1.1.2
odsOSPF: OSPF TIMER: Minlsa: sptr_database_entry generate_new_instance == TRUE
for 1.2.1.1
OSPF: originate_delayed LSA, type 1, parml: 0x0
OSPF: originate_router LSA, area 0
OSPF: difference found, restart 0
OSPF: install a new lsa, type 1, ls_id 10.2.1.1, age 0, seq 80000010 area-id 0
OSPF: NSR Sync ACK received for LSA
OSPF: ls_header.id 10.2.1.1 type 1 ToBesyncedState 2
OSPF: NSR : Sync node add, type 1, ls_id 10.2.1.1, age 0, seq 80000010
OSPF: OSPF: rcv LSA ack from 10.1.1.2, type 1, id 1.2.1.1, seq 0x8000000f, adv
10.2.1.1, age 1
OSPF: send_ls_update to interface 10.1.1.1 (224.0.0.6) tb 1017253324, retrans 0
OSPF: tx LSA Type:1 AdvRtr:10.2.1.1 Age:1 LsId:10.2.1.1
OSPF: LSA rcvd Type:1 AdvRtr:10.3.1.1 Age:1 LsId:10.3.1.1 Seq-Num 80000010 from
Neighbor 10.1.1.2
OSPF: install a new lsa, type 1, ls_id 10.3.1.1, age 1, seq 80000010 area-id 0
OSPF: NSR Sync ACK received for LSA
OSPF: ls_header.id 10.3.1.1 type 1 ToBesyncedState 2
OSPF: NSR : Sync node add, type 1, ls_id 10.3.1.1, age 1, seq 80000010
OSPF: LSA rcvd Type:2 AdvRtr:10.3.1.1 Age:1 LsId:10.1.1.2 Seq-Num 80000006 from
Neighbor 10.1.1.2
OSPF: install a new lsa, type 2, ls_id 10.1.1.2, age 1, seq 80000006 area-id 0
OSPF: NSR Sync ACK received for LSA
OSPF: ls_header.id 10.1.1.2 type 2 ToBesyncedState 2
OSPF: NSR : Sync node add, type 2, ls_id 10.1.1.2, age 1, seq 80000006
OSPF: OSPF: rcv LSA ack from 10.1.1.2, type 1, id 10.2.1.1, seq 0x80000010, adv
10.2.1.1, age 1
OSPF: originate router LSA, area 0
OSPF: No difference found, restart 0

```

debug ip ospf lsa-generation

Displays information about link state advertisements (LSAs).

Syntax

debug ip ospf lsa-generation

no debug ip ospf lsa-generation

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip ospf lsa-generation
OSPF: lsa generation debugging is on
device(config-if-e1000-1/1/15)#OSPF: originate router LSA, area 0
OSPF: trying age out LSA, id 10.2.1.1, len 36, type 1, from 10.2.1.1, age 3600
genNewLsa 0 area 0
OSPF: age out and remove lsa data base 10.2.1.1
```

debug ip ospf lsa-id

Generates information about OSPF Link-State Advertisement (LSA) IDs.

Syntax

```
debug ip ospf lsa-id
```

```
no debug ip ospf lsa-id
```

Modes

Privileged EXEC mode

Global Configuration mode

Usage Guidelines

The **debug ip ospf lsa-id** command must be enabled with the **debug ip ospf flood** or the **debug ip ospf lsa-generation** command.

Examples

```
device# debug ip ospf lsa-id
Debug message destination: Console
IP Routing:
OSPF: flooding debugging is on
OSPF: lsa generation debugging is on
OSPF: ls-id 10.2.2.2 debugging is on
device(config-ospf-router)# Debug: Jan 1 04:12:50 OSPF: LSA rcvd Type:1
AdvRtr:10.2.2.2 Age:1 LsId:10.2.2.2 Seq-Num 8000000e from Neighbor 10.9.9.2
Debug: Jan 1 04:12:50 OSPF: install a new lsa, type 1, ls_id 10.2.2.2, age 1, seq
8000000e area-id 0
Debug: Jan 1 04:12:50 OSPF: NSR Sync ACK received for LSA
Debug: Jan 1 04:12:50 OSPF: ls_header.id 10.2.2.2 type 1 ToBesyncedState 2
Debug: Jan 1 04:12:50 OSPF: NSR : Sync node add, type 1, ls_id 10.2.2.2, age 1,
seq 8000000e
Debug: Jan 1 04:12:50 OSPF: attempting to flood rcvd LSA area = 0 interface type
= 1
Debug: Jan 1 04:12:50 OSPF: flood LSA Type:1 AdvRtr:10.2.2.2 Age:1 LsId:10.2.2.2
Debug: Jan 1 04:12:50 OSPF: flood advertisement 10.2.2.2 throughout a specific
area = 0
Debug: Jan 1 04:12:51 OSPF: LSA rcvd Type:1 AdvRtr:10.2.2.2 Age:1 LsId:10.2.2.2
Seq-Num 8000000f from Neighbor 10.9.9.2
Debug: Jan 1 04:12:51 OSPF: install a new lsa, type 1, ls_id 10.2.2.2, age 1, seq
8000000f area-id 0
Debug: Jan 1 04:12:51 OSPF: NSR Sync ACK received for LSA
Debug: Jan 1 04:12:51 OSPF: ls_header.id 10.2.2.2 type 1 ToBesyncedState 2
Debug: Jan 1 04:12:51 OSPF: NSR : Sync node add, type 1, ls_id 10.2.2.2, age 1,
seq 8000000f
Debug: Jan 1 04:12:51 OSPF: attempting to flood rcvd LSA area = 0 interface type
= 1
Debug: Jan 1 04:12:51 OSPF: flood LSA Type:1 AdvRtr:10.2.2.2 Age:1 LsId:10.2.2.2
Debug: Jan 1 04:12:51 OSPF: flood advertisement 10.2.2.2 throughout a specific
area = 0
```

debug ip ospf max-metric

Displays debugging information about the max-metric configuration.

Syntax

```
debug ip ospf max-metric
no debug ip ospf max-metric
```

Modes

Privileged EXEC mode
Global Configuration mode

Examples

```
device# debug ip ospf max-metric
OSPF: max-metric debugging is on
device(config-ospf-router)# max-metric router-lsa all-lsas
Debug: Jan 1 04:20:05 OSPF: Max-metric advertisement started due to configuration
change for vrf 0
```

debug ip ospf packet

Generates debugging information about the Open Shortest Path First (OSPF) packets.

Syntax

```
debug ip ospf packet [detail decimal | in | out | peer ip-addr | port [ethernet stackid/slot/port | ve decimal] src-ip ip-addr | type {ack | dd | hello | request | update}]
```

```
no debug ip ospf packet
```

Parameters

detail *decimal*

Refers to the level by bit 0 and 1 and stack trace send by bit 2.

in

Refers only to the input packets.

out

Refers only to the output packets.

peer *ip-addr*

Matches with the peer (advertisement router).

port

Matches with the I/O port.

ethernet *stackid/slot/port*

Refers to the stack ID, slot, or Ethernet port.

ve *decimal*

Refers to the ID of the virtual Ethernet interface.

src-ip *ip-addr*

Matches with the source IP address.

type

Matches with the packet type.

ack

Indicates the acknowledgement packet type.

dd

Indicates the Database Description (DD) packet type.

hello

Indicates the hello packet type.

request

Indicates the request packets sent from a client to a server.

update

Indicates the update packets sent from a server to a client.

Debug Commands H - P
debug ip ospf packet

Modes

Privileged EXEC mode

Examples

```

device# debug ip ospf packet
device# OSPF: rcv from:10.1.14.1 to 224.0.0.5 Intf:e 2/1/14 LS-Ack L:104 Auth:0
ID:10.213.213.213
OSPF: rcv from:10.1.18.2 to 224.0.0.5 Intf:ve 18 LS-Ack L:104 Auth:0
ID:10.213.213.213
OSPF: send to:224.0.0.5 Intf:ve 36 Hello L:44 Auth:0 ID:10.10.10.77 DR:10.36.2.1
BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:ve 36 Hello L:44 Auth:0 ID:10.10.10.77
DR:10.36.100.1 BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:ve 511 Hello L:48 Auth:0 ID:10.10.10.77
DR:10.1.251.7 BDR:10.1.251.6
OSPF: send to:224.0.0.5 Intf:e 2/1/14 Hello L:48 Auth:0 ID:10.10.10.77
DR:10.1.14.2 BDR:10.1.14.1
OSPF: send to:224.0.0.5 Intf:e 2/1/21 LS-Ack L:104 Auth:0 ID:10.10.10.77
OSPF: send to:224.0.0.5 Intf:e 2/1/21 Hello L:48 Auth:0 ID:10.10.10.77 DR:0.0.0.0
BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:ve 35 Hello L:48 Auth:0 ID:10.10.10.77
DR:10.1.35.16 BDR:10.1.35.15
OSPF: send to:10.1.251.6 Intf:ve 511 Hello L:48 Auth:0 ID:10.10.10.77 DR:0.0.0.0
BDR:0.0.0.0
OSPF: send to:10.1.18.2 Intf:e 4/1/12 Hello L:48 Auth:0 ID:10.10.10.77 DR:0.0.0.0
BDR:0.0.0.0
OSPF: rcv from:10.1.35.15 to 224.0.0.5 Intf:ve 35 LS-Ack L:104 Auth:0
ID:41.41.41.41
OSPF: rcv from:10.1.251.18 to 10.1.251.17 Intf:e 2/1/21 Hello L:48 Auth:0
ID:10.116.116.1 DR:0.0.0.0 BDR:0.0.0.0
OSPF: rcv from:10.1.34.10 to 224.0.0.5 Intf:ve 34 LS-Ack L:104 Auth:0
ID:49.2.3.4
OSPF: rcv from:10.1.34.10 to 224.0.0.5 Intf:ve 34 Hello L:48 Auth:0 ID:49.2.3.4
DR:10.1.34.16 BDR:10.1.34.10
OSPF: rcv from:10.1.251.18 to 224.0.0.5 Intf:e 2/1/21 LS-Upd L:136 Auth:0
ID:10.116.116.1 Cnt:3
OSPF: send to:224.0.0.5 Intf:ve 18 LS-Upd L:136 Auth:0 ID:10.10.10.77 Cnt:3
OSPF: send to:224.0.0.5 Intf:e 2/1/14 LS-Upd L:136 Auth:0 ID:10.10.10.77 Cnt:3
OSPF: send to:224.0.0.5 Intf:e 4/1/12 LS-Upd L:136 Auth:0 ID:10.10.10.77 Cnt:3
OSPF: send to:224.0.0.5 Intf:ve 34 LS-Upd L:136 Auth:0 ID:10.10.10.77 Cnt:3
OSPF: send to:224.0.0.5 Intf:ve 35 LS-Upd L:136 Auth:0 ID:10.10.10.77 Cnt:3
OSPF: rcv from:10.1.251.6 to 224.0.0.5 Intf:ve 511 LS-Upd L:136 Auth:0
ID:10.116.116.1 Cnt:3
OSPF: send to:10.1.251.6 Intf:ve 511 LS-Ack L:84 Auth:0 ID:10.10.10.77
OSPF: rcv from:10.1.91.18 to 224.0.0.5 Intf:ve 911 LS-Upd L:136 Auth:0
ID:10.116.116.1 Cnt:3
OSPF: send to:10.1.91.18 Intf:ve 911 LS-Ack L:84 Auth:0 ID:10.10.10.77
OSPF: rcv from:10.1.14.1 to 224.0.0.5 Intf:e 2/1/14 LS-Upd L:136 Auth:0
ID:10.213.213.213 Cnt:3
OSPF: rcv from:10.1.51.1 to 224.0.0.5 Intf:e 4/1/12 LS-Upd L:136 Auth:0
ID:10.213.213.213 Cnt:3
OSPF: rcv from:10.1.18.2 to 224.0.0.5 Intf:ve 18 LS-Upd L:136 Auth:0
ID:10.213.213.213 Cnt:3
OSPF: rcv from:10.1.14.1 to 224.0.0.5 Intf:e 2/1/14 LS-Ack L:84 Auth:0
ID:10.213.213.213
OSPF: rcv from:10.1.18.2 to 224.0.0.5 Intf:ve 18 LS-Ack L:84 Auth:0
ID:10.213.213.213
OSPF: send to:224.0.0.5 Intf:ve 911 Hello L:48 Auth:0 ID:10.10.10.77
DR:10.1.91.16 BDR:10.1.91.18
OSPF: send to:224.0.0.5 Intf:loopback 1 Hello L:44 Auth:0 ID:10.10.10.77
DR:10.10.10.77 BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:loopback 2 Hello L:44 Auth:0 ID:10.10.10.77
DR:10.10.62.10 BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:loopback 3 Hello L:44 Auth:0 ID:10.10.10.77
DR:10.10.63.10 BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:loopback 4 Hello L:44 Auth:0 ID:10.10.10.77
DR:10.10.64.10 BDR:0.0.0.0
OSPF: send to:224.0.0.5 Intf:e 2/1/21 LS-Ack L:84 Auth:0 ID:10.10.10.77
OSPF: rcv from:10.1.35.15 to 224.0.0.5 Intf:ve 35 LS-Ack L:84 Auth:0
ID:41.41.41.41
OSPF: rcv from:10.1.34.10 to 224.0.0.5 Intf:ve 34 LS-Ack L:84 Auth:0 ID:49.2.3.4
OSPF: rcv from:10.1.251.18 to 224.0.0.5 Intf:e 2/1/21 LS-Upd L:100 Auth:0
ID:10.116.116.1 Cnt:2
  
```

Debug Commands H - P

debug ip ospf packet

```
OSPF: send to:224.0.0.5 Intf:ve 18 LS-Upd L:100 Auth:0 ID:10.10.10.77 Cnt:2
OSPF: send to:224.0.0.5 Intf:e 2/1/14 LS-Upd L:100 Auth:0 ID:10.10.10.77 Cnt:2
OSPF: send to:224.0.0.5 Intf:e 4/1/12 LS-Upd L:100 Auth:0 ID:10.10.10.77 Cnt:2
OSPF: send to:224.0.0.5 Intf:ve 34 LS-Upd L:100 Auth:0 ID:10.10.10.77 Cnt:2
OSPF: send to:224.0.0.5 Intf:ve 35 LS-Upd L:100 Auth:0 ID:10.10.10.77 Cnt:2
OSPF: rcv from:10.1.251.6 to 224.0.0.5 Intf:ve 511 LS-Upd L:100 Auth:0
ID:10.116.116.1 Cnt:2
OSPF: send to:10.1.251.6 Intf:ve 511 LS-Ack L:64 Auth:0 ID:10.10.10.77
OSPF: rcv from:10.1.91.18 to 224.0.0.5 Intf:ve 911 LS-Upd L:100 Auth:0
ID:10.116.116.1 Cnt:2
OSPF: send to:10.1.91.18 Intf:ve 911 LS-Ack L:64 Auth:0 ID:10.10.10.77
OSPF: rcv from:10.1.14.1 to 224.0.0.5 Intf:e 2/1/14 LS-Upd L:100 Auth:0
ID:10.213.213.213 Cnt:2
OSPF: rcv from:10.1.51.1 to 224.0.0.5 Intf:e 4/1/12 LS-Upd L:100 Auth:0
ID:10.213.213.213 Cnt:2
OSPF: rcv from:10.1.18.2 to 224.0.0.5 Intf:ve 18 LS-Upd L:100 Auth:0
ID:10.213.213.213 Cnt:2
OSPF: rcv from:10.1.251.6 to 224.0.0.5 Intf:ve 511 LS-Upd L:748 Auth:0
ID:10.116.116.1 Cnt:20
OSPF: send to:224.0.0.5 Intf:ve 18 LS-Upd L:748 Auth:0 ID:10.10.10.77 Cnt:20
OSPF: send to:224.0.0.5 Intf:e 2/1/14 LS-Upd L:748 Auth:0 ID:10.10.10.77 Cnt:20
OSPF: send to:224.0.0.5 Intf:e 4/1/12 LS-Upd L:748 Auth:0 ID:10.10.10.77 Cnt:20
OSPF: send to:224.0.0.5 Intf:ve 34 LS-Upd L:748 Auth:0 ID:10.10.10.77 Cnt:20
OSPF: send to:224.0.0.5 Intf:ve 35 LS-Upd L:748 Auth:0 ID:10.10.10.77 Cnt:20
```

debug ip ospf retransmission

Generates internal information about Open Shortest Path First (OSPF) retransmission of link state advertisements (LSAs).

Syntax

debug ip ospf retransmission

no debug ip ospf retransmission

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip ospf retransmission
device(config)# clear ip route
OSPF: examine each neighbor and add advertisement
ls-id 10.3.13.0 to the retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.13.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.1.2.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.1.2.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.3.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.3.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.1.2.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.1.2.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.24.2.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.24.2.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.3.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.3.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.13.0 to the
retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.3.13.0 to the
retransmission list if necessary
device(config)# OSPF: examine each neighbor and add advertisement ls-id 10.24.2.0
to the retransmission list if necessary
OSPF: examine each neighbor and add advertisement ls-id 10.24.2.0 to the
retransmission list if necessary
```

debug ip ospf route

Generates information about Open Shortest Path First (OSPF) routes.

Syntax

debug ip ospf route *ip_address*

no debug ip ospf route *ip_address*

Parameters

ip_address

Specifies the IP address of the OSPF route.

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip ospf route 10.3.3.0
OSPF: debug ospf route 10.3.3.0
device(config-if-e1000-1/1/15)# debug ip ospf route 192.168.30.0
OSPF: debug ospf route 192.168.30.0
device(config-if-e1000-1/1/15)#OSPF: invalidate whole table - entry
192.168.30.0, state 0, path type 3
OSPF: calc ext route 192.168.30.0
OSPF: delete route 192.168.30.0 from rtm 0x367e7270, not_in_main 0
OSPF: calc ext route 192.168.30.0
OSPF: ext route, net = 192.168.30.0, mask = 10.255.255.0 advrtr = 10.3.1.1, fwd =
0.0.0.0
OSPF: ext route changed 192.168.30.0, state 0
OSPF: ext route new 192.168.30.0, state 2, path type 3
OSPF: add route 192.168.30.0 to rtm, next hop 115.1.1.2, type 3, state 3,
not_in_main 1
OSPF: add to ospf route table, to valid 192.168.30.0, state 3, path type 3
OSPF: Modify route 192.168.30.0, type 3, state 3, not_in_main 0, next hop 10.1.1.2
OSPF: modify/modify route 192.168.30.0 (fwd 367e7333), type 3, state 3,
not_in_main 0, nhp 381c51c0
OSPF: validate route, new->valid 192.168.30.0, state 3, path type 3
```

debug ip ospf spf

Generates information about Open Shortest Path First (OSPF) activity including SPF runs and calculations.

Syntax

```
debug ip ospf spf
```

```
no debug ip ospf spf
```

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip ospf spf
OSPF: spf-short debugging is on
Disable neighbor
device(config-ospf-router)# Debug: Jan 1 02:38:55 OSPF: Schedule SPF(8001), in
prog 0, ospf build_routing_table 0 phase 1
Debug: Jan 1 02:38:55 OSPF: schedule spf, init spf delay 0, next hold 0 (ticks)
Debug: Jan 1 02:38:55 OSPF: Add to spf pending list, current time 96788,
scheduled 96788, next run 96788
Debug: Jan 1 02:38:55 OSPF: Schedule SPF(7001), in prog 0, ospf
build_routing_table 0 phase 1
Debug: Jan 1 02:38:55 OSPF: Schedule SPF(6002), in prog 0, ospf
build_routing_table 0 phase 1
Debug: Jan 1 02:38:55 OSPF: timer: give semaphore, start spf phase 1, time 96789,
scheduled 96788, run time 96788
Debug: Jan 1 02:38:55 OSPF: begin intra SPF run, chunk-id 0/-1 just_become_abr 0,
is_abr 0
Debug: Jan 1 02:38:55 OSPF: invalidate whole routing table, recal_just_become_abr
0, just_become_abr 0
Debug: Jan 1 02:38:55 OSPF: running SPF for area 0 area-18ce7068 nextarea 0
next-area-id -1
Debug: Jan 1 02:38:55 OSPF: completed SPF for all areas
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC PHASE_INTRA end at 96789, is_abr 0
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC PHASE_TRANSIT end at 96789
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC PHASE_TYPE5 end at 96789
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC PHASE_TYPE7 end at 96789
Debug: Jan 1 02:38:55 OSPF: summary phase, is_abr 0
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC PHASE_SUMMARY end at 96789
Debug: Jan 1 02:38:55 OSPF: translation phase, is_abr 0
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC PHASE_TRANSLATION end at 96789
Debug: Jan 1 02:38:55 OSPF: SPF_cleanup: current 96789, set next run time 96788,
current hold 0, next hold 0
Debug: Jan 1 02:38:55 OSPF: ROUTE CALC end at 96789, pending 0
```

debug ip ospf vrf

Generates debugging information about the Open Shortest Path First (OSPF) Virtual Routing and Forwarding (VRF) instance.

Syntax

```
debug ip ospf vrf  
no debug ip ospf vrf
```

Modes

Privileged EXEC mode

Examples

```
device# debug ip ospf vrf  
OSPF(one): send hello on area 0 interface 10.3.4.1
```

debug ip pim

Enables the Protocol Independent Multicast (PIM) debugging.

Syntax

```
debug ip pim[fdb | hash | ipc | optimization | route-change | scaling | sync-lib | timer-typenum]  
no debug ip pim[fdb | hash | ipc | optimization | route-change | scaling | sync-lib | timer-typenum]
```

Parameters

- fdb**
Enables application VLAN (vidx) and forwarding database debugging.
- hash**
Displays hash address details for debugging.
- ipc**
Debugs inter-process communication between MP and LP.
- optimization**
Debugs multicast outgoing interface (OIF) list optimization.
- route-change**
Monitors route change.
- scaling**
Monitors scaling.
- sync-lib**
Monitors sync-lib operations.
- timer-typenum**
Displays stack trace of timer.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables PIM debugging.

Examples

```
device# debug ip pim  
PIM: pim debugging is on
```

debug ip pim add-del-oif

Displays information about the mcache activity.

Syntax

```
debug ip pim add-del-oif
```

```
no debug ip pim add-del-oif
```

Modes

Privileged EXEC mode

Usage Guidelines

The command will work with the **debug ip pim group** or **debug ip pim source** commands.

Examples

```

device# debug ip pim add-del-oif
May 29 10:45:20:048649:info:fi_debug:debug_logs:1:755772510176769: Updating REP entry 299
OIFTL3:VL20/2. OIFTAny:VL4294967295/4294967040. F:1 L:4294967295
May 29 10:45:20:042437:info:fi_debug:debug_logs:1:755772510176769: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v20,lg1 to (10.1.1.55,225.1.1.55) Action(Add)
May 29 10:45:20:042333:info:fi_debug:debug_logs:1:755772510176769: PIM-OIF.VRF0: (10.1.1.55 225.1.1.55)
Entry Flags 0x2042ace1: Add lg1 on 20 (L3). OIF_FLAGS: 1
May 29 10:45:20:041731:info:fi_debug:debug_logs:1:755772510176769: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v20,lg1 to (10.1.1.55,225.1.1.55) Action(Add)
May 29 10:45:20:041654:info:fi_debug:debug_logs:1:755772510176769: PIM.VRF0: Update oifflg v120/lg1
(10.1.1.55,225.1.1.55), rcode(ImmAdd), Act(Add) cstate(0x0) nstate(0x1) newflg 0x1, #immoifs 1 #bldoifs
0 #inhoifs 0 #fwdoifs 1 sync 1
May 29 10:45:20:041572:info:fi_debug:debug_logs:1:755772510176769: PIM.VRF0: Starting Oif timer for
lg1,lg1 from (10.1.1.55, 225.1.1.55) entry, Reason(ImmAdd) ; timer_type ; interval 210
May 29 10:45:20:041479:info:fi_debug:debug_logs:1:755772510176769: PIM-OIF.VRF0: (10.1.1.55 225.1.1.55)
Entry Flags 0x42a8c1: Add lg1 on 20 (L3). OIF_FLAGS: 1
May 29 10:45:20:041397:info:fi_debug:debug_logs:1:755772510176769: PIM.VRF0: Add OIF: Adding L3OIF
v20,lg1 to (10.1.1.55,225.1.1.55), Reason(ImmAdd) Action(Add) CurrentState(0x0) NewState(0x1) holdtime
210
May 29 10:45:20:041280:info:fi_debug:debug_logs:1:755772510176769: PIMSM.VRF0: OIF FSM 1 case for
(10.1.1.55, 225.1.1.55) entry Reason(ImmAdd), Action(Add) flagAction 3 CurrentState(0x0) NewState(0x1)
May 29 10:45:01:829101:info:fi_debug:debug_logs:1:754423890445825: PIM.VRF0: OIF Add v10,3/1/5 to
(30.1.1.10 225.1.1.5) entry - receivers mbrship type 1
May 29 10:45:01:828961:info:fi_debug:debug_logs:1:754423890445825: PIMSM.VRF0: OIF FSM 1 for (*,
225.1.1.5) entry Reason(IgmpGrpJoin), Action(Update), flagAction(1) CurrentState(0x4) NewState(0x4)
May 29 10:44:54:387782:info:fi_debug:debug_logs:1:753839774893569: PIM.VRF0: OIF Add v10,3/1/5 to
(30.1.1.10 225.1.1.5) entry - receivers mbrship type 1
May 29 10:44:54:387642:info:fi_debug:debug_logs:1:753839774893569: PIMSM.VRF0: OIF FSM 1 for (*,
225.1.1.5) entry Reason(IgmpGrpJoin), Action(Update), flagAction(1) CurrentState(0x4) NewState(0x4)
May 29 10:44:44:205900:info:fi_debug:debug_logs:1:753122515355137: PIM.VRF0: OIF Add v10,3/1/5 to
(30.1.1.10 225.1.1.5) entry - receivers mbrship type 1
May 29 10:44:44:205762:info:fi_debug:debug_logs:1:753122515355137: PIMSM.VRF0: OIF FSM 1 for (*,
225.1.1.5) entry Reason(IgmpGrpJoin), Action(Update), flagAction(1) CurrentState(0x4) NewState(0x4)
May 29 10:44:40:897143:info:fi_debug:debug_logs:1:752903472023041: Updating REP entry 298
OIFTL3:VL10/1. OIFTAny:VL4294967295/4294967040. F:1 L:4294967295
May 29 10:44:40:896345:info:fi_debug:debug_logs:1:752903472023041: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (30.1.1.10,225.1.1.5) Action(Add)
May 29 10:44:40:896266:info:fi_debug:debug_logs:1:752903472023041: PIM-OIF.VRF0: (30.1.1.10 225.1.1.5)
Entry Flags 0x600680e1: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 10:44:40:896169:info:fi_debug:debug_logs:1:752903472023041: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (*,225.1.1.5) Action(Add)
May 29 10:44:40:896060:info:fi_debug:debug_logs:1:752903472023041: PIM-OIF.VRF0: (* 225.1.1.5) Entry
Flags 0x2604a0: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 10:44:40:895688:info:fi_debug:debug_logs:1:752903472023041: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (30.1.1.10,225.1.1.5) Action(Add)
May 29 10:44:40:895614:info:fi_debug:debug_logs:1:752903472023041: PIM.VRF0: Update oifflg v110/3/1/5
(30.1.1.10,225.1.1.5), rcode(IgmpGrpJoin), Act(Add) cstate(0x0) nstate(0x4) newflg 0x4, #immoifs 0
#bldoifs 0 #inhoifs 1 #fwdoifs 1 sync 1
May 29 10:44:40:895532:info:fi_debug:debug_logs:1:752903472023041: PIM-OIF.VRF0: (30.1.1.10 225.1.1.5)
Entry Flags 0x280c1: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 10:44:40:895455:info:fi_debug:debug_logs:1:752903472023041: PIM.VRF0: Add OIF: Adding L3OIF
v10,3/1/5 to (30.1.1.10,225.1.1.5), Reason(IgmpGrpJoin) Action(Add) CurrentState(0x0) NewState(0x4)
holdtime 260
May 29 10:44:40:895378:info:fi_debug:debug_logs:1:752903472023041: PIMSM.VRF0: OIF FSM 1 case for
(30.1.1.10, 225.1.1.5) entry Reason(IgmpGrpJoin), Action(Add) flagAction 3 CurrentState(0x0)
NewState(0x4)

```

debug ip pim bootstrap

Enables bootstrap debugging.

Syntax

debug ip pim bootstrap

no debug ip pim bootstrap

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables bootstrap debugging.

Examples

```
device# debug ip pim bootstrap
Apr 22 20:01:07:098455:info:fi_debug:debug_logs:1:5657425411573249: PIM-BSR.VRF0: Intf v20 - accept BSM
from BSR 99.1.1.1(Pr 250), local state CandBSR, curr BSR 99.1.1.1 (Pr 250)
Apr 22 20:01:07:098344:info:fi_debug:debug_logs:1:5657425411573249: PIM-BSR.VRF0: Prefer BSR
99.1.1.1(Pr 250) over current BSR 99.1.1.1(Pr 250)
Apr 22 20:01:06:294257:info:fi_debug:debug_logs:1:2239486142449153: DHCPV4: received packet SIP:
0.0.0.0, DIP: 255.255.255.255, SP: 68, DP: 67, PROTO: 17
Apr 22 20:01:00:311204:info:fi_debug:debug_logs:1:60053310769464064: Found UcRte: Dist 110. OutIf 20.
NHop fe80::d6c1:9eff:fe4a:2114"
```

debug ip pim clear

Clears all the Protocol Independent Multicast (PIM) debug settings.

Syntax

debug ip pim clear

no debug ip pim clear

Modes

Privileged EXEC mode

Examples

```
device# debug ip pim clear  
no debug ip pim is enabled
```

debug ip pim event

Enables debugging of Protocol Independent Multicast (PIM) events.

Syntax

debug ip pim event

no debug ip pim event

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables PIM events debugging.

Examples

```

device# debug ip pim event
May 29 10:57:40:627362:info:fi_debug:debug_logs:1:827262240818689: Mcastv4 receive event
EVENT_ID_TRUNK_MEMBER_UP(15)
May 29 10:57:40:627289:info:fi_debug:debug_logs:1:827262240818689: Suppressed 1 times: PIM-EVT: Receive
vport v21/1/1/1 (lg1) Dn state_notify
May 29 10:57:40:615591:info:fi_debug:debug_logs:1:827262240818689: PIM-EVT: Receive vport v21/1/1/1
(lg1) Dn state_notify
May 29 10:57:40:615514:info:fi_debug:debug_logs:1:827262240818689: Suppressed 1 times: PIM-EVT: Receive
vport v20/1/1/1 (lg1) Dn state_notify
May 29 10:57:40:600989:info:fi_debug:debug_logs:1:827262240818689: PIM-EVT: Receive vport v20/1/1/1
(lg1) Dn state_notify
May 29 10:57:40:491010:info:fi_debug:debug_logs:1:827262240818689: Mcastv4 receive event
EVENT_ID_TRUNK_MEMBER_UP(15)
May 29 10:57:35:882546:info:fi_debug:debug_logs:1:8879630136115968: Suppressed 1 times: PIM-EVT:
Receive vport v21/1/1/3 (lg1) Dn state_notify
May 29 10:57:01:729138:info:fi_debug:debug_logs:1:111669149697: PIM-EVT: Receive vport v21/1/1/3 (lg1)
Dn state_notify
May 29 10:57:01:729061:info:fi_debug:debug_logs:1:111669149697: Suppressed 1 times: PIM-EVT: Receive
vport v20/1/1/3 (lg1) Dn state_notify
May 29 10:57:01:716680:info:fi_debug:debug_logs:1:111669149697: PIM-EVT: Receive vport v20/1/1/3 (lg1)
Dn state_notify
May 29 10:57:01:656675:info:fi_debug:debug_logs:1:111669149697: PIM-EVT.VRF1: Receive intf v21 Dn
state_notify. AFI: IPv4.
May 29 10:57:01:656561:info:fi_debug:debug_logs:1:111669149697: MC-EVT: Port v21 state changed to DOWN.
AFI: IPv4.
May 29 10:57:01:651175:info:fi_debug:debug_logs:1:111669149697: PIM-EVT: Receive vport v21/1/1/3 (lg1)
Dn state_notify
May 29 10:57:01:616394:info:fi_debug:debug_logs:1:111669149697: PIM-EVT.VRF0: Receive intf v20 Dn
state_notify. AFI: IPv4.
May 29 10:57:01:616257:info:fi_debug:debug_logs:1:111669149697: MC-EVT: Port v20 state changed to DOWN.
AFI: IPv4.
May 29 10:57:01:601505:info:fi_debug:debug_logs:1:111669149697: PIM-EVT: Receive vport v20/1/1/3 (lg1)
Dn state_notify
May 29 10:57:01:521588:info:fi_debug:debug_logs:1:111669149697: Mcastv4 receive event
EVENT_ID_TRUNK_DOWN(13)
May 29 10:57:01:483463:info:fi_debug:debug_logs:1:111669149697: Mcastv4 receive event
EVENT_ID_TRUNK_MEMBER_DOWN(16)
May 29 10:57:01:442597:info:fi_debug:debug_logs:1:111669149697: PIM-EVT: Receive vport v21/1/1/1 (lg1)
Dn state_notify
May 29 10:57:01:405205:info:fi_debug:debug_logs:1:111669149697: PIM-EVT: Receive vport v20/1/1/1 (lg1)
Dn state_notify
May 29 10:57:01:273313:info:fi_debug:debug_logs:1:111669149697: Mcastv4 receive event
EVENT_ID_TRUNK_MEMBER_DOWN(16) "
  
```

debug ip pim group

Displays the Protocol Independent Multicast (PIM) related activities for the specified IP address of the PIM group.

Syntax

```
debug ip pim group ip_address
```

```
no debug ip pim group ip_address
```

Parameters

ip_address

Specifies the IP address of the PIM group.

Modes

Privileged EXEC mode

Examples

```
device# debug ip pim group 225.1.1.5
May 29 11:03:33:160353:info:fi_debug:debug_logs:1:9184328000996096: PIM.VRF0: Deallocated hw resources
for (* 225.1.1.5), parent: v20,Nil. olist empty
May 29 11:03:27:789834:info:fi_debug:debug_logs:1:9179758155793152: stack: 00546ee8 0114a590 010d4e38
010d6ba8 01161d70 01162008 011624d4 01146df4 010dff10 01102568 010e427c 010eb698 0011ab58 010e5e6c
011975d0 0009ac30 0009babc 005c15f8 005c2998 0119e3a8 b6d93eb0 b6f9a195
May 29 11:03:27:789701:info:fi_debug:debug_logs:1:9179758155793152: PIM.VRF0: Allocation of hw
resources for (30.1.1.10 225.1.1.5) successful. olist empty. FID NotReq. MVID Drop
May 29 11:02:58:280684:info:fi_debug:debug_logs:1:854037066941953: stack: 00546ee8 0114a590 010d4e38
010d5f48 01165f14 01166168 01166470 0116c2ec 01147130 01101c8c 010f1e9c 010fc7c8 005c1f38 005c2998
0119e3a8 b6d93eb0 b6f9a195
May 29 11:02:58:280558:info:fi_debug:debug_logs:1:854037066941953: PIM.VRF0: Allocation of hw resources
for (30.1.1.10 225.1.1.5) successful. olist not empty. FID NotReq. MVID 309
May 29 11:02:53:629497:info:fi_debug:debug_logs:1:9151295407522560: stack: 00546ee8 0114a590 010d4e38
010d6ba8 01161d70 01162008 011624d4 01146df4 010dff10 01102568 010e427c 010eb698 0011ab58 010e5e6c
011975d0 0009ac30 0009babc 005c15f8 005c2998 0119e3a8 b6d93eb0 b6f9a195
May 29 11:02:53:629353:info:fi_debug:debug_logs:1:9151295407522560: PIM.VRF0: Allocation of hw
resources for (30.1.1.10 225.1.1.5) successful. olist empty. FID NotReq. MVID Drop
```

debug ip pim join-prune

Controls join prune processing and displays debugging information related to the join prune messages.

Syntax

debug ip pim join-prune

no debug ip pim join-prune

Modes

Privileged EXEC mode

Examples

```
device# debug ip pim join-prune
May 29 11:07:24:230956:info:fi_debug:debug_logs:1:9376231434748672: PIM: End sending Join/Prune msg ---
May 29 11:07:24:230598:info:fi_debug:debug_logs:1:9376231434748672: P-Src: 98.1.1.1, wc=1 rpt=1 SM=1
May 29 11:07:24:230522:info:fi_debug:debug_logs:1:9376231434748672: PIM-JP.VRF0: Group: 225.1.1.5,
JoinSrcs: 0, PruneSrcs: 1
May 29 11:07:24:230410:info:fi_debug:debug_logs:1:9376231434748672: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to 20.1.1.2 on v20
May 29 11:07:21:231309:info:fi_debug:debug_logs:1:9373757533586176: PIM: End sending Join/Prune msg ---
May 29 11:07:21:230896:info:fi_debug:debug_logs:1:9373757533586176: P-Src: 30.1.1.10, wc=0 rpt=0
SM=1
May 29 11:07:21:230827:info:fi_debug:debug_logs:1:9373757533586176: P-Src: 98.1.1.1, wc=1 rpt=1 SM=1
May 29 11:07:21:230753:info:fi_debug:debug_logs:1:9373757533586176: PIM-JP.VRF0: Group: 225.1.1.5,
JoinSrcs: 0, PruneSrcs: 2
May 29 11:07:21:230644:info:fi_debug:debug_logs:1:9373757533586176: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to 20.1.1.2 on v20
May 29 11:07:20:155433:info:fi_debug:debug_logs:1:873025117357569: PIMSM: END J/P proc.
-----
May 29 11:07:20:155366:info:fi_debug:debug_logs:1:873025117357569: Group=225.1.1.55. Prune list: 0
srcs
May 29 11:07:20:155254:info:fi_debug:debug_logs:1:873025117357569: PIM.VRF0: Processing (S,G)
Join (10.1.1.55 225.1.1.55) from 20.1.1.2, intf v20,lg1
May 29 11:07:20:155175:info:fi_debug:debug_logs:1:873025117357569: J-Src=10.1.1.55, wc=0, rpt=0,
SM=1
May 29 11:07:20:155101:info:fi_debug:debug_logs:1:873025117357569: Group=225.1.1.55. Join list: 1 srcs
May 29 11:07:20:154994:info:fi_debug:debug_logs:1:873025117357569: PIMSM.VRF0: BEGIN J/P proc: rpf_nbr
20.1.1.1, to_me=1 from 20.1.1.2, intf v20 ----
May 29 11:07:07:510301:info:fi_debug:debug_logs:1:9362307150775040: PIM: End sending Join/Prune msg ---
May 29 11:07:07:509749:info:fi_debug:debug_logs:1:9362307150775040: J-Src: 30.1.1.10, wc=0 rpt=0
SM=1
May 29 11:07:07:509679:info:fi_debug:debug_logs:1:9362307150775040: J-Src: 98.1.1.1, wc=1 rpt=1 SM=1
May 29 11:07:07:509606:info:fi_debug:debug_logs:1:9362307150775040: PIM-JP.VRF0: Group: 225.1.1.5,
JoinSrcs: 2, PruneSrcs: 0
May 29 11:07:07:509498:info:fi_debug:debug_logs:1:9362307150775040: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to 20.1.1.2 on v20
May 29 11:07:06:400040:info:fi_debug:debug_logs:1:9361388027773696: PIM.VRF0: (10.1.1.55 225.1.1.55)
RPFIf v10. RPFNbr -. Send Join/Prune
May 29 11:07:05:288828:info:fi_debug:debug_logs:1:9360490379608832: PIM.VRF0: (30.1.1.10 225.1.1.5)
RPFIf v20. RPFNbr 20.1.1.2. Send Join/Prune
May 29 11:07:04:210117:info:fi_debug:debug_logs:1:9359571256607488: PIM.VRF0: (* 225.1.1.5) RPFIf
v20. RPFNbr 20.1.1.2. Send Join/Prune
May 29 11:07:01:999234:info:fi_debug:debug_logs:1:9357707240801024: PIM: End sending Join/Prune msg ---
May 29 11:07:01:998839:info:fi_debug:debug_logs:1:9357707240801024: J-Src: 30.1.1.10, wc=0 rpt=0
SM=1
May 29 11:07:01:998768:info:fi_debug:debug_logs:1:9357707240801024: J-Src: 98.1.1.1, wc=1 rpt=1 SM=1
May 29 11:07:01:998692:info:fi_debug:debug_logs:1:9357707240801024: PIM-JP.VRF0: Group: 225.1.1.5,
JoinSrcs: 2, PruneSrcs: 0
May 29 11:07:01:998572:info:fi_debug:debug_logs:1:9357707240801024: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to 20.1.1.2 on v20
```

debug ip pim level

Sets the Protocol Independent Multicast (PIM) level.

Syntax

debug ip pim level*decimal*

no debug ip pim level

Parameters

decimal

Specifies the number of the PIM level. The valid values are from 1 through 3.

Modes

Privileged EXEC mode

Examples

```
device# debug ip pim level 3
device# debug ip pim packet 30.1.1.10 225.1.1.5 10
May 29 10:10:02:846290:err:fi_debug:debug_logs:1:590111326602753: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:10:01:741862:err:fi_debug:debug_logs:1:586383294989825: res-sharing:
[l3mcast_remove_mcache_from_mcrep_ack_wait_inst] removing VRF0 v4 Flow Entry (10.1.1.55 225.1.1.55)
from mcrep 294 wait tree
May 29 10:10:01:741784:err:fi_debug:debug_logs:1:586383294989825: Suppressed 2 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 29 10:10:00:901210:err:fi_debug:debug_logs:1:582157047170561: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:09:39:113678:err:fi_debug:debug_logs:1:579867829601793: res-sharing:
[l3mcast_remove_mcache_from_mcrep_ack_wait_inst] removing VRF0 v4 Flow Entry (30.1.1.10 225.1.1.5) from
mcrep 293 wait tree
May 29 10:09:38:687374:err:fi_debug:debug_logs:1:577402518373889: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:09:38:549022:info:fi_debug:debug_logs:1:577162000205313:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 10. RPT=1, Local-Rcvr=1
May 29 10:09:38:548938:info:fi_debug:debug_logs:1:577162000205313:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:548462:info:fi_debug:debug_logs:1:577162000205313: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:548286:info:fi_debug:debug_logs:1:577162000205313: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:547264:info:fi_debug:debug_logs:1:577157705238017:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 9. RPT=1, Local-Rcvr=1
May 29 10:09:38:547184:info:fi_debug:debug_logs:1:577157705238017:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:546433:info:fi_debug:debug_logs:1:577157705238017: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:546304:info:fi_debug:debug_logs:1:577157705238017: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:546046:info:fi_debug:debug_logs:1:577153410270721:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 8. RPT=1, Local-Rcvr=1
May 29 10:09:38:545954:info:fi_debug:debug_logs:1:577153410270721:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:541631:info:fi_debug:debug_logs:1:577153410270721: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:541498:info:fi_debug:debug_logs:1:577153410270721: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:541224:info:fi_debug:debug_logs:1:577149115303425:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 7. RPT=1, Local-Rcvr=1
May 29 10:09:38:541135:info:fi_debug:debug_logs:1:577149115303425:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:538983:info:fi_debug:debug_logs:1:577149115303425: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:538846:info:fi_debug:debug_logs:1:577149115303425: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:538565:info:fi_debug:debug_logs:1:577144820336129:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 6. RPT=1, Local-Rcvr=1
May 29 10:09:38:538463:info:fi_debug:debug_logs:1:577144820336129:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:535620:info:fi_debug:debug_logs:1:577144820336129: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:535500:info:fi_debug:debug_logs:1:577144820336129: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:535266:info:fi_debug:debug_logs:1:577140525368833:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 5. RPT=1, Local-Rcvr=1
May 29 10:09:38:535188:info:fi_debug:debug_logs:1:577140525368833:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:534785:info:fi_debug:debug_logs:1:577140525368833: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:534659:info:fi_debug:debug_logs:1:577140525368833: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:534408:info:fi_debug:debug_logs:1:577136230401537:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 4. RPT=1, Local-Rcvr=1
May 29 10:09:38:534321:info:fi_debug:debug_logs:1:577136230401537:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:532312:info:fi_debug:debug_logs:1:577136230401537: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:532194:info:fi_debug:debug_logs:1:577136230401537: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:531955:info:fi_debug:debug_logs:1:577131935434241:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 3. RPT=1, Local-Rcvr=1
May 29 10:09:38:531875:info:fi_debug:debug_logs:1:577131935434241:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:531459:info:fi_debug:debug_logs:1:577131935434241: 30.1.1.10 225.1.1.5: 1 pkt,from
```

```
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:531331:info:fi_debug:debug_logs:1:577131935434241: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:531061:info:fi_debug:debug_logs:1:577127640466945:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 2. RPT=1, Local-Rcvr=1
May 29 10:09:38:530740:info:fi_debug:debug_logs:1:577127640466945:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:530333:info:fi_debug:debug_logs:1:577127640466945: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:530204:info:fi_debug:debug_logs:1:577127640466945: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:529933:info:fi_debug:debug_logs:1:577123345499649:      switch_to_spt: No. Thrshld: 1,
Cnt: 1. RPT=1, Local-Rcvr=1
May 29 10:09:38:529849:info:fi_debug:debug_logs:1:577123345499649:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:529365:info:fi_debug:debug_logs:1:577123345499649: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:529238:info:fi_debug:debug_logs:1:577123345499649:      send MCAST_FIRST_DATA: entry phy
port: INVALID, pkt input port: lg1. SPT-F, FAST-F, MCT IIF Flag: F.
May 29 10:09:38:528808:info:fi_debug:debug_logs:1:577123345499649:      Rx flow on intf/port diff than
entry's intf v20 or port Nil
May 29 10:09:38:528694:info:fi_debug:debug_logs:1:577123345499649: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:08:13:705055:info:fi_debug:debug_logs:1:21474836481: Cleanup Ended : 2021 May 29 09:08:13
May 29 10:08:13:704875:info:fi_debug:debug_logs:1:21474836481: Cleanup Started : 2021 May 29 09:08:13
May 29 09:52:49:280208:err:fi_debug:debug_logs:1:0: Suppressed 1 times: mct-forw:local or peer rbridge
is incorrect, local rid 0, peer rid 0
```

debug ip pim nbr

Controls the Protocol Independent Multicast (PIM) IPv4 neighbor changes.

Syntax

debug ip pim nbr*nbr_address*

no debug ip pim nbr*nbr_address*

Parameters

nbr_address

Specifies the IP address of the neighbor.

Modes

Privileged EXEC mode

Examples

```
device#debug ip pim nbr
May 29 11:10:24:499652:info:fi_debug:debug_logs:1:886373875713537: MLD: [ Port lg1 ] Query version
mismatch. Received query version 2 from fe80::d6c1:9eff:fe15:f999; Port version 1.
May 29 11:09:31:241269:info:fi_debug:debug_logs:1:9481690061734656: PIM-NBR.VRF1: Neighbor 21.0.0.2 on
interface v21, lg1 deleted on port-down
May 29 11:09:31:218936:info:fi_debug:debug_logs:1:9481690061734656: PIM-NBR.VRF0: Neighbor 20.1.1.2 on
interface v20, lg1 deleted on port-down
May 29 11:09:31:216709:info:fi_debug:debug_logs:1:9481690061734656: PIM.VRF0: (20.1.1.2 30.1.1.10) Nbr
225.1.1.5 moved; changing parent_phy_port from lg1 to INVALID
May 29 11:09:28:296654:info:fi_debug:debug_logs:1:882229232272897: PIM.VRF0: Rx Hello msg from 20.1.1.2
on intf v20, lg1
May 29 11:09:05:871728:info:fi_debug:debug_logs:1:880640094373377: PIM.VRF1: Rx Hello msg from 21.0.0.2
on intf v21, lg1
May 29 11:08:58:081982:info:fi_debug:debug_logs:1:880047388886529: PIM.VRF0: Rx Hello msg from 20.1.1.2
on intf v20, lg1
```

History

Release version	Command history
09.0.00	This command was modified to change the option nbr-change to nbr .

debug ip pim packet

Displays debugging information about the Protocol Independent Multicast (PIM) packets.

Syntax

```
debug ip pim packetsource_addressgroup_address[rate]
```

Parameters

source_address

Specifies the source address of the PIM packet.

group_address

Specifies the group address of the PIM packet.

rate

Specifies the hardware rate.

Modes

Privileged EXEC mode

Examples

```
device#debug ip pim packet 30.1.1.10 225.1.1.5 10
device#debug ip pim level 3
May 29 10:10:02:846290:err:fi_debug:debug_logs:1:590111326602753: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:10:01:741862:err:fi_debug:debug_logs:1:586383294989825: res-sharing:
[l3mcast_remove_mcache_from_mcrep_ack_wait_inst] removing VRF0 v4 Flow Entry (10.1.1.55 225.1.1.55)
from mcrep 294 wait tree
May 29 10:10:01:741784:err:fi_debug:debug_logs:1:586383294989825: Suppressed 2 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 29 10:10:00:901210:err:fi_debug:debug_logs:1:582157047170561: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:09:39:113678:err:fi_debug:debug_logs:1:579867829601793: res-sharing:
[l3mcast_remove_mcache_from_mcrep_ack_wait_inst] removing VRF0 v4 Flow Entry (30.1.1.10 225.1.1.5) from
mcrep 293 wait tree
May 29 10:09:38:687374:err:fi_debug:debug_logs:1:577402518373889: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:09:38:549022:info:fi_debug:debug_logs:1:577162000205313:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 10. RPT=1, Local-Rcvr=1
May 29 10:09:38:548938:info:fi_debug:debug_logs:1:577162000205313:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:548462:info:fi_debug:debug_logs:1:577162000205313: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:548286:info:fi_debug:debug_logs:1:577162000205313: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:547264:info:fi_debug:debug_logs:1:577157705238017:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 9. RPT=1, Local-Rcvr=1
May 29 10:09:38:547184:info:fi_debug:debug_logs:1:577157705238017:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:546433:info:fi_debug:debug_logs:1:577157705238017: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:546304:info:fi_debug:debug_logs:1:577157705238017: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:546046:info:fi_debug:debug_logs:1:577153410270721:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 8. RPT=1, Local-Rcvr=1
May 29 10:09:38:545954:info:fi_debug:debug_logs:1:577153410270721:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:541631:info:fi_debug:debug_logs:1:577153410270721: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:541498:info:fi_debug:debug_logs:1:577153410270721: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:541224:info:fi_debug:debug_logs:1:577149115303425:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 7. RPT=1, Local-Rcvr=1
May 29 10:09:38:541135:info:fi_debug:debug_logs:1:577149115303425:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:538983:info:fi_debug:debug_logs:1:577149115303425: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:538846:info:fi_debug:debug_logs:1:577149115303425: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:538565:info:fi_debug:debug_logs:1:577144820336129:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 6. RPT=1, Local-Rcvr=1
May 29 10:09:38:538463:info:fi_debug:debug_logs:1:577144820336129:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:535620:info:fi_debug:debug_logs:1:577144820336129: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:535500:info:fi_debug:debug_logs:1:577144820336129: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:535266:info:fi_debug:debug_logs:1:577140525368833:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 5. RPT=1, Local-Rcvr=1
May 29 10:09:38:535188:info:fi_debug:debug_logs:1:577140525368833:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:534785:info:fi_debug:debug_logs:1:577140525368833: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:534659:info:fi_debug:debug_logs:1:577140525368833: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:534408:info:fi_debug:debug_logs:1:577136230401537:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 4. RPT=1, Local-Rcvr=1
May 29 10:09:38:534321:info:fi_debug:debug_logs:1:577136230401537:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:532312:info:fi_debug:debug_logs:1:577136230401537: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:532194:info:fi_debug:debug_logs:1:577136230401537: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:531955:info:fi_debug:debug_logs:1:577131935434241:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 3. RPT=1, Local-Rcvr=1
May 29 10:09:38:531875:info:fi_debug:debug_logs:1:577131935434241:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:531459:info:fi_debug:debug_logs:1:577131935434241: 30.1.1.10 225.1.1.5: 1 pkt,from
```

```
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:531331:info:fi_debug:debug_logs:1:577131935434241: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:531061:info:fi_debug:debug_logs:1:577127640466945:      switch_to_spt: Yes. Thrshld: 1,
Cnt: 2. RPT=1, Local-Rcvr=1
May 29 10:09:38:530740:info:fi_debug:debug_logs:1:577127640466945:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:530333:info:fi_debug:debug_logs:1:577127640466945: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:530204:info:fi_debug:debug_logs:1:577127640466945: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:09:38:529933:info:fi_debug:debug_logs:1:577123345499649:      switch_to_spt: No. Thrshld: 1,
Cnt: 1. RPT=1, Local-Rcvr=1
May 29 10:09:38:529849:info:fi_debug:debug_logs:1:577123345499649:      SW forwarded pkt to 1 oif(s)
May 29 10:09:38:529365:info:fi_debug:debug_logs:1:577123345499649: 30.1.1.10 225.1.1.5: 1 pkt,from
v20(e1/1/3), dup. pkt to v10 phy e3/1/5, l2=0, 1/1/1 - lg1, 3/1/5-516
May 29 10:09:38:529238:info:fi_debug:debug_logs:1:577123345499649:      send MCAST_FIRST_DATA: entry phy
port: INVALID, pkt input port: lg1. SPT-F, FAST-F, MCT IIF Flag: F.
May 29 10:09:38:528808:info:fi_debug:debug_logs:1:577123345499649:      Rx flow on intf/port diff than
entry's intf v20 or port Nil
May 29 10:09:38:528694:info:fi_debug:debug_logs:1:577123345499649: Rx Pkt (30.1.1.10, 225.1.1.5) on
v20(1/1/3). hit=0
May 29 10:08:13:705055:info:fi_debug:debug_logs:1:21474836481: Cleanup Ended : 2021 May 29 09:08:13
May 29 10:08:13:704875:info:fi_debug:debug_logs:1:21474836481: Cleanup Started : 2021 May 29 09:08:13
```

debug ip pim regproc

Controls register processing.

Syntax

debug ip pim regproc

no debug ip pim regproc

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip pim regproc
May 29 11:14:05:360798:info:fi_debug:debug_logs:1:9713102899643136: PIMSM-REG.VRF0: (10.1.1.55
225.1.1.55) Sending L2-Null Reg on iface v10
```

debug ip pim rp

Controls the Rendezvous Point (RP) processing.

Syntax

debug ip pim rp

no debug ip pim rp

Modes

Privileged EXEC mode

Global Configuration mode

Examples

```
device# debug ip pim rp
May 29 11:12:03:440381:info:fi_debug:debug_logs:1:9611849045639936: PIMv4-RP.VRF1: processing C-RP-adv
from 199.1.1.1. PrefCnt 1
May 29 11:12:03:440304:info:fi_debug:debug_logs:1:9611849045639936: PIMv4-RP.VRF1: Looping C-RP-Adv msg
from 199.1.1.1 back to elected BSR (me)
May 29 11:12:03:440108:info:fi_debug:debug_logs:1:9611849045639936: PIMv4-RP.VRF0: processing C-RP-adv
from 99.1.1.1. PrefCnt 1
May 29 11:12:03:439992:info:fi_debug:debug_logs:1:9611849045639936: PIMv4-RP.VRF0: Looping C-RP-Adv msg
from 99.1.1.1 back to elected BSR (me)
```

debug ip pim show

Displays the PIM debug settings. Do not use the show debug command for this purpose. The show debug command displays general debug information.

Syntax

debug ip pim show

no debug ip pim show

Modes

Privileged EXEC mode

Examples

```
device#debug ip pim nbr
PIM nbr-change debugging is on
device#debug ip pim rp
PIM rp debugging is on
device#debug ip pim join-prune
PIM join-prune debugging is on
device#
device#debug ip pim show
debug ip pim rp
debug ip pim join-prune
debug ip pim nbr-change
```

debug ip pim source

Monitors the content related to a specific PIM server. The `ipaddr` variable refers to the IP address of the PIM server source.

Syntax

```
debug ip pim source ipaddress
```

```
no debug ip pim source ipaddress
```

Modes

Privileged EXEC mode

Examples

```
device# debug ip pim source 10.1.1.55
Apr 22 20:53:02:171799:info:fi_debug:debug_logs:1:5889370825426433: stack: 00549994 0114c014 011547b0
011567b0 01158654 0115a1e0 0115a294 005c3a0c 005c446c 011a0308 b6d23eb0 b6f32195
Apr 22 20:53:02:171708:info:fi_debug:debug_logs:1:5889370825426433: PIM.VRF0: Allocation of hw
resources for (10.1.1.55 225.1.1.1) successful. olist empty. FID 0x4fff (D). MVID Drop
Apr 22 20:53:02:171582:info:fi_debug:debug_logs:1:5889370825426433: PIMSM.VRF0: receive first data,
(10.1.1.55 225.1.1.1) entry. RP 99.1.1.1. Flags 0x200c1
Apr 22 20:53:02:169529:info:fi_debug:debug_logs:1:5889366530459137: stack: 00549994 0114c014 01155220
01155a54 01156d54 0115a1e0 0115a294 005c3a0c 005c446c 011a0308 b6d23eb0 b6f32195
Apr 22 20:53:02:169441:info:fi_debug:debug_logs:1:5889366530459137: PIM.VRF0: Allocation of hw
resources for (10.1.1.55 225.1.1.1) successful. olist empty. FID 0x4fff (D). MVID Drop
Apr 22 20:53:02:169309:info:fi_debug:debug_logs:1:5889366530459137: PIMSM.VRF0: Created (10.1.1.55
225.1.1.1) from data event
Apr 22 20:53:01:067318:info:fi_debug:debug_logs:1:2334190171325953: DHCPV4: received packet SIP:
0.0.0.0, DIP: 255.255.255.255, SP: 68, DP: 67, PROTO: 17
Apr 22 20:52:52:614347:info:fi_debug:debug_logs:1:2491081031681: Cleanup Ended : 2021 Apr 22 20:52:51
Apr 22 20:52:52:614217:info:fi_debug:debug_logs:1:2491081031681: PIM.VRF0: Deallocated hw resources for
(10.1.1.55 225.1.1.1), parent: v20,Nil. olist empty
Apr 22 20:52:52:614115:info:fi_debug:debug_logs:1:2491081031681: stack: 00549994 0114c014 010d626c
010d7fdc 010d91a4 010c6230 010c6b38 01111904 01111a6c 01276104 01276550 012765fc 001229c0 01276678
005c3a0c 005c446c 0118b0bc b6d23eb0 b6f32195
Apr 22 20:52:52:613975:info:fi_debug:debug_logs:1:2491081031681: PIM.VRF0: Allocation of hw resources
for (10.1.1.55 225.1.1.1) successful. olist empty. FID NotReq. MVID Drop"""
```

debug ip pim vrf

Displays the PIM related debugging information for the specified VRF.

Syntax

debug ip pim vrf*vrf_name*

no debug ip pim vrf*vrf_name*

Modes

Privileged EXEC mode

Examples

```
device#debug ip pim add-del-oif
device#debug ip pim rp
device#debug ip pim event
device#debug ip pim vrf SP_TN
May 29 10:25:11:613618:err:fi_debug:debug_logs:1:662627554428417: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:25:11:613424:info:fi_debug:debug_logs:1:662627554428417: Updating REP entry 297
OIFTL3:VL20/3. OIFTAny:VL4294967295/4294967040. F:1 L:4294967295
May 29 10:25:01:208794:info:fi_debug:debug_logs:1:7252249847792384: PIMv4-RP.VRF1: processing C-RP-adv
from 199.1.1.1. PrefCnt 1
May 29 10:25:01:208717:info:fi_debug:debug_logs:1:7252249847792384: PIMv4-RP.VRF1: Looping C-RP-Adv msg
from 199.1.1.1 back to elected BSR (me)
May 29 10:25:01:208639:err:fi_debug:debug_logs:1:7252249847792384: Suppressed 1 times: mct-forw:local
or peer rbridge is incorrect, local rid 0, peer rid 0
May 29 10:24:42:709340:err:fi_debug:debug_logs:1:660531610387969: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:24:01:119549:info:fi_debug:debug_logs:1:7202097514676992: PIMv4-RP.VRF1: processing C-RP-adv
from 199.1.1.1. PrefCnt 1
May 29 10:24:01:119469:info:fi_debug:debug_logs:1:7202097514676992: PIMv4-RP.VRF1: Looping C-RP-Adv msg
from 199.1.1.1 back to elected BSR (me)
May 29 10:24:01:119392:err:fi_debug:debug_logs:1:7202097514676992: Suppressed 1 times: mct-forw:local
or peer rbridge is incorrect, local rid 0, peer rid 0
May 29 10:23:38:253929:err:fi_debug:debug_logs:1:655871570871809: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:23:38:253770:info:fi_debug:debug_logs:1:655871570871809: Updating REP entry 296
OIFTL3:VL10/2. OIFTAny:VL4294967295/4294967040. F:1 L:4294967295
May 29 10:23:38:253694:err:fi_debug:debug_logs:1:655871570871809: Suppressed 1 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 29 10:23:20:080353:err:fi_debug:debug_logs:1:654557310879233: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:23:20:080191:info:fi_debug:debug_logs:1:654557310879233: Updating REP entry 295
OIFTL3:VL20/1. OIFTAny:VL4294967295/4294967040. F:1 L:4294967295
May 29 10:23:20:080114:err:fi_debug:debug_logs:1:654557310879233: Suppressed 7 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 29 10:23:11:414297:err:fi_debug:debug_logs:1:85899345921: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 29 10:23:11:413635:info:fi_debug:debug_logs:1:85899345921: Cleanup Ended : 2021 May 29 09:23:10
May 29 10:23:11:412905:info:fi_debug:debug_logs:1:85899345921: Cleanup Started : 2021 May 29 09:23:10
May 29 10:23:01:068640:info:fi_debug:debug_logs:1:7152232944370432: PIMv4-RP.VRF1: processing C-RP-adv
from 199.1.1.1. PrefCnt 1
May 29 10:23:01:068520:info:fi_debug:debug_logs:1:7152232944370432: PIMv4-RP.VRF1: Looping C-RP-Adv msg
from 199.1.1.1 back to elected BSR (me)
```

debug ip pimsm-snoop

describes the debug commands used for troubleshooting issues related to the IPv4 Protocol Independent Multicast Sparse mode (PIM-SM) snoop configurations.

Syntax

```
debug ip pimsm-snoop [ add-del-oif | all | clear | control-source | error | fsm | group | join-prune | physical-port | show | source |  
stacktrace | timer | vlan]
```

Parameters

add-del-oif

Displays debugs related to the addition and deletion of outbound interfaces (OIFs) in Mcache.

all

Enables all PIM-SM snoop related debugs.

clear

Clears all PIM-SM snoop related debug settings.

control-source

Displays PIM-SM snooping related debug information for the specified control source address

error

Monitors error messages related to PIM-SM snooping.

fsm

Enables debugging of Finite State Machine (FSM) transactions.

group

Displays PIM-SM snooping information for a specific group.

join-prune

Monitors PIM-SM snoop join and prune messages.

physical-port

Displays information of PIM-SM physical ports that are connected.

show

Displays all PIM-SM snoop related debug settings..

source

Displays PIM-SM snooping related debug information for the specified server source address.

stacktrace

Displays debug messages accompanied by call stack dump.

timer

Enables PIM-SM snoop timer debugging.

vlan

Enables PIM-SM snoop debugging for a particular VLAN.

Modes

Privileged EXEC mode

Examples

```
device(debug ip pimsm-snoop source 10.27.27.5
device# pim_snoop join (10.27.27.5 228.228.0.1), from e1/1/12
pim_snoop join (10.27.27.5 228.228.0.2), from e1/1/12
pim_snoop join (10.27.27.5 228.228.0.3), from e1/1/12
PIM from 10.27.27.2, vlan 275, port 1/1/12: Src=10.27.27.5 with 0 JOIN with 0
PRUNE
pim_snoop prune 1/1/12 from (10.27.27.5, 228.228.0.1), pim_snoop prune
1/1/12 from (10.27.27.5, 228.228.0.2), pim_snoop prune 1/1/12 from
(10.27.27.5, 228.228.0.3), PIM from 10.27.27.2, vlan 275, port 1/1/12:
Src=10.27.27.5 with 0 JOIN with 3 PRUNE, 1st Grp=228.228.0.1
pim_snoop join (10.27.27.5 228.228.0.1), from e1/1/12
pim_snoop join (10.27.27.5 228.228.0.2), from e1/1/12
pim_snoop join (10.27.27.5 228.228.0.3), from e1/1/12
PIM from 10.27.27.2, vlan 275, port 1/1/12: Src=10.27.27.5 with 0 JOIN with 0
PRUNE
```

History

Release version	Command history
	This command was introduced.
	This command was modified to...

debug ip ssh

activates the SSH debugging.

Syntax

debug ip ssh

no debug ip ssh

Modes

Privileged EXEC mode

Examples

```
device# debug ip ssh
SSH: debugging is on
device(config)#SSH: Incoming connection request received
SSH: ssh_get_free_session_id: ssh.client[0].in_use is 0
SSH: Client session (0) established
SSH: Outgoing connection is ready
ShtcpConnectionStatus[0]: connection established
SSH:ShtcpSend[0]: eSendComplete: the string length [24] !
ShtcpSendStatus[0]: eSendComplete
SSH: Outgoing connection is ready
SSH: Data is ready to receive
ShtcpReceiveStatus[0]: the string length [47]
SSH:ShtcpSend[0]: eSendComplete: the string length [216] !
ShtcpSendStatus[0]: eSendComplete
SSH: Outgoing connection is ready
SSH: Data is ready to receive
ShtcpReceiveStatus[0]: the string length [464]
```

debug ip sync

Displays debugging information about IP synchronization and faults in synchronization.

Syntax

```
debug ip sync[arpip-address|arp-all|cacheip-address|cache-all|default-route|download|next-hopredownload|routeip-subnet|route-all|show|stats[show] ]
```

```
no debug ip sync[arpip-address|arp-all|cacheip-address|cache-all|default-route|download|next-hopredownload|routeip-subnet|route-all|show|stats[show] ]
```

Parameters

arpip-address

Monitors ARP synchronisation, matches with the IP address of the ARP entry.

arp-all

Monitors all ARP synchronization.

cacheip-address

Monitors IP cache synchronization, matches with the cache IP address.

cache-all

Monitors all IP cache synchronization.

default-route

Monitors default IP route synchronization.

download

Monitors the activity during download.

next-hop

Monitors next-hop synchronization.

redownload

Monitors the activity during redownload.

routeip-subnet

Monitors IP route synchronization, matches with the IP address or IP subnet mask.

route-all

Monitors all IP route synchronization.

show

Displays all IP synchronization debug information.

stats

Displays IP tables and synchronization information.

stats show

Displays synchronization statistics for IP tables.

Modes

Privileged EXEC mode

Examples

```
device# debug ip sync
device(config-vif-11)# ND6 add sync: sent ip:2001:DB8::10 mac:none state:INCOMP
port:ve 12 vlan:12 isR:0 to all other units
ND6 add sync: sent ip:2001:DB8::10 mac:0000.0062.9f2d state:REACH port:e 3/3/1
vlan:12 isR:0 to all other units
ND6 add sync: sent ip:2001:DB8::10 mac:0000.0062.9f2d state:STALE port:e 3/3/1
vlan:12 isR:0 to all other units
```

debug ip tcp

Display debugging information about the Transmission Control Protocol (TCP) transactions.

Syntax

debug ip tcp
no debug ip tcp

Modes

Privileged EXEC mode

Examples

```

device# debug ip tcp 2001:DB8::192:111:101:25
TCP: ipv6 address 2001:DB8::192:111:101:25 debugging is on
Debug: Feb 11 10:46:57 TCP: sent packet (len=41) 2001:DB8::192:111:101:111:8197 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:18c2,seqn:11211247,ackn:835929143
Debug: Feb 11 10:46:57 TCP: sent packet (len=41) 2001:DB8::192:111:101:111:8197 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:1,hlen:5,chksum:14ac,seqn:11211268,ackn:835929143
Debug: Feb 11 10:46:57 TCP: rcvd packet (len=20) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8197
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:3bfa,seqn:835929143,ackn:11211268
Debug: Feb 11 10:46:57 TCP: rcvd packet (len=20) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8197
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:3bf9,seqn:835929143,ackn:11211290
Debug: Feb 11 10:46:57 TCP: rcvd packet (len=20) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8197
packet:
syn:0,ack:1,rst:0,fin:1,hlen:5,chksum:3bce,seqn:835929143,ackn:11211290
Debug: Feb 11 10:46:57 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8197 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:1bce,seqn:11211290,ackn:835929144
Debug: Feb 11 10:47:05 TCP: sent packet (len=24) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet: syn:1,ack:0,rst:0,fin:0,hlen:6,chksum:26f,seqn:4002716695,ackn:0
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=24) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:1,ack:1,rst:0,fin:0,hlen:6,chksum:17a4,seqn:2607451983,ackn:4002716696
Debug: Feb 11 10:47:05 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:ef48,seqn:4002716696,ackn:2607451984
Debug: Feb 11 10:47:05 TCP: sent packet (len=75) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:17de,seqn:4002716696,ackn:2607451984
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=20) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:2f49,seqn:2607451984,ackn:4002716751
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=57) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:fc84,seqn:2607451984,ackn:4002716751
Debug: Feb 11 10:47:05 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:ef11,seqn:4002716751,ackn:2607452021
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=39) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:2af6,seqn:2607452021,ackn:4002716751
Debug: Feb 11 10:47:05 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:ef11,seqn:4002716751,ackn:2607452040
Debug: Feb 11 10:47:05 TCP: sent packet (len=39) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:eabe,seqn:4002716751,ackn:2607452040
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=20) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:2f11,seqn:2607452040,ackn:4002716770

```

Debug Commands H - P

debug ip tcp

```
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=108) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:aa71,seqn:2607452040,ackn:4002716770
Debug: Feb 11 10:47:05 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:eec6,seqn:4002716770,ackn:2607452128
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=39) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:2a8b,seqn:2607452128,ackn:4002716770
Debug: Feb 11 10:47:05 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:eec6,seqn:4002716770,ackn:2607452147
Debug: Feb 11 10:47:05 TCP: rcvd packet (len=108) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:80c6,seqn:2607452147,ackn:4002716770
Debug: Feb 11 10:47:05 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:eec6,seqn:4002716770,ackn:2607452235
Debug: Feb 11 10:47:06 TCP: rcvd packet (len=108) 2001:DB8::192:111:101:25:179 ->
2001:DB8::192:111:101:111:8178
packet:
syn:0,ack:1,rst:0,fin:0,hlen:5,chksum:cd4a,seqn:2607452235,ackn:4002716770
Debug: Feb 11 10:47:06 TCP: sent packet (len=20) 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:17
```

debug ip tcp driver

Activates the TCP driver events debugging.

Syntax

debug ip tcp driver

no debug ip tcp driver

Modes

Privileged EXEC mode

Examples

```
device# debug ip tcp driver
TCP: driver debugging is on
```

debug ip tcp memory

Activates the TCP memory debugging.

Syntax

debug ip tcp memory

no debug ip tcp memory

Modes

Privileged EXEC mode

Examples

```
device# debug ip tcp memory  
TCP: memory debugging is on
```

debug ip tcp packet

Activates the TCP packets debugging.

Syntax

debug ip tcp packet

no debug ip tcp packet

Modes

Privileged EXEC mode

Examples

```
device# debug ip tcp packet
TCP: packet debugging is on
```

debug ip tcp sack

Activates the TCP Selective Acknowledgment (SACK) debugging.

Syntax

debug ip tcp sack

no debug ip tcp sack

Modes

Privileged EXEC mode

Examples

```
device# debug ip tcp sack
TCP: sack debugging is on
```

debug ip tcp transactions

Activates the TCP transactions debugging.

Syntax

debug ip tcp transactions

no debug ip tcp transactions

Modes

Privileged EXEC mode

Examples

```
device# debug ip tcp transactions
TCP: transactions debugging is on
TCP: transactions debugging is on
Debug: Feb 11 10:47:39 TCP: 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179: state change ESTABLISHED -> FIN-WAIT-1
Debug: Feb 11 10:47:39 TCP: sending FIN to 2001:DB8::192:111:101:25 port 179
Debug: Feb 11 10:47:39 TCP: FIN to 2001:DB8::192:111:101:111 port 8178 acked
Debug: Feb 11 10:47:39 TCP: 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179: state change FIN-WAIT-1 -> FIN-WAIT-2
Debug: Feb 11 10:47:39 TCP: 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179: state change FIN-WAIT-2 -> TIME-WAIT
Debug: Feb 11 10:47:39 TCP: FIN processed
Debug: Feb 11 10:47:39 TCP: 2001:DB8::192:111:101:111:8178 ->
2001:DB8::192:111:101:25:179: state change TIME-WAIT -> CLOSED
Debug: Feb 11 10:47:39 TCP: TCB 14440934 destroyed
Debug: Feb 11 10:47:58 TCP: 2001:DB8::192:111:101:111:8064 ->
2001:DB8::192:111:101:25:179: state change CLOSED -> SYN-SENT
Debug: Feb 11 10:47:58 TCP: connected to 2001:DB8::192:111:101:111 port 8064
advertising MSS 1436
Debug: Feb 11 10:47:58 TCP: connection to 10.146.1.17 port 179 received MSS 1436
MSS is 1436
Debug: Feb 11 10:47:58 TCP: 2001:DB8::192:111:101:111:8064 ->
2001:DB8::192:111:101:25:179: state change SYN-SENT -> ESTABLISHED
```

debug ip udp

Activates the UDP debugging.

Syntax

debug ip udp

no debug ip udp

Modes

Privileged EXEC mode

Examples

```
device# debug ip udp
UDP: debugging is on
```

debug ip vrrp packet

displays debugging information of any VRRP or VRRP-E packets within the device.

Syntax

debug ip vrrp packet

no debug ip vrrp packet

Modes

Privileged EXEC mode

Examples

```
device# debug ip vrrp packet
VRRP: packet debugging is on
VRRP (IPv6): send advertise! ver:3 type:1 vrid:100 pri:255 num of ip:1 adv:100
chk:44853
Num of ip addr 1
2000::7:1
VRRP (IPv4): rcvd packet! ver:2 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:1
chk:52198
Num of ip addr 1 10.10.10.2 from sender 10.10.10.2
VRRP (IPv6): rcvd packet! ver:3 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:100
chk:53518
Num of ip addr 1
fe80::7:2 from sender 2000::7:2
VRRP (IPv6): rcvd packet! ver:3 type:1 vrid:11 pri:255 #ip:1 aut:0 adv:200
chk:53417
Num of ip addr 1
fe80::8:2 from sender ::
```

debug ip vrrp events

Displays debugging information of VRRP events only within the device.

Syntax

debug ip vrrp events

no debug ip vrrp events

Modes

Privileged EXEC mode

Examples

```
device# debug ip vrrp events
VRRP: events debugging is on
[44fd]VRRP (IPv4): 10.10.10.1 transit to master! IP addr 10.10.10.2 vrid 10, pri
100
[44fd]VRRP (IPv6): fe80::7:1 transit to master! IP addr fe80::7:1 vrid 10, pri 100
[4511]VRRP (IPv6): fe80::8:1 transit to master! IP addr fe80::8:1 vrid 11, pri 255
```

debug ip vrrp packet v4

displays debugging information of VRRP or VRRP-E packets specific to IPv4 within the device.

Syntax

debug ip vrrp packet v4

no debug ip vrrp packet v4

Modes

Privileged EXEC mode

Examples

```
device# debug ip vrrp packet v4
VRRP (IPv4): packet debugging is on
VRRP (IPv4): rcvd packet! ver:2 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:1 chk:52198
Num of ip addr 1
10.10.10.2 from sender 10.10.10.2
VRRP (IPv4): rcvd packet! ver:2 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:1 chk:52198
Num of ip addr 1
10.10.10.2 from sender 10.10.10.2
VRRP (IPv4): rcvd packet! ver:2 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:1 chk:52198
Num of ip addr 1
10.10.10.2 from sender 10.10.10.2
```

debug ip vrrp packet v6

Displays debugging information of VRRP or VRRP-E packets specific to IPv6 within the device.

Syntax

debug ip vrrp packet v6

no debug ip vrrp packet v6

Modes

Privileged EXEC mode

Examples

```
device# debug ip vrrp packet v6
VRRP (IPv6): packet debugging is on
VRRP (IPv6): rcvd packet! ver:3 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:100
chk:53518
Num of ip addr 1
fe80::7:2 from sender 2000::7:2
VRRP (IPv6): rcvd packet! ver:3 type:1 vrid:11 pri:255 #ip:1 aut:0 adv:200
chk:53417
Num of ip addr 1
fe80::8:2 from sender ::
VRRP (IPv6): send advertise! ver:3 type:1 vrid:100 pri:255 num of ip:1 adv:100
chk:44853
Num of ip addr 1
2000::7:1
VRRP (IPv6): rcvd packet! ver:3 type:1 vrid:10 pri:255 #ip:1 aut:0 adv:100
chk:53518
Num of ip addr 1
fe80::7:2 from sender 2000::7:2
10.10.10.2 from sender 10.10.10.2
```

debug ip vrrp vrid

Filters VRRP or VRRP-E debugging using a virtual router identifier (VRID).

Syntax

```
debug ip vrrp vrid decimal
```

```
no debug ip vrrp vrid
```

Parameters

decimal

Specifies the VRID.

Modes

Privileged EXEC mode

Examples

```
device# debug ip vrrp vrid 100  
Debug VRID: 100 for both IPv4 and IPv6 instances
```

debug ip web

Activates the web debugging.

Syntax

debug ip web

no debug ip web

Modes

Privileged EXEC mode

Examples

```
device# debug ip web  
WEB: debugging is on
```

debug ip web-ssl

Activates web Secured Socket Layer (SSL) debugging.

Syntax

debug ip web-ssl

no debug ip web-ssl

Modes

Privileged EXEC mode

Usage Guidelines

The no form of the command deactivates web SSL debugging.

Examples

```
device# debug ip web-ssl  
WEB SSL: debugging is on
```

debug ipsec all

Displays all debugging information related to IPsec operation.

Syntax

debug ipsec all

no debug ipsec all

Modes

Privileged EXEC mode

Examples

```
device# debug ipsec all
IPSec: all debugging is on
device(config-ospf6-router)# no area 0 auth ipsec spi 400 esp sha1
abcef12345678901234fedcba098765432109876IPSEC,SA: ipipsec_pfkeyv2_input() ::
receiving 'DELETE' command
IPSEC,SA: Removing SA: ESP in spi=0x190 dst=FE80::
IPSEC,Policy: Removing flow [input use 'prot=OSPF src=FE80::/10:0 dst=::/0:0' ->
SA: ESP in spi=0x190 dst=FE80::] : ok
IPSEC,SA: ipipsec_pfkeyv2_input() :: succeeded
```

debug ipsec esp

Enables debugging of Encapsulating Security Payload (ESP)

Syntax

debug ipsec esp

no debug ipsec esp

Modes

Privileged EXEC mode

Examples

```
device# debug ipsec esp
IPSec: esp debugging is on
device(config-ospf6-router)# Debug: Jan 1 02:03:27 IPSEC,ESP: decrypt ok, seq=0
(SA: ESP in spi=0x190 dst=FE80::)
Debug: Jan 1 02:03:27 IPSEC,ESP: decrypt ok, seq=0 (SA: ESP in spi=0x190
dst=FE80::)
Debug: Jan 1 02:03:36 IPSEC,ESP: decrypt ok, seq=0 (SA: ESP in spi=0x190
dst=FE80::)
Debug: Jan 1 02:03:36 IPSEC,ESP: decrypt ok, seq=0 (SA: ESP in spi=0x190
dst=FE80::)
Debug: Jan 1 02:03:45 IPSEC,ESP: decrypt ok, seq=0 (SA: ESP in spi=0x190
dst=FE80::)
Debug: Jan 1 02:03:45 IPSEC,ESP: decrypt ok, seq=0 (SA: ESP in spi=0x190
dst=FE80::)
```

debug ipsec in

Enables the display of debugging information related to inbound OSPFv3 packets with IPsec.

Syntax

debug ipsec in

no debug ipsec in

Modes

Privileged EXEC mode

Examples

```
device# debug ipsec in
IPSec: in debugging is on
device(config-ospf6-router)# Debug: Jan 1 02:04:15 IPSEC,IN: ESP spi=400 (pkt
'ESP FE80:: -> FE80::') payloadlength =64
Debug: Jan 1 02:04:15 IPSEC,IN: Incoming packet matches Policy : input use
'prot=OSPF src=FE80::/10:0 dst::/0:0' -> SA: ESP in spi=0x190 dst=FE80::
Debug: Jan 1 02:04:15 IPSEC,IN: ESP spi=400 (pkt 'ESP FE80:: -> FE80::')
payloadlength =64
Debug: Jan 1 02:04:15 IPSEC,IN: Incoming packet matches Policy : input use
'prot=OSPF src=FE80::/10:0 dst::/0:0' -> SA: ESP in spi=0x190 dst=FE80::
Debug: Jan 1 02:04:26 IPSEC,IN: ESP spi=400 (pkt 'ESP FE80:: -> FE80::')
payloadlength =64
Debug: Jan 1 02:04:26 IPSEC,IN: Incoming packet matches Policy : input use
'prot=OSPF src=FE80::/10:0 dst::/0:0' -> SA: ESP in spi=0x190 dst=FE80::
Debug: Jan 1 02:04:26 IPSEC,IN: ESP spi=400 (pkt 'ESP FE80:: -> FE80::')
payloadlength =64
Debug: Jan 1 02:04:26 IPSEC,IN: Incoming packet matches Policy : input use
'prot=OSPF src=FE80::/10:0 dst::/0:0' -> SA: ESP in spi=0x190 dst=FE80::
Debug: Jan 1 02:04:36 IPSEC,IN: ESP spi=400 (pkt 'ESP FE80:: -> FE80::')
payloadlength =64
Debug: Jan 1 02:04:36 IPSEC,IN: Incoming packet matches Policy : input use
'prot=OSPF src=FE80::/10:0 dst::/0:0' -> SA: ESP in spi=0x190 dst=FE80::
Debug: Jan 1 02:04:36 IPSEC,IN: ESP spi=400 (pkt 'ESP FE80:: -> FE80::')
payloadlength =64
Debug: Jan 1 02:04:36 IPSEC,IN: Incoming packet matches Policy : input use
'prot=OSPF src=FE80::/10:0 dst::/0:0' -> SA: ESP in spi=0x190 dst=FE80::
```

debug ipsec out

Enables the display of debugging information related to outbound OSPFv3 packets with IPsec.

Syntax

debug ipsec out

no debug ipsec out

Modes

Privileged EXEC mode

Examples

```
device# debug ipsec out
IPSec: out debugging is on
device(config-ospf6-router)# Debug: Jan 1 02:04:55 IPSEC,OUT: Matching Flow:
output use 'prot=OSPF src=FE80::/10:0 dst=::/0:0' -> SA: ESP out spi=0x190 dst=::
Debug: Jan 1 02:04:55 IPSEC,OUT: SA ESP out spi=0x190 dst=:: payloadlength =64
Debug: Jan 1 02:04:56 IPSEC,OUT: OSPF FE80:: -> FE80::, payloadlength =40
Debug: Jan 1 02:04:56 IPSEC,OUT: OSPF FE80:: -> FE80::, payloadlength =40
Debug: Jan 1 02:05:06 IPSEC,OUT: Matching Flow: output use 'prot=OSPF
src=FE80::/10:0 dst=::/0:0' -> SA: ESP out spi=0x190 dst=::
Debug: Jan 1 02:05:06 IPSEC,OUT: SA ESP out spi=0x190 dst=:: payloadlength =64
Debug: Jan 1 02:05:07 IPSEC,OUT: OSPF FE80:: -> FE80::, payloadlength =40
Debug: Jan 1 02:05:07 IPSEC,OUT: OSPF FE80:: -> FE80::, payloadlength =40
Debug: Jan 1 02:05:15 IPSEC,OUT: Matching Flow: output use 'prot=OSPF
src=FE80::/10:0 dst=::/0:0' -> SA: ESP out spi=0x190 dst=::
Debug: Jan 1 02:05:15 IPSEC,OUT: SA ESP out spi=0x190 dst=:: payloadlength =64
Debug: Jan 1 02:05:16 IPSEC,OUT: OSPF FE80:: -> FE80::, payloadlength =40
Debug: Jan 1 02:05:16 IPSEC,OUT: OSPF FE80:: -> FE80::, payloadlength =40
```

debug ipsec policy

Enables the display of debugging information for IPsec policy.

Syntax

debug ipsec policy
no debug ipsec policy

Modes

Privileged EXEC mode

Examples

```
device# debug ipsec policy
IPSec: policy debugging is on
device(config-ospf6-router)#no area 0 auth ipsec spi 400 esp sha1
abcef12345678901234fedcba098765432109876
Debug: Jan 1 01:57:05 IPSEC,Policy: Removing flow [input use 'prot=OSPF
src=FE80::/10:0 dst=::/0:0' -> SA: ESP in spi=0x190 dst=FE80::] : ok
device(config-ospf6-router)#area 0 auth ipsec spi 400 esp sha1
abcef12345678901234fedcba098765432109876
Debug: Jan 1 01:57:26 IPSEC,Policy: Creating flow [input use 'prot=OSPF
src=FE80::/10:0 dst=::/0:0' -> SA: ESP in spi=0x190 dst=FE80::] : ok
device(config-ospf6-router)#Debug: Jan 1 02:02:21 IPSEC,Policy: Creating flow
[output use 'prot=OSPF src=FE80::/10:0 dst=::/0:0' -> SA: ESP out spi=0x190
dst=:] : ok
```

debug ipv6

Enables the collection of information about IPv6 configurations for troubleshooting.

Syntax

```
debug ipv6address cache icmp mld nd packet ra
```

Parameters

<i>address</i>	The IPv6 address.
<i>cache</i>	The IPv6 cache entry.
<i>icmp</i>	The Internet Control Message Protocol version 6 (ICMPv6) address.
<i>mld</i>	The Multicast Listener Discovery (MLD) protocol activity.
<i>nd</i>	The neighbor discovery.
<i>packet</i>	The IPv6 packet.
<i>ra</i>	The router address.

Modes

Privileged EXEC mode

debug ipv6 dhcp relay

Displays debug information related to Dynamic Host Configuration Protocol for IPv6 (DHCPv6) relay agent.

Syntax

debug ipv6 dhcp relay

no debug ipv6 dhcp relay

Modes

Privileged EXEC mode

Examples

The following output will be displayed when you enable the DHCPv6 relay agent on the Ethernet interface 8/2.

```
device# debug ipv6 dhcp relay
DHCP6: relay debugging is on
device# Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a-
>fc00:b000:cade::2]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a1]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a2]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a3]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a4]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a5]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a6]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a7]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a8]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::a9]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::aa]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::ab]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::ac]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::ad]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::ae]
Debug: Dec  9 11:15:20 DHCP6: DHCP6 relay-forward message sent [fc00:b000:cade::a->fc00:b000:cade::af]
```

debug ipv6 mld

Displays the debugging information about the received and sent packets of the Multicast Listening Discovery (MLD).

Syntax

```
debug ipv6 mld[event | ipc | profile | ifname[ethernetunit/slot/port | laglag-id | veve-num]]
```

```
no debug ipv6 mld[event | ipc | profile | ifname[ethernetunit/slot/port | laglag-id | veve-num]]
```

Parameters

- event**
Enables debugging of all infrastructure event and callback handling.
- ipc**
Debugs inter-process communication between MP and LP.
- profile**
Enables MLD profile debugging.
- ifname**
Displays matching in/out interface details.
- ethernetunit/slot/port**
Specifies the physical interface.
- laglag-id**
Specifies the LAG interface.
- veve-num**
Specifies the virtual interface.

Modes

Privileged EXEC mode

Examples

The following examples enables debugging of all infrastructure events.

```
device# debug ipv6 mld event
May 28 09:29:35:301853:info:fi_debug:debug_logs:1:74650826573313: MLD.VRF0.EVT: - Started FSM timer for
255 seconds
May 28 09:29:35:301655:info:fi_debug:debug_logs:1:74650826573313: MLD.VRF0.EVT: Rx packet is valid.
Processing packet
May 28 09:29:35:301579:err:fi_debug:debug_logs:1:74650826573313: Suppressed 1 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 28 09:29:30:767894:err:fi_debug:debug_logs:1:74294344287745: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 28 09:29:30:766798:info:fi_debug:debug_logs:1:74294344287745: MLD.VRF0.EVT: - Started FSM timer for
260 seconds
May 28 09:29:30:765631:info:fi_debug:debug_logs:1:74294344287745: MLD.VRF0.EVT: Rx packet is valid.
Processing packet
May 28 09:29:30:765555:err:fi_debug:debug_logs:1:74294344287745: Suppressed 1 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 28 09:29:26:098315:err:fi_debug:debug_logs:1:587525756289792: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 28 09:29:26:096915:info:fi_debug:debug_logs:1:587525756289792: MLD.VRF0: Group ffile::5:1 EXCL mode
aged out on port 3/1/5. Moving to INCL
May 28 09:29:25:580841:info:fi_debug:debug_logs:1:0: Suppressed 1 times: MLD.VRF0.EVT: - Started timer
for ageing group membership ffile::5:1 on port v10/3/1/5 for 1 seconds
May 28 09:29:24:086440:info:fi_debug:debug_logs:1:585850719044352: MLD.VRF0.EVT: - Started timer for
ageing group membership ffile::5:1 on port v10/3/1/5 for 1 seconds
May 28 09:29:23:610291:info:fi_debug:debug_logs:1:73705933768193: MLD.VRF0.EVT: - Started FSM timer for
1 seconds
May 28 09:29:23:609357:info:fi_debug:debug_logs:1:73705933768193: MLD.VRF0.EVT: Rx packet is valid.
Processing packet
May 28 09:29:23:076566:info:fi_debug:debug_logs:1:585000315519744: MLD.VRF0: [ Port 2/1/45,v10 ]
General Query Timer expired. Sending Query version 1
```

The following examples displays debugging information about MLD interprocess communication (IPC) activities.

```
device# debug ipv6 mld ipc
May 28 09:28:18:736997:err:fi_debug:debug_logs:1:68904160331265: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 28 09:28:18:735277:info:fi_debug:debug_logs:1:68904160331265: MLD.VRF0.IPC: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Setting src list in EXCL mode
May 28 09:28:18:734878:info:fi_debug:debug_logs:1:68904160331265: MLD.VRF0.IPC: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Interface added to group. Chg 0
May 28 09:28:18:734439:info:fi_debug:debug_logs:1:68904160331265: MLD.VRF0.IPC: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Adding port"
```

The following enables MLD profile debugging.

```
device# debug ipv6 mld profile
Jun 22 13:51:14:621348:info:fi_debug:debug_logs:1:191784854488577: MLD.PROFILE: nreports: 202, nleave:
100, V1report:32ms, V2report: 0ms, V1Leave: 36ms
Jun 22 13:49:56:803603:info:fi_debug:debug_logs:1:185810554979841: MLD.PROFILE: nreports: 200, nleave:
0, V1report:32ms, V2report: 0ms, V1Leave: 0ms
Jun 22 13:49:47:002093:info:fi_debug:debug_logs:1:184668093679105: MLD.PROFILE: nreports: 100, nleave:
0, V1report:19ms, V2report: 0ms, V1Leave: 0ms
```

History

Release version	Command history
09.0.00	The following sub-options were introduced: event , ifname , ipc , and profile .

debug ipv6 mld add-del-oif

Enabled with the MLD `debug ipv6 mcache-source` or `debug ipv6 mcache-group` commands at the same time.

Syntax

```
debug ipv6 mld add-del-oif
```

```
no debug ipv6 mld add-del-oif
```

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld add-del-oif  
May 26 18:53:28:910108:info:fi_debug:debug_logs:1:8978740801439233: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp  
ffle::5:1 ] Action IS_EXCL (Srcs 0) ver 1 Static 0 SSM 0
```

Debug Commands H - P
debug ipv6 mld add-del-oif stack

debug ipv6 mld add-del-oif stack

Displays the MLD stack trace.

Syntax

debug ipv6 mld add-del-oif stack

no debug ipv6 mld add-del-oif stack

Modes

Privileged EXEC mode

Examples

```

device# debug ipv6 mld add-del-oif stack
device# debug ipv6 mld show
debug ip6 mld mcache-source 681D is enabled
debug ip6 mld add-del-oif stack is enabled
device# Debug: Sep 16 00:33:08 MLD Snoop: Create (0x0 0x252502) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 2064096C 206414A8 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 Add 7/1/17 to (0x0 0x252502) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20640EB4 20642100 208C0D68
2064217C 20641554 20732A14 202884C4 204C1EEC 204C2288 204C235C 204C2420 20569EF0
205F0474 2056E85C 205F23E8 5010 15B58 1AAF4
Debug: Sep 16 00:33:08 Add 3/1/12 to (0x0 0x252502) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20641588 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 MLD Snoop: Create (0x0 0x252503) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 2064096C 206414A8 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 Add 7/1/17 to (0x0 0x252503) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20640EB4 20642100 208C0D68
2064217C 20641554 20732A14 202884C4 204C1EEC 204C2288 204C235C 204C2420 20569EF0
205F0474 2056E85C 205F23E8 5010 15B58 1AAF4
Debug: Sep 16 00:33:08 Add 3/1/12 to (0x0 0x252503) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20641588 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 MLD Snoop: Create (0x0 0x252504) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 2064096C 206414A8 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 Add 7/1/17 to (0x0 0x252504) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20640EB4 20642100 208C0D68
2064217C 20641554 20732A14 202884C4 204C1EEC 204C2288 204C235C 204C2420 20569EF0
205F0474 2056E85C 205F23E8 5010 15B58 1AAF4
Debug: Sep 16 00:33:08 Add 3/1/12 to (0x0 0x252504) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20641588 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 MLD Snoop: Create (0x0 0x252500) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 2064096C 206414A8 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 Add 7/1/17 to (0x0 0x252500) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20640EB4 20642100 208C0D68
2064217C 20641554 20732A14 202884C4 204C1EEC 204C2288 204C235C 204C2420 20569EF0
205F0474 2056E85C 205F23E8 5010 15B58 1AAF4
Debug: Sep 16 00:33:08 Add 3/1/12 to (0x0 0x252500) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20641588 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 MLD Snoop: Create (0x0 0x252501) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 2064096C 206414A8 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4
Debug: Sep 16 00:33:08 Add 7/1/17 to (0x0 0x252501) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20640EB4 20642100 208C0D68
2064217C 20641554 20732A14 202884C4 204C1EEC 204C2288 204C235C 204C2420 20569EF0
205F0474 2056E85C 205F23E8 5010 15B58 1AAF4
Debug: Sep 16 00:33:08 Add 3/1/12 to (0x0 0x252501) vlan 1000
Debug: Sep 16 00:33:08 stack: 20C3DA54 20640AB8 20641588 20732A14 202884C4
204C1EEC 204C2288 204C235C 204C2420 20569EF0 205F0474 2056E85C 205F23E8 5010 15B58
1AAF4

```

debug ipv6 mld clear

Clears all the MLD debug settings..

Syntax

debug ipv6 mld clear

no debug ipv6 mld clear

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld show
debug ipv6 mld protocol query
debug ipv6 mld event
debug ipv6 mld ipc
debug ipv6 mld add-del-oif
debug ipv6 mld vrf SP_TN
device#debug ipv6 mld_clear
device#debug ipv6 mld show
```

debug ipv6 mld enable

Enables debugging of MLD configurations.

Syntax

`debug ipv6 mld enable`
`no debug ipv6 mld enable`

Modes

Privileged EXEC mode

Usage Guidelines

The no form of the command disables debugging of MLD configurations.

Examples

```
device# debug ipv6 mld enable  
debug ipv6 mld is enabled
```

debug ipv6 mld error

Displays error information related to MLD.

Syntax

debug ipv6 mld error

no debug ipv6 mld error

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld error
May 28 09:26:09:460070:info:fi_debug:debug_logs:1:0: Suppressed 1 times: MLD.VRF0.ERR: Not a
forwardable group-address ff02::5. Dropping Report
May 28 09:26:05:864307:info:fi_debug:debug_logs:1:59103044961793: MLD.VRF0.ERR: Not a forwardable group-
address ff02::5. Dropping Report
```

debug ipv6 mld group

Debugs the MLD group matching.

Syntax

```
debug ipv6 mld group ipv6addr
```

```
no debug ipv6 mld group ipv6addr
```

Parameters

ipv6addr

Specifies the address of the IPv6 route.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld add-del-oif
device#debug ipv6 mld group ff1e::5:1
device#Debug: May 28 14:43:44 MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp ff1e::5:1 ] Action IS_EXCL (Srcs 0)
ver 1 Static 0 SSM 0
Debug: May 28 14:43:44 MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp ff1e::5:1 ] New group added
Debug: May 28 14:43:44 MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp ff1e::5:1 ] New group-membership added
Debug: May 28 14:43:51 MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp ff1e::5:1 ] Action IS_EXCL (Srcs 0) ver 1
Static 0 SSM 0
Debug: May 28 14:44:24 MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp ff1e::5:1 ] Action IS_EXCL (Srcs 0) ver 1
Static 0 SSM 0"
```

debug ipv6 mld phy-port ethernet

Matches the input of the physical port.

Syntax

```
debug ipv6 mld phy-port ethernetstackid/slot/port
```

```
no debug ipv6 mld phy-port ethernetstackid/slot/port
```

Parameters

stackid/slot/port

Specifies the stack ID, slot number, and port number of a specific Ethernet port.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld add-del-oif
device#debug ipv6 mld phy-port e3/1/5
May 28 09:24:53:989993:err:fi_debug:debug_logs:1:0: Suppressed 1 times: mct-forw:local or peer rbridge
is incorrect, local rid 0, peer rid 0
May 28 09:24:49:822673:err:fi_debug:debug_logs:1:53412213294593: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 28 09:24:49:821071:info:fi_debug:debug_logs:1:53412213294593: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp
ffle::5:1 ] New group-membership added
May 28 09:24:49:820989:info:fi_debug:debug_logs:1:53412213294593: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp
ffle::5:1 ] New group added
May 28 09:24:49:820901:info:fi_debug:debug_logs:1:53412213294593: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp
ffle::5:1 ] Action IS_EXCL (Srcs 0) ver 1 Static 0 SSM 0
May 28 09:24:49:820824:err:fi_debug:debug_logs:1:53412213294593: Suppressed 1 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 28 09:24:45:097708:err:fi_debug:debug_logs:1:353570297742080: mct-forw:local or peer rbridge is
incorrect, local rid 0, peer rid 0
May 28 09:24:42:891899:info:fi_debug:debug_logs:1:52905407153665: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp
ffle::5:1 ] Action TO_INCL (Srcs 0) ver 1 Static 0 SSM 0
May 28 09:24:34:901445:info:fi_debug:debug_logs:1:52368536241665: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp
ffle::5:1 ] Action IS_EXCL (Srcs 0) ver 1 Static 0 SSM 0
May 28 09:24:32:358027:info:fi_debug:debug_logs:1:52170967746049: MLD.VRF0.FSM: [ Port 3/1/5,v10. Grp
ffle::5:1 ] Action TO_INCL (Srcs 0) ver 1 Static 0 SSM 0"
```

debug ipv6 mld protocol

Displays debugging information about the IPv6 MLD queries and reports transmitted and received.

Syntax

```
debug ipv6 mld protocol[query | report | stack]
```

```
no debug ipv6 mld protocol[query | report | stack]
```

Parameters

query

Displays the IPv6 MLD query.

report

Displays the IPv6 MLD report.

report

Displays the IPv6 MLD stack trace.

Modes

Privileged EXEC mode

Examples

The following is the sample output from the **debug ipv6 mld protocol query** command.

```
device# debug ipv6 mld protocol query
May 28 09:31:02:644302:info:fi_debug:debug_logs:1:668064983024384: MLD.VRF0: [ Port 3/1/5,v10. Grp
ff1e::5:1 ] Sent Grp-Qry Ver 1. ReTx 1(Cnt 1)
May 28 09:31:01:929747:info:fi_debug:debug_logs:1:81046032877057: MLD.VRF0: [ Port 3/1/5,v10. Grp ff1e::
5:1 ] Sent Grp-Qry Ver 1. ReTx 0(Cnt 0)
May 28 09:30:20:378051:info:fi_debug:debug_logs:1:632768941785856: MLD.VRF0: [ Port 3/1/5,v10. Grp
ff1e::5:1 ] Sent Grp-Qry Ver 1. ReTx 1(Cnt 1)
May 28 09:30:19:827178:info:fi_debug:debug_logs:1:77867757078017: MLD.VRF0: [ Port 3/1/5,v10. Grp ff1e::
5:1 ] Sent Grp-Qry Ver 1. ReTx 0(Cnt 0)
```

The following is the sample output from the **debug ipv6 mld protocol report** command.

```
device# debug ipv6 mld protocol report
May 28 09:32:42:322248:info:fi_debug:debug_logs:1:88463441397249: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ff1e::5:1
May 28 09:32:33:492347:info:fi_debug:debug_logs:1:87776246629889: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ff1e::5:1
```

Debug Commands H - P
debug ipv6 mld protocol

The following is the sample output from the **debug ipv6 mld protocol stack** command.

```
device# debug ipv6 mld protocol stack
May 28 09:33:48:828442:info:fi_debug:debug_logs:1:806332865184512: MLD.VRF0: [ Port lg1,v20 ] Sent
General Query version 1 using src fe80::629c:9fff:fecl:b8d0
May 28 09:33:48:828361:info:fi_debug:debug_logs:1:806332865184512: stack: 00546ee8 01123080 010def28
010eb60c 0011ab58 010e5e6c 011b0a08 0009ac30 0009babc 005c15f8 005c2998 011b177c b6cfaeb0 b6f01195
May 28 09:33:48:828280:err:fi_debug:debug_logs:1:806332865184512: Suppressed 1 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 28 09:33:42:798038:info:fi_debug:debug_logs:1:801346408153856: stack: 00546ee8 011238e8 010e3ba4
010eb698 0011ab58 010e5e6c 011b0a08 0009ac30 0009babc 005c15f8 005c2998 011b177c b6cfaeb0 b6f01195
May 28 09:33:42:266896:info:fi_debug:debug_logs:1:92895847646721: MLD.VRF0: [ Port 3/1/5,v10. Grp ffle::
5:1 ] Sent Grp-Qry Ver 1. ReTx 0(Cnt 0)
May 28 09:33:42:266783:info:fi_debug:debug_logs:1:92895847646721: stack: 00546ee8 011238e8 010f0ff8
01121b24 005c1f38 005c2998 011b177c b6cfaeb0 b6f01195
May 28 09:33:42:248896:info:fi_debug:debug_logs:1:92895847646721: MLD.VRF0.RCV: Type V1 Leave Port
3/1/5,v10 Grp ffle::5:1
May 28 09:33:42:248780:info:fi_debug:debug_logs:1:92895847646721: stack: 00546ee8 01121908 005c1f38
005c2998 011b177c b6cfaeb0 b6f01195
May 28 09:33:35:917030:info:fi_debug:debug_logs:1:92470645884417: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffle::5:1
May 28 09:33:35:916913:info:fi_debug:debug_logs:1:92470645884417: stack: 00546ee8 0112123c 005c1f38
005c2998 011b177c b6cfaeb0 b6f01195
May 28 09:33:34:797829:info:fi_debug:debug_logs:1:794740748452608: MLD.VRF0: [ Port 2/1/45,v10 ] Sent
General Query version 1 using src fe80::629c:9fff:fecl:b8d0
May 28 09:33:34:797746:info:fi_debug:debug_logs:1:794740748452608: stack: 00546ee8 01123080 010def28
010eb60c 0011ab58 010e5e6c 011b0a08 0009ac30 0009babc 005c15f8 005c2998 011b177c b6cfaeb0 b6f01195
May 28 09:33:34:797667:err:fi_debug:debug_logs:1:794740748452608: Suppressed 1 times: mct-forw:local or
peer rbridge is incorrect, local rid 0, peer rid 0
May 28 09:33:32:889617:info:fi_debug:debug_logs:1:92200062944769: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffle::5:1
May 28 09:33:32:889501:info:fi_debug:debug_logs:1:92200062944769: stack: 00546ee8 0112123c 005c1f38
005c2998 011b177c b6cfaeb0 b6f01195
```

debug ipv6 mld rx

Displays the IPv6 MLD packets received.

Syntax

debug ipv6 mld rx

no debug ipv6 mld rx

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld rx
device#debug ipv6 mld protocol
show log debug fi_debug all all
Jun 22 13:56:39:688858:info:fi_debug:debug_logs:1:337319821313537: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ff1e::5:1
Jun 22 13:56:30:047586:info:fi_debug:debug_logs:1:305549948225025: MLD.VRF0.RCV: Type V1 Leave Port
3/1/5,v10 Grp ff1e::5:1
```

debug ipv6 mld show

Displays the IPv6 MLD debug settings.

Syntax

```
debug ipv6 mld show
```

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld show
debug ipv6 mld protocol query
debug ipv6 mld event
debug ipv6 mld ipc
debug ipv6 mld add-del-oif
debug ipv6 mld vrf SP_TN
device#
```

debug ipv6 mld source

Displays the MLD related debug information for the specified source address.

Syntax

```
debug ipv6 mld source ipaddr
```

```
no debug ipv6 mld source ipaddr
```

Parameters

ipaddr

Specifies the IP address.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld source fe80::629c:9fff:fecl:b8d0
device#debug ipv6 mld protocol
Jun 22 14:02:22:616028:info:fi_debug:debug_logs:1:1466733011404289: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:02:17:604561:info:fi_debug:debug_logs:1:1450236042020353: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:02:09:448224:info:fi_debug:debug_logs:1:2515521075413760: MLD.VRF0: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Sent Grp-Qry Ver 1. ReTx 1(Cnt 1)
Jun 22 14:02:08:324605:info:fi_debug:debug_logs:1:1419642989970945: MLD.VRF0: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Sent Grp-Qry Ver 1. ReTx 0(Cnt 0)
Jun 22 14:02:08:324090:info:fi_debug:debug_logs:1:1419642989970945: MLD.VRF0.RCV: Type V1 Leave Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:02:06:921385:info:fi_debug:debug_logs:1:1415047374964225: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:01:59:052456:info:fi_debug:debug_logs:1:1389002693281281: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:01:54:312502:info:fi_debug:debug_logs:1:2502795087315712: MLD.VRF1: [ Port lg1,v21 ] Sent
General Query version 1 using src fe80::629c:9fff:fecl:b8d0
Jun 22 14:01:54:308156:info:fi_debug:debug_logs:1:2502795087315712: MLD.VRF0: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Sent Grp-Qry Ver 1. ReTx 1(Cnt 1)
Jun 22 14:01:53:839937:info:fi_debug:debug_logs:1:1371874363704833: MLD.VRF0: [ Port 3/1/5,v10. Grp
ffile::5:1 ] Sent Grp-Qry Ver 1. ReTx 0(Cnt 0)
Jun 22 14:01:53:839417:info:fi_debug:debug_logs:1:1371874363704833: MLD.VRF0.RCV: Type V1 Leave Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:01:53:288178:info:fi_debug:debug_logs:1:2501957568692992: MLD.VRF0: [ Port lg1,v20 ] Sent
General Query version 1 using src fe80::629c:9fff:fecl:b8d0
Jun 22 14:01:51:035084:info:fi_debug:debug_logs:1:1362678838724097: MLD.VRF0.RCV: Type V1 Report Port
3/1/5,v10 Grp ffile::5:1
Jun 22 14:01:48:282786:info:fi_debug:debug_logs:1:2497765680612096: MLD.VRF0: [ Port 3/1/5,v10 ] Sent
General Query version 1 using src fe80::629c:9fff:fecl:b8d0
```

debug ipv6 mld tx

Displays the IPv6 MLD packets transmitted..

Syntax

debug ipv6 mld tx

no debug ipv6 mld tx

Modes

Privileged EXEC mode

Examples

```
device#debug ipv6 mld tx
device#debug ipv6 mld protocol
Jun 22 13:52:42:308030:info:fi_debug:debug_logs:1:2043590068929280: MLD.VRF0: [ Port 3/1/5,v10. Grp
ffle::5:1 ] Sent Grp-Qry Ver 1. ReTx 1 (Cnt 1)
Jun 22 13:52:41:132541:info:fi_debug:debug_logs:1:198055506740737: MLD.VRF0: [ Port 3/1/5,v10. Grp
ffle::5:1 ] Sent Grp-Qry Ver 1. ReTx 0 (Cnt 0)
Jun 22 13:52:33:247743:info:fi_debug:debug_logs:1:2036073876161280: MLD.VRF1: [ Port 3/1/5,v11 ] Sent
General Query version 1 using src fe80::629c:9fff:fec1:b8d0
```

debug ipv6 mld vrf

Displays MLD related debug information for the specified VRF.

Syntax

```
debug ipv6 mld vrf vrf_name
```

```
no debug ipv6 mld vrf vrf_name
```

Parameters

vrf_name

Specifies the VRF name.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 mld vrf SP_TN
device#debug ipv6 mld protocol query
device#debug ipv6 mld event
device#debug ipv6 mld ipc
device#debug ipv6 mld add-del-oif
May 29 08:42:25:981956:info:fi_debug:debug_logs:1:199780403774977: MLD.VRF1.EVT: - Started FSM timer
for 256 seconds
May 29 08:42:25:981832:info:fi_debug:debug_logs:1:199780403774977: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Interface added to group. Chg 0
May 29 08:42:25:981732:info:fi_debug:debug_logs:1:199780403774977: MLD.VRF1.FSM: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Action IS_EXCL (Srcs 0) ver 1 Static 0 SSM 0
May 29 08:42:25:981607:info:fi_debug:debug_logs:1:199780403774977: MLD.VRF1.EVT: Rx packet is valid.
Processing packet
May 29 08:42:22:720141:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.EVT: - Started FSM timer
for 260 seconds
May 29 08:42:22:720057:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Setting src list in EXCL mode
May 29 08:42:22:719881:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Interface added to group. Chg 0
May 29 08:42:22:719500:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Adding port
May 29 08:42:22:719405:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.FSM: [ Port 3/1/5,v11. Grp
ffle::9:10 ] New group-membership added
May 29 08:42:22:719325:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.FSM: [ Port 3/1/5,v11. Grp
ffle::9:10 ] New group added
May 29 08:42:22:719241:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.FSM: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Action IS_EXCL (Srcs 0) ver 1 Static 0 SSM 0
May 29 08:42:22:719117:info:fi_debug:debug_logs:1:199531295671809: MLD.VRF1.EVT: Rx packet is valid.
Processing packet
May 29 08:42:20:928518:info:fi_debug:debug_logs:1:2126915049620224: MLD.VRF1.IPC: [ Port v11,v11. Grp
ffle::9:10 ] Interface deleted from group.Chg 1
May 29 08:42:20:928268:info:fi_debug:debug_logs:1:2126915049620224: MLD.VRF1.IPC: Deleting group entry
from GLB for ffile::9:10
May 29 08:42:20:927506:info:fi_debug:debug_logs:1:2126915049620224: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Deleting port
May 29 08:42:20:927419:info:fi_debug:debug_logs:1:2126915049620224: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Physical port deleted from group. Chg 1
May 29 08:42:20:927267:info:fi_debug:debug_logs:1:2126915049620224: MLD.VRF1: Group ffile::9:10 EXCL
mode aged out on port 3/1/5. Moving to INCL
May 29 08:42:19:938481:info:fi_debug:debug_logs:1:2126073236030208: MLD.VRF1.EVT: - Started timer for
ageing group membership ffile::9:10 on port v11/3/1/5 for 1 seconds
May 29 08:42:19:938364:info:fi_debug:debug_logs:1:2126073236030208: MLD.VRF1: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Sent Grp-Qry Ver 1. ReTx 1 (Cnt 1)
May 29 08:42:19:501616:info:fi_debug:debug_logs:1:199312252339713: MLD.VRF1.EVT: - Started FSM timer
for 1 seconds
May 29 08:42:19:501225:info:fi_debug:debug_logs:1:199312252339713: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Setting src list in EXCL mode
May 29 08:42:19:501095:info:fi_debug:debug_logs:1:199312252339713: MLD.VRF1.IPC: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Interface added to group. Chg 0
May 29 08:42:19:500999:info:fi_debug:debug_logs:1:199312252339713: MLD.VRF1: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Sent Grp-Qry Ver 1. ReTx 0 (Cnt 0)
May 29 08:42:19:500506:info:fi_debug:debug_logs:1:199312252339713: MLD.VRF1.FSM: [ Port 3/1/5,v11. Grp
ffle::9:10 ] Action TO_INCL (Srcs 0) ver 1 Static 0 SSM 0
May 29 08:42:19:500380:info:fi_debug:debug_logs:1:199312252339713: MLD.VRF1.EVT: Rx packet is valid.
Processing packet
```

debug ipv6 nd

Enables Neighbor Discovery (ND) debug logs and displays the debugging information about dropped Neighbor Solicitation (NS) and Neighbor Advertisement (NA) packets.

Syntax

```
debug ipv6 nd
```

```
no debug ipv6 nd
```

Modes

Privileged EXEC mode

Global configuration mode

Usage Guidelines

Examples

```
device(config)#debug ipv6 nd
ipv6: nd debugging is on
device(config)#ND Inspect: src-ip, src-mac mismatch, packet dropped rx-sip
2001:DB8::1 rx-smac 0000.0000.0066 inspect-ip 2001:DB8::1 inspect-mac
0000.0000.0088 vlan_id 2 vrf_id 0
device(config)#show ipv6 neighbor inspection statistics
Total number of ND Solicit received 4
Total number of ND Adevert received 4
Total number of ND dropped 6
```

debug ipv6 ospf ipsec

Displays information about IPsec events. This command can show if IPsec is actually providing its services to IPv6 OSPFv3. The following output shows success in the attempts to provide various IPsec services to OSPFv3.

Syntax

```
debug ipv6 ospf ipsec
```

```
no debug ipv6 ospf ipsec
```

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 ospf ipsec
OSPFv3: ipsec debugging is on
device(config-ospf6-router)# no area 0 auth ipsec spi 400 esp sha1
abcef12345678901234fedcba098765432109876Debug: Jan 1 02:22:09 OSPFv3:
ITC_AUTHENTICATION_CONFIG message received
Debug: Jan 1 02:22:09 OSPFv3: Auth timer started
Debug: Jan 1 02:22:09 OSPFv3: Key Rollover, for area 0.0.0.0, state change
NOT_ACTIVE->STARTED
Debug: Jan 1 02:22:09 OSPFv3: Key Rollover, for v9, state change
NOT_ACTIVE->STARTED
```

debug ipv6 ospf ism

Displays debug information about the interface state machine (ISM).

Syntax

debug ipv6 ospf ism

no debug ipv6 ospf ism

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 ospf ism
        OSPFv3: ism debugging is on
Debug: Dec  9 10:47:25 OSPFv3: ISM[14368]: InterfaceDown
Debug: Dec  9 10:47:25 OSPFv3: ISM[14368]: Status change BDR -> Down (Configured)
Debug: Dec  9 10:47:25 OSPFv3: ISM[14368]: {dr:7.0.0.3,bdr:1.0.0.1} -> {dr:0.0.0.0,bdr:0.0.0.0}
Debug: Dec  9 10:47:40 OSPFv3: ISM[14368]: InterfaceUp
Debug: Dec  9 10:47:40 OSPFv3: ISM[14368]: Status change Down -> Waiting (Priority > 0)
Debug: Dec  9 10:47:40 OSPFv3: ISM[14368]: Start Wait_Timer at 639966, 619070
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: BackupSeen
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: Status change Waiting -> DROther (BackupSeen:DR Election)
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: {dr:0.0.0.0,bdr:0.0.0.0} -> {dr:7.0.0.3,bdr:1.0.0.11}
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: NeighborChange
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: Status change DROther -> DROther (NeighborChange:DR Election)
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: NeighborChange
Debug: Dec  9 10:47:44 OSPFv3: ISM[14368]: Status change DROther -> DROther (NeighborChange:DR Election)
```

debug ipv6 ospf ism-events

Displays debug information about ISM events.

Syntax

debug ipv6 ospf ism-events

no debug ipv6 ospf ism-events

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf ism-events
        OSPFv3: ism-events debugging is on
Debug: Dec  9 10:53:04 OSPFv3: ISM[14368]: InterfaceDown
Debug: Dec  9 10:53:15 OSPFv3: interface (14367) cost change to 9 due to speed change
Debug: Dec  9 10:53:15 OSPFv3: ISM[14368]: InterfaceUp
Debug: Dec  9 10:53:15 OSPFv3: ISM[14368]: Start Wait_Timer at 643319, 622306
Debug: Dec  9 10:53:22 OSPFv3: ISM[14368]: BackupSeen
```

debug ipv6 ospf ism-status

Displays debug information about the status of ISM.

Syntax

debug ipv6 ospf ism-status

no debug ipv6 ospf ism-status

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf ism-status
        OSPFv3: ism-status debugging is on
Debug: Dec  9 10:55:38 OSPFv3: ISM[14368]: Status change DROther -> Down (Configured)
Debug: Dec  9 10:55:58 OSPFv3: ISM[14368]: Status change Down -> Waiting (Priority > 0)
Debug: Dec  9 10:56:01 OSPFv3: ISM[14368]: Status change Waiting -> DROther (BackupSeen:DR Election)
Debug: Dec  9 10:56:01 OSPFv3: ISM[14368]: {dr:0.0.0.0,bdr:0.0.0.0} -> {dr:1.0.0.11,bdr:1.0.0.11}
Debug: Dec  9 10:56:02 OSPFv3: ISM[14368]: Status change DROther -> DROther (NeighborChange:DR Election)
Debug: Dec  9 10:56:02 OSPFv3: ISM[14368]: {dr:1.0.0.11,bdr:1.0.0.11} -> {dr:7.0.0.3,bdr:1.0.0.11}
Debug: Dec  9 10:56:07 OSPFv3: ISM[14368]: Status change DROther -> DROther (NeighborChange:DR Election)
```

Debug Commands H - P
debug ipv6 ospf lsa

debug ipv6 ospf lsa

Displays LSAs.

Syntax

debug ipv6 ospf lsa

no debug ipv6 ospf lsa

Modes

Privileged EXEC mode

Global configuration mode

Examples

```

device# debug ipv6 ospf lsa
OSPFv3: lsa debugging is on
device(config-vif-9)#Debug: Jan 1 17:05:01 OSPFv3: LSA: Update Router-LSA for
area 0.0.0.0
Debug: Jan 1 17:05:01 OSPFv3: LSA: Create LSA Type :Router Id: 0 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:01 OSPFv3: LSA: Type: 8193 ID: 0 AdvRouter: 10.4.4.8, Supress
Updating
Debug: Jan 1 17:05:01 OSPFv3: LSA: Delete LSA Type :Router Id: 0.0.0.0 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:01 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Checking
Interface 644
Debug: Jan 1 17:05:01 OSPFv3: LSA Update Intra-Area-Prefix(Stub): include
5001::/64
Debug: Jan 1 17:05:01 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:01 OSPFv3: LSA: Type: 8201 ID: 0 AdvRouter: 10.4.4.8, Supress
Updating
Debug: Jan 1 17:05:01 OSPFv3: LSA: Delete LSA Type :IntraPrefix Id: 0.0.0.0
Advrouter: 10.4.4.8
Debug: Jan 1 17:05:01 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Area 0.0.0.0
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Header Type :Router Id: 0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: request Type =8193 ADvRtr =10.2.2.2
ID=0
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Header Type :IntraPrefix Id: 0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: request Type =8201 ADvRtr =10.2.2.2
ID=0
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Header Type :Link Id: 2052
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: request Type =8 ADvRtr =10.2.2.2
ID=2052
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :Router Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA HEADER Type :Router Id: 0.0.0.0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[418103392]: delayed ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA HEADER Type :IntraPrefix Id:
0.0.0.0 Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[418103392]: delayed ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :Link Id: 2052 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA HEADER Type :Link Id: 10.0.8.4
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit):Interface 644
is Stub
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Checking
Interface 644
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Stub): include
5001::/64
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA: Type: 8201 ID: 0 AdvRouter: 10.4.4.8, Supress
Updating
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :IntraPrefix Id: 0.0.0.0
Advrouter: 10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Area 0.0.0.0
Debug: Jan 1 17:05:02 OSPFv3: LSA[418103392]: delayed ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :Router Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Turnover type:Router Lsa Id:0.0.0.0
AdvRouter:10.2.2.2: Debug: Jan 1 17:05:02 OSPFv3: contents changed
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :Router Id: 0.0.0.0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[418103392]: delayed ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :Router Id: 0 Advrouter:

```

Debug Commands H - P

debug ipv6 ospf lsa

```
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: direct ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :Router Id: 0.0.0.0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Turnover type:IntraPrefix Lsa Id:0.0.0.0
AdvRouter:10.2.2.2: Debug: Jan 1 17:05:02 OSPFv3: contents changed
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :IntraPrefix Id: 0.0.0.0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[418103392]: delayed ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: direct ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :IntraPrefix Id: 0.0.0.0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: direct ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :IntraPrefix Id: 0.0.0.0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 0 Advrouter:
10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA[10.2.2.2]: direct ack
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :IntraPrefix Id: 0.0.0.0
Advrouter: 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA: Update Router-LSA for area 0.0.0.0
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :Router Id: 0 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA: Turnover type:Router Lsa Id:0.0.0.0
AdvRouter:10.4.4.8: Debug: Jan 1 17:05:02 OSPFv3: contents changed
Debug: Jan 1 17:05:02 OSPFv3: LSA: Delete LSA Type :Router Id: 0.0.0.0 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Network: Interface 644
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :Network Id: 644 Advrouter:
10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): Interface
644
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit):Checking Type
:Link Id 10.0.2.132: Adv Routr : 10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): 1
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): Prefix
5001::
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): including
5001::
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit):Checking Type
:Link Id 10.0.8.4: Adv Routr : 10.2.2.2
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): 1
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): Prefix
5001::
Debug: Jan 1 17:05:02 OSPFv3: LSA Update Intra-Area-Prefix(Transit): 5001:: is
Duplicate
Debug: Jan 1 17:05:02 OSPFv3: LSA: Create LSA Type :IntraPrefix Id: 19320
Advrouter: 10.4.4.8
Debug: Jan 1 17:05:02 OSPFv3: LSA: schedule flooding 10.2.2.2
```

debug ipv6 ospf lsa-flooding

Displays debug information about LSA flooding activity.

Syntax

debug ipv6 ospf lsa-flooding

no debug ipv6 ospf lsa-flooding

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf lsa-flooding
OSPFv3: lsa-flooding debugging is on
device(config)# ipv6 router ospf
device(config-ospf6-router)# redistribute connected
device(config-ospf6-router)# redistribute connected Debug: Jan 1 17:17:49
OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:17:49 OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:17:49 OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:17:49 OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:17:49 OSPFv3: LSA: schedule flooding 10.2.2.2
Debug: Jan 1 17:17:49 OSPFv3: LSA: schedule flooding 10.2.2.2
```

debug ipv6 ospf lsa-generation

Displays debug information about LSA generation.

Syntax

debug ipv6 ospf lsa-generation

no debug ipv6 ospf lsa-generation

Modes

Privileged EXEC mode

Global configuration mode

Examples

```

device# debug ipv6 ospf lsa-generation
OSPFv3: lsa-generation debugging is on
device(config-ospf6-router)# Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type
:Router Id: 0 Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :Router Id: 0.0.0.0 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 1 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.1
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 2 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.2
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 3 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.3
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 4 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.4
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 5 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.5
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :Router Id: 0 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :Router Id: 0.0.0.0 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 1 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.1
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 2 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.2
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 3 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.3
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 4 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.4
Advrouter: 10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Create LSA Type :ASExternal Id: 5 Advrouter:
10.4.4.8
Debug: Jan 1 18:53:55 OSPFv3: LSA: Delete LSA Type :ASExternal Id: 10.0.0.5 Advrouter: 10.4.4.8
  
```

debug ipv6 ospf lsa-install

Displays debug information about installed LSAs.

Syntax

debug ipv6 ospf lsa-install

no debug ipv6 ospf lsa-install

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf lsa-install
OSPFv3: lsa-install debugging is on
device(config-ospf6-router)# Debug: Jan 1 19:03:16 OSPFv3: LSA: Turnover
type:Router Lsa Id:0.0.0.0 AdvRouter:10.4.4.8: Debug: Jan 1 19:03:16 OSPFv3:
contents changed
Debug: Jan 1 19:03:59 OSPFv3: LSA: Turnover type:Router Lsa Id:0.0.0.0
AdvRouter:10.4.4.8: Debug: Jan 1 19:03:59 OSPFv3: contents changed
```

debug ipv6 ospf lsa-inter-area

Displays debug information about inter-area LSAs.

Syntax

debug ipv6 ospf lsa-inter-area

no debug ipv6 ospf lsa-inter-area

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf lsa-inter-area
OSPFv3: lsa-inter-area debugging is on
device(config-vif-7)# disable
device(config-vif-7)# enable
device(config-vif-7)# OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Installing in LSDB Inter Area Prefix LSA for area 0.0.0.0 and prefix
2001:DB8::/64
OSPFv3: Inter Area LSA not generated, route is in same area.
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, route is in same area.
OSPFv3: Installing in LSDB Inter Area Prefix LSA for area 10.0.0.1 and prefix
2001:DB8::/64
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, path type = External
OSPFv3: Inter Area LSA not generated, route is in same area.
shOSPFv3: Inter Area LSA not generated, route is in same area.
```

debug ipv6 ospf lsa-refresh

Displays LSA refresh information.

Syntax

debug ipv6 ospf lsa-refresh

no debug ipv6 ospf lsa-refresh

Modes

Privileged EXEC mode

Global configuration mode

Examples

```

device# debug ipv6 ospf lsa-refresh
OSPFv3: lsa-refresh debugging is on
device(config-ospf6-router)# Debug: Jan 1 19:01:39 OSPFv3: LSA: Update
Router-LSA for area 0.0.0.0
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Checking
Interface 644
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Interface 644
is down
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): No prefix to
advertise for Area 0.0.0.0
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Area 0.0.0.0
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Network: Interface 644 is not DR
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Transit):Interface 644
is not DR
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Checking
Interface 644
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Interface 644
is down
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): No prefix to
advertise for Area 0.0.0.0
Debug: Jan 1 19:01:39 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Area 0.0.0.0
Debug: Jan 1 19:01:44 OSPFv3: LSA: Update Router-LSA for area 0.0.0.0
Debug: Jan 1 19:02:42 OSPFv3: LSA: Update Router-LSA for area 0.0.0.0
Debug: Jan 1 19:02:42 OSPFv3: LSA: LSA Update AS-External: ID 10.0.0.6
Debug: Jan 1 19:02:42 OSPFv3: LSA: LSA Update AS-External: ID 10.0.0.7debug ip
Debug: Jan 1 19:02:42 OSPFv3: LSA: LSA Update AS-External: ID 10.0.0.8
Debug: Jan 1 19:02:42 OSPFv3: LSA: LSA Update AS-External: ID 10.0.0.9
Debug: Jan 1 19:02:42 OSPFv3: LSA: LSA Update AS-External: ID 10.0.0.10
Debug: Jan 1 19:02:42 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Checking
Interface 644
Debug: Jan 1 19:02:42 OSPFv3: LSA Update Intra-Area-Prefix(Stub): include
2001:DB8::/64
Debug: Jan 1 19:02:42 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Area 0.0.0.0
Debug: Jan 1 19:02:42 OSPFv3: LSA Update Link: Interface 644
Debug: Jan 1 19:02:46 OSPFv3: LSA Update Link: Interface 644
Debug: Jan 1 19:02:46 OSPFv3: LSA: Type: 8 ID: 644 AdvRouter: 10.4.4.8, Supress
Updating
Debug: Jan 1 19:02:46 OSPFv3: LSA Update Link: Interface 644
Debug: Jan 1 19:02:46 OSPFv3: LSA: Type: 8 ID: 644 AdvRouter: 10.4.4.8, Supress
Updating
Debug: Jan 1 19:02:47 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Checking
Interface 644
Debug: Jan 1 19:02:47 OSPFv3: LSA Update Intra-Area-Prefix(Stub): include
2001:DB8::/64
Debug: Jan 1 19:02:47 OSPFv3: LSA: Type: 8201 ID: 0 AdvRouter: 10.4.4.8, Supress
Updating
Debug: Jan 1 19:02:47 OSPFv3: LSA Update Intra-Area-Prefix(Stub): Area 0.0.0.0
Debug: Jan 1 19:02:47 OSPFv3: LSA: Update Router-LSA for area 0.0.0.0
Debug: Jan 1 19:02:47 OSPFv3: LSA: Type: 8193 ID: 0 AdvRouter: 10.4.4.8, Supress
  
```

debug ipv6 ospf nsm

Displays debug information about the neighbor state machine (NSM).

Syntax

debug ipv6 ospf nsm

no debug ipv6 ospf nsm

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf nsm
        OSPFv3: nsm debugging is on
Debug: Dec  9 11:08:20 OSPFv3: NSM[14689]: SendHello at 652364
Debug: Dec  9 11:08:21 OSPFv3: NSM[2.0.0.1, 14341]: HelloReceived at 652379, 631072
Debug: Dec  9 11:08:22 OSPFv3: NSM[14366]: SendHello at 652386
Debug: Dec  9 11:08:24 OSPFv3: NSM[14364]: SendHello at 652403
Debug: Dec  9 11:08:25 OSPFv3: NSM[14688]: SendHello at 652415
Debug: Dec  9 11:08:25 OSPFv3: NSM[14337]: SendHello at 652416
Debug: Dec  9 11:08:26 OSPFv3: NSM[14369]: SendHello at 652430
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.13, 14364]: HelloReceived at 652434, 631127
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.11, 14368]: HelloReceived at 652437, 631130
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.11]: Status change [Down]->[Init](HelloReceived)
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.11]: 2Way-Received
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.11]: Status change [Init]->[2-way](No Need Adjacency)
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.11]: AdjOK?
Debug: Dec  9 11:08:27 OSPFv3: NSM[1.0.0.11]: Status change [2-way]->[ExStart](Need Adjacency)
Debug: Dec  9 11:08:28 OSPFv3: NSM[1.0.0.14, 14366]: HelloReceived at 652446, 631139
Debug: Dec  9 11:08:28 OSPFv3: NSM[1.0.0.11, 14369]: HelloReceived at 652447, 631140
Debug: Dec  9 11:08:29 OSPFv3: NSM[14341]: SendHello at 652453
Debug: Dec  9 11:08:29 OSPFv3: NSM[14371]: SendHello at 652457
Debug: Dec  9 11:08:30 OSPFv3: NSM[1.0.0.12, 14371]: HelloReceived at 652461, 631153
Debug: Dec  9 11:08:30 OSPFv3: NSM[14689]: SendHello at 652464
Debug: Dec  9 11:08:30 OSPFv3: NSM[14368]: SendHello at 652468
Debug: Dec  9 11:08:30 OSPFv3: NSM[1.0.0.11]: NegotiationDone
```

debug ipv6 ospf nsm-events

Displays debug information about NSM events.

Syntax

debug ipv6 ospf nsm-events

no debug ipv6 ospf nsm-events

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf nsm-events
      OSPFv3: nsm-events debugging is on
Debug: Dec  9 11:10:59 OSPFv3: NSM[1.0.0.12, 14368]: HelloReceived at 653956, 632600
Debug: Dec  9 11:10:59 OSPFv3: NSM[1.0.0.11, 14368]: HelloReceived at 653956, 632600
Debug: Dec  9 11:11:00 OSPFv3: NSM[7.0.0.3, 14368]: HelloReceived at 653968, 632612
Debug: Dec  9 11:11:01 OSPFv3: NSM[2.0.0.1, 14341]: HelloReceived at 653971, 632615
Debug: Dec  9 11:11:01 OSPFv3: NSM[14364]: SendHello at 653974
Debug: Dec  9 11:11:01 OSPFv3: NSM[14368]: SendHello at 653980
Debug: Dec  9 11:11:02 OSPFv3: NSM[1.0.0.13, 14364]: HelloReceived at 653981, 632625
Debug: Dec  9 11:11:02 OSPFv3: NSM[14337]: SendHello at 653983
Debug: Dec  9 11:11:02 OSPFv3: NSM[1.0.0.11, 14369]: HelloReceived at 653984, 632628
Debug: Dec  9 11:11:02 OSPFv3: NSM[1.0.0.12, 14371]: HelloReceived at 653985, 632628
Debug: Dec  9 11:11:02 OSPFv3: NSM[14688]: SendHello at 653985
Debug: Dec  9 11:11:03 OSPFv3: NSM[14341]: SendHello at 653993
Debug: Dec  9 11:11:03 OSPFv3: NSM[14369]: SendHello at 653993
Debug: Dec  9 11:11:03 OSPFv3: NSM[1.0.0.14, 14366]: HelloReceived at 653996, 632640
Debug: Dec  9 11:11:05 OSPFv3: NSM[14689]: SendHello at 654011
Debug: Dec  9 11:11:06 OSPFv3: NSM[14371]: SendHello at 654025
Debug: Dec  9 11:11:07 OSPFv3: NSM[14366]: SendHello at 654038
```

debug ipv6 ospf nsm-status

Displays information about the status of NSM.

Syntax

debug ipv6 ospf nsm-status

no debug ipv6 ospf nsm-status

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf nsm-status
OSPFv3: nsm-status debugging is on
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.12]: Status change [Down]->[Init] (HelloReceived)
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.12]: Status change [Init]->[2-way] (No Need Adjacency)
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.11]: Status change [Down]->[Init] (HelloReceived)
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.11]: Status change [Init]->[2-way] (No Need Adjacency)
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.11]: Status change [2-way]->[ExStart] (Need Adjacency)
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.11]: Status change [ExStart]->[ExChange] (NegotiationDone)
Debug: Dec  9 11:12:19 OSPFv3: NSM[1.0.0.11]: Status change [ExChange]->[Loading] (Requestlist Not Empty)
Debug: Dec  9 11:12:20 OSPFv3: NSM[1.0.0.11]: Status change [Loading]->[Full] (LoadingDone)
Debug: Dec  9 11:12:20 OSPFv3: NSM[7.0.0.3]: Status change [Down]->[Init] (HelloReceived)
Debug: Dec  9 11:12:20 OSPFv3: NSM[7.0.0.3]: Status change [Init]->[2-way] (No Need Adjacency)
Debug: Dec  9 11:12:20 OSPFv3: NSM[7.0.0.3]: Status change [2-way]->[ExStart] (Need Adjacency)
Debug: Dec  9 11:12:20 OSPFv3: NSM[7.0.0.3]: Status change [ExStart]->[ExChange] (NegotiationDone)
Debug: Dec  9 11:12:21 OSPFv3: NSM[7.0.0.3]: Status change [ExChange]->[Full] (Requestlist Empty)
```

debug ipv6 ospf packet

Displays all OSPFv3 packets in rx or tx mode.

Syntax

debug ipv6 ospf packet

no debug ipv6 ospf packet

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# device# debug ipv6 ospf packet
OSPFv3: packet debugging is on
device(config-ospf6-router)# Debug: Jan 1 17:20:18 OSPFv3: Rcv Hello on ve 9
OSPFv3: (fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:18 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:23 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:29 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:29 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:32 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:38 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:38 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:43 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:49 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:49 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:54 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:58 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:20:58 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:21:04 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:21:09 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:21:09 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 17:21:14 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
```

debug ipv6 ospf packet-dd

Displays all OSPFv3 data description packets in rx or tx mode.

Syntax

debug ipv6 ospf packet-dd

no debug ipv6 ospf packet-dd

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf packet-dd
OSPFv3: packet-dd debugging is on
device(config-ospf6-router)# Debug: Jan 1 19:06:18 OSPFv3: Rcv DbDesc on ve 9
OSPFv3: (fe80::224:38ff:fed6:7800->OSPFv3: fe80::224:38ff:fe21:6400)
Debug: Jan 1 19:06:18 Option:00-00-13, Bits:07 SEQ:19b40
Debug: Jan 1 19:06:18 OSPFv3: DbDesc from 10.2.2.2 Ignored: state less than Init
Debug: Jan 1 19:06:19 OSPFv3: set dbdesc seqnum 000aa922 for 10.2.2.2
Debug: Jan 1 19:06:19 OSPFv3: Snd DbDesc on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: fe80::224:38ff:fed6:7800)
Debug: Jan 1 19:06:19 Option:00-00-13, Bits:07 SEQ:aa922
Debug: Jan 1 19:06:19 OSPFv3: Rcv DbDesc on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: fe80::224:38ff:fe21:6400)
Debug: Jan 1 19:06:19 Option:00-00-13, Bits:00 SEQ:aa922
Debug: Jan 1 19:06:19 OSPFv3: Snd DbDesc on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: fe80::224:38ff:fed6:7800)
Debug: Jan 1 19:06:19 Option:00-00-13, Bits:01 SEQ:aa923
Debug: Jan 1 19:06:19 OSPFv3: Rcv DbDesc on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: fe80::224:38ff:fe21:6400)
Debug: Jan 1 19:06:19 Option:00-00-13, Bits:00 SEQ:aa923
```

debug ipv6 ospf packet-hello

Displays all OSPFv3 hello packets in rx or tx mode.

Syntax

debug ipv6 ospf packet-hello

no debug ipv6 ospf packet-hello

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf packet-hello
OSPFv3: packet-hello debugging is on
device(config-ospf6-router)# Debug: Jan 1 18:52:05 OSPFv3: Snd Hello on ve 9
OSPFv3: (fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 18:52:07 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 18:52:07 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 18:52:16 OSPFv3: Snd Hello on ve 9 OSPFv3:
(fe80::224:38ff:fe21:6400->OSPFv3: ff02::5)
RtrID:10.4.4.8 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 18:52:16 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
Debug: Jan 1 18:52:16 OSPFv3: Rcv Hello on ve 9 OSPFv3:
(fe80::224:38ff:fed6:7800->OSPFv3: ff02::5)
RtrID:10.2.2.2 DR:10.4.4.8 BDR:10.2.2.2
```

debug ipv6 ospf packet-lsa-ack

Displays all OSPFv3 LSA acknowledgment packets in rx or tx mode.

Syntax

debug ipv6 ospf packet-lsa-ack

no debug ipv6 ospf packet-lsa-ack

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf packet-lsa-ack
OSPFv3: packet-lsa-ack debugging is on
Debug: Dec 9 11:15:08 OSPFv3: Rcv LSAck on ve 2150 OSPFv3: (fe80::768e:f8ff:fe46:bf60->OSPFv3:
ff02::5)
  Type:2009, LSID:0 Adv:1.0.0.1 SEQ:80000b5e AGE:1
Debug: Dec 9 11:15:08 OSPFv3: Rcv LSAck on ve 2250 OSPFv3: (fe80::224:38ff:fe76:2a40->OSPFv3: ff02::5)
  Type:2009, LSID:0 Adv:1.0.0.1 SEQ:80000b5e AGE:1
Debug: Dec 9 11:15:08 OSPFv3: Rcv LSAck on ve 2122 OSPFv3: (fe80::277:77ff:fe77:1111->OSPFv3: ff02::5)
  Type:2009, LSID:0 Adv:1.0.0.1 SEQ:80000b5e AGE:2
Debug: Dec 9 11:15:08 OSPFv3: neighbor 7.0.0.3 not found, reject received LS ACK
Debug: Dec 9 11:15:08 OSPFv3: Rcv LSAck on ve 120 OSPFv3: (fe80::204:80ff:fe11:1111->OSPFv3: ff02::5)
  Type:2009, LSID:0 Adv:1.0.0.1 SEQ:80000b5e AGE:1
Debug: Dec 9 11:15:08 OSPFv3: Rcv LSAck on ve 1737 OSPFv3: (fe80::768e:f8ff:fef9:b8dc->OSPFv3:
ff02::5)
  Type:2009, LSID:0 Adv:1.0.0.1 SEQ:80000b5e AGE:1
Debug: Dec 9 11:15:08 OSPFv3: Rcv LSAck on ve 1837 OSPFv3: (fe80::768e:f8ff:fe34:b570->OSPFv3:
ff02::5)
  Type:2009, LSID:0 Adv:1.0.0.1 SEQ:80000b5e AGE:1
Debug: Dec 9 11:15:12 OSPFv3: Snd LSAck on ve 2250 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::224:38ff:fe76:2a40)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000035 AGE:2
Debug: Dec 9 11:15:13 OSPFv3: Snd LSAck on ve 2150 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::768e:f8ff:fe46:bf60)
  Type:2001, LSID:0 Adv:7.0.0.3 SEQ:800008cc AGE:1
Debug: Dec 9 11:15:13 OSPFv3: Snd LSAck on ve 2250 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::224:38ff:fe76:2a40)
  Type:2001, LSID:0 Adv:7.0.0.3 SEQ:800008cc AGE:1
Debug: Dec 9 11:15:13 OSPFv3: Snd LSAck on ve 2250 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::224:38ff:fe76:2a40)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000036 AGE:1
Debug: Dec 9 11:15:13 OSPFv3: Snd LSAck on ve 2150 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::768e:f8ff:fe46:bf60)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000036 AGE:1
Debug: Dec 9 11:15:13 OSPFv3: Snd LSAck on ve 2250 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::224:38ff:fe76:2a40)
  Type:2009, LSID:92550 Adv:7.0.0.3 SEQ:8000002d AGE:1
Debug: Dec 9 11:15:13 OSPFv3: Snd LSAck on ve 2150 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
fe80::768e:f8ff:fe46:bf60)
  Type:2009, LSID:92550 Adv:7.0.0.3 SEQ:8000002d AGE:1
Debug: Dec 9 11:15:13 OSPFv3: Rcv LSAck on ve 2122 OSPFv3: (fe80::768e:f8ff:fe46:bf60->OSPFv3:
ff02::5)
  Type:2001, LSID:0 Adv:7.0.0.3 SEQ:800008cc AGE:1
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000036 AGE:1
  Type:2009, LSID:92550 Adv:7.0.0.3 SEQ:8000002d AGE:1
```

Debug Commands H - P

debug ipv6 ospf packet-lsa-req

debug ipv6 ospf packet-lsa-req

Displays all OSPFv3 LSA request packets in rx or tx mode.

Syntax

debug ipv6 ospf packet-lsa-req

no debug ipv6 ospf packet-lsa-req

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf packet-lsa-req
OSPFv3: packet-lsa-req debugging is on
Debug: Dec  9 11:18:25 OSPFv3: Snd LSReq on ve 2122 OSPFv3: (fe80::207:50ff:fe75:750->OSPFv3:
fe80::768e:f8ff:fe46:bf60)
  Type:0008, LSID:2049 Adv-Router:1.0.0.11
  Type:0008, LSID:2049 Adv-Router:1.0.0.12
  Type:0008, LSID:14368 Adv-Router:1.0.0.1
  Type:0008, LSID:3085 Adv-Router:7.0.0.3
Debug: Dec  9 11:18:25 OSPFv3: Snd LSReq on ve 2122 OSPFv3: (fe80::207:50ff:fe75:750->OSPFv3:
fe80::768e:f8ff:fe46:bf60)
  Type:0008, LSID:2049 Adv-Router:1.0.0.11
  Type:0008, LSID:2049 Adv-Router:1.0.0.12
  Type:0008, LSID:14368 Adv-Router:1.0.0.1
  Type:0008, LSID:3085 Adv-Router:7.0.0.3
Debug: Dec  9 11:18:26 OSPFv3: Rcv LSReq on ve 2122  OSPFv3: (fe80::277:77ff:fe77:1111->OSPFv3:
fe80::207:50ff:fe75:750)
  Type:2001, LSID:0 Adv-Router:1.0.0.1
  Type:2009, LSID:0 Adv-Router:1.0.0.1
  Type:0008, LSID:14368 Adv-Router:1.0.0.1
```

debug ipv6 ospf packet-lsa-update

Displays all OSPFv3 LSA update packets in rx or tx mode.

Syntax

debug ipv6 ospf packet-lsa-update

no debug ipv6 ospf packet-lsa-update

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf packet-lsa-update
OSPFv3: packet-lsa-update debugging is on
Debug: Dec  9 11:20:18 OSPFv3: Rcv LSUpdate on ve 2150  OSPFv3: (fe80::768e:f8ff:fe46:bf60-
>OSPFv3:ff02::5)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000039 AGE:2
Debug: Dec  9 11:20:18 OSPFv3: Rcv LSUpdate on ve 2250  OSPFv3: (fe80::224:38ff:fe76:2a40->OSPFv3:
ff02::5)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000039 AGE:2
Debug: Dec  9 11:20:18 OSPFv3: Snd LSUpdate on ve 120  OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
ff02::5)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000039 AGE:3
Debug: Dec  9 11:20:18 OSPFv3: Snd LSUpdate on ve 1737 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
ff02::5)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000039 AGE:3
Debug: Dec  9 11:20:18 OSPFv3: Snd LSUpdate on ve 1837 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
ff02::5)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000039 AGE:3
Debug: Dec  9 11:20:18 OSPFv3: Snd LSUpdate on ve 2250 OSPFv3: (fe80::ce4e:24ff:fe39:4480->OSPFv3:
ff02::5)
  Type:2002, LSID:3085 Adv:7.0.0.3 SEQ:80000039 AGE:3
```

debug ipv6 ospf route

Displays all OSPFv3 routes.

Syntax

debug ipv6 ospf route

no debug ipv6 ospf route

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf route
OSPFv3: route debugging is on
Debug: Dec 9 11:24:18 OSPFv3: add to spf list Inst vrf id 0, flag 0
Debug: Dec 9 11:24:24 OSPFv3: delete from spf list Inst vrf id 0, flag 1
Debug: Dec 9 11:24:24 OSPFv3 ROUTE: release semaphore 1
Debug: Dec 9 11:24:24 OSPFv3: SPF: Calculation for area 0.0.0.0
Debug: Dec 9 11:24:24 OSPFv3: SPF: installing vertex 1.0.0.1
Debug: Dec 9 11:24:24 OSPFv3: SPF: 2.0.0.1:14337 is the first hop
Debug: Dec 9 11:24:24 OSPFv3: SPF : 2.0.0.1:14337 nexthop :: ifindex 14341
Debug: Dec 9 11:24:24 OSPFv3: SPF: Examining Vertex: 2.0.0.1:14337
Debug: Dec 9 11:24:24 OSPFv3: SPF: new node added to candidate list: 2.0.0.1:14337
Debug: Dec 9 11:24:24 OSPFv3: SPF: 1.0.0.13:2050 is the first hop
Debug: Dec 9 11:24:24 OSPFv3: SPF : 1.0.0.13:2050 nexthop :: ifindex 14364
Debug: Dec 9 11:24:24 OSPFv3: SPF: Examining Vertex: 1.0.0.13:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: new node added to candidate list: 1.0.0.13:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: 1.0.0.14:2050 is the first hop
Debug: Dec 9 11:24:24 OSPFv3: SPF : 1.0.0.14:2050 nexthop :: ifindex 14366
Debug: Dec 9 11:24:24 OSPFv3: SPF: Examining Vertex: 1.0.0.14:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: new node added to candidate list: 1.0.0.14:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: 1.0.0.11:2050 is the first hop
Debug: Dec 9 11:24:24 OSPFv3: SPF : 1.0.0.11:2050 nexthop :: ifindex 14369
Debug: Dec 9 11:24:24 OSPFv3: SPF: Examining Vertex: 1.0.0.11:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: new node added to candidate list: 1.0.0.11:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: 1.0.0.12:2050 is the first hop
Debug: Dec 9 11:24:24 OSPFv3: SPF : 1.0.0.12:2050 nexthop :: ifindex 14371
Debug: Dec 9 11:24:24 OSPFv3: SPF: Examining Vertex: 1.0.0.12:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: new node added to candidate list: 1.0.0.12:2050
Debug: Dec 9 11:24:24 OSPFv3: SPF: installing vertex 2.0.0.1:14337
Debug: Dec 9 11:24:24 OSPFv3: ROUTE: Creating route: 2.0.0.1:14337
```

debug ipv6 ospf route-calc-external

Displays external route calculations.

Syntax

debug ipv6 ospf route-calc-external

no debug ipv6 ospf route-calc-external

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf route-calc-external
OSPFv3: route-calc-external debugging is on
device(config-if-e1000-8/9)# Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE:
External LSA(ID= 37) is Self-originated:
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: External LSA(ID= 39) is
Self-originated:
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: External LSA(ID= 36) is
Self-originated:
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: External LSA(ID= 38) is
Self-originated:
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: External LSA(ID= 40) is
Self-originated:
Debug: Jan 1 19:21:07 OSPFv3: EXTERNAL ROUTE: Forwarding flag specified
```

debug ipv6 ospf route-calc-inter-area

Displays inter-area route calculations.

Syntax

debug ipv6 ospf route-calc-inter-area

no debug ipv6 ospf route-calc-inter-area

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf route-calc-inter-area
OSPFv3: route-calc-inter-area debugging is on
device(config-vif-7)# ipv6 ospf area 1
device(config-vif-7)# sOSPFv3: INTER AREA ROUTE: Inter Area Prefix LSA(ID= 2,
prefix 2001:DB8::/64) is Self-originated. Area id 0.0.0.0
OSPFv3: INTER AREA ROUTE: Inter Area Prefix LSA(ID= 2, prefix 2001:DB8::/64) is
Self-originated. Area id 0.0.0.0
device(config-vif-7)# disable
device(config-vif-7)# OSPFv3: INTER AREA ROUTE: Inter Area Prefix LSA(ID= 2,
prefix 2001:DB8::/64) is Self-originated. Area id 0.0.0.0
device(config-vif-7)# enable
device(config-vif-7)# OSPFv3: INTER AREA ROUTE: Inter Area Prefix LSA(ID= 11,
prefix 2001:DB8::/64) is Self-originated. Area id 0.0.0.0
device(config)# Debug: Jan 1 00:32:22 OSPFv3: INTER AREA ROUTE: Inter Area route
for prefix 2001:DB8::/64 created
```

debug ipv6 ospf route-calc-intra-area

Displays intra-area route calculations.

Syntax

debug ipv6 ospf route-calc-intra-area

no ddebug ipv6 ospf route-calc-intra-area

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf route-calc-intra-area
OSPFv3: route-calc-intra-area debugging is on
Debug: Dec 9 11:26:41 OSPFv3: Calculating Intra Area routes for area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Calculating Intra Area Stub Routes
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: found Prefix LSA type : IntraPrefix : for Id 0.0.0.0
Advrouter 1.0.0.1
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:1:1:1::/64 cost 1,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:101:1:1::/64 cost 100,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:200:1:1::/64 cost 100,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:205:1:1::/64 cost 100,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:210:1:1::/64 cost 100,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:220:1:1::/64 cost 100,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:593:1:1::/64 cost 17,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:2122:1:1::/64 cost 9,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: found Prefix LSA type : IntraPrefix : for Id 0.0.0.0
Advrouter 1.0.0.11
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:1011::1/128 cost 100,
area 0.0.0.0
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: found Prefix LSA type : IntraPrefix : for Id 0.0.0.0
Advrouter 1.0.0.12
Debug: Dec 9 11:26:41 OSPFv3: INTRA AREA ROUTE: Intra Area route install 1001:1012::1/128 cost 100,
area 0.0.0.0
```

debug ipv6 ospf route-calc-spf

Displays SPF route calculations.

Syntax

```
debug ipv6 ospf route-calc-spf
```

```
no debug ipv6 ospf route-calc-spf
```

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf route-calc-spf
OSPFv3: route-calc-spf debugging is on
Debug: Dec  9 11:29:11 OSPFv3: Schedule routing table build
Debug: Dec  9 11:29:11 OSPFv3: add to spf list Inst vrf id 0, flag 0
Debug: Dec  9 11:29:17 OSPFv3: delete from spf list Inst vrf id 0, flag 1
Debug: Dec  9 11:29:17 OSPFv3: SPF: Calculation for area 0.0.0.0
Debug: Dec  9 11:29:17 OSPFv3: SPF: installing vertex 1.0.0.1
Debug: Dec  9 11:29:17 OSPFv3: SPF: 2.0.0.1:14337 is the first hop
Debug: Dec  9 11:29:17 OSPFv3: SPF : 2.0.0.1:14337 nexthop :: ifindex 14341
Debug: Dec  9 11:29:17 OSPFv3: SPF: Examining Vertex: 2.0.0.1:14337
Debug: Dec  9 11:29:17 OSPFv3: SPF: new node added to candidate list: 2.0.0.1:14337
Debug: Dec  9 11:29:17 OSPFv3: SPF: 1.0.0.13:2050 is the first hop
Debug: Dec  9 11:29:17 OSPFv3: SPF : 1.0.0.13:2050 nexthop :: ifindex 14364
Debug: Dec  9 11:29:17 OSPFv3: SPF: Examining Vertex: 1.0.0.13:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: new node added to candidate list: 1.0.0.13:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: 1.0.0.14:2050 is the first hop
Debug: Dec  9 11:29:17 OSPFv3: SPF : 1.0.0.14:2050 nexthop :: ifindex 14366
Debug: Dec  9 11:29:17 OSPFv3: SPF: Examining Vertex: 1.0.0.14:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: new node added to candidate list: 1.0.0.14:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: 1.0.0.11:2050 is the first hop
Debug: Dec  9 11:29:17 OSPFv3: SPF : 1.0.0.11:2050 nexthop :: ifindex 14369
Debug: Dec  9 11:29:17 OSPFv3: SPF: Examining Vertex: 1.0.0.11:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: new node added to candidate list: 1.0.0.11:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: 1.0.0.12:2050 is the first hop
Debug: Dec  9 11:29:17 OSPFv3: SPF : 1.0.0.12:2050 nexthop :: ifindex 14371
Debug: Dec  9 11:29:17 OSPFv3: SPF: Examining Vertex: 1.0.0.12:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: new node added to candidate list: 1.0.0.12:2050
Debug: Dec  9 11:29:17 OSPFv3: SPF: installing vertex 2.0.0.1:14337
Debug: Dec  9 11:29:17 OSPFv3: SPF : 2.0.0.1:0 nexthop fe80::204:80ff:fe11:1111 ifindex 14341
```

debug ipv6 ospf route-install

Displays all OSPFv3 installed routes.

Syntax

debug ipv6 ospf route-install

no debug ipv6 ospf route-install

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 ospf route-install
OSPFv3: route-install debugging is on
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 2.0.0.1:14337
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 2.0.0.1:0
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.13:2050
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.14:2050
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.11:2050
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.12:2050
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.12:0
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.11:0
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.14:0
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1.0.0.13:0
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 7.0.0.3:3085
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 7.0.0.3:0
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:1:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:101:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:200:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:205:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:210:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:220:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:593:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:2122:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: route changed, new route preferred: 1001:2122:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:1011::1/128
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:1012::1/128
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1002:201:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:21:5:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:22:5:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:17:37:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:18:37:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:2122:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:120:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:1392:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Creating route: 1001:1382:1:1::/64
Debug: Dec 9 11:33:52 OSPFv3: ROUTE: Validate routing table
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:1:1:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:17:37:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:18:37:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:21:5:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:22:5:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:101:1:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:120:1:1::/64, nexthop cnt 1, route_info->flag 0x2
Debug: Dec 9 11:33:52 OSPFv3: Validating route 1001:200:1:1::/64, nexthop cnt 1, route_info->flag 0x2
```

debug ipv6 pim

Enables the IPv6 Protocol Independent Multicast (PIM) debugging.

Syntax

```
debug ipv6 pim[fdb | hash | ipc | optimization | route-change | scaling | sync-lib | timer-typenum]
```

```
no debug ipv6 pim[fdb | hash | ipc | optimization | route-change | scaling | sync-lib | timer-typenum]
```

Parameters

fdb

Enables application VLAN (vidx) and forwarding database debugging.

hash

Displays hash address details for debugging.

ipc

Debugs inter-process communication between MP and LP.

optimization

Debugs multicast outgoing interface (OIF) list optimization.

route-change

Monitors route change.

scaling

Monitors scaling.

sync-lib

Monitors sync-lib operations.

timer-typenum

Displays stack trace of timer.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables PIM debugging.

Examples

```
device# debug ipv6 pim
```

debug ipv6 pim add-del-oif

Displays information about the mcache activity.

Syntax

```
debug ipv6 pim add-del-oif
```

```
no debug ipv6 pim add-del-oif
```

Modes

Privileged EXEC mode

Usage Guidelines

The command will work with the **debug ipv6 pim group** or **debug ipv6 pim source** commands.

Examples

```
device#debug ipv6 pim add-del-oif
May 29 11:22:05:295426:info:fi_debug:debug_logs:1:940808291223041: PIM.VRF0: KAT Reset for (3111::12
ffle::5:1) to -1
May 29 11:22:05:294522:info:fi_debug:debug_logs:1:940808291223041: [mcastFlowEntrySetup]: VRF0 Setting
up mcast flow entry (3111::12 ffle::5:1)
May 29 11:22:05:294396:info:fi_debug:debug_logs:1:940808291223041: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (3111::12,ffle::5:1) Action(Add)
May 29 11:22:05:294292:info:fi_debug:debug_logs:1:940808291223041: PIM-OIF.VRF0: (3111::12 ffle::5:1)
Entry Flags 0x200680e1: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 11:22:05:293690:info:fi_debug:debug_logs:1:940808291223041: VRF0 Flow Entry removal (3111::12
ffle::5:1) in HW: 0
May 29 11:22:05:293587:info:fi_debug:debug_logs:1:940808291223041: [freeMCEntForFlow]: VRF0 Deleting
mcast flow entry (3111::12 ffle::5:1) free_l2_mac
May 29 11:22:05:290566:info:fi_debug:debug_logs:1:940808291223041: PIM.VRF0: Remove OIF: NOP: L2OIF for
v20,lg1 from (3111::12, ffle::5:1) entry, remove_now=1, Reason(IIFmatch) Action(Nop) CurrentState(0x0)
NewState(0x200)
May 29 11:22:05:290394:info:fi_debug:debug_logs:1:940808291223041: PIMSM.VRF0: OIF FSM 0 case for
(3111::12, ffle::5:1) entry Reason(IIFmatch), Action(Nop) flagAction 0 CurrentState(0x0)
NewState(0x200)
May 29 11:22:05:290316:info:fi_debug:debug_logs:1:940808291223041: PIM.VRF0: OIF FSM common events
Remove for (3111::12, ffle::5:1) entry Reason(IIFmatch), Action(Nop), flagAction(0) CurrentState(0x0)
NewFlag(0x200)
May 29 11:22:05:290187:info:fi_debug:debug_logs:1:940808291223041: PIM.VRF0: KAT Reset for (3111::12
ffle::5:1) to 180
May 29 11:22:05:191240:info:fi_debug:debug_logs:1:940808291223041: (3111::12.ffe::5:1).VRF0, parent
v20, vlan_tnml 20, oift 1 parent-phy-port 1/1/1, parent oif not found
May 29 11:22:05:185471:info:fi_debug:debug_logs:1:940533413316097: hal_fwd_mcache_insert_hash_entry
allocated VRF0 (3111::12, ffle::5:1) entry
May 29 11:22:05:185379:info:fi_debug:debug_logs:1:940533413316097: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (3111::12,ffle::5:1) Action(Add)
May 29 11:22:05:185291:info:fi_debug:debug_logs:1:940533413316097: PIM-OIF.VRF0: (3111::12 ffle::5:1)
Entry Flags 0x200600e0: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 11:22:05:185181:info:fi_debug:debug_logs:1:940533413316097: [freeMCEntForFlow]: VRF0 Deleting
mcast flow entry (3111::12 ffle::5:1) free_l2_mac
May 29 11:22:05:184111:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: KAT Reset for (3111::12
ffle::5:1) to 180
May 29 11:22:05:183968:info:fi_debug:debug_logs:1:940537708283393: PIMSM.VRF0: Created (3111::12 ffle::
5:1) entry. Parent v20. RP=98::1. Flags 0x200600e0
May 29 11:22:05:168250:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: Remove OIF: NOP: L2OIF for
v20,lg1 from (3111::12, ffle::5:1) entry, remove_now=1, Reason(IIFmatch) Action(Nop) CurrentState(0x0)
NewState(0x200)
May 29 11:22:05:168173:info:fi_debug:debug_logs:1:940537708283393: PIMSM.VRF0: OIF FSM 0 case for
(3111::12, ffle::5:1) entry Reason(IIFmatch), Action(Nop) flagAction 0 CurrentState(0x0)
NewState(0x200)
May 29 11:22:05:167746:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: OIF FSM common events
Remove for (3111::12, ffle::5:1) entry Reason(IIFmatch), Action(Nop), flagAction(0) CurrentState(0x0)
NewFlag(0x200)
May 29 11:22:05:167664:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: Remove OIF: NOP: L2OIF for
v20,INVALID from (3111::12, ffle::5:1) entry, remove_now=1, Reason(IIFNoMatch) Action(Nop)
CurrentState(0x0) NewState(0x200)
May 29 11:22:05:167590:info:fi_debug:debug_logs:1:940537708283393: PIMSM.VRF0: OIF FSM 0 case for
(3111::12, ffle::5:1) entry Reason(IIFNoMatch), Action(Nop) flagAction 0 CurrentState(0x0)
NewState(0x200)
May 29 11:22:05:167510:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: OIF FSM common events
Remove for (3111::12, ffle::5:1) entry Reason(IIFNoMatch), Action(Nop), flagAction(0) CurrentState(0x0)
NewFlag(0x200)
May 29 11:22:05:167321:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (3111::12,ffle::5:1) Action(Add)
May 29 11:22:05:167244:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: Update oifflg v10/3/1/5
(3111::12,ffle::5:1), rcode(IgmpGrpJoin), Act(Add) cstate(0x2) nstate(0x4) newflg 0x4, #immoifs 0
#bldoifs 0 #inhoifs 0 #fwdoids 0 sync 1
May 29 11:22:05:167157:info:fi_debug:debug_logs:1:940537708283393: PIM-OIF.VRF0: (3111::12 ffle::5:1)
Entry Flags 0x220080: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 11:22:05:167074:info:fi_debug:debug_logs:1:940537708283393: PIM.VRF0: Add OIF: Adding L3OIF
v10,3/1/5 to (3111::12,ffle::5:1), Reason(IgmpGrpJoin) Action(Add) CurrentState(0x2) NewState(0x4)
holdtime 210
May 29 11:22:05:166955:info:fi_debug:debug_logs:1:940537708283393: PIMSM.VRF0: OIF FSM 1 case for
(3111::12, ffle::5:1) entry Reason(IgmpGrpJoin), Action(Add) flagAction 3 CurrentState(0x0)
NewState(0x4)
```

```

May 29 11:22:05:099842:info:fi_debug:debug_logs:1:940533413316097: (*,ffle::5:1).VRF0, parent v20,
vlan_tnnl 20, oift 1 parent-phy-port 1/1/1, parent oif not found
May 29 11:21:58:769582:info:fi_debug:debug_logs:1:940129686390273: PIMSM.VRF0: OIF FSM 1 for (*, ffile::
5:1) entry Reason(IgmpGrpJoin), Action(Update), flagAction(1) CurrentState(0x4) NewState(0x4)
May 29 11:21:53:845103:info:fi_debug:debug_logs:1:939730254431745: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (*,ffle::5:1) Action(Add)
May 29 11:21:53:844411:info:fi_debug:debug_logs:1:939730254431745: PIM-OIF.VRF0: (* ffile::5:1) Entry
Flags 0x2604a0: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 11:21:53:842639:info:fi_debug:debug_logs:1:939730254431745: PIM.VRF0: OIF Update Fwdmask: Added
FwdPort L3OIF v10,3/1/5 to (*,ffle::5:1) Action(Add)
May 29 11:21:53:842519:info:fi_debug:debug_logs:1:939730254431745: PIM.VRF0: Update oifflg v110/3/1/5
(*,ffle::5:1), rcode(IgmpGrpJoin), Act(Add) cstate(0x0) nstate(0x4) newflg 0x4, #immoifs 1 #bldoifs 0
#inhoifs 0 #fwdoids 1 sync 1
May 29 11:21:53:828095:info:fi_debug:debug_logs:1:939730254431745: PIM-OIF.VRF0: (* ffile::5:1) Entry
Flags 0x220080: Add 3/1/5 on 10 (L3). OIF_FLAGS: 4
May 29 11:21:53:828015:info:fi_debug:debug_logs:1:939730254431745: PIM.VRF0: Add OIF: Adding L3OIF
v10,3/1/5 to (*,ffle::5:1), Reason(IgmpGrpJoin) Action(Add) CurrentState(0x0) NewState(0x4) holdtime
260
May 29 11:21:53:827903:info:fi_debug:debug_logs:1:939730254431745: PIMSM.VRF0: OIF FSM 1 for (*, ffile::
5:1) entry Reason(IgmpGrpJoin), Action(Add), flagAction(1) CurrentState(0x0) NewState(0x4)
May 29 11:21:53:827513:info:fi_debug:debug_logs:1:939730254431745: PIMSM.VRF0: Created (* ffile::5:1)
entry. Parent ffile::5:1. RP=v20. LIFid 141292240. Flags 0x0
  
```

History

Release version	Command history
09.0.00	This command was introduced.

debug ipv6 pim bootstrap

Enables IPv6 Protocol Independent Multicast (PIM) bootstrap debugging.

Syntax

debug ipv6 pim bootstrap

no debug ipv6 pim bootstrap

Modes

Privileged EXEC mode

Usage Guidelines

The no form of the command disables IPv6 PIM bootstrap debugging.

Examples

```
device#debug ipv6 pim bootstrap
Apr 23 15:12:03:078131:info:fi_debug:debug_logs:1:4397840352675329: DHCPV4: received packet SIP:
0.0.0.0, DIP: 255.255.255.255, SP: 68, DP: 67, PROTO: 17
Apr 23 15:12:00:810368:info:fi_debug:debug_logs:1:10556329533900289: PIM-BSR.VRF0: Intf v20 - accept
BSM from BSR 99::11(Pr 200), local state AccPref, curr BSR 99::11 (Pr 200)
Apr 23 15:12:00:810289:info:fi_debug:debug_logs:1:10556329533900289: PIM-BSR.VRF0: Prefer BSR 99::11(Pr
200) over current BSR 99::11(Pr 200)
Apr 23 15:12:00:810213:info:fi_debug:debug_logs:1:10556329533900289: Suppressed 4 times: DHCPV4:
received packet SIP: 0.0.0.0, DIP: 255.255.255.255, SP: 68, DP: 67, PROTO: 17
Apr 23 15:11:13:815545:info:fi_debug:debug_logs:1:4396341409089025: DHCPV4: received packet SIP:
0.0.0.0, DIP: 255.255.255.255, SP: 68, DP: 67, PROTO: 17
Apr 23 15:11:00:749204:info:fi_debug:debug_logs:1:10552064631375361: PIM-BSR.VRF0: Intf v20 - accept
BSM from BSR 99::11(Pr 200), local state AccPref, curr BSR 99::11 (Pr 200)
Apr 23 15:11:00:749126:info:fi_debug:debug_logs:1:10552064631375361: PIM-BSR.VRF0: Prefer BSR 99::11(Pr
200) over current BSR 99::11(Pr 200)
Apr 23 15:11:00:749048:info:fi_debug:debug_logs:1:10552064631375361: Suppressed 8 times: DHCPV4:
received packet SIP: 0.0.0.0, DIP: 255.255.255.255, SP: 68, DP: 67, PROTO: 17"
```

debug ipv6 pim clear

Clears all the IPv6 PIM debug settings.

Syntax

debug ipv6 pim clear

no debug ipv6 pim clear

Modes

Privileged EXEC mode

Examples

If no settings are enabled, output similar to the following will be displayed.

```
device# debug ipv6 pim event
PIM6 event debugging is on
device#
device#debug ipv6 pim show
debug ipv6 pim event
device#debug ipv6 pim clear
device#debug ipv6 pim show
device#
```

Debug Commands H - P
debug ipv6 pim event

debug ipv6 pim event

Enables debugging of IPv6 PIM events.

Syntax

debug ipv6 pim event

no debug ipv6 pim event

Modes

Privileged EXEC mode

Usage Guidelines

The no form of the command disables debugging of IPv6 PIM events.

Examples

```

device# debug ipv6 pim event
May 29 11:28:28:809869:info:fi_debug:debug_logs:1:10433072562438912: PIM-EVT.VRF0: Receive intf v20 Up
state_notify. AFI: IPv6.
May 29 11:28:28:809753:info:fi_debug:debug_logs:1:10433072562438912: PIM6-EVT: Recv linklocal addr add
nfn on intf v20, new link local addr fe80::629c:9fff:fecl:b8d0
May 29 11:28:28:790368:info:fi_debug:debug_logs:1:10433072562438912: PIM-EVT.VRF0: Receive intf v20 Dn
state_notify. AFI: IPv6.
May 29 11:28:28:790231:info:fi_debug:debug_logs:1:10433072562438912: PIM6-EVT: Recv global addr change
nfn on intf v20, new global addr 2111::11
May 29 11:28:28:788155:info:fi_debug:debug_logs:1:10433072562438912: PIM-EVT.VRF0: Receive intf v20 Dn
state_notify. AFI: IPv6.
May 29 11:28:28:753468:info:fi_debug:debug_logs:1:10433072562438912: PIM-EVT.VRF1: Receive intf v21 Up
state_notify. AFI: IPv6.
May 29 11:28:28:753353:info:fi_debug:debug_logs:1:10433072562438912: PIM6-EVT: Recv linklocal addr add
nfn on intf v21, new link local addr fe80::629c:9fff:fecl:b8d0
May 29 11:28:28:733333:info:fi_debug:debug_logs:1:10433072562438912: PIM-EVT.VRF1: Receive intf v21 Dn
state_notify. AFI: IPv6.
May 29 11:28:28:733216:info:fi_debug:debug_logs:1:10433072562438912: PIM6-EVT: Recv global addr change
nfn on intf v21, new global addr 21::21
May 29 11:28:28:732620:info:fi_debug:debug_logs:1:10433072562438912: PIM-EVT.VRF1: Receive intf v21 Dn
state_notify. AFI: IPv6.
May 29 11:28:27:403374:info:fi_debug:debug_logs:1:969146485442049: MLD: [ Port lg1 ] Query version
mismatch. Received query version 2 from fe80::d6c1:9eff:fe15:f999; Port version 1.
May 29 11:28:26:039090:info:fi_debug:debug_logs:1:10430130509841152: PIM6-EVT: Received vport v21/1/1/3
(lg1) Up state_notify
May 29 11:28:26:013784:info:fi_debug:debug_logs:1:10430130509841152: PIM-EVT.VRF1: Receive intf v21 Up
state_notify. AFI: IPv6.
May 29 11:28:26:013667:info:fi_debug:debug_logs:1:10430130509841152: MC-EVT: Port v21 state changed to
UP. AFI: IPv6.
May 29 11:28:25:974696:info:fi_debug:debug_logs:1:10430130509841152: PIM6-EVT: Received vport v21/1/1/1
(lg1) Up state_notify
May 29 11:28:25:943949:info:fi_debug:debug_logs:1:10430130509841152: PIM6-EVT: Received vport v20/1/1/3
(lg1) Up state_notify
May 29 11:28:25:933560:info:fi_debug:debug_logs:1:10430130509841152: PIM-EVT.VRF0: Receive intf v20 Up
state_notify. AFI: IPv6.
May 29 11:28:25:933443:info:fi_debug:debug_logs:1:10430130509841152: MC-EVT: Port v20 state changed to
UP. AFI: IPv6.
May 29 11:28:25:908923:info:fi_debug:debug_logs:1:10430130509841152: PIM6-EVT: Received vport v20/1/1/1
(lg1) Up state_notify
May 29 11:27:55:068982:info:fi_debug:debug_logs:1:966745598723585: Mcast6v6 receive event
EVENT_ID TRUNK_MEMBER UP(15)
May 29 11:27:55:068905:info:fi_debug:debug_logs:1:966745598723585: Suppressed 1 times: PIM6-EVT:
Received vport v21/1/1/3 (lg1) Dn state_notify
May 29 11:27:55:057461:info:fi_debug:debug_logs:1:966745598723585: PIM6-EVT: Received vport v21/1/1/3
(lg1) Dn state_notify
May 29 11:27:55:057387:info:fi_debug:debug_logs:1:966745598723585: Suppressed 1 times: PIM6-EVT:
Received vport v20/1/1/3 (lg1) Dn state_notify
May 29 11:27:55:046795:info:fi_debug:debug_logs:1:966745598723585: PIM6-EVT: Received vport v20/1/1/3
(lg1) Dn state_notify
May 29 11:27:54:975293:info:fi_debug:debug_logs:1:966745598723585: Mcast6v6 receive event
EVENT_ID TRUNK_MEMBER UP(15)
May 29 11:27:50:183693:info:fi_debug:debug_logs:1:10399193860408064: Suppressed 1 times: PIM6-EVT:
Received vport v21/1/1/3 (lg1) Dn state_notify
May 29 11:27:13:730348:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Received vport v21/1/1/3 (lg1)
Dn state_notify
May 29 11:27:13:730273:info:fi_debug:debug_logs:1:42949672961: Suppressed 1 times: PIM6-EVT: Received
vport v20/1/1/3 (lg1) Dn state_notify
May 29 11:27:13:717412:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Received vport v20/1/1/3 (lg1)
Dn state_notify
May 29 11:27:13:666429:info:fi_debug:debug_logs:1:42949672961: PIM-EVT.VRF1: Receive intf v21 Dn
state_notify. AFI: IPv6.
May 29 11:27:13:666314:info:fi_debug:debug_logs:1:42949672961: MC-EVT: Port v21 state changed to DOWN.
AFI: IPv6.
May 29 11:27:13:660870:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Received vport v21/1/1/3 (lg1)
Dn state_notify
May 29 11:27:13:626511:info:fi_debug:debug_logs:1:42949672961: PIM-EVT.VRF0: Receive intf v20 Dn
state_notify. AFI: IPv6.
May 29 11:27:13:626376:info:fi_debug:debug_logs:1:42949672961: MC-EVT: Port v20 state changed to DOWN.
AFI: IPv6.

```

Debug Commands H - P

debug ipv6 pim event

```
May 29 11:27:13:602469:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Received vport v20/1/1/3 (lg1)
Dn state notify
May 29 11:27:13:522699:info:fi_debug:debug_logs:1:42949672961: Mcast6v6 receive event
EVENT_ID_TRUNK_DOWN(13)
May 29 11:27:13:505021:info:fi_debug:debug_logs:1:42949672961: Mcast6v6 receive event
EVENT_ID_TRUNK_MEMBER_DOWN(16)
May 29 11:27:13:407392:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Received vport v21/1/1/1 (lg1)
Dn state notify
May 29 11:27:13:386449:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Received vport v20/1/1/1 (lg1)
Dn state notify
May 29 11:27:13:248202:info:fi_debug:debug_logs:1:42949672961: Mcast6v6 receive event
EVENT_ID_TRUNK_MEMBER_DOWN(16)
May 29 11:27:13:223184:info:fi_debug:debug_logs:1:42949672961: PIM-EVT.VRF1: Receive intf v21 Dn
state_notify. AFI: IPv6.
May 29 11:27:13:223076:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Recv linklocal addr del nfn on
intf v21,sent 0 holdtime hello, link local addr unset
May 29 11:27:13:221555:info:fi_debug:debug_logs:1:42949672961: PIM-EVT.VRF0: Receive intf v20 Dn
state_notify. AFI: IPv6.
May 29 11:27:13:221413:info:fi_debug:debug_logs:1:42949672961: PIM6-EVT: Recv linklocal addr del nfn on
intf v20,sent 0 holdtime hello, link local addr unset
```

debug ipv6 pim group

Displays the IPv6 PIM related debugging information for the specified PIM group.

Syntax

debug ipv6 pim group*group_addr*

no debug ipv6 pim group*group_addr*

Parameters

group_addr

Specifies the group address of the PIM.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim group ff1e::5:1
May 29 11:33:39:710097:info:fi_debug:debug_logs:1:995642138691073: stack: 00546ee8 0114a590 010d4e38
010d5f48 01165f14 01166168 01166470 0116c2ec 01147130 01101d20 010f1e9c 01121458 005c1f38 005c2998
011b177c b6d93eb0 b6f9a195
May 29 11:33:39:709971:info:fi_debug:debug_logs:1:995642138691073: PIM.VRF0: Allocation of hw resources
for (3111::12 ff1e::5:1) successful. olist not empty. FID NotReq. MVID 321
May 29 11:33:33:141266:info:fi_debug:debug_logs:1:10686467042968320: PIM.VRF0: Deallocated hw resources
for (* ff1e::5:1), parent: v20,Nil. olist empty
May 29 11:33:33:046453:info:fi_debug:debug_logs:1:210453397505: stack: 00546ee8 0114a590 010d4e38
010d6ba8 01161d70 01162008 011624d4 01146df4 010dff10 01102568 010e3438 010e3660 01289698 01289e6c
01289ec0 01289f40 00123350 01289fd8 005c1f38 005c2998 01187f10 b6d93eb0 b6f9a195
May 29 11:33:33:046299:info:fi_debug:debug_logs:1:210453397505: PIM.VRF0: Allocation of hw resources
for (3111::12 ff1e::5:1) successful. olist empty. FID NotReq. MVID Drop
```

debug ipv6 pim join-prune

Controls join prune processing and displays debugging information related to the IPv6 join prune messages.

Syntax

debug ipv6 pim join-prune

no debug ipv6 pim join-prune

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim join-prune
May 29 11:31:54:591512:info:fi_debug:debug_logs:1:10604531951862528: PIM: End sending Join/Prune msg
---
May 29 11:31:54:590934:info:fi_debug:debug_logs:1:10604531951862528:      J-Src: 3111::12, wc=0 rpt=0
SM=1
May 29 11:31:54:590864:info:fi_debug:debug_logs:1:10604531951862528:      J-Src: 98::1, wc=1 rpt=1 SM=1
May 29 11:31:54:590790:info:fi_debug:debug_logs:1:10604531951862528: PIM-JP.VRF0:  Group: ffile::5:1,
JoinSrcs: 2, PruneSrcs: 0
May 29 11:31:54:590684:info:fi_debug:debug_logs:1:10604531951862528: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to fe80::d6c1:9eff:fe15:f999 on v20
May 29 11:31:53:600477:info:fi_debug:debug_logs:1:10603677253370624: PIM: End sending Join/Prune msg
---
May 29 11:31:53:600014:info:fi_debug:debug_logs:1:10603677253370624:      P-Src: 98::1, wc=1 rpt=1 SM=1
May 29 11:31:53:599939:info:fi_debug:debug_logs:1:10603677253370624: PIM-JP.VRF0:  Group: ffile::5:1,
JoinSrcs: 0, PruneSrcs: 1
May 29 11:31:53:599834:info:fi_debug:debug_logs:1:10603677253370624: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to fe80::d6c1:9eff:fe15:f999 on v20
May 29 11:31:50:541119:info:fi_debug:debug_logs:1:10601117452862208: PIM: End sending Join/Prune msg
---
May 29 11:31:50:540698:info:fi_debug:debug_logs:1:10601117452862208:      P-Src: 3111::12, wc=0 rpt=0
SM=1
May 29 11:31:50:540627:info:fi_debug:debug_logs:1:10601117452862208:      P-Src: 98::1, wc=1 rpt=1 SM=1
May 29 11:31:50:540553:info:fi_debug:debug_logs:1:10601117452862208: PIM-JP.VRF0:  Group: ffile::5:1,
JoinSrcs: 0, PruneSrcs: 2
May 29 11:31:50:540438:info:fi_debug:debug_logs:1:10601117452862208: PIM-JP.VRF0: BEGIN SENDING Join/
Prune msg to fe80::d6c1:9eff:fe15:f999 on v20
```

debug ipv6 pim level

Sets the IPv6 Protocol Independent Multicast (PIM) level.

Syntax

debug ipv6 pim level*decimal*

no debug ipv6 pim level

Parameters

decimal

Specifies the number of the PIM level. The valid values are from 1 through 3.

Modes

Privileged EXEC mode

Examples

```
device#debug ipv6 pim level 3
device#debug ipv6 pim packet 3111::12 ff1e::5:1 5
May 29 11:48:14:387969:info:fi_debug:debug_logs:1:1066715257505281: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:387877:info:fi_debug:debug_logs:1:1066715257505281: Rx Pkt (3111::12, ff1e::5:1) on
v20(1/1/1). hit=0
May 29 11:48:14:387636:info:fi_debug:debug_logs:1:1066710962537985: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:387542:info:fi_debug:debug_logs:1:1066710962537985: Rx Pkt (3111::12, ff1e::5:1) on
v20(1/1/1). hit=0
May 29 11:48:14:387293:info:fi_debug:debug_logs:1:1066706667570689: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:387194:info:fi_debug:debug_logs:1:1066706667570689: Rx Pkt (3111::12, ff1e::5:1) on
v20(1/1/1). hit=0
May 29 11:48:14:386918:info:fi_debug:debug_logs:1:1066702372603393: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:386823:info:fi_debug:debug_logs:1:1066702372603393: send MCAST_FIRST_DATA: entry phy
port: INVALID, pkt input port: lg1. SPT-F, FAST-F, MCT IIF Flag: F.
May 29 11:48:14:386518:info:fi_debug:debug_logs:1:1066702372603393: Rx flow on intf/port diff than
entry's intf v20 or port INVALID
May 29 11:48:14:386443:info:fi_debug:debug_logs:1:1066702372603393: Rx Pkt (3111::12, ff1e::5:1) on
v20(1/1/1). hit=0
May 29 11:48:14:386119:info:fi_debug:debug_logs:1:1066698077636097: LP sends create nfn to MP for
intermediate (3111::12,ff1e::5:1) as hw drop route, pkt incoming at v20
May 29 11:48:14:385630:info:fi_debug:debug_logs:1:1066698077636097: pimsm, fail longest_match,drop
packet
May 29 11:48:14:385497:info:fi_debug:debug_logs:1:1066698077636097: Rx Pkt (3111::12, ff1e::5:1) on
v20(1/1/1). hit=0
May 29 11:48:14:365293:info:fi_debug:debug_logs:1:107374182401: Cleanup Ended : 2021 May 29 10:48:13
May 29 11:48:14:364622:info:fi_debug:debug_logs:1:107374182401: Cleanup Started : 2021 May 29 10:48:13
```

History

Release version	Command history
09.0.00	This command was introduced.

debug ipv6 pim nbr

Controls the IPv6 PIM neighbor changes.

Syntax

debug ipv6 pim nbr[nbr_address]

no debug ipv6 pim nbr[nbr_address]

Parameters

nbr_address

Specifies the neighbor address.

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device#debug ipv6 pim nbr
May 29 11:35:23:261982:info:fi_debug:debug_logs:1:1003257115706881: PIM.VRF1: Rx Hello msg from
fe80::d6c1:9eff:fe15:f999 on intf v21, lg1
May 29 11:35:23:261790:info:fi_debug:debug_logs:1:1003252820739585: PIM.VRF0: Rx Hello msg from
fe80::d6c1:9eff:fe15:f999 on intf v20, lg1
May 29 11:35:22:046056:info:fi_debug:debug_logs:1:1003196986164737: PIM-NBR.VRF0: Neighbor
fe80::d6c1:9eff:fe15:f999 on interface v20, lg1 added
May 29 11:35:22:042670:info:fi_debug:debug_logs:1:1003196986164737: PIM-NBR.VRF0: GenId changed for
Neighbor fe80::d6c1:9eff:fe15:f999 on interface v20, lg1 ; new GenId 1599030656
May 29 11:35:22:042562:info:fi_debug:debug_logs:1:1003196986164737: PIM-NBR.VRF0: Neighbor
fe80::d6c1:9eff:fe15:f999 on interface v20, lg1 genid changed from 2695936639 to 1599030656
May 29 11:35:22:040830:info:fi_debug:debug_logs:1:1003196986164737: PIM.VRF0: Rx Hello msg from
fe80::d6c1:9eff:fe15:f999 on intf v20, lg1
May 29 11:35:21:992606:info:fi_debug:debug_logs:1:1003188396230145: PIM-NBR.VRF1: Neighbor
fe80::d6c1:9eff:fe15:f999 on interface v21, lg1 added
May 29 11:35:21:989672:info:fi_debug:debug_logs:1:1003188396230145: PIM-NBR.VRF1: GenId changed for
Neighbor fe80::d6c1:9eff:fe15:f999 on interface v21, lg1 ; new GenId 866894994
May 29 11:35:21:989557:info:fi_debug:debug_logs:1:1003188396230145: PIM-NBR.VRF1: Neighbor
fe80::d6c1:9eff:fe15:f999 on interface v21, lg1 genid changed from 3428072301 to 866894994
May 29 11:35:21:987511:info:fi_debug:debug_logs:1:1003188396230145: PIM.VRF1: Rx Hello msg from
fe80::d6c1:9eff:fe15:f999 on intf v21, lg1
May 29 11:35:20:992019:info:fi_debug:debug_logs:1:1003119676753409: ** Warning ** IPv6 - rcvd PIM V2
packet on v21. Interface is disabled.
May 29 11:35:20:991877:info:fi_debug:debug_logs:1:1003115381786113: ** Warning ** IPv6 - rcvd PIM V2
packet on v20. Interface is disabled.
May 29 11:35:20:924054:info:fi_debug:debug_logs:1:1003089611982337: ** Warning ** IPv6 - rcvd PIM V2
packet on v21. Interface is disabled.
May 29 11:35:20:906631:info:fi_debug:debug_logs:1:1003068137145857: MLD: [ Port lg1 ] Query version
mismatch. Received query version 2 from fe80::d6c1:9eff:fe15:f999; Port version 1.
May 29 11:35:20:906441:info:fi_debug:debug_logs:1:1003063842178561: ** Warning ** IPv6 - rcvd PIM V2
packet on v20. Interface is disabled.
May 29 11:34:33:751694:info:fi_debug:debug_logs:1:10736920023794432: PIM-NBR.VRF1: Neighbor
fe80::d6c1:9eff:fe15:f999 on interface v21, lg1 deleted on port-down
May 29 11:34:33:751147:info:fi_debug:debug_logs:1:10736920023794432: PIM-NBR.VRF0: Neighbor
fe80::d6c1:9eff:fe15:f999 on interface v20, lg1 deleted on port-down
May 29 11:34:33:750413:info:fi_debug:debug_logs:1:10736920023794432: PIM.VRF0:
(fe80::d6c1:9eff:fe15:f999 3111::12) Nbr ffile::5:1 moved; changing parent_phy_port from lg1 to INVALID
```

History

Release version	Command history
09.0.00	This command was modified to change the option nbr-change to nbr .

debug ipv6 pim packet

Displays debugging information about the IPv6 PIM packets.

Syntax

```
debug ipv6 pim packetsource_address group_address [rate]
no debug ipv6 pim packetsource_address group_address [rate]
```

Parameters

source_address
Specifies the IPv6 source address of the PIM packet.

group_address
Specifies the IPv6 group address of the PIM packet.

rate
Specifies the hardware rate.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim level 3
device#debug ipv6 pim packet 3111::12 ff1e::5:1 5
May 29 11:48:14:387969:info:fi_debug:debug_logs:1:1066715257505281: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:387877:info:fi_debug:debug_logs:1:1066715257505281: Rx Pkt (3111::12, ff1e::5:1) on
v20 (1/1/1). hit=0
May 29 11:48:14:387636:info:fi_debug:debug_logs:1:1066710962537985: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:387542:info:fi_debug:debug_logs:1:1066710962537985: Rx Pkt (3111::12, ff1e::5:1) on
v20 (1/1/1). hit=0
May 29 11:48:14:387293:info:fi_debug:debug_logs:1:1066706667570689: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:387194:info:fi_debug:debug_logs:1:1066706667570689: Rx Pkt (3111::12, ff1e::5:1) on
v20 (1/1/1). hit=0
May 29 11:48:14:386918:info:fi_debug:debug_logs:1:1066702372603393: (3111::12,ff1e::5:1), pkt
incoming at v20, REG: OFF, FWD_FAST: OFF, hw_drop: ON
May 29 11:48:14:386823:info:fi_debug:debug_logs:1:1066702372603393: send MCAST_FIRST_DATA: entry phy
port: INVALID, pkt input port: lg1. SPT-F, FAST-F, MCT IIF Flag: F.
May 29 11:48:14:386518:info:fi_debug:debug_logs:1:1066702372603393: Rx flow on intf/port diff than
entry's intf v20 or port INVALID
May 29 11:48:14:386443:info:fi_debug:debug_logs:1:1066702372603393: Rx Pkt (3111::12, ff1e::5:1) on
v20 (1/1/1). hit=0
May 29 11:48:14:386119:info:fi_debug:debug_logs:1:1066698077636097: LP sends create nfn to MP for
intermediate (3111::12,ff1e::5:1) as hw drop route, pkt incoming at v20
May 29 11:48:14:385630:info:fi_debug:debug_logs:1:1066698077636097: pimsm, fail longest_match,drop
packet
May 29 11:48:14:385497:info:fi_debug:debug_logs:1:1066698077636097: Rx Pkt (3111::12, ff1e::5:1) on
v20 (1/1/1). hit=0
May 29 11:48:14:365293:info:fi_debug:debug_logs:1:107374182401: Cleanup Ended : 2021 May 29 10:48:13
May 29 11:48:14:364622:info:fi_debug:debug_logs:1:107374182401: Cleanup Started : 2021 May 29 10:48:13
```

debug ipv6 pim regproc

Controls IPv6 PIM register processing.

Syntax

debug ipv6 pim regproc

no debug ipv6 pim regproc

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim regproc
PIM6 regproc debugging is on
Apr 17 18:51:09:212526:info:fi_debug:debug_logs:1:68082816553845504: PIMSM-REG.VRF0: (10::11 ff1e::1:4)
Sending L2-Null Reg on iface v10
Apr 17 18:50:09:341680:info:fi_debug:debug_logs:1:68032385047855872: PIMSM-REG.VRF0: (10::11 ff1e::1:4)
Sending L2-Null Reg on iface v10"
```

debug ipv6 pim rp

Controls the Rendezvous Point (RP) processing for IPv6 PIM events.

Syntax

debug ipv6 pim rp

no debug ipv6 pim rp

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim rp
Apr 17 18:34:06:102442:info:fi_debug:debug_logs:1:67222410050405120: PIMv6-RP.VRF0: processing C-RP-adv
from 99::11. PrefCnt 1
Apr 17 18:34:06:102358:info:fi_debug:debug_logs:1:67222410050405120: PIMv6-RP.VRF0: Looping C-RP-Adv
msg from fe80::d6c1:9eff:fe4a:2114 back to elected BSR (me)"
```

debug ipv6 pim show

Displays the IPv6 PIM debug settings.

Syntax

debug ipv6 pim show

no debug ipv6 pim show

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim event
PIM6 event debugging is on
device#
device#debug ipv6 pim show
debug ipv6 pim event
```

debug ipv6 pim source

Displays the IPv6 PIM related debugging information for the specified source address.

Syntax

```
debug ipv6 pim source ipaddr
```

```
no debug ipv6 pim source ipaddr
```

Parameters

ipaddr

Specifies the source IP address.

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 pim source 10::11
PIM6 source 10::11 debugging is on
Apr 17 18:40:30:729083:info:fi_debug:debug_logs:1:7821393144055297: stack: 00549994 0114c014 011547b0
011567b0 01158654 0115a1e0 011af8ac 005c3a0c 005c446c 011b39fc b6d22eb0 b6f31195
Apr 17 18:40:30:728992:info:fi_debug:debug_logs:1:7821393144055297: PIM.VRF0: Allocation of hw
resources for (10::11 ff1e::1:4) successful. olist empty. FID 0x4fff (D). MVID Drop
Apr 17 18:40:30:728835:info:fi_debug:debug_logs:1:7821393144055297: PIMSM.VRF0: receive first data,
(10::11 ff1e::1:4) entry. RP 99::11. Flags 0x4288c1
Apr 17 18:40:30:727724:info:fi_debug:debug_logs:1:7821393144055297: stack: 00549994 0114c014 01155220
01155a54 01156d54 0115a1e0 011af8ac 005c3a0c 005c446c 011b39fc b6d22eb0 b6f31195
Apr 17 18:40:30:727436:info:fi_debug:debug_logs:1:7821393144055297: PIM.VRF0: Allocation of hw
resources for (10::11 ff1e::1:4) successful. olist empty. FID 0x4fff (D). MVID Drop
Apr 17 18:40:30:727297:info:fi_debug:debug_logs:1:7821393144055297: PIM.VRF0: (S,G) entry (10::11 ff1e::
1:4) created. Src Local. RP 99::11. Flags 0x4288c0. Sent L2 regist"
```

debug ipv6 pim vrf

Displays the IPv6 PIM related debugging information for the specified VRF.

Syntax

debug ipv6 pim vrf*vrf_name*

no debug ipv6 pim vrf*vrf_name*

Modes

Privileged EXEC mode

Examples

```
device#debug ipv6 pim vrf SP_TN
device#debug ipv6 pim add-del-oif
device#debug ipv6 pim event
device#debug ipv6 pim join-prune
May 29 11:39:55:499149:info:fi_debug:debug_logs:1:1027046939559425: PIM.VRF1: OIF Add v11,3/1/5 to
(31::22,ffle::9:10) entry - receivers mbrship type 1
May 29 11:39:55:498997:info:fi_debug:debug_logs:1:1027046939559425: PIMSM.VRF1: OIF FSM 1 for (*,
ffle::9:10) entry Reason(IgmpGrpJoin), Action(Update), flagAction(1) CurrentState(0x4) NewState(0x4)
May 29 11:39:54:930103:info:fi_debug:debug_logs:1:11007399884227328: PIM: End sending Join/Prune msg
---
May 29 11:39:54:929623:info:fi_debug:debug_logs:1:11007399884227328: J-Src: 31::22, wc=0 rpt=0 SM=1
May 29 11:39:54:929549:info:fi_debug:debug_logs:1:11007399884227328: PIM-JP.VRF1: Group: ffile::9:10,
JoinSrcs: 1, PruneSrcs: 0
May 29 11:39:54:929442:info:fi_debug:debug_logs:1:11007399884227328: PIM-JP.VRF1: BEGIN SENDING Join/
Prune msg to fe80::d6c1:9eff:fe15:f999 on v21
May 29 11:39:54:716279:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: OIF Update Fwdmask:
Added FwdPort L3OIF v11,3/1/5 to (31::22,ffle::9:10) Action(Add)
May 29 11:39:54:716200:info:fi_debug:debug_logs:1:1026991104984577: PIM-OIF.VRF1: (31::22,ffle::9:10)
Entry Flags 0x600680e1: Add 3/1/5 on 11 (L3). OIF_FLAGS: 4
May 29 11:39:54:716107:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: OIF Update Fwdmask:
Added FwdPort L3OIF v11,3/1/5 to (*,ffle::9:10) Action(Add)
May 29 11:39:54:716008:info:fi_debug:debug_logs:1:1026991104984577: PIM-OIF.VRF1: (* ffile::9:10) Entry
Flags 0x2604a0: Add 3/1/5 on 11 (L3). OIF_FLAGS: 4
May 29 11:39:54:715608:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: OIF Update Fwdmask:
Added FwdPort L3OIF v11,3/1/5 to (31::22,ffle::9:10) Action(Add)
May 29 11:39:54:715535:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: Update oifflg v111/3/1/5
(31::22,ffle::9:10), rcode(IgmpGrpJoin), Act(Add) cstate(0x0) nstate(0x4) newflg 0x4, #immoifs 0
#bldoifs 0 #inhoifs 1 #fwdoifs 0 sync 1
May 29 11:39:54:715455:info:fi_debug:debug_logs:1:1026991104984577: PIM-OIF.VRF1: (31::22,ffle::9:10)
Entry Flags 0x200280e1: Add 3/1/5 on 11 (L3). OIF_FLAGS: 4
May 29 11:39:54:715381:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: Add OIF: Adding L3OIF
v11,3/1/5 to (31::22,ffle::9:10), Reason(IgmpGrpJoin) Action(Add) CurrentState(0x0) NewState(0x4)
holdtime 260
May 29 11:39:54:715306:info:fi_debug:debug_logs:1:1026991104984577: PIMSM.VRF1: OIF FSM 1 case for
(31::22,ffle::9:10) entry Reason(IgmpGrpJoin), Action(Add) flagAction 3 CurrentState(0x0)
NewState(0x4)
May 29 11:39:54:715220:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: OIF Add v11,3/1/5 to
(31::22,ffle::9:10) entry - receivers mbrship type 1
May 29 11:39:54:715107:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: OIF Update Fwdmask:
Added FwdPort L3OIF v11,3/1/5 to (*,ffle::9:10) Action(Add)
May 29 11:39:54:715031:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: Update oifflg v111/3/1/5
(*,ffle::9:10), rcode(IgmpGrpJoin), Act(Add) cstate(0x0) nstate(0x4) newflg 0x4, #immoifs 1 #bldoifs 0
#inhoifs 0 #fwdoifs 1 sync 1
May 29 11:39:54:714944:info:fi_debug:debug_logs:1:1026991104984577: PIM-OIF.VRF1: (* ffile::9:10) Entry
Flags 0x220080: Add 3/1/5 on 11 (L3). OIF_FLAGS: 4
May 29 11:39:54:714866:info:fi_debug:debug_logs:1:1026991104984577: PIM.VRF1: Add OIF: Adding L3OIF
v11,3/1/5 to (*,ffle::9:10), Reason(IgmpGrpJoin) Action(Add) CurrentState(0x0) NewState(0x4) holdtime
260
May 29 11:39:54:714782:info:fi_debug:debug_logs:1:1026991104984577: PIMSM.VRF1: OIF FSM 1 for (*,
ffle::9:10) entry Reason(IgmpGrpJoin), Action(Add), flagAction(1) CurrentState(0x0) NewState(0x4)
May 29 11:39:54:714656:info:fi_debug:debug_logs:1:1026991104984577: PIMSM.VRF1: Created (* ffile::9:10)
entry. Parent ffile::9:10. RP=NULL. LIFid 141292112. Flags 0x0
May 29 11:39:54:714580:info:fi_debug:debug_logs:1:1026991104984577: Suppressed 1 times: PIM-ENTRY.VRF1:
Deleting entry (* ffile::9:10)
May 29 11:39:54:159535:info:fi_debug:debug_logs:1:11006794293838592: PIM-ENTRY.VRF1: Deleting entry (*
ffle::9:10)
May 29 11:39:54:159460:info:fi_debug:debug_logs:1:11006794293838592: Entry (* ffile::9:10) timed out as
it has no OIFs, vrf 1
May 29 11:39:54:159377:info:fi_debug:debug_logs:1:11006794293838592: Suppressed 1 times: PIM.VRF1: OIF
Update Fwdmask: Removed FwdPort L3OIF v11,3/1/5 to (31::22,ffle::9:10) Action(Remove)
May 29 11:39:47:944844:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: OIF Update Fwdmask:
Removed FwdPort L3OIF v11,3/1/5 to (31::22,ffle::9:10) Action(Remove)
May 29 11:39:47:944762:info:fi_debug:debug_logs:1:11001554433737472: PIM-OIF.VRF1: (31::22,ffle::9:10)
Entry Flags 0x200280e1: Del 3/1/5 on 11 (L3). OIF_FLAGS: 0 DelIf. #Ifs 1
May 29 11:39:47:944710:info:fi_debug:debug_logs:1:11001554433737472: Suppressed 1 times: PIM.VRF1: OIF
Update Fwdmask: Removed FwdPort L3OIF v11,3/1/5 to (*,ffle::9:10) Action(Remove)
May 29 11:39:47:944547:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: OIF Update Fwdmask:
Removed FwdPort L3OIF v11,3/1/5 to (*,ffle::9:10) Action(Remove)
May 29 11:39:47:944413:info:fi_debug:debug_logs:1:11001554433737472: PIM-OIF.VRF1: (* ffile::9:10) Entry
```

```

Flags 0x2200a0: Del 3/1/5 on 11 (L3). OIF_FLAGS: 0 DelIf. #Ifs 1
May 29 11:39:47:921003:info:fi_debug:debug_logs:1:11001554433737472: PIM: End sending Join/Prune msg
---
May 29 11:39:47:920589:info:fi_debug:debug_logs:1:11001554433737472: P-Src: 31::22, wc=0 rpt=0 SM=1
May 29 11:39:47:920516:info:fi_debug:debug_logs:1:11001554433737472: PIM-JP.VRF1: Group: ffile::9:10,
JoinSrcs: 0, PruneSrcs: 1
May 29 11:39:47:920440:info:fi_debug:debug_logs:1:11001554433737472: PIM-JP.VRF1: BEGIN SENDING Join/
Prune msg to fe80::d6c1:9eff:fe15:f999 on v21
May 29 11:39:47:920255:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: Remove OIF: Removed
L3OIF v11,3/1/5 from (31::22, ffile::9:10) entry, remove_now=1, Reason(IgmpGrpLeave)
Action(Remove) CurrentState(0x4) NewState(0x0)
May 29 11:39:47:920110:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: OIF Update Fwdmask:
Removed FwdPort L3OIF v11,3/1/5 to (31::22,ffile::9:10) Action(Remove)
May 29 11:39:47:920036:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: Update oifflg v11/3/1/5
(31::22,ffile::9:10), rcode(IgmpGrpLeave), Act(Remove) cstate(0x4) nstate(0x0) newflg 0x0, #immoifs 0
#bldoifs 0 #inhoifs 0 #fwdoids 65535 sync 2
May 29 11:39:47:919956:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: OIF Update Fwdmask:
Removed FwdPort L3OIF v11,3/1/5 to (31::22,ffile::9:10) Action(Remove)
May 29 11:39:47:919876:info:fi_debug:debug_logs:1:11001554433737472: PIM-OIF.VRF1: (31::22 ffile::9:10)
Entry Flags 0x200680e1: Del 3/1/5 on 11 (L3). OIF_FLAGS: 0 DelIf. #Ifs 1
May 29 11:39:47:919795:info:fi_debug:debug_logs:1:11001554433737472: PIMSM.VRF1: OIF FSM 0 case for
(31::22, ffile::9:10) entry Reason(IgmpGrpLeave), Action(Remove) flagAction 3 CurrentState(0x4)
NewState(0x0)
May 29 11:39:47:919709:info:fi_debug:debug_logs:1:11001554433737472: PIMSM.VRF1: Deleting oif v11,3/1/5
from (31::22 ffile::9:10) entry, reason 9
May 29 11:39:47:919602:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: Remove OIF: Removed
L3OIF v11,3/1/5 from (*, ffile::9:10) entry, remove_now=1, Reason(IgmpGrpLeave) Action(Remove)
CurrentState(0x4) NewState(0x0)
May 29 11:39:47:919492:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: OIF Update Fwdmask:
Removed FwdPort L3OIF v11,3/1/5 to (*,ffile::9:10) Action(Remove)
May 29 11:39:47:919413:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: Update oifflg v11/3/1/5
(*,ffile::9:10), rcode(IgmpGrpLeave), Act(Remove) cstate(0x4) nstate(0x0) newflg 0x0, #immoifs 0
#bldoifs 0 #inhoifs 0 #fwdoids 0 sync 2
May 29 11:39:47:919324:info:fi_debug:debug_logs:1:11001554433737472: PIM.VRF1: OIF Update Fwdmask:
Removed FwdPort L3OIF v11,3/1/5 to (*,ffile::9:10) Action(Remove)
May 29 11:39:47:919232:info:fi_debug:debug_logs:1:11001554433737472: PIM-OIF.VRF1: (* ffile::9:10) Entry
Flags 0x2604a0: Del 3/1/5 on 11 (L3). OIF_FLAGS: 0 DelIf. #Ifs 1
May 29 11:39:47:919131:info:fi_debug:debug_logs:1:11001554433737472: PIMSM.VRF1: OIF FSM 0 for (*,
ffile::9:10) entry Reason(IgmpGrpLeave), Action(Remove), flagAction(2) CurrentState(0x4) NewState(0x0)
May 29 11:39:47:918505:info:fi_debug:debug_logs:1:11001554433737472: PIMSM.VRF1: Deleting oif v11,3/1/5
from (* ffile::9:10) entry, reason 9
May 29 11:39:45:293272:info:fi_debug:debug_logs:1:1026260960544257: PIM.VRF1: OIF Add v11,3/1/5 to
(31::22 ffile::9:10) entry - receivers mbrship type 1

```

History

Release version	Command history
09.0.00	This command was introduced.

debug ipv6 pimsm-snoop

Troubleshoots issues related to IPv6 PIM-SM snoop configurations.

Syntax

```
debug ipv6 pimsm-snoop [ add-del-oif | all | clear | control-source | error | fsm | group | join-prune | physical-port | show | source |  
stacktrace | timer | vlan ]
```

```
no debug ipv6 pimsm-snoop [ add-del-oif | all | clear | control-source | error | fsm | group | join-prune | physical-port | show | source  
| stacktrace | timer | vlan ]
```

Parameters

add-del-oif

Displays debugs related to the addition and deletion of outbound interfaces (OIFs) in Mcache.

all

Enables all PIM-SM snoop related debugs.

clear

Clears all PIM-SM snoop related debug settings.

control-source

Displays PIM-SM snooping related debug information for the specified control source address.

error

Monitors error messages related to PIM-SM snooping.

fsm

Enables debugging of Finite State Machine (FSM) transactions.

group

Displays PIM-SM snooping information for a specific group.

join-prune

Monitors PIM-SM snoop join and prune messages.

physical-port

Displays information of PIM-SM physical ports that are connected.

show

Displays all PIM-SM snoop related debug settings.

source

Displays PIM-SM snooping related debug information for the specified server source address.

stacktrace

Displays debug messages accompanied by call stack dump.

timer

Enables PIM-SM snoop timer debugging.

vlan

Enables PIM-SM snoop debugging for a particular VLAN.

Modes

- Privileged EXEC mode
- Global configuration mode

Usage Guidelines

Examples

The following is sample output from the debug ipv6 pimsm-snoop timer command.

```
device# debug ipv6 pimsm-snoop timer
14d 6:29:33 - v6PSNOOP_SRC: PIMv2 Join/Prune from fe80::224:38ff:fe76:5180 to
upstream Neig-Addr fe80::224:38ff:fe77:7440 port 1/1/9 on vlan 503, holdtime 210,
payload length 70
14d 6:29:33 - v6PSNOOP_JP: Rcv Join-Prune Group : ff7e::1:2:3, #join src 1,
#prune src 0
14d 6:29:33 - v6PSNOOP_JP: join source 2222::22 flags: S WC RPT
14d 6:29:33 - v6PSNOOP_JP: Rcv Join: (* ff7e::1:2:3) -> 1/1/4
14d 6:29:33 - v6PSNOOP_FSM: (* G) Join for SG_RPT(3000::10, ff7e::1:2:3, 503),
oif(1/1/4): NI -> NI
14d 6:29:33 - v6PSNOOP_TIMER: timer restart: 217 ticks, timer type: old SG -> new
SG, fsm state: J
14d 6:29:33 - v6PSNOOP_FSM: RCV_SG(*, ff7e::1:2:3, 503), oif(1/1/4): J -> J
```

debug ipv6 ra

Enables router advertisement (RA) message debug logs and displays the debugging information about ingoing and outgoing RA messages.

Syntax

debug ipv6 ra

no debug ipv6 ra

Modes

Privileged EXEC mode

Usage Guidelines

The no form of the command disables the RA debug logs.

Examples

The following example displays debugging information for Recursive DNS server (RDNSS) address entries in an RA message.

```
device# debug ipv6 ra
...
ICMPv6-RA:  DNS server list with lifetime 400
             [1] DNS address 1::1
             [2] DNS address 1::2
ICMPv6-RA:  DNS server list with lifetime 800
             [1] DNS address 1::5
             [2] DNS address 1::6
ICMPv6-RA:  DNS server list with lifetime 1200
             [1] DNS address 1::3
             [2] DNS address 1::4
...
```

The following example displays debugging information for Domain Name System Search List (DNSSL) entries in an RA message.

```
device# debug ipv6 ra
...
ICMPv6-RA:  Domain Name list with lifetime 400
             [1] Domain Name a.com
             [2] Domain Name b.com
             [3] Domain Name c.com
             [4] Domain Name d.com

ICMPv6-RA:  Domain Name list with lifetime 800
             [1] Domain Name h.com
             [2] Domain Name i.com
             [3] Domain Name j.com
             [4] Domain Name k.com
             [5] Domain Name l.com

ICMPv6-RA:  Domain Name list with lifetime 1200
             [1] Domain Name e.com
             [2] Domain Name f.com
...
```

History

Release version	Command history
08.0.80	This command was modified to display information about DNSSL and RDNSS entries.

debug ipv6 raguard

Enables RA guard debug messages.

Syntax

debug ipv6 raguard

no debug ipv6 raguard

Modes

Privileged EXEC mode

Examples

```
device# debug ipv6 raguard
00 days 00h40m49s:I:RAGuard: prefix in router advertisement rejected by
prefix-list
00 days 00h40m49s:I:RAGuard: prefix in router advertisement passed prefix-list
00 days 00h40m49s:I:RAGuard: Packet received on Host port 1/1/5. Dropped.
00 days 00h40m49s:I:RAGuard: Packet received on a Trusted port 1/1/5. Forward.
00 days 00h40m49s:I:RAGuard: Packet preference is greater than policy configured
maximum on port 1/1/5, vlan 10
00 days 00h40m49s:I:RAGuard: IPv6 address of packet matches Whitelist
fe80:100::100:1 on port 1/1/5, vlan 10
00 days 00h40m49s:I:RAGuard: IPv6 address of the packet does not match the
whitelist fe80:100::100:1 on port 1/1/5, vlan 10
00 days 00h40m49s:I:RAGuard: packet passes prefix-list examplelist1 on port 1/1/5,
vlan 10
00 days 00h40m49s:I:RAGuard: packet does not pass prefix-list examplelist1 on port
1/1/5, vlan 10
00 days 00h40m49s:I:RAGuard: prefix-list examplelist1 on policy examplepolicy1
not found
00 days 00h40m49s:I:RAGuard: Not enabled for vlan 10, port 1/1/5
00 days 00h40m49s:I:RAGuard: Feature ON for vlan 10, port 1/1/5
```

debug ipv6 rip events

Displays debugging information about the IPv6 Routing Information Protocol (RIP) events.

Syntax

debug ipv6 rip events

no debug ipv6 rip events

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 rip events
device(config-vif-11)# RIPng: update timer expired
clear ipv routeRIPng: triggered update
RIPng: garbage prefix 2001:DB8::/64 timer 1, metric 0, tag 0
from :: on interface NULL
RIPng: garbage prefix 2001:DB8::/64 timer 1, metric 0, tag 0
from :: on interface NULL
RIPng: Adding local connected route 2001:DB8::1/64 on interface v11
RIPng: Adding local connected route 2001:DB8::1/64 on interface v12
RIPng: update timer expired
RIPng: Redistribute add route 2001:DB8::/64, type CONNECTED (1/0)
RIPng: Redistribute add route 2001:DB8::/64, type CONNECTED (1/0)
```

debug ipv6 rip receive

Displays debugging information about the IPv6 RIP packets received.

Syntax

debug ipv6 rip receive

no debug ipv6 rip receive

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug ipv6 rip receive
device(config-vif-11)# RIPng: received packet from fe80::224:38ff:fe9f:7500 port
521 on interface v11
command response version 1 packet size 64
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
RIPng: received packet from fe80::224:38ff:fe9f:7500 port 521 on interface v12
command response version 1 packet size 64
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
RIPng: received packet from fe80::224:38ff:fe9f:7500 port 521 on interface v11
command response version 1 packet size 64
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
RIPng: received packet from fe80::224:38ff:fe9f:7500 port 521 on interface v11
command response version 1 packet size 64
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
RIPng: received packet from fe80::224:38ff:fe9f:7500 port 521 on interface v11
command response version 1 packet size 64
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
prefix 2001:DB8::/64 metric 1 tag 0
```

debug keychain

Enables keychain debugging.

Syntax

debug keychain { *keychain-name* | *key-id* | **all** | **config** | **error** | **events** | **show** }

no debug keychain { *keychain-name* | *key-id* | **all** | **config** | **error** | **events** | **show** }

Parameters

keychain-name

Enables debugging of all operations with a specific keychain name.

key-id

Enables debugging of all operations with a specific key ID of a keychain.

all

Enables debugging of all keychain instances.

config

Displays debugging during configuration.

error

Displays error messages from the keychain module.

events

Enables debugging of all timer-related events.

show

Displays the keychain debug settings.

Modes

Privileged EXEC mode

Usage Guidelines

If the key ID is under multiple keychains, the debug message will be displayed.

The **no** form of the command disables keychain debugging.

Examples

The following example prints debugging during configuration.

```
device# debug keychain config
keychain config debug is enabled
ICX7450-24 Router#conf t
ICX7450-24 Router(config)#keychain abc
Debug: Sep 21 13:32:37 KEYCHAIN_DEBUG_CONFIG: Keychain abc configuration success.
Debug: Sep 21 13:32:37 KEYCHAIN_DEBUG_CONFIG: Keychain configuration success conf type Keychain Create-Update-Delete
Debug: Sep 21 13:32:37 KEYCHAIN_DEBUG_CONFIG: Keychain configuration success keychain name abc
ICX7450-24 Router(config-keychain-abc)#
```

The following example enables debugging of all keychain instances.

```
device# debug keychain all
keychain all debug is enabled

Debug: Sep 21 13:41:02 Year: 2017, Mon: 9, Day: 21, Hour: 13, Min: 40, Sec: 0 TZone: 2 -- (Secs: 3714990000, SummTime: 3714990000, GMT: 0)
Debug: Sep 21 13:41:02 Year: 2017, Mon: 9, Day: 21, Hour: 13, Min: 42, Sec: 0 TZone: 2 -- (Secs: 3714990120, SummTime: 3714990120, GMT: 0)
Debug: Sep 21 13:41:02 Keychain abc Key-Id 1: Send key end duration 58 sec □ How long the key is going to be active
Debug: Sep 21 13:41:02 KEYCHAIN_DEBUG_EVENTS: Send Timer Started - Keychain abc Key-Id 1 Active 1, 29 sec
Debug: Sep 21 13:41:31 Year: 2017, Mon: 9, Day: 21, Hour: 13, Min: 40, Sec: 0 TZone: 2 -- (Secs: 3714990000, SummTime: 3714990000, GMT: 0)
Debug: Sep 21 13:41:31 Year: 2017, Mon: 9, Day: 21, Hour: 13, Min: 42, Sec: 0 TZone: 2 -- (Secs: 3714990120, SummTime: 3714990120, GMT: 0)
Debug: Sep 21 13:41:31 Keychain abc Key-Id 1: Send key end duration 29 sec
Debug: Sep 21 13:41:31 KEYCHAIN_DEBUG_EVENTS: Send Timer Started - Keychain abc Key-Id 1 Active 1, 14 sec
Debug: Sep 21 13:41:45 Year: 2017, Mon: 9, Day: 21, Hour: 13, Min: 40, Sec: 0 TZone: 2 -- (Secs: 3714990000, SummTime: 3714990000, GMT: 0)
Debug: Sep 21 13:41:45 Year: 2017, Mon: 9, Day: 21, Hour: 13, Min: 42, Sec: 0 TZone: 2 -- (Secs: 3714990120, SummTime: 3714990120, GMT: 0)
Debug: Sep 21 13:41:45 Keychain abc Key-Id 1: Send key end duration 15 sec □ 15 seconds
Debug: Sep 21 13:41:45 KEYCHAIN_DEBUG_EVENTS: Send Timer Started - Keychain abc Key-Id 1 Active 1, 7 sec
Debug: Sep 21 13:41:47 keychain tick Last Expire 15976056, Current 15977098 Diff 1042 Delta 212715814
```

History

Release version	Command history
08.0.70	This command was introduced.

debug lacp messages

Enables Link Aggregation Control Protocol (LACP) PDU debugging.

Syntax

```
debug lacp messages { rx-pdu | tx-pdu }
```

```
no debug lacp messages { rx-pdu | tx-pdu }
```

Parameters

rx-pdu

Enables debugging of LACP PDUs that are received.

tx-pdu

Enables debugging of LACP PDUs that are transmitted.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables LACP debugging.

Examples

The following example enables debugging of LACP Rx PDUs.

```
device#debug lacp messages rx-pdu
LACP Enabling packets Rx Debugging
Jul 06 08:38:30:092469:info:l2:lag:1:64607485292447233: LACP RX(port=2/1/12,T=7360803) -> PDU info
Jul 06 08:38:30:092602:debug:l2:lag:1:64607485292447233: AC SP1.609c.9fbc.14ac:PP1.PN10=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:30:092972:debug:l2:lag:1:64607485292447233: PA SP1.609c.9f1d.cbb0:PP1.PN26=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:30:097379:info:l2:lag:1:64607489587414529: LACP RX(port=1/1/11,T=7360803) -> PDU info
Jul 06 08:38:30:097501:debug:l2:lag:1:64607489587414529: AC SP1.609c.9fbc.14ac:PP1.PN 5=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:30:097577:debug:l2:lag:1:64607489587414529: PA SP1.609c.9f1d.cbb0:PP1.PN11=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:50:283802:info:l2:lag:1:551756381245408000: LACP TX(port=1/1/11,T=7361005,TX_count=24475)
Tx on VLAN 1, time from last Tx 301 (ticks) (debug_lacp_stop_tx=0,LACPCTRL_STOP_TX_PORTS=1) -> PDU
info(lacp_global_tx_count=48949)
Jul 06 08:38:50:283942:debug:l2:lag:1:551756381245408000: AC SP1.609c.9f1d.cbb0:PP1.PN11=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:50:284018:debug:l2:lag:1:551756381245408000: PA SP1.609c.9fbc.14ac:PP1.PN 5=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:50:284479:info:l2:lag:1:551756381245408000: LACP TX(port=2/1/12,T=7361005,TX_count=24474)
Tx on VLAN 1, time from last Tx 301 (ticks) (debug_lacp_stop_tx=0,LACPCTRL_STOP_TX_PORTS=1) -> PDU
info(lacp_global_tx_count=48950)
Jul 06 08:38:50:284576:debug:l2:lag:1:551756381245408000: AC SP1.609c.9f1d.cbb0:PP1.PN26=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:38:50:284646:debug:l2:lag:1:551756381245408000: PA SP1.609c.9fbc.14ac:PP1.PN10=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:39:00:191842:info:l2:lag:1:64610126697334273: LACP RX(port=2/1/12,T=7361104) -> PDU info
Jul 06 08:39:00:191973:debug:l2:lag:1:64610126697334273: AC SP1.609c.9fbc.14ac:PP1.PN10=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:39:00:192052:debug:l2:lag:1:64610126697334273: PA SP1.609c.9f1d.cbb0:PP1.PN26=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:39:00:192650:info:l2:lag:1:64610130992301569: LACP RX(port=1/1/11,T=7361104) -> PDU info
Jul 06 08:39:00:192743:debug:l2:lag:1:64610130992301569: AC SP1.609c.9fbc.14ac:PP1.PN 5=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
Jul 06 08:39:00:192815:debug:l2:lag:1:64610130992301569: PA SP1.609c.9f1d.cbb0:PP1.PN11=K20
(Act/LT/Agg/SYN/Col/Dist/UN-Def/UN-Exp)
```

debug license

Displays the package information on which the license has been loaded.

Syntax

debug license

no debug license

Modes

Privileged EXEC mode

Global configuration mode

Usage Guidelines

show license

Examples

After enabling debugging:

```
device# debug license
License all debugging ON
device# license delete unit unit id
device# license delete unit 1 all delete all software licenses
index software license index
device# license delet unit 1 index 2 Can't delete the license specified by index(2) -
141(LICENSE_IN_USE)
device# license delet unit 1 index 2
SYSLOG: <44> Dec 9 11:18:38 device Stack 1: The 'ICX7450-PREM-LIC-SW' license has been deleted
on this unit and is available for redeployment on another unit in accordance with the terms and
conditions of use. All features associated to this license must be disabled.

SYSLOG: <46> Dec 9 11:18:38 device License: Normal license package ICX7450-PREM-LIC-SW
with LID ENG08D21100 is removed on unit 1
device# show license
Index Lic Mode Lic Name Lid/Serial No Lic Type StatusLic Period Lic
Capacity
Stack unit 1:
2 Non-Node Lock ICX7450-PREM-LIC-SW EN09429C1D8 Normal Active Unlimited 1
Stack unit 12:
1 Non-Node Lock ICX7450-PREM-LIC-SW ENG08D21100 Normal Active Unlimited 1
```

debug loop-detect

Allows the RUCKUS devices to detect loops using the RUCKUS Port Loop Detection (PLD) protocol and disable a port that is on the receiving end of a loop. The loop is detected by sending Bridge Packet Data Unit (BPDU) test packets.

Syntax

debug loop-detect

no debug loop-detect

Usage Guidelines

Examples

The following example debugs loop detection.

```
device# debug loop-detect
device#show logging debug l2 l2hitless all all
Jun 11 12:01:52:400510:debug:l2:l2hitless:1:342924188452353: Loop-detection: port 1/1/20 (vlan=2), put
into errdisable state
Jun 11 12:01:47:400477:debug:l2:l2hitless:1:342894123681281: Loop-detection: port 1/2/2 (vlan=2), put
into errdisable state
Jun 11 12:01:46:401255:debug:l2:l2hitless:1:342881238779393: Loop-detection: port 1/2/1 (vlan=2), put
into errdisable state
Jun 11 12:01:39:329626:debug:l2:l2hitless:1:10532283126645504: [T=152567]send loop-detect to vlan2
Jun 11 12:01:38:329175:debug:l2:l2hitless:1:10531544392270592: [T=152557]send loop-detect to vlan2
Jun 11 12:01:37:329256:debug:l2:l2hitless:1:10530831427699456: [T=152547]send loop-detect to vlan2
Jun 11 12:01:36:334607:debug:l2:l2hitless:1:10530114168161024: [T=152537]send loop-detect to vlan2
Jun 11 12:01:35:334394:debug:l2:l2hitless:1:10529396908622592: [T=152527]send loop-detect to vlan2
Jun 11 12:01:34:330183:debug:l2:l2hitless:1:10528683944051456: [T=152517]send loop-detect to vlan2
Jun 11 12:01:33:334048:debug:l2:l2hitless:1:10527975274447616: [T=152507]send loop-detect to vlan2
Jun 11 12:01:32:382143:debug:l2:l2hitless:1:342842584073729: insert_disable primary 1/1/19, vlan=2
Jun 11 12:01:32:382028:debug:l2:l2hitless:1:342842584073729: Recv loop-detect from 1/1/19, vlan=2, pkt:
port=Nil, vlan=2
Jun 11 12:01:32:310693:debug:l2:l2hitless:1:342838289106433: Loop-detection: port lg1 (vlan=2), put
into errdisable state
Jun 11 12:01:32:310599:debug:l2:l2hitless:1:342838289106433: insert_disable primary lg1, vlan=2
Jun 11 12:01:32:310453:debug:l2:l2hitless:1:342838289106433: Recv loop-detect from 1/1/22, vlan=2, pkt:
port=Nil, vlan=2
Jun 11 12:01:32:299618:debug:l2:l2hitless:1:10527206475301632: [T=152496]send loop-detect to vlan2
Jun 11 12:01:31:299460:debug:l2:l2hitless:1:10526472035894016: [T=152486]send loop-detect to vlan2
Jun 11 12:01:30:299226:debug:l2:l2hitless:1:10525750481388288: [T=152476]send loop-detect to vlan2
Jun 11 12:01:29:302573:debug:l2:l2hitless:1:10525016041980672: [T=152466]send loop-detect to vlan2
Jun 11 12:01:28:299907:debug:l2:l2hitless:1:10524268717671168: [T=152456]send loop-detect to vlan2
Jun 11 12:01:27:299130:debug:l2:l2hitless:1:10523547163165440: [T=152446]send loop-detect to vlan2
Jun 11 12:01:26:299457:debug:l2:l2hitless:1:10522825608659712: [T=152436]send loop-detect to vlan2
Jun 11 12:01:25:300172:debug:l2:l2hitless:1:10522108349121280: [T=152426]send loop-detect to vlan2
Jun 11 12:01:24:324905:debug:l2:l2hitless:1:10521403974484736: port lg1 enabled
Jun 11 12:01:24:324693:debug:l2:l2hitless:1:10521403974484736: port 1/1/22 enabled
Jun 11 12:01:24:314172:debug:l2:l2hitless:1:10521403974484736: remove_disable lg1, vlan=2
Jun 11 12:01:24:314015:debug:l2:l2hitless:1:10521403974484736: port 1/1/21 enabled
```

debug loop-detect level

Debugs loop detection in a particular level.

Syntax

debug loop-detect level*decimal*

no debug loop-detect level*decimal*

Parameters

decimal

Specifies the level.

Examples

```

device# debug loop-detect
device#debug loop-detect level 3
device#no debug loop-detect level 3
device#no debug loop-detect port ethernet 1/1/19
device#no debug loop-detect port ethernet 1/2/1
device#show logging debug l2 l2hitless all all
Jun 11 12:01:52:400510:debug:l2:l2hitless:1:342924188452353: Loop-detection: port 1/1/20 (vlan=2), put
into errdisable state
Jun 11 12:01:47:400477:debug:l2:l2hitless:1:342894123681281: Loop-detection: port 1/2/2 (vlan=2), put
into errdisable state
Jun 11 12:01:46:401255:debug:l2:l2hitless:1:342881238779393: Loop-detection: port 1/2/1 (vlan=2), put
into errdisable state
Jun 11 12:01:39:329626:debug:l2:l2hitless:1:10532283126645504: [T=152567]send loop-detect to vlan2
Jun 11 12:01:38:329175:debug:l2:l2hitless:1:10531544392270592: [T=152557]send loop-detect to vlan2
Jun 11 12:01:37:329256:debug:l2:l2hitless:1:10530831427699456: [T=152547]send loop-detect to vlan2
Jun 11 12:01:36:334607:debug:l2:l2hitless:1:10530114168161024: [T=152537]send loop-detect to vlan2
Jun 11 12:01:35:334394:debug:l2:l2hitless:1:10529396908622592: [T=152527]send loop-detect to vlan2
Jun 11 12:01:34:330183:debug:l2:l2hitless:1:10528683944051456: [T=152517]send loop-detect to vlan2
Jun 11 12:01:33:334048:debug:l2:l2hitless:1:10527975274447616: [T=152507]send loop-detect to vlan2
Jun 11 12:01:32:382143:debug:l2:l2hitless:1:342842584073729: insert_disable primary 1/1/19, vlan=2
Jun 11 12:01:32:382028:debug:l2:l2hitless:1:342842584073729: Recv loop-detect from 1/1/19, vlan=2, pkt:
port=Nil, vlan=2
Jun 11 12:01:32:310693:debug:l2:l2hitless:1:342838289106433: Loop-detection: port lg1 (vlan=2), put
into errdisable state
Jun 11 12:01:32:310599:debug:l2:l2hitless:1:342838289106433: insert_disable primary lg1, vlan=2
Jun 11 12:01:32:310453:debug:l2:l2hitless:1:342838289106433: Recv loop-detect from 1/1/22, vlan=2, pkt:
port=Nil, vlan=2
Jun 11 12:01:32:299618:debug:l2:l2hitless:1:10527206475301632: [T=152496]send loop-detect to vlan2
Jun 11 12:01:31:299460:debug:l2:l2hitless:1:10526472035894016: [T=152486]send loop-detect to vlan2
Jun 11 12:01:30:299226:debug:l2:l2hitless:1:10525750481388288: [T=152476]send loop-detect to vlan2
Jun 11 12:01:29:302573:debug:l2:l2hitless:1:10525016041980672: [T=152466]send loop-detect to vlan2
Jun 11 12:01:28:299907:debug:l2:l2hitless:1:10524268717671168: [T=152456]send loop-detect to vlan2
Jun 11 12:01:27:299130:debug:l2:l2hitless:1:10523547163165440: [T=152446]send loop-detect to vlan2
Jun 11 12:01:26:299457:debug:l2:l2hitless:1:10522825608659712: [T=152436]send loop-detect to vlan2
Jun 11 12:01:25:300172:debug:l2:l2hitless:1:10522108349121280: [T=152426]send loop-detect to vlan2
Jun 11 12:01:24:324905:debug:l2:l2hitless:1:10521403974484736: port lg1 enabled
Jun 11 12:01:24:324693:debug:l2:l2hitless:1:10521403974484736: port 1/1/22 enabled
Jun 11 12:01:24:314172:debug:l2:l2hitless:1:10521403974484736: remove_disable lg1, vlan=2
Jun 11 12:01:24:314015:debug:l2:l2hitless:1:10521403974484736: port 1/1/21 enabled

```

debug loop-detect port

Debugs loop detection on a physical port or VLAN.

Syntax

```
debug loop-detect port { ethernet unit/slot/port | vlan vlan-id }
```

```
no debug loop-detect port { ethernet unit/slot/port | vlan vlan-id }
```

Parameters

ethernet*unit/slot/port*

Specifies the physical port.

vlan*vlan-id*

Specifies the VLAN.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables the loop detection on the physical port or VLAN.

Examples

```

device# debug loop-detect port vlan 2
Loop-detect vlan 2 debugging is on
device#debug loop-detect port vlan 2
Loop-detect debugging enabled for vlan :2
device#debug loop-detect port ethernet 1/1/19
Loop-detect debugging enabled for port :ethernet 1/1/19
device#debug loop-detect port ethernet 1/2/1
Loop-detect debugging enabled for port :ethernet 1/2/1
device#show logging debug l2 l2hitless all all
Jun 11 12:01:52:400510:debug:l2:l2hitless:1:342924188452353: Loop-detection: port 1/1/20 (vlan=2), put
into errdisable state
Jun 11 12:01:47:400477:debug:l2:l2hitless:1:342894123681281: Loop-detection: port 1/2/2 (vlan=2), put
into errdisable state
Jun 11 12:01:46:401255:debug:l2:l2hitless:1:342881238779393: Loop-detection: port 1/2/1 (vlan=2), put
into errdisable state
Jun 11 12:01:39:329626:debug:l2:l2hitless:1:10532283126645504: [T=152567]send loop-detect to vlan2
Jun 11 12:01:38:329175:debug:l2:l2hitless:1:10531544392270592: [T=152557]send loop-detect to vlan2
Jun 11 12:01:37:329256:debug:l2:l2hitless:1:10530831427699456: [T=152547]send loop-detect to vlan2
Jun 11 12:01:36:334607:debug:l2:l2hitless:1:10530114168161024: [T=152537]send loop-detect to vlan2
Jun 11 12:01:35:334394:debug:l2:l2hitless:1:10529396908622592: [T=152527]send loop-detect to vlan2
Jun 11 12:01:34:330183:debug:l2:l2hitless:1:10528683944051456: [T=152517]send loop-detect to vlan2
Jun 11 12:01:33:334048:debug:l2:l2hitless:1:10527975274447616: [T=152507]send loop-detect to vlan2
Jun 11 12:01:32:382143:debug:l2:l2hitless:1:342842584073729: insert_disable primary 1/1/19, vlan=2
Jun 11 12:01:32:382028:debug:l2:l2hitless:1:342842584073729: Recv loop-detect from 1/1/19, vlan=2, pkt:
port=Nil, vlan=2
Jun 11 12:01:32:310693:debug:l2:l2hitless:1:342838289106433: Loop-detection: port lg1 (vlan=2), put
into errdisable state
Jun 11 12:01:32:310599:debug:l2:l2hitless:1:342838289106433: insert_disable primary lg1, vlan=2
Jun 11 12:01:32:310453:debug:l2:l2hitless:1:342838289106433: Recv loop-detect from 1/1/22, vlan=2, pkt:
port=Nil, vlan=2
Jun 11 12:01:32:299618:debug:l2:l2hitless:1:10527206475301632: [T=152496]send loop-detect to vlan2
Jun 11 12:01:31:299460:debug:l2:l2hitless:1:10526472035894016: [T=152486]send loop-detect to vlan2
Jun 11 12:01:30:299226:debug:l2:l2hitless:1:10525750481388288: [T=152476]send loop-detect to vlan2
Jun 11 12:01:29:302573:debug:l2:l2hitless:1:10525016041980672: [T=152466]send loop-detect to vlan2
Jun 11 12:01:28:299907:debug:l2:l2hitless:1:10524268717671168: [T=152456]send loop-detect to vlan2
Jun 11 12:01:27:299130:debug:l2:l2hitless:1:10523547163165440: [T=152446]send loop-detect to vlan2
Jun 11 12:01:26:299457:debug:l2:l2hitless:1:10522825608659712: [T=152436]send loop-detect to vlan2
Jun 11 12:01:25:300172:debug:l2:l2hitless:1:10522108349121280: [T=152426]send loop-detect to vlan2
Jun 11 12:01:24:324905:debug:l2:l2hitless:1:10521403974484736: port lg1 enabled
Jun 11 12:01:24:324693:debug:l2:l2hitless:1:10521403974484736: port 1/1/22 enabled
Jun 11 12:01:24:314172:debug:l2:l2hitless:1:10521403974484736: remove_disable lg1, vlan=2
Jun 11 12:01:24:314015:debug:l2:l2hitless:1:10521403974484736: port 1/1/21 enabled
  
```

debug mac

Enables the Media Access Control (MAC) address debugging action.

Syntax

```
debug mac{ action number | mac mac-address | show }  
no debug mac{ action number | mac mac-address | show }
```

Parameters

actionnumber
Monitors the MAC action based on the specified level.

macmac-address
Specifies the MAC address for debugging.

show
Displays MAC address debug settings.

Modes

Privileged EXEC mode

Usage Guidelines

no

Examples

```
device# debug mac action 1  
MAC: ACTION debugging is on  
  
device#debug mac show  
debug mac action 3  
debug mac mac 0000.0000.0101  
debug mac hw-index 0
```

debug mecid

Displays debugging information for ME-CID Manager.

Syntax

debug mecid [all | cascade-port | error | event | flow | fsm | mecid | rx | show | tx]

no debug mecid [all | cascade-port | error | event | flow | fsm | mecid | rx | show | tx]

Parameters

all

Generates all debugging information related to ME-CID.

cascade-port

Enables debugging for a specific cascade port.

error

Displays ME-CID errors.

event

Displays ME-CID events.

flow

Displays ME-CID control flow.

fsm

Displays ME-CID FSM events.

mecid

Enables debugging for a specific ME-CID manager.

rx

Displays the ME-CID packets received from a Port Extender (PE).

show

Displays debugging information enabled for ME-CID.

tx

Displays the ME-CID packets sent to a Port Extender (PE).

Modes

Privileged EXEC mode

Examples

```
device# debug mecid all
9:9:28 - MECID_FSM: mecid 16360, FSM: DELETE_AW - > delete
9:9:28 - MECID_RX: Received E-Channel Register Response from PE 18 for ECID: 16360(Msg Id: 436), ECIDs
waiting for response : 24
9:9:28 - MECID_RX: Received E-Channel Register Response from PE 18 for ECID: 16331(Msg Id: 437), ECIDs
waiting for response : 23
9:9:28 - MECID_RX: Received E-Channel Register Response from PE 18 for ECID: 16324(Msg Id: 438), ECIDs
waiting for response : 22
9:9:28 - MECID_FSM: mecid 16346, FSM: DELETE_AW - > delete
9:9:28 - MECID_RX: Received E-Channel Register Response from PE 18 for ECID: 16346(Msg Id: 439), ECIDs
waiting for response : 21
9:9:28 - MECID_FSM: mecid 16358, FSM: DELETE_AW - > delete
9:9:28 - MECID_FSM: mecid 16360, FSM: DELETE_AW - > delete
9:9:27 - MECID_RX: Received E-Channel Register Response from PE 18 for ECID: 16347(Msg Id: 435), ECIDs
waiting for response : 0
9:9:28 - MECID_TX: PE 18 tx timer scheduled
stack: 1044264c 10a48824 10cf1120 10a48d60 10cf3f20 10cf4434 10d000fc 10a48ca0 10b94550 11ee536c
11f2b490
Tx Count: 1
Sending port array TLV to unit 18 (MsgId: 436)
  ECID: 16360, Number of Ports: 1
    1. Port: e18/1/3, Action: DELETE
.
.
.
(output truncated)
```

debug mem-leak

Enables or disables memory leak detection.

Syntax

```
debug mem-leak { off | on } [ process-name name ]
```

Parameters

off

Turns off memory leak tracking. This action will result in clearing all tracking results.

on

Turns on memory leak tracking.

process-name name

Specifies the name of the process for which you want to enable memory leak tracking.

Modes

Privileged EXEC mode

Examples

The following example turns on memory leak tracking for FastIron process.

```
device# debug mem-leak on
Start memory leak monitoring in FastIron
Tracking is on
Will automatically turn off after 3 months
```

The following example turns on memory leak tracking for poed process.

```
device# debug mem-leak on process-name poed
Start memory leak monitoring in poed
Tracking is on
Will automatically turn off after 3 months
```

The following example turns off memory leak tracking for poed process.

```
device# debug mem-leak off process-name poed
Stop memory leak monitoring in poed
tracking is off and all results are cleared
```

History

Release version	Command history
09.0.00	This command was introduced.

debug metro-ring bpdu

Monitors metro ring protocol (MRP) Bridge Packet Data Unit (BPDU) packets.

Syntax

debug metro-ring bpdu

no debug metro-ring bpdu

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables MRP BPDU packet monitoring.

Examples

The following example monitors MRP BPDU packets.

```
device# debug metro-ring bpdu
      bpdu: Trace debugging is on
device# show log debug l2 mrp all all
Jun 11 08:10:49:758081:debug:l2:mrp:1:68583152420353: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13151
Jun 11 08:10:49:657543:debug:l2:mrp:1:68578857453057: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13150
Jun 11 08:10:49:557831:debug:l2:mrp:1:68574562485761: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13149
Jun 11 08:10:49:457594:debug:l2:mrp:1:68570267518465: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13148
Jun 11 08:10:49:364263:debug:l2:mrp:1:68548792681985: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13147
Jun 11 08:10:49:265651:debug:l2:mrp:1:68544497714689: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13146
Jun 11 08:10:49:157606:debug:l2:mrp:1:68540202747393: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13145
Jun 11 08:10:49:059683:debug:l2:mrp:1:68535907780097: rhp-processing : MASTER(ring2) dropping
RHP(ring#2) sequence number 13144
```

debug metro-ring diags

Enables metro ring protocol (MRP) diagnostics.

Syntax

debug metro-ring diags

no debug metro-ring diags

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables MRP diagnostics.

Examples

The following example enables MRP diagnostics.

```
device# debug metro-ring diags
      diags:  diags debugging is on
device# show log debug l2 mrp all all
Jun 11 08:19:15:947823:debug:l2:mrp:1:94911301944833: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18186 has been lost. Reseting timers
Jun 11 08:19:15:363445:debug:l2:mrp:1:94868352271873: mrp-debug: mrp_diags_receive_packet. Diag frame
received when diags are untriggered
Jun 11 08:19:15:248229:debug:l2:mrp:1:94864057304577: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18180 has been lost. Reseting timers
Jun 11 08:19:14:648409:debug:l2:mrp:1:94838287500801: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18174 has been lost. Reseting timers
Jun 11 08:19:14:047981:debug:l2:mrp:1:94808222729729: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18168 has been lost. Reseting timers
Jun 11 08:19:13:448711:debug:l2:mrp:1:94765273056769: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18162 has been lost. Reseting timers
Jun 11 08:19:12:853484:debug:l2:mrp:1:94739503252993: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18156 has been lost. Reseting timers
Jun 11 08:19:12:248068:debug:l2:mrp:1:94713733449217: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18150 has been lost. Reseting timers
Jun 11 08:19:11:648217:debug:l2:mrp:1:94687963645441: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18144 has been lost. Reseting timers
Jun 11 08:19:11:047654:debug:l2:mrp:1:94645013972481: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18138 has been lost. Reseting timers
Jun 11 08:19:10:466977:debug:l2:mrp:1:94619244168705: mrp-debug: mrp_diags_receive_packet. rpdu with
sequence number 18132 has been lost. Reseting timers
```

debug metro-ring event

Displays debugging information about metro ring protocol (MRP) events.

Syntax

debug metro-ring event

no debug metro-ring event

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables MRP event debugging.

Examples

The following example displays debugging information about MRP events.

```
device# debug metro-ring event
      event:  events debugging is on
device# show log debug l2 mrp all all
Jun 11 08:33:23:352452:debug:l2:mrp:1:1516451659777: mrp_utils_prog_filter(T=27607) (caller_ring_id=2)
mode=0 -> 2 (MIR=2,TRAP=1)
Jun 11 08:33:19:825067:debug:l2:mrp:1:1512156692481: mrp_utils_prog_filter(T=27571) (caller_ring_id=2)
mode=2 -> 0 (MIR=2,TRAP=1)
Jun 11 08:31:46:160903:debug:l2:mrp:1:1776601451725568: mrp_utils_prog_filter(T=26635)
(caller_ring_id=2) mode=1 -> 2 (MIR=2,TRAP=1)
Jun 11 08:31:46:007792:debug:l2:mrp:1:1056890159105: mrp_utils_prog_filter(T=26633) (caller_ring_id=2)
mode=2 -> 1 (MIR=2,TRAP=1)
Jun 11 08:30:05:331676:debug:l2:mrp:1:1708367306294016: mrp_utils_prog_filter(T=25627)
(caller_ring_id=2) mode=1 -> 2 (MIR=2,TRAP=1)
Jun 11 08:30:05:180302:debug:l2:mrp:1:1001055584257: mrp_utils_prog_filter(T=25625) (caller_ring_id=2)
mode=2 -> 1 (MIR=2,TRAP=1)
Jun 11 08:26:05:306038:debug:l2:mrp:1:713292775425: mrp_utils_prog_filter(T=23226) (caller_ring_id=2)
mode=0 -> 2 (MIR=2,TRAP=1)
Jun 11 08:25:57:495209:debug:l2:mrp:1:696112906241: mrp_utils_prog_filter(T=23148) (caller_ring_id=2)
mode=2 -> 0 (MIR=2,TRAP=1)
Jun 11 08:25:37:376994:debug:l2:mrp:1:1506645577302784: mrp_utils_prog_filter(T=22947)
(caller_ring_id=2) mode=1 -> 2 (MIR=2,TRAP=1)
Jun 11 08:25:33:751927:debug:l2:mrp:1:631688396801: mrp_utils_prog_filter(T=22911) (caller_ring_id=2)
mode=2 -> 1 (MIR=2,TRAP=1)
```

debug metro-ring ring-id

Sets the ring ID for metro ring protocol (MRP) events.

Syntax

debug metro-ring ring-id *id*

no debug metro-ring ring-id *id*

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables the ring ID for MRP events.

Examples

The following example sets the ring ID for MRP events.

```
device# debug metro-ring ring-id 2
device# debug metro-ring event
      event:  events debugging is on
device(config)#no vlan 2device(config)#vlan 2 by port
      tagged ethe 1/1/19 to 1/1/20
      metro-ring ICX7450-48P Router(config-vlan-2)# tagged ethe 1/1/19 to 1/1/20
2
      master
      ring-interfaces ethernet 1/1/1Added tagged port(s) ethe 1/1/19 to 1/1/20 to port-vlan 2.
device(config-vlan-2)# metro-ring 2
9 ethernet 1/1/20
      enable
!device(config-vlan-2-mrp-2)# master
device(config-vlan-2-mrp-2)# ring-interfaces ethernet 1/1/19 ethernet 1/1/20
device(config-vlan-2-mrp-2)# enable
device(config-vlan-2-mrp-2)#!
device(config-vlan-2-mrp-2)#exit
device(config)#no vlan 3
device(config)#!
device(config)#vlan 3 by port
      tagged ethe 1/2/1 to 1/2/2
      metro-ring 3
      master
      ring-interfaces ethernet 1/2/1 ethernet 1/2/2
device(config-vlan-3)# tagged ethe 1/2/1 to 1/2/2
      enable
!Added tagged port(s) ethe 1/2/1 to 1/2/2 to port-vlan 3.
device(config-vlan-3)# metro-ring 3
device(config-vlan-3-mrp-3)# master
device(config-vlan-3-mrp-3)# ring-interfaces ethernet 1/2/1 ethernet 1/2/2
device(config-vlan-3-mrp-3)# enable
device(config-vlan-3-mrp-3)#exit
device# show log debug l2 mrp all all
Jun 11 08:44:43:575652:debug:l2:mrp:1:2303851636982528: mrp-debug(T=34409): (master) STOP TC for ring 2
Jun 11 08:44:43:280569:debug:l2:mrp:1:2362560217089: mrp_state_init: Exit-1 ring 2
Jun 11 08:44:43:279519:debug:l2:mrp:1:2362560217089: mrp_utils_update_ring_mac_in_cam(T=34406): called
for vlan_id 2 done hw_timer_gone=(0 msec)
Jun 11 08:44:43:279426:debug:l2:mrp:1:2362560217089: mrp_utils_add_ring_control_mac_in_hw : added
control mac for ring 2,vlan 2
Jun 11 08:44:43:279305:debug:l2:mrp:1:2362560217089: mrp_add_ring_rhp_mac_to_hw : Added rhp-mac for
ring 2
Jun 11 08:44:43:278295:debug:l2:mrp:1:2362560217089: mrp_utils_update_ring_mac_in_cam(T=34406): called
for vlan_id 2 done hw_timer_gone=(0 msec)
Jun 11 08:44:43:278167:debug:l2:mrp:1:2362560217089: mrp-debug(T=34406): ** state BLOCKING for port
1/1/20 in ring 2 (owner=2) **
Jun 11 08:44:43:267519:debug:l2:mrp:1:2362560217089: mrp_utils_update_ring_mac_in_cam(T=34406): called
for vlan_id 2 done hw_timer_gone=(0 msec)
Jun 11 08:44:43:267428:debug:l2:mrp:1:2362560217089: mrp-debug(T=34406): ** state FORWARDING for port
1/1/19 in ring 2 (owner=2) **
Jun 11 08:44:43:267340:debug:l2:mrp:1:2362560217089:
mrp_utils_change_oper_port(ring=2,primary=0,new_port=1/1/20)(T=34406)
Jun 11 08:44:43:267256:debug:l2:mrp:1:2362560217089: mrp_state_init(ring_id=2,port=#19(1/1/20),sec) get
oper_port=1/1/20 -> mrp_utils_change_oper_port
Jun 11 08:44:43:267164:debug:l2:mrp:1:2362560217089:
mrp_utils_change_oper_port(ring=2,primary=1,new_port=1/1/19)(T=34406)
Jun 11 08:44:43:267058:debug:l2:mrp:1:2362560217089: mrp_state_init(ring_id=2,port=#18(1/1/19),pri) get
oper_port=1/1/19 -> mrp_utils_change_oper_port
Jun 11 08:44:43:266805:debug:l2:mrp:1:2362560217089: mrp-debug: event - mrp_state_init vlan 2 stg 4
Jun 11 08:44:43:258092:debug:l2:mrp:1:2362560217089: mrp-debug: ** state INIT for ring 2 **
Jun 11 08:44:43:257964:debug:l2:mrp:1:2362560217089: mrp_state_init: Enter ring 2
Jun 11 08:44:43:198517:debug:l2:mrp:1:2358265249793:
mrp_utils_change_oper_port(ring=2,primary=0,new_port=1/1/20)(T=34405)
Jun 11 08:44:43:198424:debug:l2:mrp:1:2358265249793:
mrp_conf_add_ring_interface(ring_id=2,port=#19(1/1/20),sec) get oper_port=1/1/20 ->
mrp_utils_change_oper_port
Jun 11 08:44:43:198290:debug:l2:mrp:1:2358265249793:
mrp_conf_add_ring_interface(ring_id=2,port=#19(1/1/20),sec)
```

```

Jun 11 08:44:43:198198:debug:l2:mrp:1:2358265249793:
mrp_utils_change_oper_port(ring=2,primary=1,new_port=1/1/19) (T=34405)
Jun 11 08:44:43:198100:debug:l2:mrp:1:2358265249793:
mrp_conf_add_ring_interface(ring_id=2,port=#18(1/1/19),pri) get oper_port=1/1/19 ->
mrp_utils_change_oper_port
Jun 11 08:44:43:197890:debug:l2:mrp:1:2358265249793:
mrp_conf_add_ring_interface(ring_id=2,port=#18(1/1/19),pri)
Jun 11 08:44:43:082003:debug:l2:mrp:1:2349675315201: mrp_conf_add_ring_in_group(ring=2,vlan=2) ->
Install MRP_MAC_RANGE_FILTER_MIRROR
Jun 11 08:44:30:835167:debug:l2:mrp:1:2336790413313: mrp_utils_update_ring_mac_in_cam(T=34282): called
for vlan_id 2 done hw_timer_gone=(0 msec)
Jun 11 08:44:30:835051:debug:l2:mrp:1:2336790413313: mrp_add_ring_rhp_mac_to_hw : Deleted rhp-mac for
ring 2
Jun 11 08:44:30:834677:debug:l2:mrp:1:2336790413313: mrp_utils_delete_ring_control_mac_in_hw : no
control-mac to delete for ring 2,vlan 2
Jun 11 08:44:30:834524:debug:l2:mrp:1:2336790413313:
mrp_utils_change_oper_port(ring=2,primary=0,new_port=INVALID) (T=34282)
Jun 11 08:44:30:834323:debug:l2:mrp:1:2336790413313: mrp_conf_del_ring_interface(ring=2,port=#19(1/1/20)
Jun 11 08:44:30:834151:debug:l2:mrp:1:2336790413313:
mrp_utils_change_oper_port(ring=2,primary=1,new_port=INVALID) (T=34282)
Jun 11 08:44:30:833923:debug:l2:mrp:1:2336790413313: mrp_conf_del_ring_interface(ring=2,port=#18(1/1/19)
Jun 11 08:44:30:833805:debug:l2:mrp:1:2336790413313: mrp_state_end: Exit ring 2
Jun 11 08:44:30:832859:debug:l2:mrp:1:2336790413313: mrp_utils_update_ring_mac_in_cam(T=34282): called
for vlan_id 2 done hw_timer_gone=(0 msec)
Jun 11 08:44:30:832760:debug:l2:mrp:1:2336790413313: mrp-debug(T=34282): ** state FORWARDING for port
1/1/20 in ring 2 (owner=2) **
Jun 11 08:44:30:832616:debug:l2:mrp:1:2336790413313: mrp_utils_delete_ring_control_mac_in_hw : Deleted
control mac for ring 2,vlan 2
Jun 11 08:44:30:810245:debug:l2:mrp:1:2336790413313: mrp-debug: ** state END for ring 2 **
Jun 11 08:44:30:810141:debug:l2:mrp:1:2336790413313: mrp_state_end: Enter ring 2
Jun 11 08:43:13:827824:debug:l2:mrp:1:2242867396346624: mrp_tx(T=33512): ring 3, skip RHP/TC(0) seq=3059
Jun 11 08:43:13:727452:debug:l2:mrp:1:2242815856739072: mrp_tx(T=33511): ring 3, skip RHP/TC(0) seq=3058
Jun 11 08:43:13:628275:debug:l2:mrp:1:2242712777523968: mrp_tx(T=33510): ring 3, skip RHP/TC(0) seq=3057
Jun 11 08:43:13:527877:debug:l2:mrp:1:2242652647981824: mrp_tx(T=33509): ring 3, skip RHP/TC(0) seq=3056
Jun 11 08:43:13:427532:debug:l2:mrp:1:2242583928505088: mrp_tx(T=33508): ring 3, skip RHP/TC(0) seq=3055
Jun 11 08:43:13:327828:debug:l2:mrp:1:2242528093930240: mrp_tx(T=33507): ring 3, skip RHP/TC(0) seq=3054
Jun 11 08:43:13:228413:debug:l2:mrp:1:2242467964388096: mrp_tx(T=33506): ring 3, skip RHP/TC(0) seq=3053
Jun 11 08:43:13:144003:debug:l2:mrp:1:2242377770074880: mrp_tx(T=33505): ring 3, skip RHP/TC(0) seq=3052
Jun 11 08:43:13:028600:debug:l2:mrp:1:2242296165696256: mrp_tx(T=33504): ring 3, skip RHP/TC(0) seq=3051

```

debug metro-ring trace-l2

Enables metro ring protocol (MRP) trace debugging.

Syntax

debug metro-ring trace-l2

no debug metro-ring trace-l2

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the disables MRP trace debugging.

Examples

The following example enables MRP trace debugging.

```
device# debug metro-ring trace-l2
      trace-l2: trace-l2 debugging is on
```

debug metro-ring tx_bpdu

Debugs metro ring protocol (MRP) transmit BPDU packets.

Syntax

debug metro-ring tx_bpdu

no debug metro-ring tx_bpdu

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables MRP transmit BPDU packets debugging.

Examples

The following example debugs MRP transmit BPDU packets.

```
device# debug metro-ring tx_bpdu
      tx_bpdu: Trace debugging is on
device# show log debug l2 mrp all all
Jun 11 08:59:47:233117:debug:l2:mrp:1:2916786419794688: mrp_tx(T=43446,seq=3317): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(1 msec)
Jun 11 08:59:47:232069:debug:l2:mrp:1:2916786419794688: mrp_tx(T=43446,seq=6668): VLAN 3, ring 3
sending RHP tx_port 1/2/1 [fid = 0x40] hw_timer_gone=(103 msec)
Jun 11 08:59:47:128305:debug:l2:mrp:1:2916726290252544: mrp_tx(T=43445,seq=3316): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(0 msec)
Jun 11 08:59:47:127354:debug:l2:mrp:1:2916726290252544: mrp_tx(T=43445,seq=6667): VLAN 3, ring 3
sending RHP tx_port 1/2/1 [fid = 0x40] hw_timer_gone=(97 msec)
Jun 11 08:59:47:029732:debug:l2:mrp:1:2916644685873920: mrp_tx(T=43444,seq=3315): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(1 msec)
Jun 11 08:59:47:028133:debug:l2:mrp:1:2916644685873920: mrp_tx(T=43444,seq=6666): VLAN 3, ring 3
sending RHP tx_port 1/2/1 [fid = 0x40] hw_timer_gone=(99 msec)
Jun 11 08:59:46:928336:debug:l2:mrp:1:2916558786528000: mrp_tx(T=43443,seq=3314): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(0 msec)
Jun 11 08:59:46:927410:debug:l2:mrp:1:2916558786528000: mrp_tx(T=43443,seq=6665): VLAN 3, ring 3
sending RHP tx_port 1/2/1 [fid = 0x40] hw_timer_gone=(98 msec)
Jun 11 08:59:46:829009:debug:l2:mrp:1:2916528721756928: mrp_tx(T=43442,seq=3313): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(0 msec)
Jun 11 08:59:46:828080:debug:l2:mrp:1:2916528721756928: mrp_tx(T=43442,seq=6664): VLAN 3, ring 3
sending RHP tx_port 1/2/1 [fid = 0x40] hw_timer_gone=(93 msec)
Jun 11 08:59:46:734706:debug:l2:mrp:1:2916468592214784: mrp_tx(T=43441,seq=3312): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(6 msec)
Jun 11 08:59:46:728602:debug:l2:mrp:1:2916468592214784: mrp_tx(T=43441,seq=6663): VLAN 3, ring 3
sending RHP tx_port 1/2/1 [fid = 0x40] hw_timer_gone=(99 msec)
Jun 11 08:59:46:628690:debug:l2:mrp:1:2916412757639936: mrp_tx(T=43440,seq=3311): VLAN 2, ring 2
sending RHP tx_port 1/1/19 [fid = 0x12] hw_timer_gone=(0 msec)
```

debug mld-snoop

Displays Multicast Listener Discovery (MLD) snooping debugging information.

Syntax

```
debug mld-snoop [ detail | down-port | level num | mct [ phy-port | port ] [ ethernet unit/slot/port | lag lag-id ] | port-level num | [ rx | tx ] num | show-always | source source-address | vlan vlan-id ]
```

```
no debug mld-snoop [ detail | down-port | level num | mct [ phy-port | port ] [ ethernet unit/slot/port | lag lag-id ] | port-level num | [ rx | tx ] num | show-always | source source-address | vlan vlan-id ]
```

Parameters

detail

Displays detailed MLD snooping logs.

down-port

Monitors MLD snooping ports.

level *num*

Displays MLD snoop debugging information in detail.

mct

Displays MLD snoop debugging information related to MCT.

phy-port

Displays physical port level debugging information.

port

Displays information about the MSDP messages.

ethernet *unit/slot/port*

Specifies the interface.

lag *lag-id*

Specifies the LAG interface.

port-level *num*

Displays port-level packets.

rx *num*

Displays MLD snooping rx packets.

tx *num*

Displays MLD snooping tx packets.

show-always

Enables show command to ignore snoop enable check.

source *source-address*

Filters particular source packet.

vlan *vlan-id*

Displays VLAN level MLD snooping packets.

Modes

Privileged EXEC mode

Usage Guidelines

The **debug mld-snoop source** command must be enabled along with the **packet** option.

The **no** form of the command disables MLD snooping debugging.

Examples

The following example displays detailed MLD snooping logs.

```
device# debug mld-snoop detail
Jun 29 07:42:17:444270:info:fi_debug:debug_logs:1:36495867553777153: MLD del VL900 (e6/2/4) from group
entry ffile::70:1:1
Jun 29 07:42:17:444180:info:fi_debug:debug_logs:1:36495867553777153: tracking, all source gone, remove
immediately
Jun 29 07:42:17:444062:info:fi_debug:debug_logs:1:36495867553777153: MLD: rcvd Report-V2(ty=143)
#rec=1, pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4), mld_size=28
Jun 29 07:41:54:709145:info:fi_debug:debug_logs:1:13386216197064193: Suppressed 1 times: MLD: rcvd
Report-V2(ty=143) #rec=1, pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4), mld_size=28
```

The following example monitors MLD snooping ports.

```
device# debug mld-snoop down-port
May 28 17:49:47:481867:info:fi_debug:debug_logs:6:1959024778019584: stack: 008b30d8 00ac56d8 00a37620
00a5d680 00a5bb08 00a5bda4 00a36ce0 000aa530 0071aef8 0029d274 0009ac78 0009bb04 005c1380 005c2720
003add08 002ae808 003b8ca8 b6d81eb0 b6f88195
May 28 17:49:47:481735:info:fi_debug:debug_logs:6:1959024778019584: mcast_snoop_vport_state_notify:
vlan 1, port_type 0, port 6/2/4 event 1
May 28 17:49:46:681778:info:fi_debug:debug_logs:6:1958432072532736: stack: 008b30d8 00ac56d8 00a37620
00a5d680 00a5bb08 00a5bda4 00a36ce0 000aa530 0071aef8 0029d274 0009ac78 0009bb04 005c1380 005c2720
003add08 002ae808 003b8ca8 b6d81eb0 b6f88195
May 28 17:49:46:681653:info:fi_debug:debug_logs:6:1958432072532736: mcast_snoop_vport_state_notify:
vlan 900, port_type 0, port 6/2/4 event 1
May 28 17:49:16:662032:info:fi_debug:debug_logs:6:1935930738868992: MLD down VL900 (e6/2/4)
```

The following example displays MLD snoop debugging information in detail.

```
device# debug mld-snoop level 3
Jun 29 07:45:05:691513:info:fi_debug:debug_logs:1:36509783247816193: forward to router fid 4FFF
Jun 29 07:45:05:691441:info:fi_debug:debug_logs:1:36509783247816193: group: ffile::70:1:1, life = 620
Jun 29 07:45:05:691336:info:fi_debug:debug_logs:1:36509783247816193:
Jun 29 07:45:05:691274:info:fi_debug:debug_logs:1:36509783247816193: G=ffile::70:1:1, TO_EX, #_src=0
Jun 29 07:45:05:691162:info:fi_debug:debug_logs:1:36509783247816193: MLD: rcvd Report-V2(ty=143)
#rec=1, pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4), mld_size=28
```

debug mld-snoop add-del-oif all

Displays information about the addition or deletion of all the OIFs that are Multicast Listener Discovery (MLD) snooping-enabled.

Syntax

```
debug mld-snoop add-del-oif [all|stack]
```

```
no debug mld-snoop add-del-oif [all|stack]
```

Parameters

all

Monitors all groups.

stack

Displays stack trace.

Modes

Privileged EXEC mode

Examples

```
device# debug mld-snoop add-del-oif all
May 27 06:11:15:509757:info:fi_debug:debug_logs:1:1553798908610049: Create (2001::6 ff1e::10:1) vlan
900
May 27 06:11:07:612855:info:fi_debug:debug_logs:1:1551183273526785: Create (2001::8 ff1e::80:1:1) vlan
1000
May 27 06:14:47:192725:info:fi_debug:debug_logs:1:1572653815039489: Del e6/2/4 from (2001::6 ff1e::
10:1) vlan 900
May 27 06:14:47:190304:info:fi_debug:debug_logs:1:1572649520072193: Del e7/1/1 from (2001::8 ff1e::
80:1:1) vlan 1000

device#debug mld-snoop add-del-oif stack
May 27 06:26:45:057455:info:fi_debug:debug_logs:1:1638736181855745: stack: 008bc7d8 008b3998 00f28380
0055c294 00315dc8 00316200 002b4784 003ade20 002ae9dc 003b8ea8 b6db0eb0 b6fb7195
May 27 06:26:45:057333:info:fi_debug:debug_logs:1:1638736181855745: Create (2001::8 ff1e::80:1:1) vlan
1000
May 27 06:26:45:021638:info:fi_debug:debug_logs:1:1638242260616705: stack: 008bc7d8 008b3998 00f28380
0055c294 00315dc8 00316200 002b4784 003ade20 002ae9dc 003b8ea8 b6db0eb0 b6fb7195
May 27 06:26:45:021508:info:fi_debug:debug_logs:1:1638242260616705: Create (2001::6 ff1e::10:1) vlan
900
May 27 06:28:05:252959:info:fi_debug:debug_logs:1:949187772417: stack: 008bc160 008bc2b4 0089e2dc
000f14ac 0089ee60 0089f1d0 0089f450 0089e408 00123328 0089fa6c 005c1f14 005c2974 008ac1c4 b6db0eb0
b6fb7195
May 27 06:28:05:252839:info:fi_debug:debug_logs:1:949187772417: Delete (2001::8 ff1e::80:1:1) vlan 1000
May 27 06:28:05:249282:info:fi_debug:debug_logs:1:949187772417: stack: 008bc160 008bc2b4 0089e2dc
000f14ac 0089ee60 0089f1d0 0089f450 0089e408 00123328 0089fa6c 005c1f14 005c2974 008ac1c4 b6db0eb0
b6fb7195
May 27 06:28:05:249165:info:fi_debug:debug_logs:1:949187772417: Delete (2001::6 ff1e::10:1) vlan 900
```

debug mld-snoop clear

Clears all the MLD snooping debug settings.

Syntax

`debug mld-snoop clear`

`no debug mld-snoop clear`

Modes

Privileged EXEC mode

Examples

```
device# debug mld-snoop clear  
debug mld-snoop is disabled
```

debug mld-snoop error

Displays the MLD snooping multicast error messages.

Syntax

debug mld-snoop error

no debug mld-snoop error

Modes

Privileged EXEC mode

Examples

```
device# debug mld-snoop error
May 28 17:54:34:948001:info:fi_debug:debug_logs:6:0: Suppressed 3 times: MLD: Error : Ignoring MLD
version 2 Report pkt due to version mismatch , pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4),
mld_size=44
May_28 17:54:24:260167:info:fi_debug:debug_logs:6:246904784946694: MLD: Error : Ignoring MLD version 2
Report pkt due to version mismatch , pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4), mld_size=44
```

debug mld-snoop group

Displays the MLD snooping multicast group information.

Syntax

```
debug mld-snoop group group_address
```

```
no debug mld-snoop group group_address
```

Parameters

group_address

Specifies the address of the MLD snoop multicast group.

Modes

Privileged EXEC mode

Examples

```
device# debug mld-snoop group 2001:DB8::23:1
device# debug mld-snoop packet 2001::6 ff1e::70:1:1
Jun 29 07:34:43:152233:info:fi_debug:debug_logs:1:36454077521987073: Create (2001::6 ff1e::70:1:1)
vlan 900
Jun 29 07:34:43:152128:info:fi_debug:debug_logs:1:36454077521987073: rtr_l2mcast_fwd_data (pkts:319),
(2001::6 ff1e::70:1:1), from e7/2/4 vlan 900, new fwd_entry
```

debug mld-snoop packet

Displays debugging information related to the MLD snoop packets.

Syntax

debug mld-snoop packet*source_address group_address*

no debug mld-snoop packet*source_address group_address*

Parameters

source_address

Specifies the 32-bit source address of the MLD snoop packet.

group_address

Specifies the address of the MLD snoop multicast group.

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug mld-snoop packet 2001::6 ff1e::70:1:1
```

```
Jun 29 07:34:43:152233:info:fi_debug:debug_logs:1:36454077521987073: Create (2001::6 ff1e::70:1:1)  
vlan 900
```

```
Jun 29 07:34:43:152128:info:fi_debug:debug_logs:1:36454077521987073: rtr_l2mcast_fwd_data (pkts:319),  
(2001::6 ff1e::70:1:1), from e7/2/4 vlan 900, new fwd_entry
```

debug mld-snoop show

Displays all the MLD snooping debug settings.

Syntax

debug mld-snoop show

no debug mld-snoop show

Modes

Privileged EXEC mode

Examples

```
device# debug mld-snoop show
mld-snoop debug-enable-any = 1
debug mld-snoop add-del-oif all
```

debug mld-snoop timer

Displays the MLD snooping related timer events.

Syntax

debug mld-snoop timer

no debug mld-snoop timer

Modes

Privileged EXEC mode

Examples

```
device# debug mld-snoop timer
Jun 29 08:44:27:951775:info:fi_debug:debug_logs:1:36812690111333889: MLDSnoop-VL900: (2001::6, ffile::
70:1:1) Start age timer for 46 sec
Jun 29 08:44:27:951700:info:fi_debug:debug_logs:1:36812690111333889: Suppressed 1 times: MLD: rcvd
Report-V2(ty=143) #rec=1, pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4), mld_size=28
Jun 29 08:44:20:326299:info:fi_debug:debug_logs:1:36812080225977857: MLD: rcvd Report-V2(ty=143)
#rec=1, pkt S=fe80::1 to ff02::16, on VL900 (phy e6/2/4), mld_size=28
```

debug mstp bpdu

Monitors Multiple Spanning Tree Protocol (MSTP) Bridge Packet Data Units (BPDUs).

Syntax

debug mstp bpdu

no debug mstp bpdu

Modes

Privileged EXEC mode

Usage Guidelines

Use this command to record and display information in conjunction with the **debug mstp enable** and **debug mstp events** commands.

Examples

If this command is enabled, output similar to the following is displayed.

```
device# debug mstp bpdu
MSTP Bpdu debugging ON
sh log debug l2 mstp all all
Jun 11 11:22:17:140784:info:l2:mstp:1:320659077989889: mstpMgr_rx_bpdu (pid=3072;size=135;T=128945)
Jun 11 11:22:17:140567:info:l2:mstp:1:320654783022593: mstpMgr_rx_bpdu (pid=65;size=135;T=128945)
Jun 11 11:22:17:140321:info:l2:mstp:1:320650488055297: mstpMgr_rx_bpdu (pid=64;size=135;T=128945)
Jun 11 11:22:17:140027:info:l2:mstp:1:320646193088001: mstpMgr_rx_bpdu (pid=19;size=135;T=128945)
Jun 11 11:22:17:138033:info:l2:mstp:1:320641898120705: mstpMgr_rx_bpdu (pid=18;size=135;T=128945)
Jun 11 11:22:15:142718:info:l2:mstp:1:320637603153409: mstpMgr_rx_bpdu (pid=3072;size=135;T=128925)
Jun 11 11:22:15:142502:info:l2:mstp:1:320633308186113: mstpMgr_rx_bpdu (pid=65;size=135;T=128925)
Jun 11 11:22:15:142268:info:l2:mstp:1:320629013218817: mstpMgr_rx_bpdu (pid=64;size=135;T=128925)
Jun 11 11:22:15:142033:info:l2:mstp:1:320624718251521: mstpMgr_rx_bpdu (pid=19;size=135;T=128925)
Jun 11 11:22:15:141686:info:l2:mstp:1:320620423284225: mstpMgr_rx_bpdu (pid=18;size=135;T=128925)
Jun 11 11:22:13:140148:info:l2:mstp:1:320611833349633: mstpMgr_rx_bpdu (pid=3072;size=135;T=128905)
Jun 11 11:22:13:139928:info:l2:mstp:1:320607538823337: mstpMgr_rx_bpdu (pid=65;size=135;T=128905)
Jun 11 11:22:13:139666:info:l2:mstp:1:320603243415041: mstpMgr_rx_bpdu (pid=64;size=135;T=128905)
Jun 11 11:22:13:138123:info:l2:mstp:1:320598948447745: mstpMgr_rx_bpdu (pid=19;size=135;T=128905)
Jun 11 11:22:13:137839:info:l2:mstp:1:320594653480449: mstpMgr_rx_bpdu (pid=18;size=135;T=128905)
Jun 11 11:22:11:139331:info:l2:mstp:1:320590358513153: mstpMgr_rx_bpdu (pid=3072;size=135;T=128885)
Jun 11 11:22:11:139114:info:l2:mstp:1:320586063545857: mstpMgr_rx_bpdu (pid=65;size=135;T=128885)
Jun 11 11:22:11:138865:info:l2:mstp:1:320581768578561: mstpMgr_rx_bpdu (pid=64;size=135;T=128885)
Jun 11 11:22:11:138141:info:l2:mstp:1:320577473611265: mstpMgr_rx_bpdu (pid=19;size=135;T=128885)
Jun 11 11:22:11:137799:info:l2:mstp:1:320573178643969: mstpMgr_rx_bpdu (pid=18;size=135;T=128885)
Jun 11 11:22:09:140431:info:l2:mstp:1:320568883676673: mstpMgr_rx_bpdu (pid=3072;size=135;T=128865)
Jun 11 11:22:09:140215:info:l2:mstp:1:320564588709377: mstpMgr_rx_bpdu (pid=65;size=135;T=128865)
Jun 11 11:22:09:139983:info:l2:mstp:1:320560293742081: mstpMgr_rx_bpdu (pid=64;size=135;T=128865)
Jun 11 11:22:09:139747:info:l2:mstp:1:320555998774785: mstpMgr_rx_bpdu (pid=19;size=135;T=128865)
Jun 11 11:22:09:139399:info:l2:mstp:1:320551703807489: mstpMgr_rx_bpdu (pid=18;size=135;T=128865)
Jun 11 11:22:07:109629:info:l2:mstp:1:320547408840193: mstpMgr_rx_bpdu (pid=3072;size=135;T=128844)
Jun 11 11:22:07:109381:info:l2:mstp:1:320543113872897: mstpMgr_rx_bpdu (pid=65;size=135;T=128844)
Jun 11 11:22:07:109044:info:l2:mstp:1:320538818905601: mstpMgr_rx_bpdu (pid=64;size=135;T=128844)
Jun 11 11:22:07:108087:info:l2:mstp:1:320534523938305: mstpMgr_rx_bpdu (pid=19;size=135;T=128844)
Jun 11 11:22:07:107734:info:l2:mstp:1:320530228971009: mstpMgr_rx_bpdu (pid=18;size=135;T=128844)
Jun 11 11:22:05:811869:debug:l2:mstp:1:8829483212604160: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:22:05:811775:debug:l2:mstp:1:8829483212604160: MSTP[0x1f73f]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:22:05:811652:debug:l2:mstp:1:8829483212604160: MSTP[0x1f73f]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:22:05:810434:debug:l2:mstp:1:8829483212604160: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:22:05:810331:debug:l2:mstp:1:8829483212604160: MSTP[0x1f73f]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:22:05:810174:debug:l2:mstp:1:8829483212604160: MSTP[0x1f73f]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:22:05:113474:debug:l2:mstp:1:320525934003713: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:22:05:113391:debug:l2:mstp:1:320525934003713: MSTP[0x1f738]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:22:05:113307:debug:l2:mstp:1:320525934003713: MSTP[0x1f738]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:22:05:113217:debug:l2:mstp:1:320525934003713: MSTP[0x1f738]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:22:05:113130:debug:l2:mstp:1:320525934003713: MSTP[0x1f738]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:22:05:113029:debug:l2:mstp:1:320525934003713: MSTP[0x1f738]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:22:05:112938:info:l2:mstp:1:320525934003713: mstpMgr_rx_bpdu (pid=3072;size=135;T=128824)
Jun 11 11:22:05:112723:info:l2:mstp:1:320521639036417: mstpMgr_rx_bpdu (pid=65;size=135;T=128824)
Jun 11 11:22:05:112490:info:l2:mstp:1:320517344069121: mstpMgr_rx_bpdu (pid=64;size=135;T=128824)
Jun 11 11:22:05:112247:info:l2:mstp:1:320513049101825: mstpMgr_rx_bpdu (pid=19;size=135;T=128824)
Jun 11 11:22:05:112029:debug:l2:mstp:1:320508754134529: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:22:05:111941:debug:l2:mstp:1:320508754134529: MSTP[0x1f738]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:22:05:111853:debug:l2:mstp:1:320508754134529: MSTP[0x1f738]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:22:05:111758:debug:l2:mstp:1:320508754134529: MSTP[0x1f738]: PIM RECEIVE->OTHER - MST 0, Port
```

```
1/1/19
Jun 11 11:22:05:111665:debug:l2:mstp:1:320508754134529: MSTP[0x1f738]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:22:05:111539:debug:l2:mstp:1:320508754134529: MSTP[0x1f738]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:22:05:111364:info:l2:mstp:1:320508754134529: mstpMgr_rx_bpdu(pid=18;size=135;T=128824)
Jun 11 11:22:03:810395:debug:l2:mstp:1:8828014333788928: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:22:03:810303:debug:l2:mstp:1:8828014333788928: MSTP[0x1f72b]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:22:03:810184:debug:l2:mstp:1:8828014333788928: MSTP[0x1f72b]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:22:03:808971:debug:l2:mstp:1:8828014333788928: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:22:03:808867:debug:l2:mstp:1:8828014333788928: MSTP[0x1f72b]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:22:03:808703:debug:l2:mstp:1:8828014333788928: MSTP[0x1f72b]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:22:03:110408:debug:l2:mstp:1:320504459167233: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:22:03:110325:debug:l2:mstp:1:320504459167233: MSTP[0x1f724]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:22:03:110239:debug:l2:mstp:1:320504459167233: MSTP[0x1f724]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:22:03:110151:debug:l2:mstp:1:320504459167233: MSTP[0x1f724]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:22:03:110064:debug:l2:mstp:1:320504459167233: MSTP[0x1f724]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:22:03:109962:debug:l2:mstp:1:320504459167233: MSTP[0x1f724]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:22:03:109870:info:l2:mstp:1:320504459167233: mstpMgr_rx_bpdu(pid=3072;size=135;T=128804)
Jun 11 11:22:03:109653:info:l2:mstp:1:320500164199937: mstpMgr_rx_bpdu(pid=65;size=135;T=128804)
Jun 11 11:22:03:109421:info:l2:mstp:1:320495869232641: mstpMgr_rx_bpdu(pid=64;size=135;T=128804)
Jun 11 11:22:03:109189:info:l2:mstp:1:320491574265345: mstpMgr_rx_bpdu(pid=19;size=135;T=128804)
Jun 11 11:22:03:108961:debug:l2:mstp:1:320487279298049: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:22:03:108871:debug:l2:mstp:1:320487279298049: MSTP[0x1f724]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:22:03:108780:debug:l2:mstp:1:320487279298049: MSTP[0x1f724]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:22:03:108658:debug:l2:mstp:1:320487279298049: MSTP[0x1f724]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:22:03:108102:debug:l2:mstp:1:320487279298049: MSTP[0x1f724]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:22:03:107974:debug:l2:mstp:1:320487279298049: MSTP[0x1f724]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:22:03:107810:info:l2:mstp:1:320487279298049: mstpMgr_rx_bpdu(pid=18;size=135;T=128804)
Jun 11 11:22:01:780730:debug:l2:mstp:1:8826579814712064: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:22:01:780635:debug:l2:mstp:1:8826579814712064: MSTP[0x1f717]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:22:01:780517:debug:l2:mstp:1:8826579814712064: MSTP[0x1f717]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:22:01:779301:debug:l2:mstp:1:8826579814712064: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:22:01:779196:debug:l2:mstp:1:8826579814712064: MSTP[0x1f717]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:22:01:779027:debug:l2:mstp:1:8826579814712064: MSTP[0x1f717]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:22:01:110568:debug:l2:mstp:1:320478689363457: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:22:01:110484:debug:l2:mstp:1:320478689363457: MSTP[0x1f710]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:22:01:110399:debug:l2:mstp:1:320478689363457: MSTP[0x1f710]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:22:01:110312:debug:l2:mstp:1:320478689363457: MSTP[0x1f710]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:22:01:110227:debug:l2:mstp:1:320478689363457: MSTP[0x1f710]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:22:01:110125:debug:l2:mstp:1:320478689363457: MSTP[0x1f710]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:22:01:110029:info:l2:mstp:1:320478689363457: mstpMgr_rx_bpdu(pid=3072;size=135;T=128784)
Jun 11 11:22:01:109811:info:l2:mstp:1:320474394396161: mstpMgr_rx_bpdu(pid=65;size=135;T=128784)
Jun 11 11:22:01:109570:info:l2:mstp:1:320470099428865: mstpMgr_rx_bpdu(pid=64;size=135;T=128784)
```

Debug Commands H - P

debug mstp bpd

```
Jun 11 11:22:01:109283:info:l2:mstp:1:320465804461569: mstpmgr_rx_bpdu(pid=19;size=135;T=128784)
Jun 11 11:22:01:107773:debug:l2:mstp:1:320461509494273: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:22:01:107686:debug:l2:mstp:1:320461509494273: MSTP[0x1f710]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:22:01:107597:debug:l2:mstp:1:320461509494273: MSTP[0x1f710]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:22:01:107501:debug:l2:mstp:1:320461509494273: MSTP[0x1f710]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:22:01:107407:debug:l2:mstp:1:320461509494273: MSTP[0x1f710]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:22:01:107283:debug:l2:mstp:1:320461509494273: MSTP[0x1f710]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:22:01:107112:info:l2:mstp:1:320461509494273: mstpmgr_rx_bpdu(pid=18;size=135;T=128784)
Jun 11 11:21:59:780451:debug:l2:mstp:1:8825145295635200: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:59:780357:debug:l2:mstp:1:8825145295635200: MSTP[0x1f703]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:59:780237:debug:l2:mstp:1:8825145295635200: MSTP[0x1f703]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:59:779028:debug:l2:mstp:1:8825145295635200: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:59:778926:debug:l2:mstp:1:8825145295635200: MSTP[0x1f703]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:59:778762:debug:l2:mstp:1:8825145295635200: MSTP[0x1f703]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:59:121122:debug:l2:mstp:1:320452919559681: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:59:121037:debug:l2:mstp:1:320452919559681: MSTP[0x1f6fc]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:59:120953:debug:l2:mstp:1:320452919559681: MSTP[0x1f6fc]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:59:120866:debug:l2:mstp:1:320452919559681: MSTP[0x1f6fc]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:59:120780:debug:l2:mstp:1:320452919559681: MSTP[0x1f6fc]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:59:120680:debug:l2:mstp:1:320452919559681: MSTP[0x1f6fc]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:59:120590:info:l2:mstp:1:320452919559681: mstpmgr_rx_bpdu(pid=3072;size=135;T=128764)
Jun 11 11:21:59:120377:info:l2:mstp:1:320448624592385: mstpmgr_rx_bpdu(pid=65;size=135;T=128764)
Jun 11 11:21:59:120148:info:l2:mstp:1:320444329625089: mstpmgr_rx_bpdu(pid=64;size=135;T=128764)
Jun 11 11:21:59:119922:info:l2:mstp:1:320440034657793: mstpmgr_rx_bpdu(pid=19;size=135;T=128764)
Jun 11 11:21:59:119704:debug:l2:mstp:1:320435739690497: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:59:119617:debug:l2:mstp:1:320435739690497: MSTP[0x1f6fc]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:59:119523:debug:l2:mstp:1:320435739690497: MSTP[0x1f6fc]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:59:119410:debug:l2:mstp:1:320435739690497: MSTP[0x1f6fc]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:59:119314:debug:l2:mstp:1:320435739690497: MSTP[0x1f6fc]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:59:119186:debug:l2:mstp:1:320435739690497: MSTP[0x1f6fc]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:59:119007:info:l2:mstp:1:320435739690497: mstpmgr_rx_bpdu(pid=18;size=135;T=128764)
Jun 11 11:21:57:780420:debug:l2:mstp:1:8823706481591040: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:57:780325:debug:l2:mstp:1:8823706481591040: MSTP[0x1f6ef]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:57:780208:debug:l2:mstp:1:8823706481591040: MSTP[0x1f6ef]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:57:779002:debug:l2:mstp:1:8823706481591040: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:57:778898:debug:l2:mstp:1:8823706481591040: MSTP[0x1f6ef]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:57:778730:debug:l2:mstp:1:8823706481591040: MSTP[0x1f6ef]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:57:106684:debug:l2:mstp:1:320431444723201: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:57:106601:debug:l2:mstp:1:320431444723201: MSTP[0x1f6e8]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:57:106516:debug:l2:mstp:1:320431444723201: MSTP[0x1f6e8]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
```

```
Jun 11 11:21:57:106427:debug:l2:mstp:1:320431444723201: MSTP[0x1f6e8]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:57:106340:debug:l2:mstp:1:320431444723201: MSTP[0x1f6e8]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:57:106225:debug:l2:mstp:1:320431444723201: MSTP[0x1f6e8]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:57:105619:debug:l2:mstp:1:320414264854017: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:57:105530:debug:l2:mstp:1:320414264854017: MSTP[0x1f6e8]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:57:105442:debug:l2:mstp:1:320414264854017: MSTP[0x1f6e8]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:57:105346:debug:l2:mstp:1:320414264854017: MSTP[0x1f6e8]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:57:105248:debug:l2:mstp:1:320414264854017: MSTP[0x1f6e8]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:57:105057:debug:l2:mstp:1:320414264854017: MSTP[0x1f6e8]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:55:780537:debug:l2:mstp:1:8822241897743104: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:55:780443:debug:l2:mstp:1:8822241897743104: MSTP[0x1f6db]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:55:780324:debug:l2:mstp:1:8822241897743104: MSTP[0x1f6db]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:55:779118:debug:l2:mstp:1:8822241897743104: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:55:779018:debug:l2:mstp:1:8822241897743104: MSTP[0x1f6db]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:55:778854:debug:l2:mstp:1:8822241897743104: MSTP[0x1f6db]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:55:114749:debug:l2:mstp:1:320405674919425: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:55:114665:debug:l2:mstp:1:320405674919425: MSTP[0x1f6d4]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:55:114580:debug:l2:mstp:1:320405674919425: MSTP[0x1f6d4]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:55:114491:debug:l2:mstp:1:320405674919425: MSTP[0x1f6d4]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:55:114403:debug:l2:mstp:1:320405674919425: MSTP[0x1f6d4]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:55:114287:debug:l2:mstp:1:320405674919425: MSTP[0x1f6d4]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:55:113670:debug:l2:mstp:1:320388495050241: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:55:113580:debug:l2:mstp:1:320388495050241: MSTP[0x1f6d4]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:55:113477:debug:l2:mstp:1:320388495050241: MSTP[0x1f6d4]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:55:113383:debug:l2:mstp:1:320388495050241: MSTP[0x1f6d4]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:55:113285:debug:l2:mstp:1:320388495050241: MSTP[0x1f6d4]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:55:113093:debug:l2:mstp:1:320388495050241: MSTP[0x1f6d4]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:53:785377:debug:l2:mstp:1:8820815968600832: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:53:785286:debug:l2:mstp:1:8820815968600832: MSTP[0x1f6c7]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:53:785173:debug:l2:mstp:1:8820815968600832: MSTP[0x1f6c7]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:53:783977:debug:l2:mstp:1:8820815968600832: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:53:783875:debug:l2:mstp:1:8820815968600832: MSTP[0x1f6c7]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:53:783709:debug:l2:mstp:1:8820815968600832: MSTP[0x1f6c7]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:53:111538:debug:l2:mstp:1:320384200082945: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:53:111456:debug:l2:mstp:1:320384200082945: MSTP[0x1f6c0]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:53:111371:debug:l2:mstp:1:320384200082945: MSTP[0x1f6c0]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:53:111284:debug:l2:mstp:1:320384200082945: MSTP[0x1f6c0]: PIM RECEIVE->OTHER - MST 0, Port
lg1
```

Debug Commands H - P

debug mstp bpdu

```
Jun 11 11:21:53:111198:debug:l2:mstp:1:320384200082945: MSTP[0x1f6c0]: PIM CURRENT->RECEIVE - MST 0, Port lg1
Jun 11 11:21:53:111084:debug:l2:mstp:1:320384200082945: MSTP[0x1f6c0]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:53:110480:debug:l2:mstp:1:320367020213761: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port 1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:53:110394:debug:l2:mstp:1:320367020213761: MSTP[0x1f6c0]: PIM RECEIVE->REPEATED_DESIGNATED - MST 1, Port 1/1/19
Jun 11 11:21:53:110304:debug:l2:mstp:1:320367020213761: MSTP[0x1f6c0]: PIM CURRENT->RECEIVE - MST 1, Port 1/1/19
Jun 11 11:21:53:110207:debug:l2:mstp:1:320367020213761: MSTP[0x1f6c0]: PIM RECEIVE->OTHER - MST 0, Port 1/1/19
Jun 11 11:21:53:110106:debug:l2:mstp:1:320367020213761: MSTP[0x1f6c0]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/19
Jun 11 11:21:53:109910:debug:l2:mstp:1:320367020213761: MSTP[0x1f6c0]: PRX RECEIVE->RECEIVE - Port 1/1/19
Jun 11 11:21:51:730613:debug:l2:mstp:1:8819372859589376: MSTP: transmit_bpdu Port lg1, real-prot 1/1/21, send type=2, vlan=4087
Jun 11 11:21:51:730522:debug:l2:mstp:1:8819372859589376: MSTP[0x1f6b3]: PTX IDLE->TRANSMIT_RSTP - Port lg1
Jun 11 11:21:51:730406:debug:l2:mstp:1:8819372859589376: MSTP[0x1f6b3]: PTX IDLE->TRANSMIT_PERIODIC - Port lg1
Jun 11 11:21:51:729196:debug:l2:mstp:1:8819372859589376: MSTP: transmit_bpdu Port 1/1/19, real-prot 1/1/19, send type=2, vlan=4087
Jun 11 11:21:51:729094:debug:l2:mstp:1:8819372859589376: MSTP[0x1f6b3]: PTX IDLE->TRANSMIT_RSTP - Port 1/1/19
Jun 11 11:21:51:728933:debug:l2:mstp:1:8819372859589376: MSTP[0x1f6b3]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/19
Jun 11 11:21:51:110561:debug:l2:mstp:1:320354135311873: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port lg1, rcvdInfoWhile 4->6
Jun 11 11:21:51:110478:debug:l2:mstp:1:320354135311873: MSTP[0x1f6ac]: PIM RECEIVE->REPEATED_DESIGNATED - MST 2, Port lg1
Jun 11 11:21:51:110394:debug:l2:mstp:1:320354135311873: MSTP[0x1f6ac]: PIM CURRENT->RECEIVE - MST 2, Port lg1
Jun 11 11:21:51:110307:debug:l2:mstp:1:320354135311873: MSTP[0x1f6ac]: PIM RECEIVE->OTHER - MST 0, Port lg1
Jun 11 11:21:51:110218:debug:l2:mstp:1:320354135311873: MSTP[0x1f6ac]: PIM CURRENT->RECEIVE - MST 0, Port lg1
Jun 11 11:21:51:110095:debug:l2:mstp:1:320354135311873: MSTP[0x1f6ac]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:51:109450:debug:l2:mstp:1:320336955442689: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port 1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:51:109339:debug:l2:mstp:1:320336955442689: MSTP[0x1f6ac]: PIM RECEIVE->REPEATED_DESIGNATED - MST 1, Port 1/1/19
Jun 11 11:21:51:109145:debug:l2:mstp:1:320336955442689: MSTP[0x1f6ac]: PIM CURRENT->RECEIVE - MST 1, Port 1/1/19
Jun 11 11:21:51:109016:debug:l2:mstp:1:320336955442689: MSTP[0x1f6ac]: PIM RECEIVE->OTHER - MST 0, Port 1/1/19
Jun 11 11:21:51:108147:debug:l2:mstp:1:320336955442689: MSTP[0x1f6ac]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/19
Jun 11 11:21:51:108019:debug:l2:mstp:1:320336955442689: MSTP[0x1f6ac]: PRX RECEIVE->RECEIVE - Port 1/1/19
Jun 11 11:21:49:730467:debug:l2:mstp:1:8817929750577920: MSTP: transmit_bpdu Port lg1, real-prot 1/1/21, send type=2, vlan=4087
Jun 11 11:21:49:730373:debug:l2:mstp:1:8817929750577920: MSTP[0x1f69f]: PTX IDLE->TRANSMIT_RSTP - Port lg1
Jun 11 11:21:49:730255:debug:l2:mstp:1:8817929750577920: MSTP[0x1f69f]: PTX IDLE->TRANSMIT_PERIODIC - Port lg1
Jun 11 11:21:49:729025:debug:l2:mstp:1:8817929750577920: MSTP: transmit_bpdu Port 1/1/19, real-prot 1/1/19, send type=2, vlan=4087
Jun 11 11:21:49:728907:debug:l2:mstp:1:8817929750577920: MSTP[0x1f69f]: PTX IDLE->TRANSMIT_RSTP - Port 1/1/19
Jun 11 11:21:49:728743:debug:l2:mstp:1:8817929750577920: MSTP[0x1f69f]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/19
Jun 11 11:21:49:088841:debug:l2:mstp:1:320328365508097: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port lg1, rcvdInfoWhile 4->6
Jun 11 11:21:49:088718:debug:l2:mstp:1:320328365508097: MSTP[0x1f698]: PIM RECEIVE->REPEATED_DESIGNATED - MST 2, Port lg1
Jun 11 11:21:49:088070:debug:l2:mstp:1:320328365508097: MSTP[0x1f698]: PIM CURRENT->RECEIVE - MST 2, Port lg1
Jun 11 11:21:49:087983:debug:l2:mstp:1:320328365508097: MSTP[0x1f698]: PIM RECEIVE->OTHER - MST 0, Port lg1
Jun 11 11:21:49:087895:debug:l2:mstp:1:320328365508097: MSTP[0x1f698]: PIM CURRENT->RECEIVE - MST 0, Port lg1
```

```
Jun 11 11:21:49:087780:debug:l2:mstp:1:320328365508097: MSTP[0x1f698]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:49:087175:debug:l2:mstp:1:320311185638913: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:49:087087:debug:l2:mstp:1:320311185638913: MSTP[0x1f698]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:49:086999:debug:l2:mstp:1:320311185638913: MSTP[0x1f698]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:49:086902:debug:l2:mstp:1:320311185638913: MSTP[0x1f698]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:49:086800:debug:l2:mstp:1:320311185638913: MSTP[0x1f698]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:49:086602:debug:l2:mstp:1:320311185638913: MSTP[0x1f698]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:47:731377:debug:l2:mstp:1:8816495231501056: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:47:731283:debug:l2:mstp:1:8816495231501056: MSTP[0x1f68b]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:47:731163:debug:l2:mstp:1:8816495231501056: MSTP[0x1f68b]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:47:729938:debug:l2:mstp:1:8816495231501056: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:47:729835:debug:l2:mstp:1:8816495231501056: MSTP[0x1f68b]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:47:729682:debug:l2:mstp:1:8816495231501056: MSTP[0x1f68b]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:47:064795:debug:l2:mstp:1:320302595704321: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:47:064705:debug:l2:mstp:1:320302595704321: MSTP[0x1f684]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:47:064609:debug:l2:mstp:1:320302595704321: MSTP[0x1f684]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:47:064445:debug:l2:mstp:1:320302595704321: MSTP[0x1f684]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:47:058083:debug:l2:mstp:1:320302595704321: MSTP[0x1f684]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:47:057970:debug:l2:mstp:1:320302595704321: MSTP[0x1f684]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:47:057362:debug:l2:mstp:1:320285415835137: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:47:057276:debug:l2:mstp:1:320285415835137: MSTP[0x1f684]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:47:057184:debug:l2:mstp:1:320285415835137: MSTP[0x1f684]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:47:057088:debug:l2:mstp:1:320285415835137: MSTP[0x1f684]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:47:056985:debug:l2:mstp:1:320285415835137: MSTP[0x1f684]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:47:056787:debug:l2:mstp:1:320285415835137: MSTP[0x1f684]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:45:730889:debug:l2:mstp:1:8815065007391488: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:45:730796:debug:l2:mstp:1:8815065007391488: MSTP[0x1f677]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:45:730673:debug:l2:mstp:1:8815065007391488: MSTP[0x1f677]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:45:729437:debug:l2:mstp:1:8815065007391488: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:45:729335:debug:l2:mstp:1:8815065007391488: MSTP[0x1f677]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:45:729167:debug:l2:mstp:1:8815065007391488: MSTP[0x1f677]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:45:061995:debug:l2:mstp:1:320281120867841: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:45:061912:debug:l2:mstp:1:320281120867841: MSTP[0x1f670]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:45:061828:debug:l2:mstp:1:320281120867841: MSTP[0x1f670]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:45:061740:debug:l2:mstp:1:320281120867841: MSTP[0x1f670]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:45:061650:debug:l2:mstp:1:320281120867841: MSTP[0x1f670]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:45:061535:debug:l2:mstp:1:320281120867841: MSTP[0x1f670]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:45:060924:debug:l2:mstp:1:320263940998657: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
```

Debug Commands H - P

debug mstp bpdu

```
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:45:060837:debug:l2:mstp:1:320263940998657: MSTP[0x1f670]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:45:060749:debug:l2:mstp:1:320263940998657: MSTP[0x1f670]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:45:060651:debug:l2:mstp:1:320263940998657: MSTP[0x1f670]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:45:060551:debug:l2:mstp:1:320263940998657: MSTP[0x1f670]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:45:060359:debug:l2:mstp:1:320263940998657: MSTP[0x1f670]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:43:730435:debug:l2:mstp:1:8813609013478144: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:43:730342:debug:l2:mstp:1:8813609013478144: MSTP[0x1f663]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:43:730222:debug:l2:mstp:1:8813609013478144: MSTP[0x1f663]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:43:729002:debug:l2:mstp:1:8813609013478144: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:43:728896:debug:l2:mstp:1:8813609013478144: MSTP[0x1f663]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:43:728733:debug:l2:mstp:1:8813609013478144: MSTP[0x1f663]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:43:059086:debug:l2:mstp:1:320255351064065: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:43:058132:debug:l2:mstp:1:320255351064065: MSTP[0x1f65c]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:43:058045:debug:l2:mstp:1:320255351064065: MSTP[0x1f65c]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:43:057955:debug:l2:mstp:1:320255351064065: MSTP[0x1f65c]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:43:057866:debug:l2:mstp:1:320255351064065: MSTP[0x1f65c]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:43:057740:debug:l2:mstp:1:320255351064065: MSTP[0x1f65c]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:43:056832:debug:l2:mstp:1:320238171194881: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:43:056745:debug:l2:mstp:1:320238171194881: MSTP[0x1f65c]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:43:056655:debug:l2:mstp:1:320238171194881: MSTP[0x1f65c]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:43:056558:debug:l2:mstp:1:320238171194881: MSTP[0x1f65c]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:43:056457:debug:l2:mstp:1:320238171194881: MSTP[0x1f65c]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:43:056265:debug:l2:mstp:1:320238171194881: MSTP[0x1f65c]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:41:780466:debug:l2:mstp:1:8812226034008832: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:41:780370:debug:l2:mstp:1:8812226034008832: MSTP[0x1f64f]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:41:780248:debug:l2:mstp:1:8812226034008832: MSTP[0x1f64f]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:41:779006:debug:l2:mstp:1:8812226034008832: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:41:778900:debug:l2:mstp:1:8812226034008832: MSTP[0x1f64f]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:41:778734:debug:l2:mstp:1:8812226034008832: MSTP[0x1f64f]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:41:058719:debug:l2:mstp:1:320233876227585: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:41:058098:debug:l2:mstp:1:320233876227585: MSTP[0x1f648]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:41:058012:debug:l2:mstp:1:320233876227585: MSTP[0x1f648]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:41:057924:debug:l2:mstp:1:320233876227585: MSTP[0x1f648]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:41:057838:debug:l2:mstp:1:320233876227585: MSTP[0x1f648]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:41:057726:debug:l2:mstp:1:320233876227585: MSTP[0x1f648]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:41:057124:debug:l2:mstp:1:320216696358401: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:41:057038:debug:l2:mstp:1:320216696358401: MSTP[0x1f648]: PIM RECEIVE->REPEATED_DESIGNATED
```

```
- MST 1, Port 1/1/19
Jun 11 11:21:41:056950:debug:l2:mstp:1:320216696358401: MSTP[0x1f648]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:41:056857:debug:l2:mstp:1:320216696358401: MSTP[0x1f648]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:41:056760:debug:l2:mstp:1:320216696358401: MSTP[0x1f648]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:41:056579:debug:l2:mstp:1:320216696358401: MSTP[0x1f648]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:39:780549:debug:l2:mstp:1:8810838759572224: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:39:780456:debug:l2:mstp:1:8810838759572224: MSTP[0x1f63b]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:39:780342:debug:l2:mstp:1:8810838759572224: MSTP[0x1f63b]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:39:779133:debug:l2:mstp:1:8810838759572224: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:39:779031:debug:l2:mstp:1:8810838759572224: MSTP[0x1f63b]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:39:778852:debug:l2:mstp:1:8810838759572224: MSTP[0x1f63b]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:39:063656:debug:l2:mstp:1:320212401391105: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:39:063563:debug:l2:mstp:1:320212401391105: MSTP[0x1f634]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:39:063475:debug:l2:mstp:1:320212401391105: MSTP[0x1f634]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:39:063383:debug:l2:mstp:1:320212401391105: MSTP[0x1f634]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:39:063287:debug:l2:mstp:1:320212401391105: MSTP[0x1f634]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:39:063146:debug:l2:mstp:1:320212401391105: MSTP[0x1f634]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:39:062094:debug:l2:mstp:1:320195221521921: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:39:062005:debug:l2:mstp:1:320195221521921: MSTP[0x1f634]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:39:061916:debug:l2:mstp:1:320195221521921: MSTP[0x1f634]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:39:061818:debug:l2:mstp:1:320195221521921: MSTP[0x1f634]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:39:061704:debug:l2:mstp:1:320195221521921: MSTP[0x1f634]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:39:061218:debug:l2:mstp:1:320195221521921: MSTP[0x1f634]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:37:765430:debug:l2:mstp:1:8809391355593472: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:37:765331:debug:l2:mstp:1:8809391355593472: MSTP[0x1f627]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:37:765203:debug:l2:mstp:1:8809391355593472: MSTP[0x1f627]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:37:764010:debug:l2:mstp:1:8809391355593472: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:37:763909:debug:l2:mstp:1:8809391355593472: MSTP[0x1f627]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:37:763744:debug:l2:mstp:1:8809391355593472: MSTP[0x1f627]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:37:037706:debug:l2:mstp:1:320190926554625: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:37:037624:debug:l2:mstp:1:320190926554625: MSTP[0x1f620]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:37:037540:debug:l2:mstp:1:320190926554625: MSTP[0x1f620]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:37:037452:debug:l2:mstp:1:320190926554625: MSTP[0x1f620]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:37:037363:debug:l2:mstp:1:320190926554625: MSTP[0x1f620]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:37:037247:debug:l2:mstp:1:320190926554625: MSTP[0x1f620]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:37:036640:debug:l2:mstp:1:320173746685441: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:37:036553:debug:l2:mstp:1:320173746685441: MSTP[0x1f620]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:37:036463:debug:l2:mstp:1:320173746685441: MSTP[0x1f620]: PIM CURRENT->RECEIVE - MST 1,
```

Debug Commands H - P

debug mstp bpdu

```
Port 1/1/19
Jun 11 11:21:37:036367:debug:l2:mstp:1:320173746685441: MSTP[0x1f620]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:37:036267:debug:l2:mstp:1:320173746685441: MSTP[0x1f620]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:37:036081:debug:l2:mstp:1:320173746685441: MSTP[0x1f620]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:35:761110:debug:l2:mstp:1:8807974016385792: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:35:761014:debug:l2:mstp:1:8807974016385792: MSTP[0x1f613]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:35:760891:debug:l2:mstp:1:8807974016385792: MSTP[0x1f613]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:35:759664:debug:l2:mstp:1:8807974016385792: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:35:759562:debug:l2:mstp:1:8807974016385792: MSTP[0x1f613]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:35:759393:debug:l2:mstp:1:8807974016385792: MSTP[0x1f613]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:35:041936:debug:l2:mstp:1:320169451718145: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:35:041852:debug:l2:mstp:1:320169451718145: MSTP[0x1f60c]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:35:041767:debug:l2:mstp:1:320169451718145: MSTP[0x1f60c]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:35:041679:debug:l2:mstp:1:320169451718145: MSTP[0x1f60c]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:35:041592:debug:l2:mstp:1:320169451718145: MSTP[0x1f60c]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:35:041478:debug:l2:mstp:1:320169451718145: MSTP[0x1f60c]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:35:040873:debug:l2:mstp:1:320152271848961: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:35:040786:debug:l2:mstp:1:320152271848961: MSTP[0x1f60c]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:35:040698:debug:l2:mstp:1:320152271848961: MSTP[0x1f60c]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:35:040603:debug:l2:mstp:1:320152271848961: MSTP[0x1f60c]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:35:040503:debug:l2:mstp:1:320152271848961: MSTP[0x1f60c]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:35:040321:debug:l2:mstp:1:320152271848961: MSTP[0x1f60c]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:33:761114:debug:l2:mstp:1:8806513727505152: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:33:761015:debug:l2:mstp:1:8806513727505152: MSTP[0x1f5ff]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:33:760874:debug:l2:mstp:1:8806513727505152: MSTP[0x1f5ff]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:33:759661:debug:l2:mstp:1:8806513727505152: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:33:759557:debug:l2:mstp:1:8806513727505152: MSTP[0x1f5ff]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:33:759407:debug:l2:mstp:1:8806513727505152: MSTP[0x1f5ff]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:33:037379:debug:l2:mstp:1:320147976881665: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:33:037296:debug:l2:mstp:1:320147976881665: MSTP[0x1f5f8]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:33:037210:debug:l2:mstp:1:320147976881665: MSTP[0x1f5f8]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:33:037121:debug:l2:mstp:1:320147976881665: MSTP[0x1f5f8]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:33:037032:debug:l2:mstp:1:320147976881665: MSTP[0x1f5f8]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:33:036918:debug:l2:mstp:1:320147976881665: MSTP[0x1f5f8]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:33:036311:debug:l2:mstp:1:320130797012481: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:33:036220:debug:l2:mstp:1:320130797012481: MSTP[0x1f5f8]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:33:036130:debug:l2:mstp:1:320130797012481: MSTP[0x1f5f8]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:33:036032:debug:l2:mstp:1:320130797012481: MSTP[0x1f5f8]: PIM RECEIVE->OTHER - MST 0, Port
```

```
1/1/19
Jun 11 11:21:33:035934:debug:l2:mstp:1:320130797012481: MSTP[0x1f5f8]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:33:035742:debug:l2:mstp:1:320130797012481: MSTP[0x1f5f8]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:31:730511:debug:l2:mstp:1:8805079208428288: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:31:730418:debug:l2:mstp:1:8805079208428288: MSTP[0x1f5eb]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
Jun 11 11:21:31:730298:debug:l2:mstp:1:8805079208428288: MSTP[0x1f5eb]: PTX IDLE->TRANSMIT_PERIODIC -
Port lg1
Jun 11 11:21:31:729077:debug:l2:mstp:1:8805079208428288: MSTP: transmit_bpdu Port 1/1/19, real-prot
1/1/19, send type=2, vlan=4087
Jun 11 11:21:31:728972:debug:l2:mstp:1:8805079208428288: MSTP[0x1f5eb]: PTX IDLE->TRANSMIT_RSTP - Port
1/1/19
Jun 11 11:21:31:728811:debug:l2:mstp:1:8805079208428288: MSTP[0x1f5eb]: PTX IDLE->TRANSMIT_PERIODIC -
Port 1/1/19
Jun 11 11:21:31:037501:debug:l2:mstp:1:320122207077889: MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port
lg1, rcvdInfoWhile 4->6
Jun 11 11:21:31:037416:debug:l2:mstp:1:320122207077889: MSTP[0x1f5e4]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 2, Port lg1
Jun 11 11:21:31:037331:debug:l2:mstp:1:320122207077889: MSTP[0x1f5e4]: PIM CURRENT->RECEIVE - MST 2,
Port lg1
Jun 11 11:21:31:037242:debug:l2:mstp:1:320122207077889: MSTP[0x1f5e4]: PIM RECEIVE->OTHER - MST 0, Port
lg1
Jun 11 11:21:31:037151:debug:l2:mstp:1:320122207077889: MSTP[0x1f5e4]: PIM CURRENT->RECEIVE - MST 0,
Port lg1
Jun 11 11:21:31:037024:debug:l2:mstp:1:320122207077889: MSTP[0x1f5e4]: PRX RECEIVE->RECEIVE - Port lg1
Jun 11 11:21:31:036116:debug:l2:mstp:1:320105027208705: MSTP: mstp_updtRcvdInfoWhileMsti mst=1, Port
1/1/19, rcvdInfoWhile 4->6
Jun 11 11:21:31:036027:debug:l2:mstp:1:320105027208705: MSTP[0x1f5e4]: PIM RECEIVE->REPEATED_DESIGNATED
- MST 1, Port 1/1/19
Jun 11 11:21:31:035940:debug:l2:mstp:1:320105027208705: MSTP[0x1f5e4]: PIM CURRENT->RECEIVE - MST 1,
Port 1/1/19
Jun 11 11:21:31:035845:debug:l2:mstp:1:320105027208705: MSTP[0x1f5e4]: PIM RECEIVE->OTHER - MST 0, Port
1/1/19
Jun 11 11:21:31:035745:debug:l2:mstp:1:320105027208705: MSTP[0x1f5e4]: PIM CURRENT->RECEIVE - MST 0,
Port 1/1/19
Jun 11 11:21:31:035554:debug:l2:mstp:1:320105027208705: MSTP[0x1f5e4]: PRX RECEIVE->RECEIVE - Port
1/1/19
Jun 11 11:21:29:730739:debug:l2:mstp:1:8803640394384128: MSTP: transmit_bpdu Port lg1, real-prot
1/1/21, send type=2, vlan=4087
Jun 11 11:21:29:730624:debug:l2:mstp:1:8803640394384128: MSTP[0x1f5d7]: PTX IDLE->TRANSMIT_RSTP - Port
lg1
```

debug mstp enable

Enables MSTP debugging.

Syntax

`debug mstp enable`

Modes

Privileged EXEC mode

Examples

The following example enables MSTP debugging.

```
device# debug mstp enable
```

debug mstp events

Displays MSTP state machine events.

Syntax

debug mstp events

no debug mstp events

Modes

Privileged EXEC mode

Usage Guidelines

Use this command to monitor any MSTP event that takes place.

Examples

If MSTP events are enabled, output similar to the following is displayed.

```
device# debug mstp events
MSTP Event debugging ON
device# debug mstp enable
device# MSTP[0xeda7f]: PRX RECEIVE->RECEIVE - Port 1/1/1
MSTP[0xeda7f]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/1
MSTP[0xeda7f]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/1, rcvdInfoWhile 5->7
MSTP[0xeda7f]: PRX RECEIVE->RECEIVE - Port 1/1/2
MSTP[0xeda7f]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/2
MSTP[0xeda7f]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/2, rcvdInfoWhile 5->7
MSTP[0xeda89]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/1
MSTP[0xeda89]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/2
MSTP[0xeda93]: PRX RECEIVE->RECEIVE - Port 1/1/1
MSTP[0xeda93]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/1
MSTP[0xeda93]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/1
```

If MSTP events are disabled, output similar to the following is displayed.

```
device# no debug mstp events
MSTP Event debugging OFF
```

debug mstp msti

Displays information for a specific MSTP instance.

Syntax

debug mstp msti *decimal*

no debug mstp msti *decimal*

Parameters

decimal

Specifies the following values:

Value 0 for the Common and Internal Spanning Tree (CIST)

Value from 1 through 4094 for the Multiple Spanning Tree Instance (MSTI).

Modes

Privileged EXEC mode

Examples

```
device#debug mstp msti 0  
MSTP debugging turned on for instances 0
```

If this command is enabled, output similar to the following is displayed.

```

device#debug mstp msti 2
MSTP debugging turned on for instances 2 ,0
device# debug mstp enable
device# debug mstp events
MSTP Event debugging ON
device# MSTP[0x175f15]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/1
MSTP[0x175f15]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/2
MSTP[0x175f21]: PRX RECEIVE->RECEIVE - Port 1/1/1
MSTP[0x175f21]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/1
MSTP[0x175f21]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/1, rcvdInfoWhile 5->7
MSTP[0x175f21]: PIM CURRENT->RECEIVE - MST 2, Port 1/1/1
MSTP[0x175f21]: PIM RECEIVE->REPEATED DESIGNATED - MST 2, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port 1/1/1, rcvdInfoWhile 4->7
MSTP[0x175f21]: PRX RECEIVE->RECEIVE - Port 1/1/2
MSTP[0x175f21]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/2
MSTP[0x175f21]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/2, rcvdInfoWhile 5->7
MSTP[0x175f21]: PIM CURRENT->RECEIVE - MST 2, Port 1/1/2
MSTP[0x175f21]: PIM RECEIVE->REPEATED DESIGNATED - MST 2, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port 1/1/2, rcvdInfoWhile 4->7
MSTP[0x175f29]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/1
MSTP[0x175f29]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/2
noMSTP[0x175f35]: PRX RECEIVE->RECEIVE - Port 1/1/1
MSTP[0x175f35]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/1
MSTP[0x175f35]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/1, rcvdInfoWhile 5->7
MSTP[0x175f35]: PIM CURRENT->RECEIVE - MST 2, Port 1/1/1
MSTP[0x175f35]: PIM RECEIVE->REPEATED DESIGNATED - MST 2, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port 1/1/1, rcvdInfoWhile 4->7
MSTP[0x175f35]: PRX RECEIVE->RECEIVE - Port 1/1/2
MSTP[0x175f35]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/2
MSTP[0x175f35]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/2, rcvdInfoWhile 5->7
MSTP[0x175f35]: PIM CURRENT->RECEIVE - MST 2, Port 1/1/2
MSTP[0x175f35]: PIM RECEIVE->REPEATED DESIGNATED - MST 2, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port 1/1/2, rcvdInfoWhile 4->7
deMSTP[0x175f3d]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/1
MSTP[0x175f3d]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/2
bug msMSTP[0x175f49]: PRX RECEIVE->RECEIVE - Port 1/1/1
MSTP[0x175f49]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/1
MSTP[0x175f49]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/1, rcvdInfoWhile 5->7
MSTP[0x175f49]: PIM CURRENT->RECEIVE - MST 2, Port 1/1/1
MSTP[0x175f49]: PIM RECEIVE->REPEATED DESIGNATED - MST 2, Port 1/1/1
MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port 1/1/1, rcvdInfoWhile 4->7
MSTP[0x175f49]: PRX RECEIVE->RECEIVE - Port 1/1/2
MSTP[0x175f49]: PIM CURRENT->RECEIVE - MST 0, Port 1/1/2
MSTP[0x175f49]: PIM RECEIVE->REPEATED DESIGNATED - MST 0, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileCist mst=0, Port 1/1/2, rcvdInfoWhile 5->7
MSTP[0x175f49]: PIM CURRENT->RECEIVE - MST 2, Port 1/1/2
MSTP[0x175f49]: PIM RECEIVE->REPEATED DESIGNATED - MST 2, Port 1/1/2
MSTP: mstp_updtRcvdInfoWhileMsti mst=2, Port 1/1/2, rcvdInfoWhile 4->7
tpMSTP[0x175f51]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/1
MSTP[0x175f51]: PTX IDLE->TRANSMIT_PERIODIC - Port 1/1/2
eventMSTP[0x175f5d]: PRX RECEIVE->RECEIVE - Port 1/1/1

```

debug mstp ports

Debugs specific MSTP ports.

Syntax

```
debug mstp ports{ethernet unit/slot/port |lag lag-id}  
no debug mstp ports{ethernet unit/slot/port |lag lag-id}
```

Parameters

ethernet *unit/slot/port*
Specifies the physical port.

lag *lag-id*
Specifies the LAG .

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables the debugging on specific MSTP ports.

Examples

```
device# debug mstp ports lag 10
```

debug mstp port-level

Displays the hardware level of the port on which the MSTP is running.

Syntax

debug mstp port-level *decimal*

no debug mstp port-level *decimal*

Parameters

decimal

Specifies the following values:

Value 0 for the Common and Internal Spanning Tree (CIST)

Value from 1 through 4094 for the Multiple Spanning Tree Instance (MSTI).

Modes

Privileged EXEC mode

Usage Guidelines

Use this command to determine the port-level information.

Examples

```
device# debug mstp port-level 1
Configuration for port-level 1 :
device# debug mstp port-level
DECIMAL 0 -- print nothing
device# debug mstp port-level 1
device# configure terminal
device(config)# interface ethernet 1/1/1
device(config-if-e1000-1/1/1)# disable
device(config-if-e1000-1/1/1)# enable
device(config-if-e1000-1/1/1)# ^Z
```

debug mstp show

Displays the currently enabled MSTP debug parameters.

Syntax

debug mstp show

no debug mstp show

Modes

Privileged EXEC mode

Examples

```
device#debug mstp show
mstp debug is on because of enabled, level or port-level level 4
parameters: Brief, StateMachineEvents BpduEvents are being tracked
Ports: All
MSTP instances: 0
```

debug mstp state

Displays information about the MSTP port state events.

Syntax

debug mstp state

no debug mstp state

Modes

Privileged EXEC mode

Examples

```
device#debug mstp state  
MSTP Port State debugging ON
```

Debug Commands H - P
debug mstp verbose

debug mstp verbose

Displays the MSTP debug information in the verbose mode.

Syntax

debug mstp verbose

no debug mstp verbose

Modes

Privileged EXEC mode

Examples

```
device#debug mstp verbose
MSTP debugging set to VERBOSE mode
```

debug mvrp

Enables Multiple VLAN Registration Protocol (MVRP) debugging.

Syntax

```
debug mvrp [ all | cli | config | db-event | error-event | ethernet unit/slot/port | event | itc | lag lag-id | pdu { err | rx | tx } | reset | rx-event | show | sm-event | timer | tx-event | verbose ]
```

```
no debug mvrp [ all | cli | config | db-event | error-event | ethernet unit/slot/port | event | itc | lag lag-id | pdu { err | rx | tx } | reset | rx-event | show | sm-event | timer | tx-event | verbose ]
```

Parameters

- all**
Enables all attributes and for all ports.
- cli**
Enables MVRP CLI debugging.
- config**
Enables MVRP configuration debugging.
- db-event**
Enables MVRP database event debugging.
- error-event**
Enables MVRP error event debugging.
- ethernet** *unit/slot/port*
Enables MVRP port debugging.
- event**
Enables MVRP event debugging.
- itc**
Enables MVRP ITC debugging.
- lag** *lag-id*
Enables MVRP LAG port debugging.
- pdu**
Enables MVRPDU message debugging.
- err**
Enables MVRPDU error message debugging.
- rx**
Enables MVRPDU RX message debugging.
- tx**
Enables MVRPDU TX message debugging.
- reset**
Resets all MVRP debugging parameters to the default.

Debug Commands H - P

debug mvrp

rx-event

Enables MVRP Rx-Event debugging.

show

Displays current MVRP debug parameters.

sm-event

Enables MVRP State-machine event debugging.

timer

Enables MVRP timer debugging.

tx-event

Enables MVRP TX event debugging.

verbose

Enables MVRP verbose debugging mode.

Modes

Privileged EXEC mode

Examples

The following example sets debugging on the MVRP CLI.

```
device# debug mvrp cli
MVRP CLI debugging ON
device# debug mvrp
```

The following example displays current MVRP debug parameters.

```
device# debug mvrp show

MVRP Debug Parameters
-----
MVRP ALL debugging is ON [Mode: Brief]
Event: ON
PDU Tx: OFF
PDU Rx: OFF
PDU Error: OFF
Timer: OFF
CLI: ON
Config: ON
ITC: OFF
Rx-Event: OFF
Tx-Event: OFF
Db-Event: OFF
Error-Event: OFF
State-machine Event: OFF
```

History

Release version	Command history
08.0.90	This command was introduced.

debug packet-capture

Displays information about packet-capture activity.

Syntax

```
debug packet-capture [ all | count-reset | count-show | exclude-mgmt-port | filter | max | mode | no-l2-ctrl-packet | no-limit | no-mgmt-port | receive | send ]
```

Parameters

all

Displays the debugging information of the packets transmitted and received.

count-reset

Clears the total packet count of the packets captured.

count-show

Displays the total packet count of the packets captured for debugging.

exclude-mgmt-port

Enables debugging of the packets that are excluded for the management.

filter

Enables the raw packet filter for debugging.

max

Displays the maximum number of packets.

mode

Displays the various packet modes.

no-l2-ctrl-packet

Toggles to display the packets excluding L2 control packets.

no-limit

Displays the debugging information of an unlimited number of packets.

no-mgmt-port

Toggles the display of packets from the management port.

receive

Debugs only the packets that are received.

send

Debugs only the packets that are transmitted.

Modes

Privileged EXEC mode

debug packet-capture filter

Enables the filter option for the raw packets.

Syntax

```
debug packet-capture filter filter_index filter_options
```

Parameters

filter_index

Specifies the filter number. The decimal value ranges from 1 through 20.

filter_options

Specifies the filter option.

Modes

Privileged EXEC mode

Usage Guidelines

There are 36 filter options that can be configured within a single filter.

- all—Matches all packets
- arp—Matches an ARP request or response
- broadcast-mac—Matches the destination broadcast MAC address (0000.00FF.FFFF)
- cdp—Matches with the CDP
- clear—Clears the filter entry
- clear-counter—Clears the counter
- cpu-code—Matches the CPU code
- da—Matches the destination MAC address
- dhcp—Matches with the DHCP
- dot1x—Matches the dot1x protocol
- dpa—Matches the destination IP address
- dport—Matches the destination protocol port
- ether-type—Matches the Ethernet type packets
- fdp—Matches with the FDP
- in-port—Matches the input port
- l2-802.1w—Matches the 802.1w BPDU
- l2-lacp—Matches the LACP PDU
- l2-mstp—Matches the MSTP BPD
- l2-stp—Matches the spanning tree BPDU
- l3-bgp—Matches with the BGP

- l3-ospf—Matches the OSPF protocol
- l3-vrrp—Matches the VRRP
- l3-vrrpe—Matches the VRRP-E
- lldp—Matches the LLDP
- mrp—Matches the MRP
- out-port—Matches the output port
- priority—Matches the priority
- protocol—Matches the IP
- pvst—Matches the PVST protocol
- sa—Matches the source MAC address
- snmp—Matches the SNMP
- spa—Matches the source IP address
- sport—Matches the source protocol port
- udld—Matches the UDLD protocol
- vlan-id—Matches the VLAN ID
- vsrp—Matches the VSRP

Examples

```
device# debug packet-capture filter 2 protocol
```

debug packet-capture filter match

Toggles to display all matched packets.

Syntax

```
debug packet-capture filter match
```

Modes

Privileged EXEC mode

Examples

```
device# debug packet-capture filter match
```

debug packet-capture filter none

Removes all the filters that are configured.

Syntax

```
debug packet-capture filter none
```

Modes

Privileged EXEC mode

Examples

```
device# debug packet-capture filter none
```

debug packet-capture filter show

Displays the filter information for the particular filter index..

Syntax

```
debug packet-capture filter show [ all | decimal ]
```

Parameters

decimal

Specifies the number of the packet captured for filter.

Modes

Privileged EXEC mode

Examples

Execute the following command to display the complete filter information.

```
device# debug packet-capture filter show all
Filter 1:
                Match STP
Filter 2:
                Match 802.1W
```

Execute the following command to display filter information for a particular filter number.

```
device# debug packet-capture filter show 2
Filter 2:
                Match 802.1W
```

debug packet-capture mode

Displays the format of the packets to be captured for debugging information.

Syntax

```
debug packet-capture mode [ brief | no-display | normal | pcap-fmt { default | decimal } ]
```

Parameters

brief

Specifies the increment counters and displays the packet summary.

no-display

Specifies the increment counters alone.

normal

Specifies the increment counters and displays the packet header and the first 48 raw bytes.

pcap-fmt

Specifies the increment counters and dumps the packet in pcap (packet capture) hexadecimal format.

default

Specifies the normal mode.

decimal

Specifies the first 48 bytes of the packets received.

Modes

Privileged EXEC mode

debug pki

Enables Public Key Infrastructure (PKI) debugging.

Syntax

```
debug pki { error | itc | logging | timer | trace | user }
```

```
no debug pki { error | itc | logging | timer | trace | user }
```

Parameters

error

Enables error debugging for PKI.

itc

Enables ITC messages exchange debugging for PKI.

logging

Captures information whenever a PKI message is logged.

timer

Enables debugging when timer is started/renewed/expired.

trace

Enables trace path debugging for PKI messages.

user

Enables debugging whenever there is a PKI user request received.

Modes

Privileged EXEC mode

Usage Guidelines

The no form of the command disables the PKI debugging.

Examples

```
device# debug pki error
May 27 10:50:16:966541:info:fi_debug:debug_logs:1:51539607553: KEY already exist with label
trustpoint210
May 27 10:23:39:778688:info:fi_debug:debug_logs:1:0: PKI : Error msg from slam : HTTP operation timed
out
May 27 10:23:39:778574:info:fi_debug:debug_logs:1:0: PKI : Output buffer length is zero for the Slam
response with request-id 73 msg-type 3
```

debug port hw-state

Monitors the hardware status of a port.

Syntax

debug port hw-state

no debug port hw-state

Modes

Privileged EXEC mode

Usage Guidelines

Use this command to enable or disable port debugging in the hardware state.

Examples

```
device# debug port hw-state
Topology: Port 1/1/31 is connected to port 1/1/32.
```

If port 1/1/31 is disabled, an output similar to the following is displayed.

```
device(config)# interface ethernet 1/1/31
device(config-if-e1000-1/1/31)# disable ( when port is disabled)
Change port 1/1/31 hw_state from PORT_READY(7) to DISABLED(0)
stack: 4040 2050A970 2050AA44 2060D498 20608BF8 2060B5A4 20576A90 20576C74
2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418 2011BBC8
20047698 2011CF7C 5008
device(config-if-e1000-1/1/31)# change port 1/1/32 hw_state from PORT_READY(7)
to SEQ_INIT(1)
stack: 4040 2050A970 2050AA44 2060D498 20608E18 20609344 20609AFC 2055FA50
2050A214 200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
```

If port 1/1/31 is enabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/32)# interface ethernet 1/1/31
device(config-if-e1000-1/1/31)# enable
Change port 1/1/31 hw_state from DISABLED(0) to SEQ_INIT(1)
stack: 4040 2050A970 2050AA44 2060D498 20608A34 2060B598 20576BC4 20576C74
2057707C 202A4F84 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418 2011BBC8
20047698 2011CF7C 5008
device(config-if-e1000-1/1/31)# change port 1/1/31 hw_state from SEQ_INIT(1) to
PORT_READY(7)
stack: 4040 2050A970 2050AA44 2060D498 206093D0 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
Change port 1/1/32 hw_state from SEQ_INIT(1) to PORT_READY(7)
stack: 4040 2050A970 2050AA44 2060D498 206093D0 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
```

debug port port

Monitors a specific physical port.

Syntax

debug port port *stackid/slot/port*

Parameters

stackid/slot/port

Identifies the specific interface (port), by device, slot, and port number in the format shown.

Modes

Privileged EXEC mode

Global configuration mode

Usage Guidelines

debug port up-down
debug port hw-state

Examples

```
device# debug port port 1/1/2  
Topology: Port 1/1/31 is connected to port 1/1/2.
```

When the **debug port hw-state** command is enabled after the **debug port port** command, the output similar to the following example is displayed.

```
device# debug port port 1/1/2  
monitor port 1/1/2  
device# debug port hw-state
```

If port 1/1/2 is disabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/2)# disable
port_disable_cmd: for port 0x1 1/1/2
U1, hal_pp_link_port_enable(1/1/2, 0), is_stby=0, to_shadow=0, parsed = 3,
stack=1
stack: 0116c83c 000de8f0 00accc3c 00acd6ac 00ad21f4 0136c614 0136c850 0136cf00
012b842c 0084b3b0 0084e0a0 00847608 00966c0c 0086c110 0086c154 00243f98 000f0524
00246f54 0159f920 017713c4
pp_link_port_en_dis(port=1/1/2, 0), return 0
stack: 0116ca20 000de8f0 00accc3c 00acd6ac 00ad21f4 0136c614 0136c850 0136cf00
012b842c 0084b3b0 0084e0a0 00847608 00966c0c 0086c110 0086c154 00243f98 000f0524
00246f54 0159f920 017713c4
Change 1/1/2 state from Forward to Disable
stack: 00acb98c 00ad1e14 00aebd74 0071dddc 0071ebbc 00af0e8c 00af18e8 00ad0e20
00acccf4 00acd6ac 00ad21f4 0136c614 0136c850 0136cf00 012b842c 0084b3b0 0084e0a0
00847608 00966c0c 0086c110 0086c154 00243f98 000f0524 00246f54 0159f920 017713c4
Change port 1/1/2 hw_state from PORT_READY(7) to DISABLED(0)
stack: 00ad5d4c 00accd2c 00acd6ac 00ad21f4 0136c614 0136c850 0136cf00 012b842c
0084b3b0 0084e0a0 00847608 00966c0c 0086c110 0086c154 00243f98 000f0524 00246f54
0159f920 017713c4
Change 1/1/2 state from Disable to Blocked
stack: 00acb98c 00acba3c 00acbce4 00accd38 00acd6ac 00ad21f4 0136c614 0136c850
0136cf00 012b842c 0084b3b0 0084e0a0 00847608 00966c0c 0086c110 0086c154 00243f98
000f0524 00246f54 0159f920 017713c4
Change 1/1/2 state from Blocked to Disable
stack: 00acb98c 00acba3c 00accd48 00acd6ac 00ad21f4 0136c614 0136c850 0136cf00
012b842c 0084b3b0 0084e0a0 00847608 00966c0c 0086c110 0086c154 00243f98 000f0524
00246f54 0159f920 017713c4
```

If port 1/1/2 is enabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/2)# enable
device(config-if-e1000-1/1/2)# change port 1/1/2 hw_state from SEEQ_INIT(1) to
PORT_READY(7)
stack: 4040 2050A970 2050AA44 2060D498 206093D0 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
Change 1/1/2 state from Disable to Blocked
stack: 4040 2050A970 2050AA44 206082E0 2060B354 206215F8 203F9F10 203FB4D8
203FA2B4 2062268C 20623404 2060A624 20609520 20609AFC 2055FA50 2050A214 200478DC
2011BBCC 20047698 2011CF7C
Change 1/1/2 state from Blocked to Listen
stack: 4040 2050A970 2050AA44 206082E0 2060B354 20621734 203F9F10 203FD490
203FD1C4 203FA2BC 2062268C 20623404 2060A624 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698
Change 1/1/2 state from Listen to Learn
stack: 4040 2050A970 2050AA44 206082E0 2060B354 2062178C 203F9F10 20400F38
20400C84 20400A1C 203F9980 2050A214 200478DC 2011BBCC 20047698 2011CF7C 5008 135C8
18524
Change 1/1/2 state from Learn to Blocked
stack: 4040 2050A970 2050AA44 206082E0 2060B354 206215F8 203F9F10 203FD70C
203FD248 203FDFD8 204F3C8C 20616AB8 20612D30 200DC33C 200DC600 200DC6C0 200DC780
200444C4 2011BC28 20047698
```

The **debug port up-down** command disables or enables a port to get output information of the specified port. When the **debug port up-down** command is enabled after the **debug port port** command, output similar to the following example is displayed.

```
device# debug port port 1/1/32
monitor port 1/1/32
device# debug port up-down
```

Debug Commands H - P

debug port port

If port 1/1/32 is disabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/32)# disable
port_down_indication. port=1/1/32, UNTAG, vlan-idx=1
stack: 4040 2050A970 2050AA44 2060A8FC 20608BEC 2060B5A4 20576A90 20576C74
2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418 2011BBC8
20047698 2011CF7C 5008
Change 1/1/32 state from Blocked to Disable
stack: 4040 2050A970 2050AA44 206082E0 2060B354 206214F0 203F9F10 203FA3A0
20622F60 20623404 2060AA38 20608BEC 2060B5A4 20576A90 20576C74 2057707C 202A50A8
20491E9C 20492DC0 204906D8
Change 1/1/32 state from Disable to Blocked
stack: 4040 2050A970 2050AA44 206082E0 20608330 206084C4 20608C00 2060B5A4
20576A90 20576C74 2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 204A03C8
204A0418 2011BBC8 20047698
Change 1/1/32 state from Blocked to Disable
stack: 4040 2050A970 2050AA44 206082E0 20608330 20608C0C 2060B5A4 20576A90
20576C74 2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418
2011BBC8 20047698 2011CF7C
```

If port 1/1/32 is enabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/32)# enable
Change 1/1/32 state from Disable to Blocked
stack: 4040 2050A970 2050AA44 206082E0 206089A0 2060B598 20576BC4 20576C74
2057707C 202A4F84 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418 2011BBC8
20047698 2011CF7C 5008
device(config-if-e1000-1/1/32)# pp_link_change_final. port=1/1/32, up=1
port_up_indication. port=1/1/32, UNTAG, vlan-idx=1
stack: 4040 2050A970 2050AA44 2060A2C8 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
Change 1/1/32 state from Blocked to Listen
stack: 4040 2050A970 2050AA44 206082E0 2060B354 20621734 203F9F10 203FD490
203FD1C4 203FA2BC 2062268C 20623404 2060A624 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698
Change 1/1/32 state from Listen to Blocked
stack: 4040 2050A970 2050AA44 206082E0 2060B354 206215F8 203F9F10 203FD70C
203FD248 203FDFD8 204F3C8C 20616AB8 20612D30 200DC33C 200DC600 200DC6C0 200DC780
200444C4 2011BC28 20047698
```

debug port ten-gig

Monitors all 10 Gigabit ports in the Ruckus RUCKUS devices.

Syntax

debug port ten-gig

Modes

Privileged EXEC mode

Global configuration mode

Usage Guidelines

Use this command in conjunction with the **debug port hw-state** command.

Examples

```
device# debug port ten-gig
Topology: Port 2/3/1 is the 10 gig port which is Up and forwarding on stack.
device# debug port ten-gig
device# debug port hw-state
hw-state monitor hw_state change
device# debug port hw-state
```

If port 2/3/1 is disabled, an output similar to the following is displayed.

```
device(config-if-e10000-2/3/1)# disable
Change port 2/3/1 hw_state from PORT_READY(7) to DISABLED(0)
stack: 4040 2050A970 2050AA44 2060D498 20608BF8 2060B5A4 20576A90 20576C74
2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 2027FD8C 20280888 202809F0
2015FCDC 2015FF44 20160B80
```

If port 2/3/1 is enabled, an output similar to the following is displayed.

```
device(config-if-e10000-2/3/1)# enable
Change port 2/3/1 hw_state from DISABLED(0) to SEQ_INIT(1)
stack: 4040 2050A970 2050AA44 2060D498 20608A34 2060B598 20576BC4 20576C74
2057707C 202A4F84 20491E9C 20492DC0 204906D8 2050BF48 2027FD8C 20280888 202809F0
2015FCDC 2015FF44 20160B80
device(config-if-e10000-2/3/1)# change port 2/3/1 hw_state from SEQ_INIT(1) to
PORT_READY(7)
stack: 4040 2050A970 2050AA44 2060D498 206093D0 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
```

debug port up-down

Monitors the status of the ports.

Syntax

debug port up-down *decimal*

no debug port up-down *decimal*

Parameters

decimal

Specifies the status of the port.

Modes

Privileged EXEC mode

Global configuration mode

Usage Guidelines

This command disables or enables a port to get output information of the specified port. The port status up, down, and up/down are indicated by 1, 2, and 3 respectively.

Examples

```
device# debug port up-down 1
Monitor port up
Topology: Port 1/1/31 is connected to port 1/1/32.
```

If port 1/1/31 is disabled, an output similar to the following is displayed.

```
device(config)# interface ethernet 1/1/31
device(config-if-e1000-1/1/31)# disable
port_down_indication. port=1/1/31, UNTAG, vlan-idx=1
stack: 4040 2050A970 2050AA44 2060A8FC 20608BEC 2060B5A4 20576A90 20576C74
2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418 2011BBC8
20047698 2011CF7C 5008
device(config-if-e1000-1/1/31)# port_down_indication. port=1/1/32, UNTAG,
vlan-idx=3
stack: 4040 2050A970 2050AA44 2060A8FC 20608DA0 20609344 20609AFC 2055FA50
2050A214 200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
pp_link_change_final. port=1/1/32, up=0
```

If port 1/1/31 is enabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/31)# enable
device(config-if-e1000-1/1/31)# pp_link_change_final. port=1/1/31, up=1
port_up_indication. port=1/1/31, UNTAG, vlan-idx=1
stack: 4040 2050A970 2050AA44 2060A2C8 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
pp_link_change_final. port=1/1/32, up=1
port_up_indication. port=1/1/32, UNTAG, vlan-idx=3
stack: 4040 2050A970 2050AA44 2060A2C8 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
```

History

Release version	Command history
	This command was introduced.
	This command was modified to...

debug port vlan

Monitors a specific VLAN.

Syntax

debug port vlan *decimal*

no debug port vlan *decimal*

Parameters

decimal

Specifies the number of the VLAN.

Modes

Privileged EXEC mode

Global configuration mode

Usage Guidelines

debug port up-down
debug port port

Examples

```
device# debug port vlan 1
monitor vlan 1
Topology: Port 1/1/31 is connected to port 1/1/32.
device# debug port vlan 2
monitor vlan 2
device# debug port up-down
up-down monitor port up/down event. 1: up, 2: down, 3: up/down
device# debug port up-down 3
Monitor both port up and down
```

If port 1/1/31 is disabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/31)# disable
port_down_indication. port=1/1/31, TAG, vlan-idx=4096
stack: 4040 2050A970 2050AA44 2060A8FC 20608BEC 2060B5A4 20576A90 20576C74
2057707C 202A50A8 20491E9C 20492DC0 204906D8 2050BF48 204A03C8 204A0418 2011BBC8
20047698 2011CF7C 5008
device(config-if-e1000-1/1/31)# port_down_indication. port=1/1/32, TAG,
vlan-idx=4096
stack: 4040 2050A970 2050AA44 2060A8FC 20608DA0 20609344 20609AFC 2055FA50
2050A214 200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
pp_link_change_final. port=1/1/32, up=0
```

If port 1/1/31 is enabled, an output similar to the following is displayed.

```
device(config-if-e1000-1/1/31)# enable
device(config-if-e1000-1/1/31)# pp_link_change_final. port=1/1/31, up=1
port_up_indication. port=1/1/31, TAG, vlan-idx=4096
stack: 4040 2050A970 2050AA44 2060A2C8 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
pp_link_change_final. port=1/1/32, up=1
port_up_indication. port=1/1/32, TAG, vlan-idx=4096
stack: 4040 2050A970 2050AA44 2060A2C8 20609520 20609AFC 2055FA50 2050A214
200478DC 2011BBCC 20047698 2011CF7C 5008 135C8 18524
```

debug pp-trunk-hash

Traces and displays the output port through which a given packet can be sent out in a LAG.

Syntax

```
debug pp-trunk-hash lag-id { non-unicast-distribution | unicast-distribution } ip vlan-id dst_ipv4/ipv6 src_ipv4/ipv6 protocol_num  
dest_tcp/udp tcp/udp_src_port
```

```
debug pp-trunk-hash lag-id { non-unicast-distribution | unicast-distribution } non-ip dmac smac
```

```
no debug pp-trunk-hash
```

Parameters

lag_id

Specifies the ID of the LAG.

non-unicast-distribution

Generates debugging information related to non-unicast distribution for unknown unicast destination or destination lookup failed traffic.

unicast-distribution

Generates debugging information related to unicast distribution for single trunk destination.

ip

Generates debugging information related to IP traffic distribution.

non-ip

Generates debugging information related to routed traffic.

vlan_id

Specifies the VLAN ID in the packet.

dst_ipv4/ipv6

Specifies the destination IPv4 address or destination IPv6 address.

src_ipv4/ipv6

Specifies the source IPv4 address or destination IPv6 address.

protocol-number

Specifies the protocol in IP headers.

dest_tcp/udp

Specifies the destination TCP or UDP port number.

tcp/udp_src_port

Specifies the source TCP or UDP port number.

dmac

Specifies the destination MAC address.

smac

Specifies the source MAC address.

Modes

Privileged EXEC mode

Examples

For the non-unicast IPv4 distribution, the command resembles the following example.

```
device#debug pp-trunk-hash 3 non-unicast-distribution ip 1 2.2.2.2 3.3.3.3 6 22 23  
Lag with id 1 (hw_trunk_i=3)does not have any up ports. Atleast one up port should be present in the lag
```

For the non-unicast IPv6 distribution, the command resembles the following example.

```
device#debug pp-trunk-hash 3 non-unicast-distribution ip 1 2:2::2:2 4:4::4:4 3 22 23  
Lag with id 1 (hw_trunk_i=3)does not have any up ports. Atleast one up port should be present in the lag
```

For the non-unicast non-IP distribution, the command resembles the following example.

```
device#debug pp-trunk-hash 3 non-unicast-distribution non-ip 2222.3333.4444 4444.3333.2222  
Lag with id 1 (hw_trunk_i=3)does not have any up ports. Atleast one up port should be present in the lag
```

For the unicast IP distribution, the command resembles the following example.

```
device#debug pp-trunk-hash 3 unicast-distribution ip 2 2.2.2.2 3.3.3.3 6 22 23  
Lag with id 1 (hw_trunk_i=3)does not have any up ports. Atleast one up port should be present in the lag
```

For the unicast non-IP distribution, the command resembles the following example.

```
device#debug pp-trunk-hash 3 unicast-distribution non-ip 2222.3333.4444 4444.3333.2222  
Lag with id 1 (hw_trunk_i=3)does not have any up ports. Atleast one up port should be present in the lag
```

debug pvlan cli

Debugs private VLAN (PVLAN) CLI.

Syntax

debug pvlan cli

no debug pvlan cli

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables the debugging of PVLAN CLI.

Examples

The following example debugs PVLAN CLI.

```

device# debug pvlan cli
device# show log debug l2 pvlan all all
Jun 11 10:48:24:653301:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:48:24:647723:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:48:24:647563:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:48:24:647402:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 10:39:51:376523:debug:l2:pvlan:1:6833621172225: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
3
Jun 11 10:38:04:635720:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 14
Jun 11 10:38:04:568381:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 13
Jun 11 10:38:04:473738:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 12
Jun 11 10:38:04:472285:debug:l2:pvlan:1:6704772153345: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
0
Jun 11 10:38:00:703442:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 4
Jun 11 10:38:00:632858:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 3
Jun 11 10:38:00:605732:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 2
Jun 11 10:37:54:089673:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:37:54:089581:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:37:54:089421:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:37:54:089303:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:58:13:017866:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:58:13:017746:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:58:13:017040:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:58:13:016941:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:52:596658:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:57:52:596572:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:57:52:596414:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:57:52:596257:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:32:812601:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:57:32:812218:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 0
Jun 11 09:57:26:691179:debug:l2:pvlan:1:5845778694145: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:55:48:310910:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 4
Jun 11 09:55:48:117997:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 3
Jun 11 09:55:48:022861:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 2
Jun 11 09:55:48:005228:debug:l2:pvlan:1:5704044773377: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:52:09:764567:debug:l2:pvlan:1:5665390067713: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:51:54:060246:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 4
Jun 11 09:51:54:030673:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 3
Jun 11 09:51:53:945283:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 2
Jun 11 09:51:53:943820:debug:l2:pvlan:1:5575195754497: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:50:51:322329:debug:l2:pvlan:1:5446346735617: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:50:30:972768:debug:l2:pvlan:1:5364742356993: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 0
Jun 11 09:48:12:178717:debug:l2:pvlan:1:5338972553217: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 3
Jun 11 09:32:30:671284:debug:l2:pvlan:1:4278115631105: PVLAN: removing vlan 4
Jun 11 09:32:29:682047:debug:l2:pvlan:1:4273820663809: PVLAN: removing vlan 3
Jun 11 09:32:27:284027:debug:l2:pvlan:1:4269525696513: PVLAN: removing vlan 2
Jun 11 09:29:27:640221:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:29:27:640074:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:24:31:814627:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 4
Jun 11 09:24:31:783089:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 3
Jun 11 09:24:31:753162:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 2

```

debug pvlan egr-trans

Debugs egress translation on secondary VLAN ports.

Syntax

debug pvlan egr-trans

no debug pvlan egr-trans

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables debugging of egress translation on secondary VLAN ports.

Examples

The following example debugs egress translation on secondary VLAN ports.

```

device# debug pvlan egr-trans
device# show log debug l2 pvlan all all
Jun 11 10:48:24:653301:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:48:24:647723:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:48:24:647563:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:48:24:647402:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 10:39:51:376523:debug:l2:pvlan:1:6833621172225: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
3
Jun 11 10:38:04:635720:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 14
Jun 11 10:38:04:568381:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 13
Jun 11 10:38:04:473738:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 12
Jun 11 10:38:04:472285:debug:l2:pvlan:1:6704772153345: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
0
Jun 11 10:38:00:703442:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 4
Jun 11 10:38:00:632858:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 3
Jun 11 10:38:00:605732:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 2
Jun 11 10:37:54:089673:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:37:54:089581:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:37:54:089421:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:37:54:089303:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:58:13:017866:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:58:13:017746:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:58:13:017040:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:58:13:016941:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:52:596658:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:57:52:596572:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:57:52:596414:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:57:52:596257:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:32:812601:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:57:32:812218:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 0
Jun 11 09:57:26:691179:debug:l2:pvlan:1:5845778694145: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:55:48:310910:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 4
Jun 11 09:55:48:117997:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 3
Jun 11 09:55:48:022861:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 2
Jun 11 09:55:48:005228:debug:l2:pvlan:1:5704044773377: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:52:09:764567:debug:l2:pvlan:1:5665390067713: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:51:54:060246:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 4
Jun 11 09:51:54:030673:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 3
Jun 11 09:51:53:945283:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 2
Jun 11 09:51:53:943820:debug:l2:pvlan:1:5575195754497: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:50:51:322329:debug:l2:pvlan:1:5446346735617: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:50:30:972768:debug:l2:pvlan:1:5364742356993: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 0
Jun 11 09:48:12:178717:debug:l2:pvlan:1:5338972553217: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 3
Jun 11 09:32:30:671284:debug:l2:pvlan:1:4278115631105: PVLAN: removing vlan 4
Jun 11 09:32:29:682047:debug:l2:pvlan:1:4273820663809: PVLAN: removing vlan 3
Jun 11 09:32:27:284027:debug:l2:pvlan:1:4269525696513: PVLAN: removing vlan 2
Jun 11 09:29:27:640221:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:29:27:640074:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:24:31:814627:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 4
Jun 11 09:24:31:783089:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 3
Jun 11 09:24:31:753162:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 2

```

debug pvlan event

Monitors private VLAN (PVLAN) event.

Syntax

debug pvlan event

no debug pvlan event

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables monitoring of PVLAN events.

Examples

The following example monitors PVLAN event.

```

device# debug pvlan event
device# show log debug l2 pvlan all all
Jun 11 10:48:24:653301:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:48:24:647723:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:48:24:647563:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:48:24:647402:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 10:39:51:376523:debug:l2:pvlan:1:6833621172225: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
3
Jun 11 10:38:04:635720:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 14
Jun 11 10:38:04:568381:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 13
Jun 11 10:38:04:473738:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 12
Jun 11 10:38:04:472285:debug:l2:pvlan:1:6704772153345: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
0
Jun 11 10:38:00:703442:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 4
Jun 11 10:38:00:632858:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 3
Jun 11 10:38:00:605732:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 2
Jun 11 10:37:54:089673:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:37:54:089581:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:37:54:089421:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:37:54:089303:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:58:13:017866:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:58:13:017746:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:58:13:017040:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:58:13:016941:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:52:596658:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:57:52:596572:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:57:52:596414:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:57:52:596257:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:32:812601:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:57:32:812218:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 0
Jun 11 09:57:26:691179:debug:l2:pvlan:1:5845778694145: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:55:48:310910:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 4
Jun 11 09:55:48:117997:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 3
Jun 11 09:55:48:022861:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 2
Jun 11 09:55:48:005228:debug:l2:pvlan:1:5704044773377: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:52:09:764567:debug:l2:pvlan:1:5665390067713: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:51:54:060246:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 4
Jun 11 09:51:54:030673:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 3
Jun 11 09:51:53:945283:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 2
Jun 11 09:51:53:943820:debug:l2:pvlan:1:5575195754497: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:50:51:322329:debug:l2:pvlan:1:5446346735617: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:50:30:972768:debug:l2:pvlan:1:5364742356993: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 0
Jun 11 09:48:12:178717:debug:l2:pvlan:1:5338972553217: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 3
Jun 11 09:32:30:671284:debug:l2:pvlan:1:4278115631105: PVLAN: removing vlan 4
Jun 11 09:32:29:682047:debug:l2:pvlan:1:4273820663809: PVLAN: removing vlan 3
Jun 11 09:32:27:284027:debug:l2:pvlan:1:4269525696513: PVLAN: removing vlan 2
Jun 11 09:29:27:640221:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:29:27:640074:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:24:31:814627:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 4
Jun 11 09:24:31:783089:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 3
Jun 11 09:24:31:753162:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 2

```

debug pvlan vlan

Debugs specific private VLAN (PVLAN).

Syntax

```
debug pvlan vlan vlan_id
```

```
no debug pvlan vlan vlan_id
```

Parameters

vlan_id

Specifies the VLAN ID.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables the debugging of a specific VLAN.

Examples

The following example debugs a specific private VLAN.

```

device# debug pvlan vlan 100
device# show log debug l2 pvlan all all
Jun 11 10:48:24:653301:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:48:24:647723:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:48:24:647563:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:48:24:647402:debug:l2:pvlan:1:6936700387329: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 10:39:51:376523:debug:l2:pvlan:1:6833621172225: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
3
Jun 11 10:38:04:635720:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 14
Jun 11 10:38:04:568381:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 13
Jun 11 10:38:04:473738:debug:l2:pvlan:1:6704772153345: PVLAN: removing vlan 12
Jun 11 10:38:04:472285:debug:l2:pvlan:1:6704772153345: cpssDxChBrgStpEntryGet 1/2/4 vlan 14 stp 5 state
0
Jun 11 10:38:00:703442:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 4
Jun 11 10:38:00:632858:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 3
Jun 11 10:38:00:605732:debug:l2:pvlan:1:6696182218753: PVLAN: removing vlan 2
Jun 11 10:37:54:089673:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 10:37:54:089581:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 10:37:54:089421:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 10:37:54:089303:debug:l2:pvlan:1:6683297316865: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:58:13:017866:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:58:13:017746:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:58:13:017040:debug:l2:pvlan:1:6000397516801: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:57:52:596257:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:52:596658:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 14 is not a primary
Jun 11 09:57:52:596572:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 13 is not a primary
Jun 11 09:57:52:596414:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:57:52:596257:debug:l2:pvlan:1:5953152876545: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:57:32:812601:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:57:32:812218:debug:l2:pvlan:1:5888728367105: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 0
Jun 11 09:57:26:691179:debug:l2:pvlan:1:5845778694145: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 7 state 3
Jun 11 09:55:48:310910:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 4
Jun 11 09:55:48:117997:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 3
Jun 11 09:55:48:022861:debug:l2:pvlan:1:5704044773377: PVLAN: removing vlan 2
Jun 11 09:55:48:005228:debug:l2:pvlan:1:5704044773377: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:52:09:764567:debug:l2:pvlan:1:5665390067713: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:51:54:060246:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 4
Jun 11 09:51:54:030673:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 3
Jun 11 09:51:53:945283:debug:l2:pvlan:1:5575195754497: PVLAN: removing vlan 2
Jun 11 09:51:53:943820:debug:l2:pvlan:1:5575195754497: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 0
Jun 11 09:50:51:322329:debug:l2:pvlan:1:5446346735617: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 5 state 3
Jun 11 09:50:30:972768:debug:l2:pvlan:1:5364742356993: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 0
Jun 11 09:48:12:178717:debug:l2:pvlan:1:5338972553217: cpssDxChBrgStpEntryGet 1/2/4 vlan 4 stp 6 state 3
Jun 11 09:32:30:671284:debug:l2:pvlan:1:4278115631105: PVLAN: removing vlan 4
Jun 11 09:32:29:682047:debug:l2:pvlan:1:4273820663809: PVLAN: removing vlan 3
Jun 11 09:32:27:284027:debug:l2:pvlan:1:4269525696513: PVLAN: removing vlan 2
Jun 11 09:29:27:640221:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 4 is not a primary
Jun 11 09:29:27:640074:debug:l2:pvlan:1:4162151514113: PVLAN: cu_show_pvlan() vlan 3 is not a primary
Jun 11 09:24:31:814627:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 4
Jun 11 09:24:31:783089:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 3
Jun 11 09:24:31:753162:debug:l2:pvlan:1:3947403149313: PVLAN: removing vlan 2

```


Debug Commands Q - Z

restconf platform-debug-level

Enables debugging for the RESTCONF Service Module.

Syntax

```
restconf platform-debug-level { critical | debug | error | info }
```

```
no restconf platform-debug-level { critical | debug | error | info }
```

Command Default

The RESTCONF platform debug level is set to info.

Parameters

critical

Sets the RESTCONF platform debug level to critical.

debug

Sets the RESTCONF platform debug level to debug.

error

Sets the RESTCONF platform debug level to error.

info

Sets the RESTCONF platform debug level to info.

Modes

Configuration mode

Examples

The following example sets the RESTCONF platform debug level to error.

```
device# configure terminal
device(config)# restconf platform-debug-level error
```

History

Release version	Command history
09.0.00	This command was introduced.

restconf protocol-debug-level

Enables RESTCONF management interface.

Syntax

```
restconf platform-debug-level { debug | debug2 | debug3 | debug4 | error | info | warn }
```

Command Default

The RESTCONF protocol debug level is set to info.

Parameters

- debug**
Sets the RESTCONF protocol debug level to debug.
- debug2**
Sets the RESTCONF protocol debug level to debug2 (caution).
- debug3**
Sets the RESTCONF protocol debug level to debug3 (caution).
- debug4**
Sets the RESTCONF protocol debug level to debug4 (caution).
- error**
Sets the RESTCONF protocol debug level to error.
- info**
Sets the RESTCONF protocol debug level to info.
- warn**
Sets the RESTCONF protocol debug level to warn.

Modes

Configuration mode

Examples

The following example sets the RESTCONF protocol debug level to warn.

```
device# configure terminal  
device(config)# restconf protocol-debug-level warn
```

History

Release version	Command history
09.0.00	This command was introduced.

debug rate-limiting

Enables port-based rate limiting debugging.

Syntax

```
debug rate-limiting { pi | pd } show [ unit/slot/port | number ]
no debug rate-limiting { pi | pd } show [ unit/slot/port | number ]
```

Parameters

pi
Specifies platform independent rate-limiting.

pd
Specifies platform dependent rate-limiting.

show *unit/slot/port*
Displays platform dependent or independent rate-limiting configurations on specific ports.

Modes

Privileged EXEC mode

Examples

The following example displays platform dependent rate-limiting configurations on interface ethernet 1/1/1.

```
device#debug rate-limiting pd show 1/1/1
PBRL PD configuration for port 1/1/1 devport 2
Ingress rate limit: 1024 burst: 442
```

The following example displays platform independent rate-limiting configurations on interface ethernet 1/1/2.

```
device#debug rate-limiting pi show 1/1/2
Ingress Rate-limiting config for 1/1/2:
  Rate 2000          (kbps) burst_size 100
```

debug rip database

Displays Routing Information Protocol (RIP) database events.

Syntax

```
debug rip database
no debug rip database
```

Modes

Privileged EXEC mode

Examples

```
device# debug rip database
device(config-vif-11)# RIP(default-vrf): (v2) process response packet
header: type:RESPONSE PACKET, version:2
RIP(default-vrf): refresh 10.1.2.0/24 metric 3 from 10.5.5.2 ve 11
RIP(default-vrf): existing route metric 2 from 10.4.4.1 ve 12
RIP(default-vrf): refresh 10.24.2.0/24 metric 4 from 10.5.5.2 ve 11
RIP(default-vrf): existing route metric 4 from 10.5.5.2 ve 11
RIP(default-vrf): (v2) process response packet
header: type:RESPONSE PACKET, version:2
RIP(default-vrf): refresh 10.24.2.0/24 metric 4 from 10.4.4.2 ve 12
RIP(default-vrf): existing route metric 4 from 10.5.5.2 ve 11
```

debug rip events

Displays RIP events.

Syntax

debug rip events

no debug rip events

Modes

Privileged EXEC mode

Global configuration mode

Examples

```
device# debug rip events
device(config-vif-11)# RIPng: update timer expired
clear ipv routeRIPng: triggered update
RIPng: garbage prefix 2001:DB8::/64 timer 1, metric 0, tag 0
from :: on interface NULL
RIPng: garbage prefix 2001:DB8::/64 timer 1, metric 0, tag 0
from :: on interface NULL
RIPng: Adding local connected route 2001:DB8::1/64 on interface v11
RIPng: Adding local connected route 2001:DB8::1/64 on interface v12
RIPng: update timer expired
RIPng: Redistribute add route 2001:DB8::/64, type CONNECTED (1/0)
RIPng: Redistribute add route 2001:DB8::/64, type CONNECTED (1/0)
```

debug sflow

Enables sFlow debugging.

Syntax

```
debug sflow { jetcore | masteripc | problems | ptrace | slaveipc }
```

```
no debug sflow { jetcore | masteripc | problems | ptrace | slaveipc }
```

Parameters

jetcore

Displays information about sFlow registers for debugging.

masteripc

Enables debugging on master received and sent sflow IPC messages.

problems

Enables debugging of the internal sFlow.

ptrace

Enables debugging of messages on sflow samplings.

slaveipc

Enables debugging on slave received and sent sflow IPC messages.

Modes

Privileged EXEC mode

Usage Guidelines

The **show logging debug security sflow all** command does not display the debug logs in the output in 09.0.00 release.

sFlow is a system for observing traffic flow patterns and quantities within and among a set of RUCKUS devices.

The no form of the command disables sFlow debugging.

Examples

```
device# debug sflow problems  
sflow: problem debugging is on
```

debug span all_802_1d_events

Monitors information about all the events, timers, and packets on a specific VLAN.

Syntax

`debug span all_802_1d_events decimal`

`no debug span all_802_1d_events decimal`

Parameters

variable

Specifies the number of the VLAN.

Modes

Privileged EXEC mode

Examples

```
device# debug span all_802_1d_events vlan 201
STP Enabling All events Debugging for VLAN 201
device#STP[898211]: Received Config BPDU - VLAN 201 -port 54/1/21
port_state_selection(T=898211,vlan=201) -->
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 1/1/1(0) VLAN 201
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 2/1/1(256) VLAN 201
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 3/1/1(512) VLAN 201
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 51/1/1(12800) VLAN 201
STP:port_state_selection PORT 51/1/21 vlan 201 transitions to BLOCKING
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 52/1/1(13056) VLAN 201
STP:port_state_selection PORT 52/1/21 vlan 201 transitions to BLOCKING
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 53/1/1(13312) VLAN 201
STP:port_state_selection PORT 53/1/21 vlan 201 transitions to BLOCKING
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 54/1/1(13568) VLAN 201
port_state_selection root port 54/1/21
STP[898211]: Received Config BPDU - VLAN 201 -port 51/1/21 port_state_selection(T=898211,vlan=201) -->
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 1/1/1(0) VLAN 201
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 2/1/1(256) VLAN 201
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 3/1/1(512) VLAN 201
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 51/1/1(12800) VLAN 201
STP:port_state_selection PORT 51/1/21 vlan 201 transitions to BLOCKING
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 52/1/1(13056) VLAN 201
STP:port_state_selection PORT 52/1/21 vlan 201 transitions to BLOCKING
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 53/1/1(13312) VLAN 201
STP:port_state_selection PORT 53/1/21 vlan 201 transitions to BLOCKING
STP:port_state_selection PORT transitions to DESIGNATED_FORWARD state , port 54/1/1(13568) VLAN 201
port_state_selection root port 54/1/21
```

debug span config

Monitors information about STP Bridge Protocol Data Unit (BPDU) configuration on a specific VLAN.

Syntax

```
debug span config vlan decimal ]
```

```
no debug span config vlan decimal ]
```

Parameters

decimal

Specifies the number of the VLAN.

Modes

Privileged EXEC mode

Examples

If the configuration of VLAN 2 on the RUCKUS ICX is enabled, output similar to the following is displayed.

```
device# debug span config vlan 2
STP Enabling packets Debugging for VLAN 2

device# STP: Transmitting Config BPDU - VLAN 2 - Port 1/1/5
0000 00 00 00 80000012f2dbfd80 00000004
8000002438154580 08 05 0100 1400 0200 0f00
STP: Transmitting Config BPDU - VLAN 2 - Port 1/1/6
0000 00 00 00 80000012f2dbfd80 00000004
8000002438154580 08 06 0100 1400 0200 0f00
STP: Transmitting Config BPDU - VLAN 2 - Port 1/1/5
0000 00 00 00 80000012f2dbfd80 00000004
8000002438154580 08 05 0100 1400 0200 0f00
STP: Transmitting Config BPDU - VLAN 2 - Port 1/1/6
0000 00 00 00 80000012f2dbfd80 00000004
8000002438154580 08 06 0100 1400 0200 0f00
STP: Transmitting Config BPDU - VLAN 2 - Port 1/1/5
0000 00 00 00 80000012f2dbfd80 00000004
8000002438154580 08 05 0100 1400 0200 0f00
STP: Transmitting Config BPDU - VLAN 2 - Port 1/1/6
0000 00 00 00 80000012f2dbfd80 00000004
8000002438154580 08 06 0100 1400 0200 0f00
```

If the configuration of VLAN 2 on the RUCKUS ICX is disabled, output similar to the following is displayed.

```
device# no debug span config vlan 2
STP : Disabling Packets Debugging for VLAN 2
```

debug span timers

Displays information about the specific STP timer events.

Syntax

```
debug span timers vlan decimal
```

```
no debug span timers vlan decimal
```

Parameters

decimal

Specifies the number of the VLAN.

Modes

Privileged EXEC mode

Examples

If the STP timer event on VLAN 2 of the RUCKUS FastIron device is enabled, output similar to the following is displayed.

```
device# debug span timers vlan 2
STP Enabling Timer Debugging for VLAN 2
Sample output:
STP: Timer Alert - Forward Delay Timer expired On port 1/1/6(5) , VLAN 2
STP: Timer Alert - Forward Delay Timer expired On port 1/1/1(0) , VLAN 2
STP: Timer Alert - Forward Delay Timer expired On port 1/1/6(5) , VLAN 2
STP: Timer Alert - Message Age Timer expired On port 1/1/1(0) , VLAN 2
STP: Timer Alert - Message Age Timer expired On port 1/1/2(1) , VLAN 2
STP: Timer Alert - Forward Delay Timer expired On port 1/1/2(1) , VLAN 2
STP: Timer Alert - Forward Delay Timer expired On port 1/1/2(1) , VLAN 2
```

If the STP timer event on VLAN 2 of the RUCKUS FastIron device is disabled, output similar to the following is displayed.

```
device# no debug span timers vlan 2
STP Disabling Timer Debugging for VLAN 2
```

debug system campram

Traces Content Addressable Memory (CAM) or Parallel Random Access Machine (PRAM) operations.

Syntax

debug system campram

no debug system campram

Modes

Privileged EXEC mode

Examples

```
device# debug system campram  
cam/pram: Trace debugging is on
```

debug system mem-leak

Enables memory leak detection for a specific process from bootup.

Syntax

```
debug system mem-leak
```

Modes

Privileged EXEC mode

Examples

The following example turns on memory leak tracking for poed process.

```
device# debug system mem-leak
```

History

Release version	Command history
09.0.00	This command was introduced.

debug system optics

Activates optical monitor debugging.

Syntax

debug system optics

no debug system optics

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug system optics  
optics: Trace debugging is on
```

debug trunk

Enables trunk debugging.

Syntax

```
debug trunk { ctrl | event | functioncallback }
```

```
no debug trunk { ctrl | event | functioncallback }
```

Parameters

ctrl

Displays trunk control debug information.

event

Displays trunk event debug information.

functioncallback

Displays trunk function callback debug information.

Modes

Privileged EXEC mode

Usage Guidelines

The **no** form of the command disables trunk debugging.

Examples

The following example enables trunk debugging.

```
device#debug trunk ctrl
device#debug trunk event
device#debug trunk functioncallback
Jul 06 08:44:26:406809:debug:12:lag:1:700724543489: sw_cu_lag_generic_port_add_validation(lag=2,mask=
1/1/20,add,static,force_delete=0) (T=7364366,task=l2config) (I)
Jul 06 08:44:26:407030:debug:12:lag:1:700724543489: sw_cu_lag_generic_port_add_validation(lag=2,mask=
1/1/20,add,static,force_delete=0) (T=7364366,task=l2config) find cb@0x97825af8 (lag_primary_port=lg2,
lag_num_ports=0, deployed=0)
Jul 06 08:44:26:407232:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L3
function callname: L3_trunk_validation_callback
Jul 06 08:44:26:407316:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L4
function callname: uac_common_trunk_validation_callback
Jul 06 08:44:26:407597:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L4
function callname: qos_xCP_common_trunk_validation_callback
Jul 06 08:44:26:416707:debug:12:lag:1:700724543489: sw_cu_lag_generic_port_add_validation(lag=2,mask=
lg2,add,static,force_delete=1) (T=7364366,task=l2config) (I)
Jul 06 08:44:26:416943:debug:12:lag:1:700724543489: sw_cu_lag_generic_port_add_validation(lag=2,mask=
lg2,add,static,force_delete=1) (T=7364366,task=l2config) find cb@0x97825af8 (lag_primary_port=lg2,
lag_num_ports=0, deployed=0)
Jul 06 08:44:26:417122:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L3
function callname: L3_trunk_validation_callback
Jul 06 08:44:26:417199:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L4
function callname: uac_common_trunk_validation_callback
Jul 06 08:44:26:417278:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L4
function callname: qos_xCP_common_trunk_validation_callback
Jul 06 08:44:26:425804:debug:12:lag:1:700724543489: cu_lag_create_trunk(lag=test1,lag_id=2,dep)
(T=7364366,task=l2config) >>
Jul 06 08:44:26:425877:debug:12:lag:1:700724543489: cu_lag_create_trunk(lag=test1,lag_id=2,dep)
(T=7364366,task=l2config) current lag_mac=0000.0000.0000 -> lagctrl_refresh_active_lag_mac
Jul 06 08:44:26:425951:debug:12:lag:1:700724543489:
>>> lagctrl_lag_deploy(lag=2,deploy,dynamic) (T=7364366,task=l2config) (I) pri=lg2
(port_group_id=512,port_trunk_id=2,config_trunk_id=3073,trunk_state=0,trunk_primary=lg2), #_port=1,
Port List:
Jul 06 08:44:26:426016:debug:12:lag:1:700724543489: (lg2)
Jul 06 08:44:26:426077:debug:12:lag:1:700724543489:
Jul 06 08:44:26:426140:debug:12:lag:1:700724543489: lagctrl_lag_deploy(lag=2,deploy,dynamic)
(T=7364366,task=l2config) (I) -> sw_trunk_precreate_event()
Jul 06 08:44:26:426727:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_PRECREATE LAG id: 2
Jul 06 08:44:26:426820:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_PRECREATE Module: L2 function
callname: sw_cu_rstp_trunk_update_callback trunk id: 2
Jul 06 08:44:26:427098:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_PRECREATE Module: L2 function
callname: sw_cu_spanningTree_trunk_update_callback trunk id: 2
Jul 06 08:44:26:427179:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_PRECREATE Module: L2 function
callname: sw_cu_vsrp_trunk_update_callback trunk id: 2
Jul 06 08:44:26:427247:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_PRECREATE Module: L2 function
callname: sw_cu_mrp_trunk_update_callback trunk id: 2
Jul 06 08:44:26:427315:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_PRECREATE Module: L2 function
callname: sw_cu_vlan_vport_trunk_update_callback trunk id: 2
Jul 06 08:44:26:427494:debug:12:lag:1:700724543489: lagctrl_lag_deploy(lag=2,deploy,dynamic)
(T=7364366,task=l2config) (I) done, pri=lg2
(port_group_id=512,port_trunk_id=2,config_trunk_id=3073,trunk_state=0,trunk_primary=lg2)
Jul 06 08:44:26:429522:debug:12:lag:1:700724543489: EVENT_ID_TRUNK_CREATE LAG id: 2
Jul 06 08:44:26:434731:debug:12:lag:1:700724543489: cu_lag_create_trunk(lag_id=2) deploy done, HW Trunk
Id 2
Jul 06 08:44:26:434809:debug:12:lag:1:700724543489: cu_lag_create_trunk(lag_id=2) (T=7364367) deploy
done&
Jul 06 08:44:26:435537:debug:12:lag:1:700724543489: sw_cu_lag_generic_port_add_validation(lag=2,mask=
1/1/20,add,static,force_delete=1) (T=7364367,task=l2config) (I)
Jul 06 08:44:26:435733:debug:12:lag:1:700724543489: sw_cu_lag_generic_port_add_validation(lag=2,mask=
1/1/20,add,static,force_delete=1) (T=7364367,task=l2config) find cb@0x97825af8 (lag_primary_port=lg2,
lag_num_ports=1, deployed=1)
Jul 06 08:44:26:435920:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L3
function callname: L3_trunk_validation_callback
Jul 06 08:44:26:436002:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L4
function callname: uac_common_trunk_validation_callback
Jul 06 08:44:26:436214:info:12:lag:1:700724543489: sw_lag_config_ports_add_validation(lag_id=2) L4
function callname: qos_xCP_common_trunk_validation_callback
```

```

Jul 06 08:44:26:444255:debug:12:lag:1:700724543489:
lagctrl_add_ports_to_deployed_lag(T=7364367,lag_id=2,num_of_ports=1,ports={1/1/20,1/1/1,1/1/1,1/1/1,...}
) -> TrunkPreCreateCallbackTable -> (2,sw_cu_rstp_trunk_update_callback)
Jul 06 08:44:26:444574:debug:12:lag:1:700724543489:
lagctrl_add_ports_to_deployed_lag(T=7364367,lag_id=2,num_of_ports=1,ports={1/1/20,1/1/1,1/1/1,1/1/1,...}
) -> TrunkPreCreateCallbackTable -> (2,sw_cu_spanningTree_trunk_update_callback)
Jul 06 08:44:26:444668:debug:12:lag:1:700724543489:
lagctrl_add_ports_to_deployed_lag(T=7364367,lag_id=2,num_of_ports=1,ports={1/1/20,1/1/1,1/1/1,1/1/1,...}
) -> TrunkPreCreateCallbackTable -> (2,sw_cu_vsrp_trunk_update_callback)
Jul 06 08:44:26:444743:debug:12:lag:1:700724543489:
lagctrl_add_ports_to_deployed_lag(T=7364367,lag_id=2,num_of_ports=1,ports={1/1/20,1/1/1,1/1/1,1/1/1,...}
) -> TrunkPreCreateCallbackTable -> (2,sw_cu_mrp_trunk_update_callback)
Jul 06 08:44:26:444828:debug:12:lag:1:700724543489:
lagctrl_add_ports_to_deployed_lag(T=7364367,lag_id=2,num_of_ports=1,ports={1/1/20,1/1/1,1/1/1,1/1/1,...}
) -> TrunkPreCreateCallbackTable -> (2,sw_cu_vlan_vport_trunk_update_callback)
Jul 06 08:44:26:449384:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_set_trunk_link_deb_callback trunk id: 2
Jul 06 08:44:26:449471:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_bum_limit_trunk_update_callback trunk id: 2
Jul 06 08:44:26:449542:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_dhcpnoop_trunk_update_callback trunk id: 2
Jul 06 08:44:26:449879:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_dhcpv6noop_trunk_update_callback trunk id: 2
Jul 06 08:44:26:450171:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_raguard_trunk_update_callback trunk id: 2
Jul 06 08:44:26:450252:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_ratelimit_trunk_update_callback trunk id: 2
Jul 06 08:44:26:450319:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L1 function
callname: sw_pp_mirror_trunk_event_callback trunk id: 2
Jul 06 08:44:26:450391:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_webAuth_trunk_update_callback trunk id: 2
Jul 06 08:44:26:450458:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_mct_trunk_update_callback trunk id: 2
Jul 06 08:44:26:450522:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L4 function
callname: sw_cu_sflow_trunk_update_callback trunk id: 2
Jul 06 08:44:26:450605:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L3 function
callname: L3_trunk_event_callback trunk id: 2
Jul 06 08:44:26:455974:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_static_mac_trunk_update_callback trunk id: 2
Jul 06 08:44:26:456092:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_igmp_snoop_trunk_deploy_callback trunk id: 2
Jul 06 08:44:26:456168:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_mld_snoop_trunk_deploy_callback trunk id: 2
Jul 06 08:44:26:456233:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_set_trunk_packet_inerror_callback trunk id: 2
Jul 06 08:44:26:456300:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: erlbTrunkMemberUpdateCallback trunk id: 2
Jul 06 08:44:26:456364:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_protected_port_trunk_callback trunk id: 2
Jul 06 08:44:26:456431:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: qinq_trunk_event_callback trunk id: 2
Jul 06 08:44:26:456495:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: vlan_mapping_trunk_event_callback trunk id: 2
Jul 06 08:44:26:456558:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: sw_cu_rspan_trunk_callback trunk id: 2
Jul 06 08:44:26:456623:err:12:lag:1:700724543489: EVENT_ID_TRUNK_MEMBER_ADD Module: L2 function
callname: flexlink_trunk_member_add_delete_callback trunk id: 2
Jul 06 08:45:02:880189:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_MEMBER_DELETE Module: L2 function
callname: sw_cu_protected_port_trunk_callback trunk id: 2
Jul 06 08:45:02:880278:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_MEMBER_DELETE Module: L2 function
callname: qinq_trunk_event_callback trunk id: 2
Jul 06 08:45:02:880349:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_MEMBER_DELETE Module: L2 function
callname: vlan_mapping_trunk_event_callback trunk id: 2
Jul 06 08:45:02:880416:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_MEMBER_DELETE Module: L1 function
callname: sw_pp_mirror_trunk_event_callback trunk id: 2
Jul 06 08:45:02:880482:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_MEMBER_DELETE Module: L2 function
callname: sw_cu_rspan_trunk_callback trunk id: 2
Jul 06 08:45:02:880549:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_MEMBER_DELETE Module: L2 function
callname: flexlink_trunk_member_add_delete_callback trunk id: 2
Jul 06 08:45:02:888214:debug:12:lag:1:726494347265: cu_lag_create_trunk(lag=test1,lag_id=2,undep)
(T=7364731,task=l2config) >>
Jul 06 08:45:02:888328:debug:12:lag:1:726494347265:

```

Debug Commands Q - Z

debug trunk

```
>>> lagctrl_lag_deploy(lag=2,un-deploy,dynamic)(T=7364731,task=l2config)(I) pri=lg2
(port_group_id=2,port_trunk_id=2,config_trunk_id=3073,trunk_state=1,trunk_primary=lg2), #_port=1, Port
List:
Jul 06 08:45:02:888397:debug:12:lag:1:726494347265: (lg2)
Jul 06 08:45:02:888459:debug:12:lag:1:726494347265:
Jul 06 08:45:02:888524:debug:12:lag:1:726494347265: lagctrl_lag_deploy(lag=2,un-deploy,dynamic)
(T=7364731,task=l2config)(I) -> sw_trunk_predelete_event()
Jul 06 08:45:02:889573:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE LAG id: 2
Jul 06 08:45:02:889670:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_rstp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:889954:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_spanningTree_trunk_update_callback trunk id: 2
Jul 06 08:45:02:890035:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_vsrp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:890101:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_mrp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:890170:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_vlan_vport_trunk_update_callback trunk id: 2
Jul 06 08:45:02:890342:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_protected_port_trunk_callback trunk id: 2
Jul 06 08:45:02:890420:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_PREDELETE Module: L2 function
callname: sw_cu_rspan_trunk_callback trunk id: 2
Jul 06 08:45:02:890496:debug:12:lag:1:726494347265: lagctrl_lag_deploy(lag=2,un-deploy,dynamic)
(T=7364731,task=l2config)(I) done, pri=lg2
(port_group_id=2,port_trunk_id=2,config_trunk_id=3073,trunk_state=1,trunk_primary=lg2)
Jul 06 08:45:02:892130:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_vlan_vport_trunk_update_callback trunk id: 2
Jul 06 08:45:02:892597:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_vsrp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:892683:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_spanningTree_trunk_update_callback trunk id: 2
Jul 06 08:45:02:892871:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_rstp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:893127:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_mrp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:893201:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_mstp_trunk_update_callback trunk id: 2
Jul 06 08:45:02:893872:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_mac_trunk_update_callback trunk id: 2
Jul 06 08:45:02:893961:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_pms_trunk_update_callback trunk id: 2
Jul 06 08:45:02:894045:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_bum_limit_trunk_update_callback trunk id: 2
Jul 06 08:45:02:894114:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L3 function callname:
L3 trunk event_callback trunk id: 2
Jul 06 08:45:02:894263:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_dhcpnoop_trunk_update_callback trunk id: 2
Jul 06 08:45:02:894883:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_dhcpv6noop_trunk_update_callback trunk id: 2
Jul 06 08:45:02:895205:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_arp_inspec_trunk_update_callback trunk id: 2
Jul 06 08:45:02:895294:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_sourceguard_validation_callback trunk id: 2
Jul 06 08:45:02:895619:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_webAuth_trunk_update_callback trunk id: 2
Jul 06 08:45:02:895694:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_raguard_trunk_update_callback trunk id: 2
Jul 06 08:45:02:895760:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_ratelimit_trunk_update_callback trunk id: 2
Jul 06 08:45:02:895826:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L4 function callname:
sw_cu_sflow_trunk_update_callback trunk id: 2
Jul 06 08:45:02:896324:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_static_mac_trunk_update_callback trunk id: 2
Jul 06 08:45:02:896405:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_igmp_snoop_trunk_deploy_callback trunk id: 2
Jul 06 08:45:02:896473:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_gvrp_trunk_event_callback trunk id: 2
Jul 06 08:45:02:896538:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_protected_port_trunk_callback trunk id: 2
Jul 06 08:45:02:896604:debug:12:lag:1:726494347265: EVENT_ID_TRUNK_Delete Module: L2 function callname:
sw_cu_rspan_trunk_callback trunk id: 2
Jul 06 08:45:02:896677:debug:12:lag:1:726494347265: cu_lag_create_trunk(lag_id=2) undeploy done, HW
```

```
Trunk Id 0
Jul 06 08:45:02:896741:debug:12:lag:1:726494347265: cu_lag_create_trunk(lag_id=2) (T=7364731) undeploy
done&
Jul 06 08:45:02:897228:debug:12:lag:1:726494347265: sw_cu_lag_generic_port_add_validation(lag=2,mask=
lg2,remove,static,force_delete=1) (T=7364731,task=l2config) (I)
Jul 06 08:45:02:897418:debug:12:lag:1:726494347265: sw_cu_lag_generic_port_add_validation(lag=2,mask=
lg2,remove,static,force_delete=1) (T=7364731,task=l2config) find cb0x97825af8 (lag_primary_port=lg2,
lag_num_ports=1, deployed=0)
Jul 06 08:45:02:892022:err:12:lag:1:726494347265: EVENT_ID_TRUNK_DELETE LAG id: 2
```

debug web events

Enables web events debugging.

Syntax

debug web events

no debug web events

Modes

Privileged EXEC mode

Examples

```
device# debug web events  
web: Events debugging is on
```

debug webauth timers

Enables debugging of web authentication timers.

Syntax

debug webauth timers

no debug webauth timers

Modes

Privileged EXEC mode

Examples

```
device# debug webauth timers  
webauth: Timers debugging is on
```

debug webauth events

Enables debugging of web authentication events.

Syntax

debug webauth events

no debug webauth events

Modes

Privileged EXEC mode

Usage Guidelines

Examples

```
device# debug webauth events  
webauth: Events debugging is on
```

show debug

Displays all the enabled debug functions.

Syntax

show debug

Modes

User EXEC mode

Examples

The following example shows that ACL log and IPv6 debugging are enabled, with the console as the output destination.

```
device# show debug
Debug message destination: Console
Enabling ACL log
IPv6 Routing:
ipv6: icmp debugging is on
```

show log debug management restconf all

Displays LogMgr debug logs for RESTCONF..

Syntax

```
show log debug management restconf all all
```

Parameters

all

Specifies all units..

Modes

User EXEC mode

Examples

The following example shows LogMgr debug logs for RESTCONF.

```
device> show log debug management restconf all all
...

Apr 06 08:05:00:054372:err:management:restconf:1:4294968064:
Config Sync :
oper : merge,
xpath : /openconfig-acl:acl,
xvalue : <acl><interfaces><interface><id></id><config><id></id></config><interface-
ref><config><interface></interface></config></interface-ref><ingress-acl-sets><ingress-acl-set><set-
name>mac1</set-name><type>ACL_L2</type><config><set-name>mac1</set-name><type>ACL_L2</type></config><</
ingress-acl-set></ingress-acl-sets></interface></interfaces></acl>
Apr 06 08:05:00:052220:err:management:restconf:1:4294968064:
Edit failed with error: 310 'required value instance not found'

Apr 06 08:05:00:052176:err:management:restconf:1:4294968064:
Config Sync :
oper : merge,
xpath : /openconfig-acl:acl,
xvalue : <acl><interfaces><interface><id></id><config><id></id></config><interface-
ref><config><interface></interface></config></interface-ref><ingress-acl-sets><ingress-acl-set><set-
name>scale23</set-name><type>ACL_IPV6</type><config><set-name>scale23</set-name><type>ACL_IPV6</type><</
config></ingress-acl-set></ingress-acl-sets></interface></interfaces></acl>
Apr 06 08:05:00:049967:err:management:restconf:1:4294968064:
Edit failed with error: 310 'required value instance not found'

Apr 06 08:05:00:049922:err:management:restconf:1:4294968064:
Config Sync :
oper : merge,
xpath : /openconfig-acl:acl,
xvalue : <acl><interfaces><interface><id></id><config><id></id></config><interface-
ref><config><interface></interface></config></interface-ref><ingress-acl-sets><ingress-acl-set><set-
name>tcpl</set-name><type>ACL_IPV4</type><config><set-name>tcpl</set-name><type>ACL_IPV4</type><</
config></ingress-acl-set></ingress-acl-sets></interface></interfaces></acl>
Apr 06 08:05:00:048079:err:management:restconf:1:4294968064:
Edit failed with error: 310 'required value instance not found'
```

History

Release version	Command history
09.0.00	This command was introduced.

show tech-support

Displays the output of several show commands at once. The output from this command varies depending on the router configuration.

Syntax

```
show tech-support [ acl | cluster | cpu | license | l2 | l3 | memory | multicast | packet-loss | stack ]
```

```
no show tech-support [ acl | cluster | cpu | license | l2 | l3 | memory | multicast | packet-loss | stack ]
```

Parameters

acl

Generates system and debugging information specific to ACL configurations and counters.

cluster

Generates system and debugging information specific to cluster configurations.

cpu

Generates CPU-related information.

license

Generates license-related information.

l2

Generates system and debugging information specific to Layer 2 configurations.

l3

Generates system and debugging information specific to Layer 3 configurations.

memory

Generates memory-related information of the device.

multicast

Generates system and debugging information specific to Layer 2 and Layer 3 multicast configurations.

packet-loss

Generates packet statistics-related debugging information.

stack

Generates system and debugging information specific to stacking configurations.

Modes

Privileged EXEC mode

Usage Guidelines

The **show tech-support** command is useful when collecting a large amount of information about the RUCKUS FastIron devices for troubleshooting purposes. The output of this command can be used by technical support representatives when a problem is reported.

The default output of the **show tech-support** command includes the following information:

- Header for all the show commands

- Running configuration
- Image version
- Port status
- Port counters
- Static and dynamic log buffers
- dm statistics
- Boot, monitor, and system
- Registers information
- Possible stack trace
- Active stack (if applicable)
- Last packet (Application Data)
- Possible data structure
- MCT cluster details
- License details
- Stacking information
- Dot1x
- DHCP snooping
- SSH
- System Health

The format of the **show tech-support** command output is modified to include a header and a footer by default for each of the **show tech-support** commands which gets called from the CLI to automatically parse the output for easier lookup.

The header contains the following information:

- BEGIN - Indicates a sub-command that will begin execution next.
- CONTEXT - Indicates in which context and session the sub-commands are executed.

If more than one telnet session and console session for a device is accessed, then **show tech-support** command displays CONTEXT as Console#0 for console session and telnet#1 and telnet#2 and so on for telnet sessions.

- TIME STAMP - A time stamp, with millisecond granularity, helps to determine the time difference between separate runs of the same command.

If NTP or local clock is not set in a device, then header displays Epoch time in the TIMESTAMP field. Epoch time is a universal time which starts from Jan 1, 1970. Therefore, for Linux platforms, the Epoch time format is 00:00:00.000 GMT+00 Thu Jan 01 1970. For non-Linux platforms, the Epoch time format is Jan 01 00:00:00.000.

- HW/SW INFO - Indicates the hardware and software version information of the device.

The footer contains the following information:

- TIME STAMP - A time stamp, with millisecond granularity, helps to determine the time difference between separate runs of the same command.

If NTP or local clock is not set in a device, then header displays Epoch time in the TIMESTAMP field. Epoch time is a universal time which starts from Jan 1, 1970. Therefore, for Linux platforms, the Epoch time format is 00:00:00.000 GMT+00 Thu Jan 01 1970. For non-Linux platforms, the Epoch time format is Jan 01 00:00:00.000.

- END - Indicates the sub-command which has completed execution.
- TIME TAKEN - Indicates the total time taken in nanoseconds for the command execution.

Examples

The following example shows the truncated output of the **show tech-support** command.

```

device# show tech-support
=====
BEGIN : show tech-support
CONTEXT : TELNET#1 : show tech-support
TIME STAMP : 01:47:54.763 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
BEGIN : show running-config
CONTEXT : TELNET#1 : CONFIG
TIME STAMP : 01:47:54.763 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
Current configuration:
!
ver 08.0.40b1T213
!
stack unit 1
  module 1 icx7250-24-port-management-module
  module 2 icx7250-sfp-plus-8port-80g-module
  priority 200
  default-ports 1/2/5 1/2/7
  stack-trunk 1/2/5 to 1/2/6
  stack-trunk 1/2/7 to 1/2/8
  stack-port 1/2/5 1/2/7
...
=====
TIME STAMP : 01:47:55.061 Pacific Wed Dec 09 2015
END : show running-config
TIME TAKEN : 148914220 ticks (148914220 nsec)
=====
BEGIN : show version
CONTEXT : TELNET#1 : HW INFO
TIME STAMP : 01:47:55.061 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
  Copyright (c) 1996-2015 RUCKUS Wireless, Inc. All rights reserved.
  UNIT 1: compiled on Dec  3 2015 at 16:12:49 labeled as SPR08040b1
    (22418510 bytes) from Primary spr08040b1.bin
    SW: Version 08.0.40b1T213
    Compressed Boot-Monitor Image size = 786944, Version:10.1.06T215 (spz10106b002)
    Compiled on Thu Sep 10 06:30:24 2015
  UNIT 2: compiled on Dec  3 2015 at 16:12:49 labeled as SPR08040b1
    (22418510 bytes) from Primary spr08040b1.bin
    SW: Version 08.0.40b1T213
    Compressed Boot-Monitor Image size = 786944, Version:10.1.06T215 (spz10106b002)

  HW: Stackable ICX7250-24
=====
UNIT 1: SL 1: ICX7250-24 24-port Management Module
  Serial #:DUN3245K00N
  License: ICX7250_L3_SOFT_PACKAGE (LID: fwpIHJKmFFp)
  License Compliance: ICX7250-PREM-LIC-SW is Non-Compliant
  P-ASIC 0: type B344, rev 01 Chip BCM56344_A0
=====
UNIT 1: SL 2: ICX7250-SFP-Plus 8-port 80G Module
=====
UNIT 2: SL 1: ICX7250-24 24-port Management Module
  Serial #:DUN3245K01W
  License: ICX7250_L3_SOFT_PACKAGE (LID: fwpIHJKmFGy)
  License Compliance: ICX7250-PREM-LIC-SW is Non-Compliant
=====
UNIT 2: SL 2: ICX7250-SFP-Plus 8-port 80G Module
=====
  1000 MHz ARM processor ARMv7 88 MHz bus
  8192 KB boot flash memory

```

```
2048 MB code flash memory
2048 MB DRAM
STACKID 1 system uptime is 1 day(s) 10 hour(s) 41 minute(s) 57 second(s)
STACKID 2 system uptime is 1 day(s) 10 hour(s) 41 minute(s) 53 second(s)
The system started at 15:14:06 Pacific Mon Dec 07 2015
```

```
The system : started=warm start reloaded=by "reload"
My stack unit ID = 1, bootup role = active
*** NOT FOR PRODUCTION ***
```

```
=====
TIME STAMP : 01:47:55.065 Pacific Wed Dec 09 2015
END : show version
TIME TAKEN : 2038801 ticks (2038801 nsec)
=====
```

```
=====
BEGIN : show interfaces brief
CONTEXT : TELNET#1 : PORT STATUS
TIME STAMP : 01:47:55.938 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
```

```
Interface Information for all the ports :
Port      Link   State Dupl Speed Trunk Tag Pvid Pri MAC           Name
1/1/1     Down  None  None None None No  4010 0   cc4e.24b4.88b0
1/1/2     Disable None  None None None No  4010 0   cc4e.24b4.88b1
1/1/3     Up     Forward Full 1G  None Yes N/A  0   cc4e.24b4.88b2
1/1/4     Disable None  None None None No  4010 0   cc4e.24b4.88b3
1/1/5     Disable None  None None None No  4010 0   cc4e.24b4.88b4
=====
```

```
TIME STAMP : 01:47:55.962 Pacific Wed Dec 09 2015
END : show interfaces brief
TIME TAKEN : 12071127 ticks (12071127 nsec)
=====
```

```
=====
BEGIN : show statistics ethernet
CONTEXT : TELNET#1 : PACKET COUNTERS
TIME STAMP : 01:47:55.986 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
```

```
Statistics Information for each port :
Port      Link   State Dupl Speed Trunk Tag Pvid Pri MAC           Name
1/1/3     Up     Forward Full 1G  None Yes N/A  0   cc4e.24b4.88b2
```

```
Port 1/1/3 Counters:
      InOctets          52710812588          OutOctets          31386393616
      InPkts            623806726            OutPkts            365249013
InBroadcastPkts      0          OutBroadcastPkts      0
InMulticastPkts      623211850          OutMulticastPkts      365249013
InUnicastPkts        0          OutUnicastPkts        0
InBadPkts            0
InFragments          0
InDiscards           0          OutErrors           0
      CRC              0          Collisions          0
InErrors             0          LateCollisions       0
InGiantPkts          0
InShortPkts          0
InJabber             0          OutDiscards          3242924084
InFlowCtrlPkts      0          OutFlowCtrlPkts      0
InBitsPerSec         2872          OutBitsPerSec         160
InPktsPerSec          5          OutPktsPerSec         0
InUtilization         0.00%          OutUtilization        0.00%
=====
```

```
TIME STAMP : 01:47:56.413 Pacific Wed Dec 09 2015
END : show statistics ethernet
TIME TAKEN : 213778306 ticks (213778306 nsec)
=====
```

```
=====
BEGIN : show logging
CONTEXT : TELNET#1 : STATIC/DYNAMIC LOG
TIME STAMP : 01:47:55.089 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
```

Debug Commands Q - Z

show tech-support

```
=====
Syslog logging: enabled ( 0 messages dropped, 1 flushes, 540 overruns)
  Buffer logging: level ACDMEINW, 1000 messages logged
  level code: A=alert C=critical D=debugging M=emergency E=error
              I=informational N=notification W=warning

Static Log Buffer:
Dec  7 23:06:21:I:System: Stack unit 1   PS 1, Internal Power supply  is up
Dec  2 18:27:47:A:System: Stack unit 1   PS 2, Standby Power supply  is down
Dec  7 15:06:44:I:System: Stack unit 2   PS 1, Internal Power supply  is up
Dec  7 15:06:44:A:System: Stack unit 2   PS 2, Standby Power supply  is down

Dynamic Log Buffer (1000 lines):
Dec  9 01:46:02:W:IGMP: [ Port 1/2/4 ] v1570. Query version mismatch. Received query version 2 from
157.0.0.151; Port version 3.
Dec  9 01:43:55:W:IGMP: [ Port 1/2/4 ] v1570. Query version mismatch. Received query version 2 from
157.0.0.151; Port version 3.
...
(output truncated)
```

You can disable the display of the header and footer for **show tech-support** commands by using the **supportsave info disable** command. If disabled, you can enable the display of the header and footer for **show tech-support** commands by using the **supportsave info enable** command.

The following sample output of the **show tech-support license** command shows the header and footer displayed.

```
device# supportsave info enable
device# show tech-support license
=====
BEGIN : show license
CONTEXT : CONSOLE#0 : LICENSE
TIME STAMP : 01:30:20.093 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7650-48C/SWR08040q078
=====
License Information
=====
License record empty
=====
TIME STAMP : 01:30:20.093 Pacific Wed Dec 09 2015
END : show license
TIME TAKEN : 1459 ticks (61278 nsec)
=====
```

supportsave

Use the supportsave utility for collecting logs from the driver, internal libraries, and firmware. The collected logs are shared with the technical support personnel for investigating issues seen on the device.

Syntax

```
supportsave{all|custom|infra|l2|l3|os|platform|system}{tftp_server_IPtftp_server's_relative_path_name[user_tag]|display|unit-idunit-number}
```

```
supportsavecore{tftp_server_IPtftp_server's_relative_path_name[user_tag]|unit-idunit-number}
```

```
supportsavecancel
```

Parameters

all

Collects all supportsave related log files.

core

Collects core logs from all devices.

custom

Executes all commands present in the default and custom commands list and sends the output to the specified TFTP server address.

infra

Collects stacking related information.

l2

Collects Layer 2 related information.

l3

Collects Layer 3 related information.

os

Collects operating system (OS) related information.

platform

Collects platform related information.

system

Collects all general commands information.

tftp_server_IP

Specifies the IP address of the TFTP server.

tftp_server's_relative_path_name

Specifies the file path name of TFTP server relative to TFTP server's default directory to dump supportsave logs. To specify the default directory itself, use '/'.

user_tag

Specifies the user tag to be added in the supportsave collected file name. Maximum of 10 characters are allowed.

display

Displays the supportsave information (except the non-textual output like core files) in the console window.

unit-id*unit-number*

Collects data from a specific stack unit and the active unit and sends to the TFTP server. If the specified unit-id and the active unit are same, only the active unit data is collected.

cancel

Cancels supportsave.

Modes

Privileged EXEC mode

Usage Guidelines

The **supportsave** command has the following advantages over the **show tech-support** command:

- Allows you to add additional commands to collect more data.
- Allows to transfer the collected data to an external server such as Trivial File Transfer Protocol (TFTP) server.

TFTP is disabled by default, if FIPS is enabled. Enable TFTP manually for uploading supportsave data. It is a prerequisite to have the TFTP server with a write permission and the server must be accessible from the device.

Use the **fips policy allow tftp-access** command in configuration mode to enable TFTP access while the FIPS is enabled.

Limitations and prerequisites

The following are the limitations and pre-requisites of the supportsave utility:

- Parallel execution of the **supportsave** command from two different sessions is not allowed.
- Parallel execution of the **supportsave** command and the copy tftp/scp commands is not allowed.
- It is recommended that you do not run any CLIs when supportsave operation is in progress.
- Only IPv4 address is supported for the TFTP destination.
- Only up to 32 commands can be added to the custom command list.
- Commands are not expanded while adding a command to the custom commands list.
- Commands added to the custom command list must be privileged EXEC mode MP commands.
- It is recommended that you do not add any filters with the commands.
- The **supportsave** command cannot be added to the custom commands list. Also, the commands which change the CLI mode (exit, quit, end) and commands which restart the router (switchover, reload, reload-yes) must not be added.
- Modifying the custom commands list using the **supportsave add-cmd** or **supportsave del-cmd** commands is not allowed while the supportsave data collection is in progress.
- Time taken by the **supportsave** command depends on the commands present in the list.
- The **supportsave** command does not support collecting crash logs from standby units in a mixed stack.
- The filename length including tag string must be less than 32 characters.
- The **supportsave custom** command denies commands other than show commands, dm commands, and fips show command.
- Few **show** output commands are restricted to display only the first page in the console. This restriction is not applicable for sending the **supportsave** command output through file transfer.
- **Display** option is available for modules like I2, I3, platform, system, infra, custom and all. Non-textual output like core files are not displayed in the console.

Examples

When the **display** option is enabled, some of the **show** commands are restricted to display only the first page. However, the *tftp_server_IP* option, transfers the complete command output to the TFTP server.

NOTE

RUCKUS recommends to use **all** option to collect complete logs.

To collect all **supportsave** related logs, enter the **supportsave all** command as shown in the following example.

```
device# supportsave all 10.37.2.40 fi/prince/supportsave
Supportsave started. This operation may take several minutes.
Press "A" to abort supportsave operation.
ICX7650-48C
device#.*****
.....
Supportsave completed in 10 seconds
```

supportsave

Collects logs from different modules and uploads the logs into a remote SCP or TFTP server.

Syntax

```
supportsave [ add_cust_cmd | all | cancel | core | del_cust_cmd | info | infra | l2 | l3 | list_cust_cmd | os | platform | show | system ]  
            [ scp | tftp ] [ ipv4-address ] [ server-path ] [ optional-tagname ]
```

Command Default

The supportsave functionality is not active.

Parameters

add_cust_cmd

Adds the given command at the given index in the custom commands list. If there is already a command present at the index passed, the add operation fails.

all

Sends all information to the remote server.

cancel

Cancels the **supportsave** command operation.

core

Sends core information to the remote server.

del_cust_cmd

Deletes the given command at the given index in the custom commands list. If there is already a command present at the index passed, the add operation will fail.

info

Displays information about the **supportsave** command. If info is enabled, then the collected commands contain additional information like BEGIN, CONTEXT, TIME STAMP, HW/SW INFO, and so on.

infra

Sends infrastructure information to the remote server.

l2

Sends Layer 2 information to the remote server.

l3

Sends Layer 3 information to the remote server.

list_cust_cmd

Displays the custom command list.

os

Sends Operating System information to the remote server.

platform

Sends platform information to the remote server.

show

Displays the amount of percentage executed in the currently executing command process.

system

Sends system information to the remote server.

scp

Specifies the remote SCP server.

tftp

Specifies the remote TFTP server.

ipv4-address

Specifies the IP address for the server.

server-path

Specifies the file pathname for the remote server in ASCII text, up to 128 characters. The default is /.

optional-tagname

Appends a text string to the collected file name on the remote server.

NOTE

Not all parameters are supported for 9.0.0, but will be available in an upcoming patch release.

Modes

Privileged EXEC mode

Usage Guidelines

The collected logs are shared with the technical support personnel for investigating issues seen on the device. Once the **supportsave** command is executed, logs are collected and uploaded into the remote server.

Parallel execution of **supportsave** command from two different sessions is not allowed. Parallel execution of **supportsave** command and the **copy tftp** or **copy scp** commands is not allowed.

The **supportsave** command supports IPv4.

A maximum of 32 commands can be added to the custom command list. Commands are not expanded while adding a command to the custom commands list. It is recommended not to add any filters with the commands.

Modifying the custom commands list using **supportsave add_cust_cmd** or **supportsave del_cust_cmd** is not allowed while supportsave data collection is in progress.

Time taken by the **supportsave** commands depends on the commands present in the list and the distance of the remote server.

In order to avoid looping, the **supportsave** command cannot be added to the custom command list. Also, the commands which changes the CLI mode (exit, quit) and commands which restart the router (switchover, reload) are not accepted.

The tag string should be 10 characters or less. If more than 10 characters are entered, an error message, "File tag is longer than max(10) chars" appears.

The **supportsave** command uses the outbound SSH session

SCP or TFTP operations are not allowed while **supportsave** is in progress.

Cancelling the **supportsave** command during the file transfer does not cancel the current file transfer. While cancelling the **supportsave** command, you must wait for the current file transfer to complete before executing the **supportsave** command again.

Debug Commands Q - Z

supportsave

Supportsave is not High Availability (HA) aware.

The **supportsave** command aborts when the remote server is terminated. Additionally, when the data is collected from the remote unit, and if the corresponding unit is powered off, the **supportsave** command is terminated.

Use the **supportsave cancel** command to stop supportsave operations.

Examples

The following example collects Layer 3 information.

```
device# supportsave 13 scp 10.xx.xx.104
User name:root
Password:Supportsave started. This operation may take several minutes.
Press "Shift-A" to abort supportsave operation.
asethura#####
Connecting to remote host.....

Sending data (8192 bytes per dot)
.

SCP transfer from device completed

Connection Closed

Supportsave completed in 1 seconds
```

The following example adds a custom command to the fifth position in the index.

```
device# supportsave add_cust_cmd index 5 "host-max-num 512"
```

The following example deletes a custom command from the fifth position in the index.

```
device# supportsave del_cust_cmd index 5
```

The following example sends all information to the default remote TFTP server.

```
DUT# supportsave all tftp 10.176.198.2 / CustTagNam
```

History

Release version	Command history
08.0.61	This command was introduced.
09.0.00	The command syntax was modified.

supportsave add_cust_cmd index

Adds a run-time executable command into the custom module at a particular index of 32 characters long (maximum of 32 characters are allowed) during the run time.

Syntax

```
supportsave add_cust_cmd index index_number "cli string"
```

Parameters

index_number

Specifies the index in the custom commands list where an additional command need to be added. The valid range is from 1 through 32.

cli string

Specifies the commands to be added to the custom commands list.

Modes

Privileged EXEC mode

Examples

```
device# supportsave add_cust_cmd index 1 "show chassis"
```

supportsave del_cust_cmd all

Deletes all the custom module commands.

Syntax

```
supportsave del_cust_cmd all
```

Modes

Privileged EXEC mode

supportsave del_cust_cmd index

Deletes a command from the custom module at a particular index during the run time.

Syntax

```
supportsave del_cust_cmd index index_number
```

Parameters

index_number

Specifies the index in the custom commands list where an additional command need to be removed. The valid range is from 1 through 32.

Modes

Privileged EXEC mode

Examples

```
device# supportsave add_cust_cmd index 1 "show chassis"
```

supportsave info disable

Disables the header to be displayed for all supportsave and show tech-support commands being executed on CLI.

Syntax

supportsave info disable

Modes

Privileged EXEC mode

supportsave info enable

display BEGIN headers.

Syntax

supportsave info enable

Modes

Privileged EXEC mode

Usage Guidelines

By default, the **supportsave** command outputs display BEGIN headers. and **show tech-support** command outputs display both BEGIN and END headers. The commands under show tech command, which is a part of supportsave output, will have both BEGIN and END headers.

You can disable the header display by using the supportsave info disable command. You can use the supportsave info enable command to re-enable the header display. Even if supportsave info enable command is issued, other show commands do not display the headers.

The header format is modified to include the following information:

- BEGIN - Indicates the command that will begin execution next.
- CONTEXT - Indicates in which session the command is executed.
If Supportsave command is issued in more than one terminal, the respective terminal information is displayed in the CONTEXT field.
- TIME STAMP - A time stamp, with millisecond granularity, helps to determine time difference between separate runs of the same command. If NTP or local clock is not set in a device, then header displays Epoch time in the TIMESTAMP field. Epoch time is a universal time which starts from Jan 1, 1970. Therefore, for Linux platforms, the Epoch time format is 00:00:00.000 GMT+00 Thu Jan 01 1970. For non-Linux platforms, the Epoch time format is Jan 01 00:00:00.000.
- HW/SW INFO - Indicates the hardware and software version information of the device.

Examples

The following sample output of supportsave all display command shows the modified header format.

```
device# supportsave info enable
device# supportsave all display
Supportsave started. This operation may take several minutes.
Press "A" to abort supportsave operation.
=====
BEGIN : show flash
CONTEXT : TELNET#1 : show flash
TIME STAMP : 01:47:24.377 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
Stack unit 1:
  Compressed Pri Code size = 22418510, Version:08.0.40T213 (spr08040b1.bin)
  Compressed Sec Code size = 24128807, Version:08.0.40qT213 (SPR08040q081.bin)
  Compressed Boot-Monitor Image size = 786944, Version:10.1.06T215
  Code Flash Free Space = 1825419264
Stack unit 2:
  Compressed Pri Code size = 22418510, Version:08.0.40T213 (spr08040b1.bin)
  Compressed Sec Code size = 24128807, Version:08.0.40qT213 (SPR08040q081.bin)
  Compressed Boot-Monitor Image size = 786944, Version:10.1.06T215
  Code Flash Free Space = 1766633472
telnet@ACC-SICA-171#
=====END OF A COMMAND=====
104126_000100
=====show module=====
=====
BEGIN : show module
CONTEXT : TELNET#1 : show module
TIME STAMP : 01:47:24.382 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
Module                               Status Ports Starting MAC
U1:M1  ICX7250-24 24-port Management Module    OK      24  cc4e.24b4.88b0
U1:M2  ICX7250-SFP-Plus 8-port 80G Module    OK       8  cc4e.24b4.88b0
U2:M1  ICX7250-24 24-port Management Module    OK      24  cc4e.24b4.81f0
U2:M2  ICX7250-SFP-Plus 8-port 80G Module    OK       8  cc4e.24b4.88b0
telnet@ACC-SICA-171#
=====END OF A COMMAND=====
104126_000100
=====show chassis=====
=====
BEGIN : show chassis
CONTEXT : TELNET#1 : show chassis
TIME STAMP : 01:47:24.384 Pacific Wed Dec 09 2015
HW/SW INFO : ICX7250-24/SPR08040b1
=====
The stack unit 1 chassis info:

Power supply 1 (AC - Regular) present, status ok
Power supply 2 not present

Fan ok, speed (auto): [[1]]<->2

Fan controlled temperature: 84.5 deg-C

Fan speed switching temperature thresholds:
Speed 1: NM<---->98      deg-C
Speed 2:      67<---->105 deg-C (shutdown)

Fan 1 Air Flow Direction: Front to Back
Slot 1 Current Temperature: 84.5 deg-C (Sensor 1)
Slot 2 Current Temperature: NA
Warning level.....: 100.0 deg-C
Shutdown level.....: 105.0 deg-C
Boot Prom MAC : cc4e.24b4.88b0
Management MAC: cc4e.24b4.88b0

The stack unit 2 chassis info:
```

Power supply 1 (AC - Regular) present, status ok
Power supply 2 not present

Fan ok, speed (auto): [[1]]<->2

Fan controlled temperature: 81.8 deg-C

Fan speed switching temperature thresholds:

Speed 1: NM<----->98 deg-C

Speed 2: 67<----->105 deg-C (shutdown)

Fan 1 Air Flow Direction:Front to Back
Slot 1 Current Temperature: 82.4 deg-C (Sensor 1)
Slot 2 Current Temperature: NA
Warning level.....: 100.0 deg-C
Shutdown level.....: 105.0 deg-C
Boot Prom MAC : cc4e.24b4.81f0

=====
=====END OF A COMMAND=====

104126_000100

=====
=====show files=====

=====
=====BEGIN : show files

CONTEXT : TELNET#1 : show files

TIME STAMP : 01:47:24.429 Pacific Wed Dec 09 2015

HW/SW INFO : ICX7250-24/SPR08040b1

=====
=====

Type	Size	Name
F	22418510	primary
F	24128807	secondary
F	256	primary.sig
F	7138	script.log_000347_000000_SPR08040q017_cc4e.24b4.88b0.txt
F	13805	startup-config.backup
F	256	bootrom.sig
F	393	stacking.boot
F	13297	startup-config.old
F	13297	startup-config.txt
F	94	dhcpsnoop_data
F	1576	\$\$ssh8rsa80864.key
F	256	secondary.sig

46597685 bytes 12 File(s) in FI root

1825419264 bytes free in FI root

telnet@ACC-SICA-171#

=====
=====END OF A COMMAND=====

104126_000100

=====
=====show memory=====

=====
=====BEGIN : show memory

CONTEXT : TELNET#1 : show memory

TIME STAMP : 01:47:24.444 Pacific Wed Dec 09 2015

HW/SW INFO : ICX7250-24/SPR08040b1

=====
=====Stack unit 1:

Total DRAM: 2147483648 bytes

Dynamic memory: 2095140864 bytes total, 1530638336 bytes free, 26% used

Stack unit 2:

Total DRAM: 2147483648 bytes

Dynamic memory: 2095140864 bytes total, 1547481088 bytes free, 26% used

telnet@ACC-SICA-171#

=====
=====END OF A COMMAND=====

104126_000100

=====
=====show media=====

..
(output truncated)

supportsave list_cust_cmd

Displays all commands present in the custom commands list.

Syntax

```
supportsave list_cust_cmd
```

Modes

Privileged EXEC mode

supportsave show

Collects and displays debugging information related to stacking configurations.

Syntax

```
supportsave show [ show | cancel ]
```

Parameters

show

Displays the progress of the log collection that has been executed on a terminal other than the one on which the **supportsave** command is executed.

cancel

Cancels the current log collection that has been executed on a terminal other than the one on which the **supportsave** command is executed.

Modes

Privileged EXEC mode

Examples

The following is the sample output from the **supportsave show** command.

```
device# supportsave show
Supportsave is executing commands: 19% completed
device# supportsave show
Supportsave is executing commands: 34% completed
device# supportsave show
Supportsave is executing commands: 60% completed
device# supportsave show.
Supportsave is executing commands: 100% completed
Supportsave is transporting files...
```

