



Ruckus Wireless™ SmartCell Insight™ Release 2.5

API User Guide

Part Number: 800-71460-001 Rev A
Published: 12 February 2017

www.ruckuswireless.com

Contents

Copyright Notice and Proprietary Information

About This Guide.....	4
Document Conventions.....	4
Related Documentation.....	5
Documentation Feedback.....	5

1 SmartCell Insight Overview

Accessing the API.....	6
Navigating to the UI.....	6
Generating Access Token.....	6
Using the API Dialog Box.....	9

2 Report Types

Common Tasks.....	11
Parameters for Generating API Reports.....	12
Accessing and Retrieving Data.....	14
Find the ID of the Report.....	14
Find the ID of the Section.....	15
Query the Data Endpoint.....	16
Generating API Reports.....	16

Copyright Notice and Proprietary Information

Copyright 2017. Ruckus Wireless, Inc. All rights reserved.

No part of this documentation may be used, reproduced, transmitted, or translated, in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without prior written permission of Ruckus Wireless, Inc. (“Ruckus”), or as expressly provided by under license from Ruckus.

Destination Control Statement

Technical data contained in this publication may be subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader’s responsibility to determine the applicable regulations and to comply with them.

Disclaimer

THIS DOCUMENTATION AND ALL INFORMATION CONTAINED HEREIN (“MATERIAL”) IS PROVIDED FOR GENERAL INFORMATION PURPOSES ONLY. RUCKUS AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THE MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE, OR THAT THE MATERIAL IS ERROR-FREE, ACCURATE OR RELIABLE. RUCKUS RESERVES THE RIGHT TO MAKE CHANGES OR UPDATES TO THE MATERIAL AT ANY TIME.

Limitation of Liability

IN NO EVENT SHALL RUCKUS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, OR DAMAGES FOR LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY YOU OR ANY THIRD PARTY, WHETHER IN AN ACTION IN CONTRACT OR TORT, ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIAL.

Trademarks

Ruckus Wireless, Ruckus, the bark logo, BeamFlex, ChannelFly, Dynamic PSK, FlexMaster, Simply Better Wireless, SmartCell, SmartMesh, SmartZone, Unleashed, ZoneDirector and ZoneFlex are trademarks of Ruckus Wireless, Inc. in the United States and other countries. All other product or company names may be trademarks of their respective owners.

About This Guide

This *SmartCell Insight 2.4 API User Guide* provides instructions about how the Ruckus Wireless™ SmartCell Insight (SCI) APIs work to access the various functionalities provided by the core SCI engine.

This guide is written for service operators and system administrators who are responsible for managing, configuring, and troubleshooting Wi-Fi networks. It assumes basic working knowledge of local area networks, wireless networking, and wireless devices.

NOTE: Refer to the release notes shipped with your product to be aware of certain challenges when upgrading to this release.

Most user guides and release notes are available in Adobe Acrobat Reader Portable Document Format (PDF) or HTML on the Ruckus Wireless Support Web site at <https://support.ruckuswireless.com/contact-us>.

Document Conventions

[Table 1: Text conventions](#) on page 4 and [Table 2: Notice conventions](#) on page 5 list the text and notice conventions that are used throughout this guide.

Table 1: Text conventions

Convention	Description	Example
message phrase	Represents messages displayed in response to a command or a status	[Device Name] >
user input	Represents information that you enter	[Device Name] > set ipaddr 10.0.0.12
user interface controls	Keyboard keys, software buttons, and field names	Click Create New
Start > All Programs	Represents a series of commands, or menus and submenus	Select Start > All Programs
ctrl+V	Represents keyboard keys pressed in combination	Press ctrl+V to paste the text from the clipboard.
screen or page names		Click Advanced Settings . The Advanced Settings page appears.
command name	Represents CLI commands	
parameter name	Represents a parameter in a CLI command or UI feature	
<i>variable name</i>	Represents variable data	{ZoneDirectorID}

Convention	Description	Example
filepath	Represents file names or URI strings	http://ruckuswireless.com

Table 2: Notice conventions

Notice type	Description
NOTE:	Information that describes important features or instructions
CAUTION:	Information that alerts you to potential loss of data or potential damage to an application, system, or device
WARNING:	Information that alerts you to potential personal injury

Related Documentation

For a complete list of documents that accompany this release, refer to the Release Notes.

Documentation Feedback

Ruckus Wireless is interested in improving its documentation and welcomes your comments and suggestions.

You can email your comments to Ruckus Wireless at: docs@ruckuswireless.com

When contacting us, please include the following information:

- Document title
- Document part number (on the cover page)
- Page number (if appropriate)

SmartCell Insight Overview

In this chapter:

- [Accessing the API](#)
- [Using the API Dialog Box](#)

SmartCell Insight (SCI) is a Big Data analytics and reporting engine that provides deep visibility into the performance and operational statistics of your Ruckus Wireless WiFi infrastructure.

SmartCell Insight (SCI) is designed to collect data from Ruckus network equipment, analyze that data, and then present it using a wide variety of standard and custom reports. SCI provides visibility, analytics and reports about network transmission statistics, equipment status and user traffic. It also provides details about the devices and applications that are used on the network, so that decision-makers can make better informed decisions about what types of devices and content their customers are using and will be using more of in the future.

SCI provides a rich set of APIs to access the various functionality provided by the core SCI engine.

NOTE: Refer to the Ruckus Smart Analytics Appendix on using each of the APIs.

Accessing the API

You can access the API after you log into the SCI User Interface.

You can access most of the reports mentioned in this section using the user interface, but if you require a detailed report at a granular level you can query the API which pulls the data from the core engine. Also the user interface limits the reports to top 100, if you require more than that you can access the API and procure them.

Navigating to the UI

To log into the SCI User Interface, use the following URL and the credentials.

1. Enter `https://<your SCI IP address>/explorer` in your web browser.
2. Log in using the following default credentials:

Username: admin

Password: admin

This page exposes all the APIs from the SCI core engine. If you have changed the default password, please use the new password accordingly.


Generating Access Token

You can access these APIs after you generate an access token.

To generate the access token:

1. Go to the section **Users > Login**. The following screenshot illustrates the same.

Figure 1: User Login



2. In the **credentials** section, enter the user credentials you used to log into the user interface.

Username: admin

Password: admin

Input a string in the format `{"username":"admin", "password":"admin"}`

3. Click the **Try it out!** tab

Figure 2: Credentials

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
credentials	<pre>{ "username": "admin", "password": "admin" }</pre>		body	Model Model Schema <pre>{ }</pre> Click to set as parameter value
include	<input type="text"/>	Related objects to include in the response. See the description of return value for more details.	query	string

Parameter content type:

[Try it out!](#) [Hide Response](#)

You will get your access token in the **Response body** of the curl script as displayed below.

Figure 3: Access Token

```

Curl
curl -X POST --header "Content-Type: application/json" --header "Accept: application/json" -d '{"username":"rsa", \

Request URL
https://rsa-staging.ruckuslbs.com/api/users/login?access_token=Jn4mgkNl8dIEFAAR4nvtwGFJ6KuCedGTxZ5uZFnSS0ZdLFJ3gApGbWj3

Response Body
{
  "id": "tn33XDf40CsAiWmP0hXUu3I1KNUTWtUVlf8MJ9aUwmqoIZTzjmahD9GNvLDORbTb",
  "ttl": 1209600,
  "created": "2016-07-21T02:39:03.265Z",
  "userId": 1
}
  
```

- Copy this access token and paste it in the **Token Set** field displayed at the top of the SCI user interface.
- Click **Set Access Token**

Figure 4: Set Access Token



Now you can access all the API reports in the system.

NOTE: You might not get the whole report in the Response Body if it is huge amount of data. You can access the reports by using:

- A Request URL. Paste this URL in a web browser to access the reports.
- A curl script to SSH on to your machine and direct those reports to a desired location.

Using the API Dialog Box

Use the API dialog box to view and modify the messages to generate your API reports.

On clicking each of the parameters and the resource URL the API dialog box is displayed.

Figure 5: API Dialog Box




Table 3: API Dialog Box

Name	Description
Response Class	The Response interface of the API represents the response to a request.
Response Content Type	Content-type: application/json; designates the content to be in JSON format. This is the default type.
Parameters	
Parameter	Use the filter parameter, to supply a dimension you want to filter on, followed by the filter expression.
Value	The Parameter Value contains the value to be included in the request.
Description	Auto displays the parameter description
Parameter Type	Lists the API parameter types that you can use in the path or query parameters for your

Name	Description
	backend API methods, and the types you can use as method return types or request body types.
Data Type	Lists the data types used in API parameters and notification message fields.
Try it out	Click on this icon to view the response body based on the parameters set.
Curl	Curl is a command line tool and library for transferring data with URL syntax. Use the curl command to simulate HTTP verbs such as HEAD, GET, POST, PUT and DELETE request calls to the API.
Request URL	Contains the URL of the response.
Response Body	The response interface represents the response to a request.
Response Code	Contains the status code of the response. For example, 200 for a success.
Response Header	Contains the headers object associated with the response.

Report Types

In this chapter:

- [Common Tasks](#)
- [Parameters for Generating API Reports](#)
- [Accessing and Retrieving Data](#)
- [Generating API Reports](#)

This section lists and describes the report types available in SCI.

Occurrence

This provides the API report related to the retrieval of occurrence records based on the scheduler. (Refer to the SCI User Guide for details).

Report

Report type is for various reports available in the application such as Network, WLAN, and Clients.

Schedule

This is to schedule automatic report generation and delivery. You can also specify occurrences for a particular schedule. (Refer to the SCI User Guide for details).

Setting

This report type is for system level settings including SMTP settings.

System

This report type is based on all the controllers that report to the SCI as data sources.

User

The user usage report returns activities pertaining to SCI across the user's accounts.

ZDXML

This report type is Zone Director's specific calls.

NOTE: Refer to the **Ruckus Smart Analytics Appendix** on using each of the report types.

Common Tasks

SCI's API allows you to build your custom specified reports, based on the available parameters. Each of these parameters has the following tasks, which is common .

Show / Hide

This toggle command shows or hides the rows dynamically in a table.

List Operations

This command displays the list of HTTP verbs such as GET, PUT, POST, HEAD or DELETE row dynamically in a table.

Expand Operations

This command expands the API dialog box for each listed operation. Use List Operations to contract the view.

Figure 6: Common tasks

occurrence	Show/Hide	List Operations	Expand Operations
report	Show/Hide	List Operations	Expand Operations
schedule	Show/Hide	List Operations	Expand Operations
setting	Show/Hide	List Operations	Expand Operations
system	Show/Hide	List Operations	Expand Operations
user	Show/Hide	List Operations	Expand Operations
zdXml	Show/Hide	List Operations	Expand Operations

Parameters for Generating API Reports

This section lists the parameters available to generate a report pertaining to occurrence. Similarly, an array of parameters are available for different report types.

The table below contains a sample of the parameters available in generating a report pertaining to occurrence.

Table 4: Parameter Details

Resource URL	Method	Response	Description
/occurrence	GET	Timestamp Status ID Schedule ID	Finds all instances of the model matched by filter from the data source.
/occurrences	PUT	Timestamp Status	Updates an existing model instance or

Resource URL	Method	Response	Description
		ID Schedule ID	inserts a new model into the data source.
/occurrences	POST	Timestamp Status ID Schedule ID	Creates a new instance of the model and persist it into the data source.
/occurrences/{id}	GET	Timestamp Status ID Schedule ID	Finds a model instance by identifier from the data source.
/occurrences/{id}	HEAD	Exists	Checks if a model instance exists in the data source.
/occurrences/{id}	PUT	Timestamp Status ID Schedule ID	Updates attributes for a model instance and persist it into the data source.
/occurrences/{id}	DELETE		Deletes a model instance by identifier from the data source.
/occurrences/{id}/exists	GET	Exists	Checks whether a model instance exists in the data source.
/occurrences/{id}/schedule	GET	Name Filter Format Frequency Day Hour Enabled Timezone Recipients	Retrieves the relation schedule.

Resource URL	Method	Response	Description
		ID Report ID	
/occurrences/change-stream	GET		Finds a change stream.
/occurrences/change-stream	POST		Creates a change stream.
/occurrences/count	GET	Count	Counts the instances of models matched based on data source.
/occurrences/findOne	GET	Timestamp Status ID Schedule ID	Finds the first instance of the model matched by filter from the data source.
/occurrences/update	POST		Updates instances of the models matched based on the data source.

Accessing and Retrieving Data

You can access and retrieve data for different sections of the Ruckus Smart Analytics. This section contains the available options and how to use them.

The options are:

- [Find the ID of the report](#)
- [Find the ID of the section](#)
- [Query the data endpoint](#)

Find the ID of the Report

You can click on this link to search for a report using the ID.

Figure 7: Report

report Show/Hide List Operations Expand Operations

GET /reports Find all instances of the model matched by filter from the data source.

Response Class (Status 200)

Model | Model Schema

```
[
  {
    "title": "string",
    "urlSegmentName": "string",
    "filterDataSource": "string",
    "id": 0,
    "facetId": 0
  }
]
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
filter	<input type="text"/>	Filter defining fields, where, include, order, offset, and limit	query	string

Find the ID of the Section

You can search using the report ID you are interested in. Take note of the default Parameters attribute, it specifies the required parameters for the section.

You can browse to the section for which you want the report using this link.

Example: If you enter 3 at the ID you get the respective information in the **Response Content Type** section

Figure 8: Search by ID of the Section

Response Class (Status 200)

Model | Model Schema

```
[
  {
    "order": 0,
    "title": "string",
    "queryName": "string",
    "component": "string",
    "defaultParameters": {},
    "layout": {},
    "url": "string",
    "id": 0,
    "facetId": 0
  }
]
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
filter	<input type="text"/>		query	string
id	<input type="text" value="3"/>	PersistedModel id	path	string

Query the Data Endpoint

You can query the data endpoint with the report ID, section ID and other required parameters.

Figure 9: Query Data Endpoint

Implementation Notes
For the **filter** field below, an example would be

```
{ "type": "or", "fields": [{ "type": "selector", "dimension": "apMac", "value": "000000000000" }] }
```

Response Class (Status 200)
Model | Model Schema

```
{
  "data": [
    {}
  ],
  "metadata": {}
}
```

Response Content Type:

Parameter	Value	Description	Parameter Type	Data Type
id	<input type="text" value="(required)"/>	Report Id	path	string
sectionId	<input type="text" value="(required)"/>	Section Id	path	string
start	<input type="text" value="(required)"/>	2016-04-06T16:04:46+00:00	formData	string
end	<input type="text" value="(required)"/>	2016-04-07T16:04:46+00:00	formData	string
granularity	<input type="text"/>	fifteen_minute, thirty_minute, hour, day	formData	string

NOTE:

You have to specify the mandatory parameters such as id, sectionId, start, and end as string values.

For each of the steps, click **Try it out!** to query the API server.

Generating API Reports

Based on report type you can generate various reports.

The following is an illustration of generating reports based on the report identifier.

1. Navigate to the **URL - GET /reports**
2. Click **Try it out!** which displays all the reports along with its report identifier
3. Navigate to the **GET /reports/{id}**
4. Enter the parameter identifier.
5. Click **Try it out!** which displays the reports pertaining to the identifier
6. Use the curl command or the request URL to view the report.

Index

A

access API [6](#)
access token [6](#)
API dialog box [9](#)
API report parameters [12](#)

C

common tasks [11](#)

D

data endpoint [16](#)

I

Identity [14](#)

N

navigation [6](#)

R

Report [14](#)
reports [11](#)

S

SCI [6](#)
section ID [15](#)
SmartCell Insight [6](#)

U

user interface [6](#)