

Unleashed 200.5 SNMP Reference Guide

Supporting Release 200.5

Draft

Copyright Notice and Proprietary Information

Copyright 2017. Ruckus Wireless, Inc. All rights reserved.

No part of this documentation may be used, reproduced, transmitted, or translated, in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without prior written permission of Ruckus Wireless, Inc. ("Ruckus"), or as expressly provided by under license from Ruckus.

Destination Control Statement

Technical data contained in this publication may be subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

THIS DOCUMENTATION AND ALL INFORMATION CONTAINED HEREIN ("MATERIAL") IS PROVIDED FOR GENERAL INFORMATION PURPOSES ONLY. RUCKUS AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THE MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE, OR THAT THE MATERIAL IS ERROR-FREE, ACCURATE OR RELIABLE. RUCKUS RESERVES THE RIGHT TO MAKE CHANGES OR UPDATES TO THE MATERIAL AT ANY TIME.

Limitation of Liability

IN NO EVENT SHALL RUCKUS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, OR DAMAGES FOR LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY YOU OR ANY THIRD PARTY, WHETHER IN AN ACTION IN CONTRACT OR TORT, ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIAL.

Trademarks

Ruckus Wireless, Ruckus, the bark logo, BeamFlex, ChannelFly, Dynamic PSK, FlexMaster, Simply Better Wireless, SmartCell, SmartMesh, SmartZone, Unleashed, ZoneDirector and ZoneFlex are trademarks of Ruckus Wireless, Inc. in the United States and other countries. All other product or company names may be trademarks of their respective owners.

Contents

- About This Guide..... 5**
 - Introduction.....5
 - Changes in This Version.....5
 - Related Documentation.....5
 - Documentation Feedback.....5
 - Online Training Resources.....6

- Unleashed MIBs..... 7**
 - Root MIBs.....7
 - Event MIBs.....8
 - System MIBs.....13
 - WLAN MIBs..... 19

Draft

Draft

About This Guide

- Introduction..... 5
- Changes in This Version..... 5
- Related Documentation..... 5
- Documentation Feedback..... 5
- Online Training Resources..... 6

Introduction

This *Reference Guide* provides information on the Ruckus Wireless™ Unleashed Simple Network Management Protocol Management Information Base (MIBs) that Unleashed supports.

NOTE

For information on how to enable SNMP trap delivery and configure other SNMP settings on the Unleashed Web interface, refer to the Unleashed Online Help, available from within the web interface.

Changes in This Version

This section lists the changes in SNMP MIBs and OIDs between this version and the previous release.

Unleashed release 200.5 contains the following SNMP MIB changes from the previous release (200.4):

MIB Tree	OID	Node Name	Change
ruckusUnleashedEventObjects	.1.3.6.1.4.1.25053.2.15.2.11	ruckusUnleashedEventAPRadiolIndex	Added "; or 2.4G, 5G."

Related Documentation

In addition to this *Reference Guide*, each Unleashed documentation set includes the following:

- *Unleashed Online Help*: Provides instructions for performing tasks using the Unleashed web interface. The online help is accessible from the web interface and is searchable.
- *Unleashed Release Notes*: Provide information about the current software release, including new features, enhancements, and known issues.
- *Unleashed Troubleshooting Guide*: Provides installation guidelines and troubleshooting information for Unleashed deployments.

Documentation Feedback

Ruckus Wireless is interested in improving its documentation and welcomes your comments and suggestions. You can email your comments to Ruckus Wireless at: docs@ruckuswireless.com

When contacting us, please include the following information:

- Document title
- Document part number (on the cover page)

About This Guide

Online Training Resources

- Page number (if appropriate)

For example:

- Unleashed 200.5 SNMP Reference Guide
- Part number: 800-71620-001 Revision A
- Page 28

Online Training Resources

To access a variety of online Ruckus Wireless training modules, including free introductory courses to wireless networking essentials, site surveys, and Ruckus Wireless products, visit the Ruckus Wireless Training Portal at: <https://training.ruckuswireless.com>.

Draft

Unleashed MIBs

- Root MIBs.....7
- Event MIBs.....8
- System MIBs.....13
- WLAN MIBs.....19

Root MIBs

This section describes the Unleashed SNMP MIBs contained in the RUCKUS-ROOT-MIB.txt file.

```
RUCKUS-ROOT-MIB DEFINITIONS ::= BEGIN

IMPORTS
    enterprises,
    MODULE-IDENTITY
        FROM SNMPv2-SMI;

ruckusRootMIB MODULE-IDENTITY
    LAST-UPDATED "201510150800Z"
    ORGANIZATION "Ruckus Wireless, Inc."
    CONTACT-INFO
        "Ruckus Wireless, Inc.

        Postal:
        350 West Java Dr.
        Sunnyvale, CA 94089
        USA

        EMail: support@ruckuswireless.com

        Phone: +1-650-265-4200"
    DESCRIPTION
        "Ruckus top level mib."
    ::= { enterprises 25053 }

-- Groups
--

ruckusObjects OBJECT IDENTIFIER ::= { ruckusRootMIB 1 }
ruckusCommon OBJECT IDENTIFIER ::= { ruckusObjects 1 }
ruckusCommonTCModule OBJECT IDENTIFIER ::= { ruckusCommon 1 }
ruckusUnleashed OBJECT IDENTIFIER ::= { ruckusObjects 15 }
ruckusUnleashedSystemModule OBJECT IDENTIFIER ::= { ruckusUnleashed 1 }
ruckusUnleashedWLANModule OBJECT IDENTIFIER ::= { ruckusUnleashed 2 }
ruckusEvents OBJECT IDENTIFIER ::= { ruckusRootMIB 2 }

END
```

Event MIBs

This section describes the contents of the RUCKUS-UNLEASHED-EVENT-MIB.txt file.

NOTE

By default, all SNMP traps are disabled. If you need to enable a trap, you can enable it using an **SNMP set** command under the scalar MIB nodes: *ruckusUnleashedEventTrapSwitchCmd*.

```
RUCKUS-UNLEASHED-EVENT-MIB DEFINITIONS ::= BEGIN

IMPORTS
    ruckusEvents
        FROM RUCKUS-ROOT-MIB
    MacAddress,
    DisplayString
        FROM SNMPv2-TC
    OBJECT-GROUP,
    MODULE-COMPLIANCE
        FROM SNMPv2-CONF
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    IpAddress
        FROM SNMPv2-SMI;

ruckusUnleashedEventMIB MODULE-IDENTITY
    LAST-UPDATED "201010150800Z"
    ORGANIZATION "Ruckus Wireless, Inc."
    CONTACT-INFO
        "Ruckus Wireless Inc.

        Postal:
        350 West Java Dr.
        Sunnyvale, CA 94089
        USA

        EMail: support@ruckuswireless.com

        Phone: +1-650-265-4200"
    DESCRIPTION
        "Ruckus Unleashed event objects, including trap OID and trap payload."
    ::= { ruckusEvents 15 }

-- Groups
--

ruckusUnleashedEventTraps OBJECT IDENTIFIER      ::= { ruckusUnleashedEventMIB 1 }

ruckusUnleashedEventObjects OBJECT IDENTIFIER    ::= { ruckusUnleashedEventMIB 2 }

ruckusUnleashedEventTrapSwitchCmd OBJECT IDENTIFIER ::= { ruckusUnleashedEventMIB 3 }

-- Ruckus Traps
--

ruckusUnleashedEventAPJoinTrap NOTIFICATION-TYPE
    OBJECTS      { ruckusUnleashedEventSerial,
                  ruckusUnleashedEventNEID,
                  ruckusUnleashedEventSeverity,
                  ruckusUnleashedEventType,
                  ruckusUnleashedEventTime,
                  ruckusUnleashedEventStatus,
                  ruckusUnleashedEventTitle,
                  ruckusUnleashedEventAPMacAddr }
    STATUS      current
    DESCRIPTION
        "Trigger when there is a AP join event.
```



```

    The AP's MAC address is enclosed."
 ::= { ruckusUnleashedEventTraps 1 }

```

```

ruckusUnleashedEventAPLostTrap NOTIFICATION-TYPE
OBJECTS      { ruckusUnleashedEventSerial,
               ruckusUnleashedEventNEID,
               ruckusUnleashedEventSeverity,
               ruckusUnleashedEventType,
               ruckusUnleashedEventTime,
               ruckusUnleashedEventStatus,
               ruckusUnleashedEventTitle,
               ruckusUnleashedEventAPMacAddr }
STATUS       current
DESCRIPTION
    "Trigger when AP lost contact.
    The AP's MAC address is enclosed."
 ::= { ruckusUnleashedEventTraps 5 }

```

```

ruckusUnleashedEventAPSystemColdStartTrap NOTIFICATION-TYPE
OBJECTS      { ruckusUnleashedEventSerial,
               ruckusUnleashedEventNEID,
               ruckusUnleashedEventSeverity,
               ruckusUnleashedEventType,
               ruckusUnleashedEventTime,
               ruckusUnleashedEventStatus,
               ruckusUnleashedEventTitle,
               ruckusUnleashedEventAPMacAddr,
               ruckusUnleashedEventOccurTime }
STATUS       current
DESCRIPTION
    "Trigger when an AP performs cold start."
 ::= { ruckusUnleashedEventTraps 31 }

```

```

ruckusUnleashedEventAPSystemWarmStartTrap NOTIFICATION-TYPE
OBJECTS      { ruckusUnleashedEventSerial,
               ruckusUnleashedEventNEID,
               ruckusUnleashedEventSeverity,
               ruckusUnleashedEventType,
               ruckusUnleashedEventTime,
               ruckusUnleashedEventStatus,
               ruckusUnleashedEventTitle,
               ruckusUnleashedEventAPMacAddr,
               ruckusUnleashedEventOccurTime }
STATUS       current
DESCRIPTION
    "Trigger when an AP performs warm start."
 ::= { ruckusUnleashedEventTraps 32 }

```

```

ruckusUnleashedEventAPRadioOn NOTIFICATION-TYPE
OBJECTS      { ruckusUnleashedEventSerial,
               ruckusUnleashedEventNEID,
               ruckusUnleashedEventSeverity,
               ruckusUnleashedEventType,
               ruckusUnleashedEventTime,
               ruckusUnleashedEventStatus,
               ruckusUnleashedEventTitle,
               ruckusUnleashedEventAPMacAddr,
               ruckusUnleashedEventAPRadioIndex,
               ruckusUnleashedEventOccurTime
               }
STATUS       current
DESCRIPTION
    "AP Radio ON, the period is 60 seconds"
 ::= { ruckusUnleashedEventTraps 130 }

```

```

ruckusUnleashedEventAPRadioOff NOTIFICATION-TYPE
OBJECTS      { ruckusUnleashedEventSerial,
               ruckusUnleashedEventNEID,
               ruckusUnleashedEventSeverity,
               ruckusUnleashedEventType,

```

Unleashed MIBs
Event MIBs

```
        ruckusUnleashedEventTime,
        ruckusUnleashedEventStatus,
        ruckusUnleashedEventTitle,
        ruckusUnleashedEventAPMacAddr,
        ruckusUnleashedEventAPRadioIndex,
        ruckusUnleashedEventOccurTime
    }
STATUS      current
DESCRIPTION
    "AP Radio OFF, the period is 60 seconds"
 ::= { ruckusUnleashedEventTraps 131 }

ruckusUnleashedEventMasterAPSwitch NOTIFICATION-TYPE
OBJECTS     { ruckusUnleashedEventSerial,
              ruckusUnleashedEventNEID,
              ruckusUnleashedEventSeverity,
              ruckusUnleashedEventType,
              ruckusUnleashedEventTime,
              ruckusUnleashedEventStatus,
              ruckusUnleashedEventTitle,
              ruckusUnleashedEventContent}
STATUS      current
DESCRIPTION
    "[master ap switch: Unleashed network change master role
     from [172.18.151.1]/[e0:10:7f:28:2d:70]
     into [172.18.151.9]/[6c:aa:b3:3d:66:30]"
 ::= { ruckusUnleashedEventTraps 138 }

-- Trap payload
--

ruckusUnleashedEventSerial OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Trap serial number."
 ::= { ruckusUnleashedEventObjects 1 }

ruckusUnleashedEventNEID OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Network element ID."
 ::= { ruckusUnleashedEventObjects 2 }

ruckusUnleashedEventSeverity OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Severity level of the trap."
 ::= { ruckusUnleashedEventObjects 3 }

ruckusUnleashedEventType OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Trap type."
 ::= { ruckusUnleashedEventObjects 4 }

ruckusUnleashedEventTime OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Time when trap reported."
 ::= { ruckusUnleashedEventObjects 5 }

ruckusUnleashedEventStatus OBJECT-TYPE
```

```

SYNTAX      INTEGER { raise(1),
                    clear(2) }
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Trap status."
 ::= { ruckusUnleashedEventObjects 6 }

ruckusUnleashedEventTitle OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Trap title."
 ::= { ruckusUnleashedEventObjects 7 }

ruckusUnleashedEventContent OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Trap content."
 ::= { ruckusUnleashedEventObjects 8 }

ruckusUnleashedEventOccurTime OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "Time when trap occur."
 ::= { ruckusUnleashedEventObjects 10 }

ruckusUnleashedEventAPRadioIndex OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "AP radio index, 0, 2.4G, 1, 5G; or 2.4G 5G"
 ::= { ruckusUnleashedEventObjects 11 }

ruckusUnleashedEventClientMacAddr OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "The client's MAC address."
 ::= { ruckusUnleashedEventObjects 15 }

ruckusUnleashedEventAPMacAddr OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "The AP's MAC address, or the AP's name."
 ::= { ruckusUnleashedEventObjects 18 }

ruckusUnleashedEventSSID OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "SSID."
 ::= { ruckusUnleashedEventObjects 23 }

ruckusUnleashedEventIpAddr OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  accessible-for-notify
STATUS      current
DESCRIPTION
    "IpAddress (ipv4 and ipv6)."
 ::= { ruckusUnleashedEventObjects 30 }

```

```
ruckusUnleashedEventAPJoinTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "trap switch command."
        DEFVAL {disable}
    ::= { ruckusUnleashedEventTrapSwitchCmd 1 }

ruckusUnleashedEventAPLostTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "trap switch command."
        DEFVAL {disable}
    ::= { ruckusUnleashedEventTrapSwitchCmd 5 }

ruckusUnleashedEventAPSystemColdStartTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "trap switch command."
        DEFVAL {disable}
    ::= { ruckusUnleashedEventTrapSwitchCmd 31 }

ruckusUnleashedEventAPSystemWarmStartTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "trap switch command."
        DEFVAL {disable}
    ::= { ruckusUnleashedEventTrapSwitchCmd 32 }

ruckusUnleashedEventAPRadioOnTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "trap switch command."
        DEFVAL {disable}
    ::= { ruckusUnleashedEventTrapSwitchCmd 130 }

ruckusUnleashedEventAPRadioOffTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "trap switch command."
        DEFVAL {disable}
    ::= { ruckusUnleashedEventTrapSwitchCmd 131 }

ruckusUnleashedEventMasterAPSwitchTrapSwitchCmd OBJECT-TYPE
    SYNTAX  INTEGER{
        enable(1),
        disable(0)}
    MAX-ACCESS read-write
```

```

STATUS current
DESCRIPTION
    "trap switch command."
    DEFVAL {disable}
::= { ruckusUnleashedEventTrapSwitchCmd 138 }

```

```
END
```

System MIBs

This section describes the contents of the RUCKUS-UNLEASHED-SYSTEM-MIB.txt file.

```

RUCKUS-UNLEASHED-SYSTEM-MIB DEFINITIONS ::= BEGIN

IMPORTS
    ruckusUnleashedSystemModule
        FROM RUCKUS-ROOT-MIB
    DisplayString,
    MacAddress,
    RowStatus,
    TruthValue
        FROM SNMPv2-TC
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ifIndex,
    InterfaceIndex
        FROM IF-MIB
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Counter32,
    Integer32,
    Unsigned32,
    IPAddress
        FROM SNMPv2-SMI;

ruckusUnleashedSystemMIB MODULE-IDENTITY
    LAST-UPDATED "201510150800Z"
    ORGANIZATION "Ruckus Wireless, Inc."
    CONTACT-INFO
        "Ruckus Wireless, Inc.

        Postal:
        350 West Java Dr.
        Sunnyvale, CA 94089
        USA

        EMail: support@ruckuswireless.com

        Phone: +1-650-265-4200"
    DESCRIPTION
        "Ruckus Unleashed System mib"
    ::= { ruckusUnleashedSystemModule 1 }

ruckusUnleashedSystemObjects OBJECT IDENTIFIER ::= { ruckusUnleashedSystemMIB 1 }

ruckusUnleashedSystemInfo OBJECT IDENTIFIER ::= { ruckusUnleashedSystemObjects 1 }

ruckusUnleashedSystemName OBJECT-TYPE
    SYNTAX DisplayString(SIZE(1..32))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "System name"
    ::= { ruckusUnleashedSystemInfo 1 }

ruckusUnleashedSystemIPAddr OBJECT-TYPE
    SYNTAX IPAddress
    MAX-ACCESS read-only

```

Unleashed MIBs
System MIBs

```
STATUS current
DESCRIPTION
  "IP Address"
 ::= { ruckusUnleashedSystemInfo 2 }

ruckusUnleashedSystemMacAddr OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (6))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "MAC Address"
 ::= { ruckusUnleashedSystemInfo 3 }

ruckusUnleashedSystemUptime OBJECT-TYPE
SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Up time"
 ::= { ruckusUnleashedSystemInfo 8 }

ruckusUnleashedSystemModel OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Model"
 ::= { ruckusUnleashedSystemInfo 9 }

ruckusUnleashedSystemLicensedAPs OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Licensed APs"
 ::= { ruckusUnleashedSystemInfo 12 }

ruckusUnleashedSystemMaxSta OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Number of max stations allowed."
 ::= { ruckusUnleashedSystemInfo 13 }

ruckusUnleashedSystemSerialNumber OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Serial number"
 ::= { ruckusUnleashedSystemInfo 15 }

ruckusUnleashedSystemVersion OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Software version"
 ::= { ruckusUnleashedSystemInfo 18 }

ruckusUnleashedSystemCountryCode OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (2))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Specifies the country code.
   Each country represented as a two character.

  Here is the lsit:

  ALBANIA      ->   AL
```

ALGERIA	->	DZ
ARGENTINA	->	AR
ARMENIA	->	AM
AUSTRALIA	->	AU
AUSTRIA	->	AT
AZERBAIJAN	->	AZ
BAHRAIN	->	BH
BELARUS	->	BY
BELGIUM	->	BE
BELIZE	->	BZ
BOLIVIA	->	BO
BRAZIL	->	BR
BRUNEI_DARUSSALAM	->	BN
BULGARIA	->	BG
CANADA	->	CA
CHILE	->	CL
CHINA	->	CN
COLOMBIA	->	CO
COSTA_RICA	->	CR
CROATIA	->	HR
CYPRUS	->	CY
CZECH	->	CZ
DENMARK	->	DK
DOMINICAN_REPUBLIC	->	DO
ECUADOR	->	EC
EGYPT	->	EG
EL_SALVADOR	->	SV
ESTONIA	->	EE
FINLAND	->	FI
FRANCE	->	FR
FRANCE2	->	F2
GEORGIA	->	GE
GERMANY	->	DE
GREECE	->	GR
GUATEMALA	->	GT
HONDURAS	->	HN
HONG_KONG	->	HK
HUNGARY	->	HU
ICELAND	->	IS
INDIA	->	IN
INDONESIA	->	ID
IRAN	->	IR
IRELAND	->	IE
ISRAEL	->	IL
ITALY	->	IT
JAPAN	->	JP
JAPAN1	->	J1
JAPAN2	->	J2
JAPAN3	->	J3
JAPAN4	->	J4
JAPAN5	->	J5
JAPAN6	->	J6
JAPAN7	->	JP
JAPAN8	->	JP
JAPAN9	->	JP
JAPAN10	->	JP
JAPAN11	->	JP
JAPAN12	->	JP
JAPAN13	->	JP
JAPAN14	->	JP
JAPAN15	->	JP
JAPAN16	->	JP
JAPAN17	->	JP
JAPAN18	->	JP
JAPAN19	->	JP
JAPAN20	->	JP
JAPAN21	->	JP
JAPAN22	->	JP
JAPAN23	->	JP
JAPAN24	->	JP
JORDAN	->	JO
KAZAKHSTAN	->	KZ

Unleashed MIBs
System MIBs

```

KOREA_NORTH      -> KP
KOREA_ROC        -> KR
KOREA_ROC2       -> K2
KUWAIT           -> KW
LATVIA           -> LV
LEBANON          -> LB
LIECHTENSTEIN   -> LI
LITHUANIA        -> LT
LUXEMBOURG       -> LU
MACAU            -> MO
MACEDONIA        -> MK
MALAYSIA         -> MY
MEXICO           -> MX
MONACO           -> MC
MOROCCO          -> MA
NETHERLANDS      -> NL
NEW_ZEALAND      -> NZ
NORWAY           -> NO
OMAN             -> OM
PAKISTAN         -> PK
PANAMA           -> PA
PERU             -> PE
PHILIPPINES      -> PH
POLAND           -> PL
PORTUGAL         -> PT
PUERTO_RICO      -> PR
QATAR            -> QA
ROMANIA          -> RO
RUSSIA           -> RU
SAUDI_ARABIA     -> SA
SINGAPORE        -> SG
SLOVAKIA         -> SK
SLOVENIA         -> SI
SOUTH_AFRICA     -> ZA
SPAIN            -> ES
SWEDEN           -> SE
SWITZERLAND      -> CH
SYRIA            -> SY
TAIWAN           -> TW
THAILAND         -> TH
TRINIDAD_Y_TOBAGO -> TT
TUNISIA          -> TN
TURKEY           -> TR
UKRAINE          -> UA
UAE              -> AE
UNITED_KINGDOM   -> GB
UNITED_STATES    -> US
UNITED_STATES_FCC49 -> US
URUGUAY          -> UY
UZBEKISTAN       -> UZ
VENEZUELA        -> VE
VIET_NAM         -> VN
YEMEN            -> YE
ZIMBABWE         -> ZW"

```

```
 ::= { ruckusUnleashedSystemInfo 20 }
```

```
--
```

```
-- Unleashed System Statistics, Operation Status
```

```
--
```

```
ruckusUnleashedSystemStats OBJECT IDENTIFIER ::= { ruckusUnleashedSystemObjects 15 }
```

```
ruckusUnleashedSystemStatsNumAP OBJECT-TYPE
```

```
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
```

```
"Number of AP"
```

```
 ::= { ruckusUnleashedSystemStats 1 }
```

```
ruckusUnleashedSystemStatsNumSta OBJECT-TYPE
```



```

SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Number of authorized client devices"
 ::= { ruckusUnleashedSystemStats 2 }

ruckusUnleashedSystemStatsWLANTotalRxPkts OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total received packets of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 5 }

ruckusUnleashedSystemStatsWLANTotalRxBytes OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total received bytes of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 6 }

ruckusUnleashedSystemStatsWLANTotalRxMulticast OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total received multicast packets of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 7 }

ruckusUnleashedSystemStatsWLANTotalTxPkts OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total transmitted packets of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 8 }

ruckusUnleashedSystemStatsWLANTotalTxBytes OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total transmitted bytes of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 9 }

ruckusUnleashedSystemStatsWLANTotalTxMulticast OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total transmitted multicast packets of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 10 }

ruckusUnleashedSystemStatsWLANTotalTxFail OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total transmitted fail packets of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 11 }

ruckusUnleashedSystemStatsWLANTotalTxRetry OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total transmitted retry packets of wireless interfaces"
 ::= { ruckusUnleashedSystemStats 12 }

ruckusUnleashedSystemStatsCPUUtil OBJECT-TYPE

```

Unleashed MIBs
System MIBs

```
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "CPU utilization"
 ::= { ruckusUnleashedSystemStats 13 }

ruckusUnleashedSystemStatsMemoryUtil OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Memory utilization"
 ::= { ruckusUnleashedSystemStats 14 }

ruckusUnleashedSystemStatsNumRegisteredAP OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Number of registered AP"
 ::= { ruckusUnleashedSystemStats 15 }

ruckusUnleashedSystemStatsWLANTotalAssocFail OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Total number of failed station associations."
 ::= { ruckusUnleashedSystemStats 16 }

ruckusUnleashedSystemStatsWLANTotalRxErrFrm OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Total number of erroneous downlink frames."
 ::= { ruckusUnleashedSystemStats 17 }

ruckusUnleashedSystemStatsWLANTotalTxDroppedPkt OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Total number of dropped downlink packets."
 ::= { ruckusUnleashedSystemStats 19 }

ruckusUnleashedSystemStatsWLANTotalTxErrFrm OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Total number of erroneous downlink frames."
 ::= { ruckusUnleashedSystemStats 20 }

ruckusUnleashedSystemStatsWLANTotalTxDroppedFrm OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION "Total number of dropped downlink frames."
 ::= { ruckusUnleashedSystemStats 21 }

ruckusUnleashedSystemStatsAllNumSta OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Number of All client devices"
 ::= { ruckusUnleashedSystemStats 30 }

END
```

WLAN MIBs

This section describes the contents of the RUCKUS-UNLEASHED-WLAN-MIB.txt file.

```

RUCKUS-UNLEASHED-WLAN-MIB DEFINITIONS ::= BEGIN

IMPORTS
    ruckusUnleashedWLANModule
        FROM RUCKUS-ROOT-MIB
    DisplayString,
    MacAddress,
    RowStatus,
    PhysAddress,
    TruthValue
        FROM SNMPv2-TC
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ifIndex,
    InterfaceIndex
        FROM IF-MIB
    IANAifType
        FROM IANAifType-MIB
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Counter32,
    Integer32,
    Unsigned32,
    IPAddress
        FROM SNMPv2-SMI;

ruckusUnleashedWLANMIB MODULE-IDENTITY
    LAST-UPDATED "201510150800Z"
    ORGANIZATION "Ruckus Wireless, Inc."
    CONTACT-INFO
        "Ruckus Wireless, Inc.

        Postal:
        350 West Java Dr.
        Sunnyvale, CA 94089
        USA

        EMail: support@ruckuswireless.com

        Phone: +1-650-265-4200"
    DESCRIPTION
        "Ruckus Unleashed WLAN mib"
    ::= { ruckusUnleashedWLANModule 1 }

ruckusUnleashedWLANObjects OBJECT IDENTIFIER ::= { ruckusUnleashedWLANMIB 1 }
ruckusUnleashedWLANInfo OBJECT IDENTIFIER ::= { ruckusUnleashedWLANObjects 1 }
ruckusUnleashedWLANAPInfo OBJECT IDENTIFIER ::= { ruckusUnleashedWLANObjects 2 }

ruckusUnleashedWLANAPEthStatusTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RuckusUnleashedWLANAPEthStatusEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Unleashed WLAN AP Ethernet Interface status table per each AP."
    ::= { ruckusUnleashedWLANAPInfo 8 }

ruckusUnleashedWLANAPEthStatusEntry OBJECT-TYPE
    SYNTAX RuckusUnleashedWLANAPEthStatusEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Specifies each Unleashed WLAN AP ethernet interface status entry."
    INDEX {

```

Unleashed MIBs
WLAN MIBs

```
        ruckusUnleashedWLANAPMacAddress,
        ruckusUnleashedWLANAPEthPortId }
 ::= { ruckusUnleashedWLANAPEthStatusTable 1 }

RuckusUnleashedWLANAPEthStatusEntry ::= SEQUENCE {
    ruckusUnleashedWLANAPMacAddress      MacAddress,
    ruckusUnleashedWLANAPEthPortId      INTEGER,
    ruckusUnleashedWLANAPEthIfname      OCTET STRING,
    ruckusUnleashedWLANAPEthPhyStatus   INTEGER,
    ruckusUnleashedWLANAPEthPhyIfSpeed  INTEGER,
    ruckusUnleashedWLANAPEthPhyLinkStatus INTEGER,
    ruckusUnleashedWLANAPEthLabel      OCTET STRING
}

ruckusUnleashedWLANAPMacAddress OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The AP's Mac Address."
    ::= { ruckusUnleashedWLANAPEthStatusEntry 1 }

ruckusUnleashedWLANAPEthPortId  OBJECT-TYPE
    SYNTAX      INTEGER
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The ap ethernet port id."
    ::= { ruckusUnleashedWLANAPEthStatusEntry 2 }

ruckusUnleashedWLANAPEthIfname  OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The name of interface."
    ::= { ruckusUnleashedWLANAPEthStatusEntry 5 }

ruckusUnleashedWLANAPEthPhyStatus  OBJECT-TYPE
    SYNTAX      INTEGER {
        up(1),
        down(2) }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The ap ethernet port physical status."
    ::= { ruckusUnleashedWLANAPEthStatusEntry 8 }

ruckusUnleashedWLANAPEthPhyIfSpeed  OBJECT-TYPE
    SYNTAX      INTEGER
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The ap ethernet interface's current bandwidth in Mbits,."
    ::= { ruckusUnleashedWLANAPEthStatusEntry 9 }

ruckusUnleashedWLANAPEthPhyLinkStatus  OBJECT-TYPE
    SYNTAX      INTEGER {
        full(1),
        half(2) }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The ap ethernet port physical link status."
    ::= { ruckusUnleashedWLANAPEthStatusEntry 10 }

ruckusUnleashedWLANAPEthLabel  OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-only
    STATUS      current
```

```
DESCRIPTION  
    "The ap ethernet port label."  
 ::= { ruckusUnleashedWLANAPEthStatusEntry 11 }
```

END

Draft

Draft



Copyright © 2006-2017. Ruckus Wireless, Inc.
350 West Java Dr. Sunnyvale, CA 94089. USA
www.ruckuswireless.com