

Unleashed 200.7 Refresh 1 Release Notes

Supporting Unleashed 200.7 Refresh 1

Copyright, Trademark and Proprietary Rights Information

© 2019 ARRIS Enterprises LLC. All rights reserved.

No part of this content may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS International plc and/or its affiliates ("ARRIS"). ARRIS reserves the right to revise or change this content from time to time without obligation on the part of ARRIS to provide notification of such revision or change.

Export Restrictions

These products and associated technical data (in print or electronic form) may be subject to export control laws of the United States of America. It is your responsibility to determine the applicable regulations and to comply with them. The following notice is applicable for all products or technology subject to export control:

These items are controlled by the U.S. Government and authorized for export only to the country of ultimate destination for use by the ultimate consignee or end-user(s) herein identified. They may not be resold, transferred, or otherwise disposed of, to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. government or as otherwise authorized by U.S. law and regulations.

Disclaimer

THIS CONTENT AND ASSOCIATED PRODUCTS OR SERVICES ("MATERIALS"), ARE PROVIDED "AS IS" AND WITHOUT WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED. TO THE FULLEST EXTENT PERMISSIBLE PURSUANT TO APPLICABLE LAW, ARRIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TITLE, NON-INFRINGEMENT, FREEDOM FROM COMPUTER VIRUS, AND WARRANTIES ARISING FROM COURSE OF DEALING OR COURSE OF PERFORMANCE. ARRIS does not represent or warrant that the functions described or contained in the Materials will be uninterrupted or error-free, that defects will be corrected, or are free of viruses or other harmful components. ARRIS does not make any warranties or representations regarding the use of the Materials in terms of their completeness, correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise. As a condition of your use of the Materials, you warrant to ARRIS that you will not make use thereof for any purpose that is unlawful or prohibited by their associated terms of use.

Limitation of Liability

IN NO EVENT SHALL ARRIS, ARRIS AFFILIATES, OR THEIR OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, SUPPLIERS, LICENSORS AND THIRD PARTY PARTNERS, BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, EXEMPLARY OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER, EVEN IF ARRIS HAS BEEN PREVIOUSLY ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT, OR ANY OTHER THEORY ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIALS. Because some jurisdictions do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of liability for consequential or incidental damages, some of the above limitations may not apply to you.

Trademarks

ARRIS, the ARRIS logo, Ruckus, Ruckus Wireless, Ruckus Networks, Ruckus logo, the Big Dog design, BeamFlex, ChannelFly, Edgelron, FastIron, HyperEdge, ICX, IronPoint, OPENG, SmartCell, Unleashed, Xclaim, ZoneFlex are trademarks of ARRIS International plc and/or its affiliates. Wi-Fi Alliance, Wi-Fi, the Wi-Fi logo, the Wi-Fi CERTIFIED logo, Wi-Fi Protected Access (WPA), the Wi-Fi Protected Setup logo, and WMM are registered trademarks of Wi-Fi Alliance. Wi-Fi Protected Setup™, Wi-Fi Multimedia™, and WPA2™ are trademarks of Wi-Fi Alliance. All other trademarks are the property of their respective owners.

Contents

About This Release.....	4
Introducing Ruckus Unleashed.....	4
Supported Platforms and Upgrade Information.....	4
Supported Platforms.....	4
Upgrade Information.....	4
Enhancements and Resolved Issues.....	5
New Access Points.....	5
Enhancements in Release 200.7.10.102.64.....	6
Enhancements/New Features in the GA Release.....	6
Resolved Issues in Build 200.7.10.102.64	7
Caveats, Limitations and Known Issues.....	8

About This Release

This document provides release information on Ruckus Unleashed release 200.7, including new features and enhancements, along with known issues, caveats, workarounds, supported platforms and upgrade information for this release.

Introducing Ruckus Unleashed

Unleashed is a controller-less WLAN solution that allows small businesses to deliver an enterprise-class Wi-Fi user experience in a cost effective, easy to implement, intuitive and yet feature-rich platform.

The Unleashed solution scales up to 50 Access Points and 1,024 concurrent clients.

For more information on Unleashed configuration, administration and maintenance, please see the Unleashed Online Help, available at <https://docs.ruckuswireless.com/unleashed/200.7/index.html>.

Supported Platforms and Upgrade Information

Supported Platforms

Unleashed version **200.7.10.102.64** supports the following Ruckus AP models:

Indoor AP	Outdoor AP
C110	E510
H320	T300
H510	T300e
M510*	T301n
R310	T301s
R320*	T310c
R500	T310d
R510	T310n
R600	T310s
R610	T610
R710	T610s
R720	T710
	T710s

NOTE

The M510 and R320 are new in the 200.7 GA release.

NOTE

The M510-JP (Japan SKU) is new in release 200.7.10.102.64.

Upgrade Information

The following release builds can be directly upgraded to Unleashed version **200.7.10.102.64**:

Online Upgrade:

- 200.0.9.9.608 (Unleashed 200.0 GA)
- 200.1.9.12.62 (Refresh of Unleashed 200.1 GA)
- 200.2.9.13.186 (Unleashed 200.2 GA)
- 200.3.9.13.228 (Unleashed 200.3 GA)
- 200.4.9.13.47 (Unleashed 200.4 GA)
- 200.5.10.0.235 (Unleashed 200.5 GA Refresh)
- 200.5.10.0.291 (Unleashed 200.5 GA Refresh 3)
- 200.6.10.1.308 (Unleashed 200.6 GA)
- 200.6.10.1.310 (Unleashed 200.6 GA Refresh 1)
- 200.6.10.1.312 (Unleashed 200.6 GA Refresh 2)
- 200.7.10.2.339 (Unleashed 200.7 GA)

Local Upgrade:

- 200.2.9.13.186 (Unleashed 200.2 GA)
- 200.3.9.13.228 (Unleashed 200.3 GA)
- 200.4.9.13.47 (Unleashed 200.4 GA)
- 200.5.10.0.235 (Unleashed 200.5 GA Refresh)
- 200.5.10.0.291 (Unleashed 200.5 GA Refresh 3)
- 200.6.10.1.308 (Unleashed 200.6 GA)
- 200.6.10.1.310 (Unleashed 200.6 (GA Refresh 1)
- 200.6.10.1.312 (Unleashed 200.6 GA Refresh 2)
- 200.7.10.2.339 (Unleashed 200.7 GA)

Enhancements and Resolved Issues

This section lists new features and enhancements that have been added in this release, and any customer-reported issues from previous releases that have been resolved in this release.

New Access Points

This release adds Unleashed support for two new APs: Unleashed M510 and Unleashed R320.

- Unleashed M510

This release adds Unleashed support for the M510 Wave 2 802.11ac LTE Wi-Fi access point (AP). The M510 is designed to leverage LTE networks as a backhaul to connect wirelessly back to any network without the need for an Ethernet cable connection.

NOTE

The M510-JP (Japan SKU) is new in release 200.7.10.102.64.

- Unleashed R320

The R320 is an entry-level 2x2:2 802.11ac Wave 2 indoor AP designed for medium-density enterprise deployments. It features one GbE port, dual 2.4/5 GHz radios, BeamFlex support, 802.3af/at PoE support and a small form factor for flexible installation.

Enhancements in Release 200.7.10.102.64

Release 200.7.10.102.64 introduces the following new features and enhancements:

- This release adds support for the Japan version of the Unleashed M510 LTE Access Point.
- Unleashed Admin accounts can now be created with limited monitoring privileges, in addition to full administrative access.
- Enhanced the Hotspot web interface.
- Enhanced PoE Mode settings in AP model-specific controls to provide better control over AP power settings.
- External DPSK: Dynamic PSKs can now be created for clients authenticated via external RADIUS server, in addition to internal database.
- Extended the maximum size of the guest WLAN "Terms and Conditions" to 16,000 bytes.

Enhancements/New Features in the GA Release

Release 200.7 (GA) introduces the following new features and enhancements:

- AP Groups

AP Groups can now be configured, allowing admins to apply multiple configuration profiles to different groups of APs.

- CLI Setup Wizard

A new CLI setup wizard provides another way to perform the initial network configuration, in addition to the mobile app and browser-based setup methods.

- Increase Scale to 50 APs and 1,024 Clients

Unleashed now supports up to 50 APs (up from 25), and 1,024 clients (up from 512).

NOTE

As of this release, this increase applies only to Unleashed 802.11ac Wave 2 APs.

NOTE

The 50 AP maximum does not apply when the Master AP is in Gateway Mode, regardless of AP model. If the Master AP is deployed in Gateway Mode, the maximum remains 25 APs.

- 802.1X Authentication Caching

This feature allows the APs to cache 802.1X client credentials at the AP, so that clients will not have to perform additional authentications in case of disconnection from the RADIUS server within a specified time limit.

- WPA2+Hotspot WLANs

This release adds support for creating an SSID using WPA2-PSK and Hotspot service at the same time.

- Bonjour Fencing

Bonjour Fencing provides a mechanism to limit the scope of Bonjour service discovery in the physical/spatial domain. This is useful because logical network boundaries (e.g. VLANs) do not always correlate well to physical boundaries within a building/floor.

This feature can be configured via CLI commands only in this release.

- Ethernet Port VLAN Support
Allows VLAN configuration of Ethernet ports on wall-plate type APs (H320 and H510).
- Merge Guest and Social Media WLAN Types
Social Media WLANs are now a subcategory of Guest WLAN, rather than being a separate WLAN type as in previous releases.
- Captive Portal Customization
Provides several new options for customizing the Captive Portal login page for Guest WLANs.
- Portal Page Multi-Language Support
This feature is enabled by default for the Guest WLAN login portal page when the web interface language is not English.
- Client Connection Diagnostics Enhancement
Client connection troubleshooting can now be run on clients connected to Web Auth, Hotspot (WISPr), and Social Media Guest WLANs, in addition to standard usage WLANs.
- Save Debug Info Progress Indication
A progress indicator is now displayed when the Save Debug Info button is pressed to download a debug log file.
- Display Unleashed Version on First Installation Page
The firmware version number currently being configured is now displayed on the first installation wizard screen.
- Favorite Client Support
Mark a client as a "favorite," to receive notifications when the client connects or disconnects.
- L3 Fast Path Performance Enhancement
This feature improves throughput performance when the AP is gateway mode, increasing efficiency by allowing certain packets to bypass bridge and route processes based on information learned from traffic analysis.
- Event Level Setting in Diagnostics Logs
Provides a configuration option to set the level of debug logs to display on the Events page.
- Display "Uploading" Progress Bar on Upgrade Page
A progress bar is now displayed to indicate the image file upload progress.
- Increased Max Bind IP Addresses for DHCP Server to 128 from 32.
- Improved speed of Setup Wizard process.
- MAC Auth authentication can now use local database as the auth server.
- Reduce Channel Change Frequency.

Resolved Issues in Build 200.7.10.102.64

- Resolved an issue with high CPU utilization caused by bulk login and logoff attempts from the network. [ER-7081]
- Resolved an issue with R310 APs that could cause instability when 5 GHz radio channelization was set to 20. [ER-6969]
- Resolved an issue on R720 APs where wireless clients could experience low uplink throughput if they had previously associated to a WLAN with rate limiting enabled on the same R720 AP. [ER-6567, ER-6830, ER-6576]
- Resolved an issue that could cause R720 APs to reboot due to kernel panic. [ER-6689]

Caveats, Limitations and Known Issues

This section lists the caveats, limitations, and known issues in this release.

Issue	UN-2817
Description	5 GHz SSIDs fail to deploy immediately after completing the CLI setup wizard when DFS channels are used.

Issue	UN-2855
Description	Windows 10 clients running Chrome version 70.0.3538.67 may not properly redirect to the setup wizard screen when attempting to configure an AP in factory default state.

Issue	UN-2936
Description	Guest login pages may display incorrect language after changing the language setting.

Issue	UN-2480
Description	iOS 11.3 devices may fail to download Zero-IT profiles using the onboarding portal. Workaround: Enable Bypass Apple CNA feature in WLAN settings.

Issue	UN-2990
Description	M510 does not support hot-swapping SIM cards. Removing and reinserting a SIM card or replacing a SIM card with another one will require an AP reboot to bring the new SIM card into service.

Issue	UN-2802
Description	Upload progress indicator does not display correctly in Microsoft Internet Explorer and Edge browsers.

Issue	UN-3035
Description	Android clients are unable to download the Zero-IT activation file when connected to a guest network via CNA.

Issue	UN-3034
Description	Mac OS clients are unable to download the Zero-IT activation file when connected to a guest network via CNA.

Issue	UN-3031
Description	801.1X Zero-IT profiles are not created properly for Windows 10 OS version 17134.407 clients. Clients are prompting for username and password when connecting.