



API REFERENCE GUIDE

# Using Cloudpath APIs to Interact With External Systems

Supporting Software Release 5.2

# Copyright, Trademark and Proprietary Rights Information

© 2018 ARRIS Enterprises LLC. All rights reserved.

No part of this content may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS International plc and/or its affiliates ("ARRIS"). ARRIS reserves the right to revise or change this content from time to time without obligation on the part of ARRIS to provide notification of such revision or change.

## Export Restrictions

These products and associated technical data (in print or electronic form) may be subject to export control laws of the United States of America. It is your responsibility to determine the applicable regulations and to comply with them. The following notice is applicable for all products or technology subject to export control:

*These items are controlled by the U.S. Government and authorized for export only to the country of ultimate destination for use by the ultimate consignee or end-user(s) herein identified. They may not be resold, transferred, or otherwise disposed of, to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. government or as otherwise authorized by U.S. law and regulations.*

## Disclaimer

THIS CONTENT AND ASSOCIATED PRODUCTS OR SERVICES ("MATERIALS"), ARE PROVIDED "AS IS" AND WITHOUT WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED. TO THE FULLEST EXTENT PERMISSIBLE PURSUANT TO APPLICABLE LAW, ARRIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TITLE, NON-INFRINGEMENT, FREEDOM FROM COMPUTER VIRUS, AND WARRANTIES ARISING FROM COURSE OF DEALING OR COURSE OF PERFORMANCE. ARRIS does not represent or warrant that the functions described or contained in the Materials will be uninterrupted or error-free, that defects will be corrected, or are free of viruses or other harmful components. ARRIS does not make any warranties or representations regarding the use of the Materials in terms of their completeness, correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise. As a condition of your use of the Materials, you warrant to ARRIS that you will not make use thereof for any purpose that is unlawful or prohibited by their associated terms of use.

## Limitation of Liability

IN NO EVENT SHALL ARRIS, ARRIS AFFILIATES, OR THEIR OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, SUPPLIERS, LICENSORS AND THIRD PARTY PARTNERS, BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, EXEMPLARY OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER, EVEN IF ARRIS HAS BEEN PREVIOUSLY ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT, OR ANY OTHER THEORY ARISING FROM YOUR ACCESS TO, OR USE OF, THE MATERIALS. Because some jurisdictions do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of liability for consequential or incidental damages, some of the above limitations may not apply to you.

## Trademarks

ARRIS, the ARRIS logo, Ruckus, Ruckus Wireless, Ruckus Networks, Ruckus logo, the Big Dog design, BeamFlex, ChannelFly, Edgelron, FastIron, HyperEdge, ICX, IronPoint, OPENG, SmartCell, Unleashed, Xclaim, ZoneFlex are trademarks of ARRIS International plc and/or its affiliates. Wi-Fi Alliance, Wi-Fi, the Wi-Fi logo, the Wi-Fi CERTIFIED logo, Wi-Fi Protected Access (WPA), the Wi-Fi Protected Setup logo, and WMM are registered trademarks of Wi-Fi Alliance. Wi-Fi Protected Setup™, Wi-Fi Multimedia™, and WPA2™ are trademarks of Wi-Fi Alliance. All other trademarks are the property of their respective owners.

# Contents

---

|   |          |
|---|----------|
| <b>How to Use The Cludpath API.....</b>                                       | <b>5</b> |
| Overview.....   | 5        |
| <b>Outbound: Sending Notifications to External Systems</b>                    | 5        |
| <b>Format for Variables .....</b>   | 5        |
| Inbound: Querying Cludpath.....   | 5        |
| Creating an API Key.....  | 6        |
| <b>API Examples.....</b>  | <b>9</b> |
| Enrollment Queries and Actions.....   | 9        |
| Retrieve Enrollment Data.....   | 9        |
| Revoke/Unrevoke Enrollment.....   | 9        |
| Certificate Queries.....  | 10       |
| Generate Certificate.....   | 10       |
| Generate a P12 Certificate.....   | 10       |
| Revoke/Unrevoke Certificate.....  | 11       |
| Return Certificate Data.....  | 11       |
| Revoke Certificate by Certificate Serial Number.....                          | 12       |
| User Queries.....   | 12       |
| Blocking/Unblocking User.....   | 12       |
| Revoke Enrollments.....   | 13       |
| Device Queries.....   | 13       |
| Block/Unblock Device.....   | 13       |
| Revoke Certificates.....  | 14       |
| Register MAC address.....   | 14       |
| Device Configuration Queries and Actions.....                                 | 15       |
| Generate Mobileconfig File.....   | 15       |
| External Queries .....  | 15       |
| Device Capabilities Query.....  | 17       |
| Device Authorization.....   | 17       |
| Change MAC Address.....   | 18       |
| Get Device Information by Certificate Serial Number.....                      | 19       |
| Get Devices Associated with a Customer Account Number.....                    | 19       |
| Get Device Information by MAC Address and Customer Account Number.....        | 20       |
| Revoke Certificate by MAC Address and Customer Account Number.....            | 20       |
| Clear Device Capability Cache (For Testing Only).....                         | 21       |
| Destroy Enrollment Records by Customer Account Number (For Testing Only)..... | 21       |
| Destroy Enrollment Records by GUID.....                                       | 22       |
| Modifying Settings in Cludpath.....   | 22       |
| Return Passphrase Information.....  | 22       |
| Return Passphrase String.....   | 23       |
| Change Passphrase.....  | 23       |
| Create Voucher Object.....  | 24       |
| Troubleshooting.....  | 24       |



# How to Use The Cloudpath API

---

|  |          |
|--|----------|
| • Overview.....  | 5        |
| • <b>Outbound: Sending Notifications to External Systems .....</b> | <b>5</b> |
| • Inbound: Querying Cloudpath.....                                 | 5        |

## Overview

Cloudpath provides REST APIs to enable integration with existing processes or third-party applications. The REST APIs allow the system to actively notify external systems (outbound calls) and to be queried and manipulated by external systems (inbound calls).

## Outbound: Sending Notifications to External Systems

You can pass data from Cloudpath using notifications through email or URL requests. Variables are populated in the Enrollment Record and may be passed through the URL call.

For example, you might want to include enrollment data in a certificate issuance notification email. In this case, the URL containing the variables is sent to the server using a simple GET request, and the HTTP reply is the result data, included as part of the email notification.

**NOTE**

Some API calls support POST requests. If supported, POST is listed in the parameters.

## Format for Variables

Variables in Cloudpath are in the following format: \${MAC\_ADDRESS}, \${USERNAME}, or

`\${IP\_ADDRESS}`. See the Enrollment Variables section on the Enrollment Record page to view available variables, variable syntax, and expected values.

The variables are passed through a URL as in this example: `http://test.company.net/ registration?user=${USERNAME}&mac=${MAC_ADDRESS}`. The result from this example would be the username and device MAC address sent within the notification.

Only variables which are populated at the time of the notification event are sent. MAC addresses and other variables may be populated through events other than onboarding, such as data prompts.

**NOTE**

We recommend that you use URL requests for large amounts of data. Send the enrollment GUID value in the REST URL and then query the Cloudpath system for the enrollment record.

## Inbound: Querying Cloudpath

You can retrieve information from Cloudpath through a REST type API query and perform an action, based on the result data. For example, you might use an API query to block a user or revoke a certificate.

## How to Use The Cloudpath API

### Inbound: Querying Cloudpath

The API query, containing the identifier information and appropriate action, is sent to the server and the objects are returned in either JSON or XML.

The RESTAPI call is structured as follows:

**http://test.company.net/adm in/api/zAdBCLcgrwca/enrollment/IdentityCN/bob/get**

- **http ://test.company.net/admin** = HTTP authentication
- **api** = API entry point
- **zAdBCLcgrwca** = API key
- **enrollment** = realm
- **IdentityCN** = Identity type
- **bob** = Identity value
- **get** = Action

Each realm allows a different set of identity information. See the appropriate sections in API Examples for the list of valid identity types.

## Creating an API Key

For Cloudpath to honor inbound requests from external systems, the external system must authenticate using an API key. The API key is part of the REST API query used to retrieve information from the Cloudpath system. To create an API Key, perform the following steps:

1. Go to **Configuration > API Keys** .
2. Click **API Keys**

**FIGURE 1** Create API Key

The screenshot shows a web-based configuration interface for creating an API key. At the top, a navigation bar reads "Configuration > API Keys > Create". On the right side of the bar are two buttons: "Cancel" and "Save". Below the navigation bar, the title "API Key Information" is displayed in orange. The form contains several input fields and labels:

- Name:** A text input field containing "Device Capabilities" with a mandatory asterisk (\*) symbol.
- Description:** A large, empty text area for entering a description.
- Enabled:** A checkbox that is checked.
- API Key:** A text input field containing "BmGsez6evQc8" with a mandatory asterisk (\*) symbol.
- Allowed Path Regex:** A text input field containing an empty string, indicated by a single asterisk (\*) symbol.
- Expiration Date:** A text input field containing the date "20180404".

Cloudpath provides a generated **APIKey**, or you can specify a custom key. An API key must be URL-safe.

The **Allowed Path Regex** is a regex specifying the paths allowed to be called with this API key. For example,/admin/api/.\*/certificate/.\* can query anything in the 'certificate' realm. If left blank, there is no restriction.

For the **Expiration Date**, the Cloudpath system defaults to a one-year expiration, but this value can be modified.



# API Examples

|   |    |
|---|----|
| • Enrollment Queries and Actions.....           | 9  |
| • Certificate Queries.....                      | 10 |
| • User Queries.....                             | 12 |
| • Device Queries.....                           | 13 |
| • Device Configuration Queries and Actions..... | 15 |
| • External Queries .....                        | 15 |
| • Modifying Settings in Cloupath.....           | 22 |
| • Troubleshooting.....                          | 24 |

This section provides some common API queries for use with Cloupath.

## Enrollment Queries and Actions

When specifying which enrollment should be queried or manipulated by a request, the enrollments can be specified in various formats, such as *Pk*, *Guid*, *MACAddress*, *Username*, *Assistanceld*, and *Email*. Many of the requests contain a section similar to *Username/bob*, meaning any environment where the *username* is *bob*.

### Retrieve Enrollment Data

Returns data for the specified enrollment.

#### Resource URIs

| URI  | Description         |
|--|---------------------|
| /admin/api/{API_KEY}/enrollment/{IDENTITY_TYPE}/{IDENTITY_VALUE}/get | Get enrollment data |

#### Example

<http://test.company.net/admin/api/zAdBCLcgrwca/enrollment/Username/bob/get>

### Revoke/Unrevoke Enrollment

Revoke (or unrevoke) the specified enrollment.

#### Resource URIs

| URI   | Description         |
|---|---------------------|
| /admin/api/{API_KEY}/enrollment/{IDENTITY_TYPE}/{IDENTITY_VALUE}/revoke   | Revoke enrollment   |
| /admin/api/{API_KEY}/enrollment/{IDENTITY_TYPE}/{IDENTITY_VALUE}/unrevoke | Unrevoke enrollment |

### Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/enrollment/Email/bob@company.net/revoke>  
<http://test.company.net/admin/api/zAdBCLcgrwca/enrollment/MACAddress/A1:B2:C3:D4:E5:F6/unrevoke>

## Certificate Queries

When specifying which certificate should be queried or manipulated by a request, the certificates can be specified in various formats, such as *Pk*, *Cn*, and *Serial*.

### Generate Certificate

Generates a certificate based on the CSR provided. This query supports description (optional) and CUSTOM\_VARIABLES (any variable used in the certificate template).

#### Resource URIs

| URI                                       | Description          |
|---|----------------------|
| /admin/api/{API_KEY}/certificate/generate | Generate Certificate |

#### GET/POST Parameters

##### csr

Required

##### certificateTemplateName

Required. Required. Name of certificate template in Cloudpath from which to issue.

### Examples

[http://test.company.net/admin/api/zAdBCLcgrwca/certificate/generate?  
csr={CSR}&certificateTemplateName=TestCompanyTemplate](http://test.company.net/admin/api/zAdBCLcgrwca/certificate/generate?csr={CSR}&certificateTemplateName=TestCompanyTemplate)

## Generate a P12 Certificate

Generates a certificate in P12 format, without a CSR. This query supports description (optional) and CUSTOM\_VARIABLES (any variable used in the certificate template).

#### Resource URIs

| URI  | Description              |
|--|--------------------------|
| /admin/api/{API_KEY}/certificate/generateP12 | Generate P12 certificate |

## GET/POST Parameters

### *certificateTemplateName*

Required. Required. Name of certificate template in Cloudpath from which to issue.

### *password*

Required. Password to use to encrypt the P12. May be left blank if not encrypted.

### *validForDaysOverride*

Optional. If provided, this overrides the certificate template's validity period.

## Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/certificate/generateP12?  
certificateTemplate=ServerTemplate&password=test
```

## Revoke/Unrevoke Certificate

Revoke the specified certificate.

## Resource URIs

| URI  | Description          |
|--|----------------------|
| /admin/api/{API_KEY}/certificate/{IDENTITY_TYPE}/{IDENTITY_VALUE}/revoke   | Revoke certificate   |
| /admin/api/{API_KEY}/certificate/{IDENTITY_TYPE}/{IDENTITY_VALUE}/unrevoke | Unrevoke certificate |

## Usage Guidelines

### NOTE

For external CAs, the CA must support unrevoke.

## Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/certificate/Pk/235/revoke
```

Unrevoke the specified certificate

```
http://test.company.net/admin/api/zAdBCLcgrwca/certificate/Cn/bob@company.net/unrevoke
```

## Return Certificate Data

Returns data about the specified certificate.

## Resource URIs

| URI   | Description          |
|---|----------------------|
| /admin/api/{API_KEY}/certificate/{IDENTITY_TYPE}/{IDENTITY_VALUE}/get | Get certificate data |

## Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/certificate/Serial/d8a76ccc42e6f3c5048fee0aa7d6e411841db54b/get>

## Revoke Certificate by Certificate Serial Number

Revokes a certificate with a specified serial number.

### Resource URIs

| URI  | Description                         |
|--|-------------------------------------|
| /admin/api/{apiKey}/certificate/Serial/{serialNumber}/revoke | Revoke certificate by serial number |

### GET/POST Parameters

*serialNumber*

Required. Serial number of the certificate.

*reason*

Optional. Description of why the certificate was revoked

## Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/certificate/Serial/00fde721f1bb5e45e3feb7b49e1e8728b561936b/revoke>

## User Queries

When specifying which user should be queried or manipulated by a request, the user can be specified in various formats, such as IdentityCN, IdentityDN, CertificateCN, CertificateSerial, and Email. Many of the requests contain a section similar to Email/bob@company.net, meaning any environment where the Email is bob@company.net.

## Blocking/Unblocking User

Blocks the specified user account, which includes revoking all associated certificates and MAC registrations, and prevents the user from enrolling again.

### Resource URIs

| URI  | Description  |
|--|--------------|
| /admin/api/{API_KEY}/user/{IDENTITY_TYPE}/{IDENTITY_VALUE}/block   | Block user   |
| /admin/api/{API_KEY}/user/{IDENTITY_TYPE}/{IDENTITY_VALUE}/unblock | Unblock user |

## Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/user/IdentityCN/bob/block>

**Unblocks the specified user account:**

<http://test.company.net/admin/api/zAdBCLcgrwca/user/CertificateCN/bob/unblock>

## Revoke Enrollments

Revokes all enrollments for the user account, which includes revoking all associated certificates and MAC registrations. This does not block the user account, and allows the user to enroll again.

### Resource URIs

| URI  | Description            |
|--|------------------------|
| /admin/api/{API_KEY}/user/{IDENTITY_TYPE}/{IDENTITY_VALUE}/revokeAll | Revoke all enrollments |

## Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/user>Email/bob@company.net/revokeAll>

## Device Queries

When specifying which device should be queried or manipulated by a request, the devices can be specified by *MACAddress*. Many of the requests contain a section similar to *MACAddress/A1:B2:C3:D4:E5:F6*, meaning any environment where the device *MACAddress* is A1:B2:C3:D4:E5:F6.

## Block/Unblock Device

Blocks the specified device.

### Resource URIs

| URI  | Description                  |
|--|------------------------------|
| /admin/api/{API_KEY}/device/{IDENTITY_TYPE}/{IDENTITY_VALUE}/block   | Block the specified device   |
| /admin/api/{API_KEY}/device/{IDENTITY_TYPE}/{IDENTITY_VALUE}/unblock | Unblock the specified device |

## Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/device/MACAddress/A1:B2:C3:D4:E5:F6/block>

**Unblocks the specified device:**

<http://test.company.net/admin/api/zAdBCLcgrwca/device/MACAddress/A1:B2:C3:D4:E5:F6/unblock>

## Revoke Certificates

Revokes all certificate for the specified device.

### Resource URIs

| URI  | Description                         |
|--|-------------------------------------|
| /admin/api/{API_KEY}/device/{IDENTITY_TYPE}/{IDENTITY_VALUE}/revokeAll | Revoke all certificate for a device |

### Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/device/MACAddress/A1:B2:C3:D4:E5:F6/revokeAll`

## Register MAC address

Registers the MAC address for the specified device to a specified MAC Registration list.

### Resource URIs

| URI                                     | Description          |
|---|----------------------|
| /admin/api/{API_KEY}/device/registerMac | Register MAC Address |

### GET/POST Parameters

*macRegistrationName*

Required. The name of the MAC registration list.

*macAddress*

Required. The MAC address to register.

*username*

Optional. If specified, this value is saved as the associated username.

*email*

Optional. If specified, this value is saved as the associated email.

*deviceName*

Optional. If specified, this value is saved as the device name.

*location*

Optional. If specified, this value is saved as the location.

*expirationDate*

Optional. If specified, this value overrides the default expiration date.

### Usage Guidelines

#### NOTE

The expiration Date must be entered using the UNIX time format (yyyymmdd), regardless of the date format of the system.

## Examples

http://test.company.net/admin/api/zAdBCLcgrwca/device/registerMac?  
macRegistrationName=MacRegList1&macAddress=A1:B2:C3:D4:E5:F6

# Device Configuration Queries and Actions

## Generate Mobileconfig File

Generates a signed mobileconfig file containing a certificate and device configuration. This query supports the optional parameters for validForDaysOverride and description, and CUSTOM\_VARIABLES (any variable used in the certificate template must also be provided as a parameter).

### Resource URIs

| URI  | Description                |
|--|----------------------------|
| /admin/api/{API_KEY}/deviceConfig/generateMobileconfig | Generate Mobileconfig file |

### GET/POST Parameters

*deviceConfigName*

Required. Name of the device configuration in Cloudpath from which to use.

*certificateTemplateName*

Required. Name of certificate template in Cloudpath from which to issue.

*validForDaysOverride*

Optional. If not zero, this overrides the expiration date specified in the certificate template.

## Examples

http://test.company.net/admin/api/zAdBCLcgrwca/deviceConfig/generateMobileconfig?  
deviceConfigName=SecureNetwork1&certificateTemplateName=CertTemplate1

# External Queries

Certain external queries (**checkCapability** and **authorizeDevice**) require the location URL name, which is specified in the URL Name field on the **Configuration > Workflows** Properties tab.

**FIGURE 2 Location URL Name**

The screenshot shows the 'Configuration > Workflows' interface. At the top right is a blue 'Add Workflow' button with a white arrow. Below it is a table with columns: 'Workflows', 'Status', 'Published URL', and 'Last Publish Time'. A single row is visible, showing 'Production' in the first column, a green circular 'Published' status icon in the second, a blue link icon followed by '/enroll/Anna44TestXPC/Production/' in the third, and '20170404 1035 MDT' in the fourth. Below the table is a navigation bar with tabs: 'Properties' (highlighted in blue), 'Enrollment Process', 'Look & Feel', 'Snapshot(s)', and 'Advanced'. Under the 'Properties' tab, there's a section titled 'Workflow Properties' with a 'Save' button at the top right. It contains two fields: 'Name:' with 'Production' entered and an asterisk, and 'Description:' with an empty text area. Below this is another section titled 'Enrollment Portal URL Options' with three fields: 'URL Name:' with 'Production', 'Enable DNS Shortcut:' with an unchecked checkbox, and 'Enforce Required Parameters:' with an unchecked checkbox.

The examples in this section use Production for the locationUrlName.

## Device Capabilities Query

Queries the capabilities of a device based on the user agent and device configuration. An HS2R1 or HS2R2 response value is returned only if the HS2R1/HS2R2 SSID Type has been set for the device configuration.

### Resource URIs

| URI  | Description               |
|--|---------------------------|
| /admin/api/{apiKey}/external/{locationUrlName}/checkCapability | Queries device capability |

### GET/POST Parameters

#### *userAgent*

Required. A string representing the user agent of a device.

#### *screenHeight*

Optional. Necessary to exclude iPhone 4s and iPad 2 and earlier devices from hotspot 2 support.

#### *screenWidth*

Optional. Necessary to exclude iPhone 4s and iPad 2 and earlier devices from hotspot 2 support.

### Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/external/Production/checkCapability?userAgent=Mozilla%2F5.0%20(iPad%3B%20CPU%20OS%208_3%20like%20Mac%20OS%20X)%20AppleWebKit%2F537.51.1%20(KHTML%2C%20like%20Gecko)%20CriOS%2F30.0.1599.12%20Mobile%2F11A465%20Safari%2F8536.25%20
```

## Device Authorization

Authorizes a device using the customer account number and optional parameters

### Resource URIs

| URI  | Description        |
|--|--------------------|
| /admin/api/{apiKey}/external/{locationUrlName}/authorizeDevice | Authorize a device |

### GET/POST Parameters

#### *externalId*

Required. A string representing the customer account number. This can be up to 14 characters.

#### *macAddress*

Optional. The device MAC address, formatted as aa:bb:cc:dd:ee:ff.

#### *userAgent*

Optional. A string representing the user agent of a device.

#### *username*

Optional. Username of the device.

*screenHeight*

Optional. Necessary to exclude iPhone 4s and iPad 2 and earlier devices from hotspot 2 support.

*screenWidth*

Optional. Necessary to exclude iPhone 4s and iPad 2 and earlier devices from hotspot 2 support.

## Usage Guidelines

**NOTE**

The *userAgent* parameter is optional. However, if the user agent is not part of the enrollment record, other API calls may not return the correct OS family.

Optional parameters, if specified, are set in the device record.

## Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/external/Production/authorizeDevice?  
externalId=123456789012&macAddress=aa:bb:cc:dd:ee:ff&username=bob&userAgent=Mozilla%2F5.0%20(iPad%3B  
%20CPU%20OS%208_3%20like%20Mac%20OS%20X)%20AppleWeb%20Kit%2F537.51.1%20(KHTML%2C%20like%20Gecko)  
%20CriOS%2F30.0.1599.12%20Mobile%2F11A46 5%20Safari%2F8536.25%20
```

## Change MAC Address

Changes the MAC address for an enrollment record.

### Resource URIs

| URI                                    | Description                             |
|--|---|
| /admin/api/{apiKey}/external/changeMac | Change MAC address for enrolment record |

### GET/POST Parameters

*externalId*

Required. A string representing the customer account number. This can be up to 14 characters

*oldMacAddress*

Required. The MAC address currently populated in the enrollment record, formatted as aa:bb:cc:dd:ee:ff.

*newMacAddress*

Required. The new MAC address to be set in the enrollment record, formatted as aa:bb:cc:dd:ff.

## Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/external/ changeMac?  
externalId=123456789012&oldMacAddress=aa:bb:cc:dd:ee:ff&newMacAddress=11:22:3 3:44:55:66
```

## Get Device Information by Certificate Serial Number

Queries the customer account number and MAC address associated with a certificate serial number. The associated information is returned regardless of revocation status.

### Resource URIs

| URI  | Description                             |
|--|---|
| /admin/api/{apiKey}/external/getDeviceBySerialNumber | Get device information by serial number |

### GET/POST Parameters

#### *certificateSerialNumber*

Required. The serial number of the client certificate to query, formatted 00fde721f1bb5e45e3feb7b49e1e8728b561936b. The serial number must be exactly 40 characters. If less than 40 characters, the value must be left-padded with zeros.

### Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/external/getDeviceBySerialNumber?  
certificateSerialNumber=00fde721f1bb5e45e3feb7b49e1e8728b561936b
```

## Get Devices Associated with a Customer Account Number

Returns all devices associated with a customer account number.

### Resource URIs

| URI                                     | Description                              |
|---|--|
| /admin/api/{apiKey}/external/getDevices | Get devices with customer account number |

### GET/POST Parameters

#### *externalId*

Required. A string representing the customer account number. This can be up to 14 characters.

#### *includeRevoked*

Optional. If '1', the response includes revoked enrollments and certificates. If not specified or '0', revoked enrollments and certificates are excluded from the response.

### Usage Guidelines

#### NOTE

This call places a heavy load on the system.

### Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/external/getDevices?externalId=123456789012
```

## Get Device Information by MAC Address and Customer Account Number

Returns the data associated with a customer account number and specified MAC address.

### Resource URIs

| URI  | Description  |
|--|--|
| /admin/api/{apiKey}/external/getDeviceByMacAddress | Get device information by MAC Address and customer account |

### GET/POST Parameters

#### externalId

Required. A string representing the customer account number. This can be up to 14 characters.

#### macAddress

Required. The device MAC address, formatted as aa:bb:cc:dd:ee:ff.

### Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/external/getDeviceexternalId=CustomerA&macAddress=00:bb:cc:dd:ee:ff`

## Revoke Certificate by MAC Address and Customer Account Number

Revokes one or more certificates associated with a customer account number and specified MAC address.

### Resource URIs

| URI   | Description                             |
|---|---|
| /admin/api/{apiKey}/external/revokeByMacAndExternalId | Revoke certificate for customer account |

### GET/POST Parameters

#### externalId

Required. A string representing the customer account number. This can be up to 14 characters.

#### macAddress

Required. The device MAC address, formatted as aa:bb:cc:dd:ee:ff.

#### destroy

Optional. If specified and set to '1', the enrollment record(s) are permanently deleted rather than revoked. This causes the enrollment record and all associated data (including certificates) to be permanently deleted. After deletion, the log will be the only record of the existence of the certificate. OCSP responses will be "not found".

### Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/external/revokeByMacAndExternalId?externalId=CustomerA&macAddress=00:bb:cc:dd:ee:ff`

## Clear Device Capability Cache (For Testing Only)

This method allows the cache to be flushed without restarting the server.

### Resource URIs

| URI                                     | Description     |
|---|-----------------|
| /admin/api/{apiKey}/external/clearCache | Clear the cache |

### Usage Guidelines

#### NOTE

Caching occurs by a combination of the user agent and location. The only time the cache should need to be cleared is if the location's device configuration is changed.

### Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/external/clearCache>

## Destroy Enrollment Records by Customer Account Number (For Testing Only)

Allows a call to destroy all elements for a specified customer account number.

### Resource URIs

| URI  | Description           |
|--|-----------------------|
| /admin/api/{apiKey}/external/destroyByExternalIdForTestingOnly | Clear customer record |

### GET/POST Parameters

#### externalId

Required. The customer account number for which all enrollments will be destroyed. If the externalId is blank, this call is ignored by the system.

### Examples

<http://test.company.net/admin/api/zAdBCLcgrwca/external/destroyByExternalIdForTestingOnly?externalId=CustomerA>

## Destroy Enrollment Records by GUID

This method allows a caller to destroy all data related to an enrollment based on the enrollment's GUID. This causes the enrollment record and all associated data (including certificates) to be permanently deleted.

### Resource URIs

| URI  | Description             |
|--|-------------------------|
| /admin/api/{apiKey}/external/destroyByEnrollmentGuid | Destroy enrollment data |

### GET/POST Parameters

*guid*

Required. The GUID for the enrollment to be destroyed.

### Usage Guidelines

#### NOTE

After deletion, the log will contain the only record of the existence of the certificate in the system. OCSP responses will be "not found".

The system logs a message (at INFO level) containing the enrollment GUID, MAC address, external ID, certificate PK, certificate serial number, certificate thumbprint, certificate expiration date, MAC registration PK, and the MAC registration expiration date. If permanent storage is desired, use the syslog.

### Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/external/destroyByEnrollmentGuid?guid=xyz`

## Modifying Settings in Cloudpath

Settings can be manipulated using REST APIs. When specifying which setting should be manipulated by a request, specify the OBJECT\_GUID for passphrase information, and the desired parameter for voucher information. See the appropriate Parameters section for details.

## Return Passphrase Information

Returns information about the specified shared passphrase.

### Resource URIs

| URI  | Description                |
|--|----------------------------|
| /admin/api/{API_KEY}/object/ss/{OBJECT_GUID}/get | Get passphrase information |

## Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/object/ss/SharedSecretPrompt-FC1C020C-6A62-4581-B661-18ED883831C2/get`

## Return Passphrase String

Returns only the shared passphrase string for a shared passphrase.

### Resource URIs

| URI   | Description                  |
|---|------------------------------|
| /admin/api/{API_KEY}/object/ss/{OBJECT_GUID}/get/ss | Get shared passphrase string |

## Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/object/ss/SharedSecretPrompt-FC1C020C-6A62-4581-B661-18ED883831C2/get/ss`

## Change Passphrase

Changes the shared passphrase.

### Resource URIs

| URI   | Description       |
|---|-------------------|
| /admin/api/{API_KEY}/object/ss/{OBJECT_GUID}/change | Change passphrase |

### GET/POST Parameters

*newSs*

Optional. If specified, this value is used as the new shared passphrase. If not specified, a random shared passphrase is generated

*length*

Optional. If a random shared passphrase is generated, this will be the length of it.

## Examples

`http://test.company.net/admin/api/zAdBCLcgrwca/object/ss/SharedSecretPrompt-FC1C020C-6A62-4581-B661-18ED883831C2/change?newSs=brandnewpassphrase`

## Create Voucher Object

Sets a value in the voucher.

### Resource URIs

| URI  | Description      |
|--|------------------|
| /admin/api/{API_KEY}/object/otp/{OBJECT_GUID}/create | Create a voucher |

### GET/POST Parameters

*name*

Optional. If specified, this value will be set as the name in the voucher.

*company*

Optional. If specified, this value will be set as the company in the voucher.

*email*

Optional. If specified, this value will be set as the email in the voucher.

*sponsor*

Optional. If specified, this value will be set as the sponsor in the voucher.

*accessDays*

Optional. If specified, this value will be set as the number of days of access in the voucher.

*sms*

Optional. If specified, this value will be set as the SMS in the voucher.

*otp*

Optional. If specified, this value will be set as the voucher in the voucher. If not specified, a random voucher will be generated.

*sendEmail*

Optional. Defaults to 1. If 1, the user will be emailed the voucher code (if an email is populated).

*sendSms*

Optional. Defaults to 1. If 1, the user will be sent the voucher code (if an SMS is populated) via SMS.

*daysToRedeem*

Optional. Defaults to 3. If specified, this is the number of days within which the voucher must be redeemed.

### Examples

```
http://test.company.net/admin/api/zAdBCLcgrwca/object/otp/xyz/ create?  
name=bob&email=bob@test.com&sendEmail=1
```

## Troubleshooting

To assist with troubleshooting, append the following to the API query.

- Append ?debug=true for diagnostics.
- Append ?format=xml for XML formatted response on GETs.

**TABLE 1** Common API Error Messages

| Error Code | Error Message                         |
|------------|---------------------------------------|
| 204        | No records found matching parameters. |
| 400        | Invalid parameter or value.           |
| 401        | Unauthorized.                         |
| 500        | Internal Server Error.                |